

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



**Photobiological safety of lamps and lamp systems –  
Part 6: Ultraviolet lamp products**

**Sécurité photobiologique des lampes et des appareils utilisant des lampes –  
Partie 6: Appareils à lampes ultraviolettes**

<https://standards.iteh.ai/catalog/standards/sist/89ba1094-9553-4c5b-ac7d-14bceb9a1905/iec-62471-6-2022>



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2022 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

---

#### A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

#### A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

#### Recherche de publications IEC -

#### [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 300 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 19 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

#### Service Clients - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: [sales@iec.ch](mailto:sales@iec.ch).

#### IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



**Photobiological safety of lamps and lamp systems –  
Part 6: Ultraviolet lamp products**

**Sécurité photobiologique des lampes et des appareils utilisant des lampes –  
Partie 6: Appareils à lampes ultraviolettes**

<https://standards.iteh.ai/catalog/standards/sist/89ba1094-9553-4c5b-ac7d-14bceb9a1905/iec-62471-6-2022>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

ICS 29.140.01; 31.260

ISBN 978-2-8322-5828-6

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references .....	8
3 Terms and definitions .....	9
4 Risk groups applied for ultraviolet lamp-product safety assessments .....	12
4.1 Basis for optical radiation safety risk group determination.....	12
4.2 Assessment criteria (background) for UV lamp products .....	12
5 Measurements to determine applicable risk group .....	13
5.1 General.....	13
5.2 Time-weighted averaged irradiance .....	14
5.3 Risk group assessment conditions .....	14
5.3.1 Maximum output conditioning .....	14
5.3.2 Measurement and assessment distances for UV lamp products .....	15
5.3.3 Risk-group assessment distances.....	15
5.3.4 Dose-limited products .....	18
5.3.5 Products intended to expose the skin or eyes .....	18
6 Engineering requirements for RG-2 and RG-3 ultraviolet systems.....	18
6.1 General.....	18
6.2 Protective housing .....	19
6.2.1 General .....	19
6.2.2 Enclosures .....	19
6.2.3 Openings, panels and doors .....	19
6.3 RG-2 and RG-3 products .....	19
6.3.1 General .....	19
6.3.2 Proximity sensor.....	20
6.3.3 Orientation control .....	20
6.3.4 Upper-room germicidal UV luminaire alignment .....	20
6.3.5 Delayed-ON timer .....	20
6.3.6 Exposure time control / auto-shutoff .....	20
6.4 Emission warning.....	20
6.5 Reliability.....	21
6.6 Emission controls.....	21
6.6.1 General .....	21
6.6.2 Emissions stop .....	21
6.6.3 Key control .....	21
7 Information and Labelling – Manufacturer’s Requirements .....	21
7.1 General.....	21
7.2 User information .....	22
7.3 Labelling on UV lamps .....	22
7.4 Labelling on UV lamp products.....	22
7.4.1 RG-0 UV lamp products .....	22
7.4.2 RG-1 UV lamp products .....	22
7.4.3 RG-2 UV lamp products .....	22
7.4.4 RG-3 UV lamp products .....	23
7.5 User manual .....	23

7.5.1	General .....	23
7.5.2	Risk reduction measures .....	23
7.5.3	Limited use .....	24
7.6	Maintenance and service .....	24
Annex A (informative)	Typical applications of UV lamp products .....	25
A.1	Background.....	25
A.2	Applications of UV lamp products.....	25
A.2.1	Near-UV (UV-A) “black-light” sources to view fluorescent pigments .....	25
A.2.2	Near-UV (UV-A) insect attractant lamp products .....	25
A.2.3	UV germicidal (UV-C) lamp products .....	26
A.2.4	UV nail curing and treatment .....	26
A.2.5	UV medical and dental sources.....	27
Annex B (informative)	Potentially hazardous biological effects .....	28
B.1	Background.....	28
B.2	Adverse acute biological effects from ultraviolet irradiation .....	28
B.2.1	Photokeratitis and photoconjunctivitis .....	28
B.2.2	UV-Cornea reference documents .....	29
B.2.3	Erythema (sunburn) .....	29
B.2.4	Erythema reference documents .....	29
B.3	Adverse biological effects from chronic exposure to ultraviolet irradiation .....	30
B.3.1	Skin cancer .....	30
B.3.2	Skin cancer reference documents .....	31
B.3.3	Pterygium and pinguecula .....	31
B.3.4	Pterygium and pinguecula reference documents .....	31
B.3.5	Cataract .....	32
B.3.6	Cataract reference documents .....	32
B.3.7	Labrador keratopathy.....	32
B.3.8	Corneal reference documents .....	32
B.3.9	Visual effects from UV-A exposure – Lens fluorescence .....	33
B.3.10	Photoretinitis – or photic maculopathy (blue light hazard) .....	33
B.3.11	Retinal-photochemical biological effects reference documents.....	34
Annex C (informative)	Measurement of ultraviolet lamp products .....	35
C.1	General.....	35
C.2	Radiometers .....	35
C.3	Spectroradiometers.....	35
C.4	Entrance optic.....	36
C.5	Spectroradiometer- radiometer approach .....	37
C.6	Measurement distance versus assessment distance .....	37
C.6.1	General .....	37
C.6.2	Spectroradiometer approach.....	37
C.6.3	Radiometer approach .....	38
C.7	Reference documents .....	38
Annex D (informative)	Spectral weighting function $S(\lambda)$ from 180 nm to 400 nm for assessing actinic radiation hazard .....	39
Annex E (informative)	Examples of risk group classification applying the concept of TWA of a spectrally-weighted emission.....	42
E.1	Spectral weighting to determine effective irradiance using $S(\lambda)$ .....	42
E.2	Time weighting of an exposure.....	42

E.3	Field radiometric measurements for final acceptance testing of a GUV installation .....	45
Annex F (informative)	Upper room GUV – Background and rationale to achieve safety .....	46
F.1	General.....	46
F.2	Product Goals .....	46
F.3	Product test measurement conditions.....	46
F.3.1	General .....	46
F.3.2	Elevation plane for radiometric measurements.....	47
F.3.3	Test grid for measurements .....	47
F.3.4	Detector acceptance angle (field-of-view) .....	47
F.3.5	Instrument performance specifications.....	47
F.4	GUV luminaires.....	47
F.4.1	Adjustable UV luminaires.....	47
F.4.2	Interlock safeguards on removable baffles.....	47
F.4.3	Labelling requirements .....	48
F.4.4	Efficacy and information for the user.....	48
F.5	Acceptance testing.....	48
F.5.1	Scope of the installation acceptance testing .....	48
F.5.2	Time-weighted averaging.....	48
F.6	Reference documents.....	48
Bibliography	.....	50
Figure 1	– Based on Graphic 6040 of UV lamp inside triangle from IEC 60417.....	23
Figure 2	– Alternative labels to provide added information for narrow-band UV lamps.....	23
Figure B.1	– CIE Standard Action Spectrum for NMSC .....	30
Figure B.2	– Semi-logarithmic comparison of three action spectra (ICNIRP $S(\lambda)$ – solid line; McKinlay, Diffey erythema – dashed; NMSC – dots).....	31
Figure C.1	– Geometry of irradiance / spectral irradiance measurements.....	36
Figure E.1	– Example of how an occupational hygienist might determine different zones of exposure by time-weighting .....	43
Figure E.2	– Time-weighted averaging (TWA) over an 8 h period.....	44
Figure E.3	– Field GUV safety meter with 80° full field of view .....	45
Table 1	– Emission limits for risk groups for time-weighted averaged irradiance .....	14
Table 2	– Risk group assessment distances for unrestricted-use <sup>a</sup> products .....	16
Table 3	– Risk group assessment distances for restricted-use products intended to be used by instructed persons .....	17
Table 4	– Risk group assessment distances for lamps or lamp products intended for use by professional, competent persons .....	18
Table D.1	– Spectral weighting function $S(\lambda)$ values at 1 nm intervals .....	39

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**PHOTOBIOLOGICAL SAFETY OF LAMPS AND LAMP SYSTEMS –****Part 6: Ultraviolet lamp products****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62471-6 has been prepared by IEC technical committee 76: Optical radiation safety and laser equipment. It is an International Standard.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
76/714/FDIS	76/718/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/standardsdev/publications](http://www.iec.ch/standardsdev/publications).

In this standard, the following print types are used:

*conformity statements: in italic type.*

A list of all parts in the IEC 62471 series, published under the general title *Photobiological safety of lamps and lamp systems*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[IEC 62471-6:2022](https://standards.iteh.ai/catalog/standards/sist/89ba1094-9553-4c5b-ac7d-14bceb9a1905/iec-62471-6-2022)

<https://standards.iteh.ai/catalog/standards/sist/89ba1094-9553-4c5b-ac7d-14bceb9a1905/iec-62471-6-2022>



## INTRODUCTION

Most lamps and lamp products are safe and do not pose photobiological risks except under unusual exposure conditions; however, one group of products-ultraviolet lamp products-can under some conditions pose optical hazards during use and require risk assessment for direct and indirect exposure of the eyes and skin. Optical radiation hazards from all types of lamps or other broadband light sources are assessed by the application of IEC 62471:2006/CIE S009:2002. IEC 62471 covers light emitting diodes (LEDs), incandescent, low- and high- pressure gas-discharge, arc and other lamps. It also covers lamps which are designed primarily to emit ultraviolet radiant energy, such as ultraviolet sources intended to excite fluorescence of irradiated materials, for insect light traps, for scientific studies, mineral identification, for non-destructive testing, germicidal irradiation, and other purposes.

This document provides a risk group (RG) classification system for all ultraviolet lamp products, and the assessment distances and measurement conditions for different products (Annex A and Annex C). It includes manufacturing and user safety requirements that may be required as a result of an ultraviolet lamp product being assigned to a particular risk group. The scope is limited to products where the sole intent is to emit ultraviolet radiant energy. The advantage of applying this document, intended solely for ultraviolet lamp products, instead of the horizontal IEC 62471 standard, is that the risks from visible and infrared optical radiation need not be assessed using this document, as they are assumed to be insignificant for a lamp that emits mainly UV. The assigned risk group of an ultraviolet lamp product using this document may also be used to assist with any needed risk assessments, e.g. for occupational exposure in workplaces.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[IEC 62471-6:2022](https://standards.iteh.ai/catalog/standards/sist/89ba1094-9553-4c5b-ac7d-14bceb9a1905/iec-62471-6-2022)

<https://standards.iteh.ai/catalog/standards/sist/89ba1094-9553-4c5b-ac7d-14bceb9a1905/iec-62471-6-2022>

# PHOTOBIOLOGICAL SAFETY OF LAMPS AND LAMP SYSTEMS –

## Part 6: Ultraviolet lamp products

### 1 Scope

This part of IEC 62471 provides the optical radiation safety requirements for ultraviolet lamp products, including UV LED lamp products.

This document provides requirements for:

- optical radiation safety assessment and ultraviolet-product risk groups;
- user information for safety measures;
- appropriate labelling of ultraviolet lamp products.

This document addresses those lamps and lamp products where the ultraviolet emission serves the primary purpose of the product and where more than half of the radiant power emitted between 180 nm and 3 000 nm is in the spectral region 180 nm to 400 nm. If more than half of the optical radiation emitted between 180 nm and 3 000 nm is outside of the spectral region 180 nm to 400 nm, then the base standard IEC 62471 should be used. This document covers medical diagnostic and cosmetic devices/products that emit primarily UV radiation.

Because photobiological effects from UV radiation are based on the total accumulated exposure (dose) received, this document relies on the concept of ‘time-weighted average’ exposures where the assessment distance for determining the RG is chosen based on realistic exposure distances and exposure durations. In other words, it is not expected that people will be exposed at very close distances, e.g. 20 cm to 30 cm, for extended periods of time. This document provides assessment distances and specific guidance that are application-specific and realistic rather than the more general values in IEC 62471 where the specific application is unknown and time-weighted average exposures are not application-specific.

This document does not provide requirements for:

- lamps which primarily emit visible (such as GLS – general lighting source) and/or infrared radiant energy;
- lamp products used for general lighting or infrared illumination or heating, which are treated in separate standards;
- fluorescent ultraviolet lamps for tanning (covered by IEC 60335-2-27 and IEC 61228);
- medical treatment devices/products (see IEC 60601-2-57), but covers UV medical diagnostic products;
- non-optical hazards, e.g. ozone, mercury, etc.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60335-2-27, *Household and similar electrical appliances – Safety – Part 2-27: Particular requirements for appliances for skin exposure to optical radiation*

IEC 60417:2002, *Graphical symbols for use on equipment – 12-month subscription to regularly updated online database comprising all graphical symbols published in IEC 60417*

IEC 60601-2-57, *Medical electrical equipment – Part 2-57: Particular requirements for the basic safety and essential performance of non-laser light source equipment intended for therapeutic, diagnostic, monitoring and cosmetic/aesthetic use*

IEC 61549, *Miscellaneous lamps*

IEC 62471:2006/CIE S009:2002, *Photobiological safety of lamps and lamp systems*

ISO 7010: *Graphical symbols – Safety colours and safety signs – Registered safety signs*

ISO 15004-2: *Ophthalmic instruments – Fundamental requirements and test methods – Part 2: Light hazard protection*

CIE 247:2021, *Guide for the Gonioradiometric Measurement of Upper Air Ultraviolet Germicidal Irradiation Luminaires*, ISBN 978-3-902842-19-0, Vienna

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

#### 3.1 **actinic UV**

UV radiation capable of producing a photochemical effect

Note 1 to entry: In the context of this document, the biological effects have a demonstrated action spectrum,  $S(\lambda)$ , and refer most significantly to UV-B and UV-C effects, e.g. UV erythema (skin reddening), UV photokeratitis ('welder's flash' or 'snowblindness'), etc. See also Annex B.

#### 3.2 **assessment distance**

distance used to determine the risk group classification of a lamp or lamp product

Note 1 to entry: The risk group assessment distance takes account of the TWA exposure (variable irradiance, exposure distances and durations).

Note 2 to entry: This is usually the distance from the closest point of human access to the emission, to the point of assessment or measurement.

#### 3.3 **blue light hazard**

potential for a photochemically induced retinal injury resulting from radiation exposure at wavelengths primarily between 400 nm and 500 nm

Note 1 to entry: This damage mechanism normally dominates over thermal mechanisms for intense visible light for viewing times exceeding 10 s, but is rarely of concern from UV lamps (unless the basic lamp is an arc lamp).

[SOURCE: IEC 60050-845:2020, 845-26-055]

### **3.4 competent person**

person who can demonstrate a combination of knowledge and skills to effectively, efficiently, and safely carry out specific activities

### **3.5 consumer**

person who purchases or employs goods and services for personal use

Note 1 to entry: Consumers include not only users of the ultraviolet lamp product, but also all persons who may have access to the lamp product or who may be in the vicinity of the product.

Note 2 to entry: Also termed “ordinary person” in IEC 62368-1.

### **3.6 controlled access location**

location where an engineering and/or administrative control measure is established to restrict access except to authorised personnel with appropriate safety training

### **3.7 dose-limited product**

product where the emitted radiant exposure (dose) is limited by time or actual exposure monitoring at the assessment distance to a set level during any day

Note 1 to entry: The emission limit is expressed in  $J/m^2$ .

### **3.8 emission limit**

limit defined for each risk group, based upon reasonably foreseeable conditions of time-weighted average (TWA) exposure

Note 1 to entry: The emission limit incorporates both the concept of exposure duration and variable exposure distance and is derived from exposure limits, however, the risk group assessment distance incorporates the TWA exposure.

### **3.9 general lighting source GLS**

general term for lamps, nominally of “white” colour, intended for lighting spaces that are typically occupied or viewed by people

Note 1 to entry: See IEC 62471 for requirements.

Note 2 to entry: This document does not cover GLS lamps or lamp products.

### **3.10 germicidal lamp product**

any UV lamp product designed to disinfect by ultraviolet germicidal (UVG) irradiation to inactivate microorganisms so they are no longer capable of replicating and causing adverse health effects

### **3.11 instructed person**

person who has been instructed and trained by a competent person, or who is supervised by a competent person, to identify ultraviolet sources that may cause pain or injury and to take precautions to avoid unintentional exposure to those sources

[SOURCE: IEC 62368-1:2018, 0.2.3, modified to use competent instead of skilled person]

### 3.12

#### **intended use**

usage of a product, process or service in accordance with specifications, instructions and information provided by the manufacturer or supplier

### 3.13

#### **UV lamp**

electric lamp or light emitting diode (LED) lamp that radiates especially strongly in the ultraviolet, the visible radiation produced, if any, not being of direct interest

Note 1 to entry: There are several types of ultraviolet lamp used for photobiological, photochemical and biomedical purposes.

[SOURCE: IEC 60050-845:2020, 845-27-091, modified, with Note 2 to entry omitted and with LED lamp (845-27-054) addition]

### 3.14

#### **UV lamp product**

product incorporating a UV lamp or UV lamps, including fixtures, and possibly filters, where the ultraviolet emission is the primary purpose of the lamp product and where more than half of the optical radiation emitted between 180 nm and 3 000 nm is in the spectral region 180 nm to 400 nm

### 3.15

#### **UV luminaire**

apparatus which distributes, filters or transforms the ultraviolet radiant energy transmitted from at least one source of optical radiation and which includes, except the sources themselves, all the parts necessary for fixing and protecting the sources and, where necessary, circuit auxiliaries together with the means for connecting them to the power supply

[SOURCE: IEC 60050-845:2020, 845-30-001, modified for UV]

<https://standards.iteh.ai/catalog/standards/sist/89ba1094-9553-4c5b-ac7d-14bceb9a1905/iec-62471-6-2022>

### 3.16

#### **photocuring lamp product**

lamp product that usually employs UV-A to photopolymerize liquid polymers to a solid state

Note 1 to entry: Examples include photopolymerization of liquid inks in printing or rapid curing of plastic products.

### 3.17

#### **time-weighted average exposure**

##### **TWA exposure**

averaged cumulative exposure dose over a given period of time (normally any 30 000 s to approximately 8 h period) divided by the exposure duration to provide an effective irradiance for both variable distances and durations

Note 1 to entry: The TWA is essential in considering lengthy exposures to ultraviolet hazards, since variable exposure distances at different irradiances and durations determine the reasonably foreseeable worst-case exposures (for photochemical hazards) which correspond therefore to the measured/calculated irradiance at a specified distance for RG determination (analogous to the 500-lx assessment distance for GLS lamps). See Annex E.

### 3.18

#### **ultraviolet radiation**

optical radiation within the wavelength range from 100 nm to 400 nm

Note 1 to entry: The UV-C extends from 100 nm to 280 nm, UV-B from 280 nm to 315 nm, and UV-A from 315 nm to 400 nm.

Note 2 to entry: Ultraviolet radiation at wavelengths less than 180 nm is considered vacuum ultraviolet radiation for the purpose of this document and is not included in the scope.

[SOURCE: IEC 60050-845:2020, 845-21-008, modified: Notes 2 to 5 to entry omitted and new Note 2.]

### 3.19

#### **ultraviolet-fluorescence illuminator**

any UV-A lamp designed to illuminate and excite fluorescence to permit increased visualization of the material

Note 1 to entry: Examples include “black-light” fluorescent illuminators, security-code reading UV-A lamps used for counterfeit money detection, medical applications, etc.

## **4 Risk groups applied for ultraviolet lamp-product safety assessments**

### **4.1 Basis for optical radiation safety risk group determination**

IEC 62471/CIE S009 provides the fundamental method to determine the risk group of any individual lamp and also the default measurement condition to determine the risk group of any lamp or any product incorporating a lamp, unless a vertical (application-specific) standard exists that includes measurement conditions for its specific application. The risk groups in IEC 62471 indicate the degree of risk from potential optical radiation hazards and minimize the need for further measurements. The risk groups were developed based upon decades of lamp use experience and the analysis of accidental injuries related to optical radiation emission (where injuries were, generally, quite rare except from ultraviolet-emitting lamps or arc lamps). The risk groups are also used in determining appropriate measures for risk management. There are four basic risk groups:

- Exempt group (RG-0) where no optical hazard is considered reasonably foreseeable, even for continuous, unrestricted use. Typical examples are small UV-A LED lamps and UV-A fluorescent lamps used in ultraviolet fluorescence illuminators or in domestic insect light traps;
- Risk group 1 (RG-1) products are safe for most use applications, except where prolonged direct ocular exposures may be expected. An example of a risk group 1 lamp products are some battery-operated UV-A torches (flashlights) or large, industrial insect light traps;
- Risk group 2 (RG-2) products generally do not pose a realistic optical hazard because of either discomfort glare from lens fluorescence or where lengthy exposures are unrealistic; examples include some UV-C germicidal fixtures;
- Risk group 3 (RG-3) products pose a potential hazard even for very brief exposures at close distance, and product safety requirements are generally essential; examples include sunlamp products (IEC 60335-2-27), Vitamin-D lamp products and unenclosed UV-C germicidal lamp products.

IEC 62471 does not provide guidance on manufacturing requirements and control measures. These issues are addressed in application-specific vertical standards such as this document. Labelling requirements and user information for each UV-lamp-product risk group are provided in this document (see 7.2 and 7.3).

### **4.2 Assessment criteria (background) for UV lamp products**

The standard measurement conditions consider the emission spectrum and, for ultraviolet radiation, the irradiance to determine risk to the eye and/or the skin. The measurement conditions are intended to optimize the signal of trace amounts of UV-B and UV-C radiation that are emitted from lamp products intended to emit largely in the UV-A spectral region. The risk-group assessment distance is related to potentially hazardous exposure conditions and time-weighted-average (TWA) effective assessment distances based upon reasonably foreseeable worst-case exposure durations. This is built into the emission limits. The concept of a hazard distance normally does not apply to photochemical hazards, since UV hazardous doses accumulate, and the daily exposure determines the potential hazard. For time-varying sources, the accumulated exposure (dose) determining the TWA exposure will be the same as a continuous (CW) exposure for the same total duration. Optical sources are rarely at a fixed distance from the eyes, nor does an individual stare at a UV source for 30 000 s (approximately 8 h) a day, or more. The UV (actinic) S(λ) corneal/skin limit (see Annex D) applies to chronic exposure, where daily skin exposure will be higher than ocular exposure in almost all

applications. The risk-group assessment distances, therefore, vary for each application and are listed in Table 2, Table 3 and Table 4 for various types of lamp products.

Assessment and measurement conditions necessarily differ for different special application lamp systems, such as insect light-traps, germicidal lamps, UV photocuring lamp products or UV-A fluorescence illuminators. Different application groups define a range of operational, maintenance and servicing conditions. Thus, the assessment applied to UV lamp products in this document justifies somewhat different measurement conditions than default measurement/assessment conditions in IEC 62471 for some products.

In general, the assessment of a single lamp/LED cannot be automatically transferred to the final lamp product. Under specific conditions, the assessment of a single lamp/LED is directly transferable to the lamp system. The risk group will remain the same, or may be reduced (e.g., by filters, etc.). However, as a general rule the UV luminaire will alter the spectrum or geometry of the irradiance field. The use of reflectors or appropriate focussing optics may increase the irradiance and increase the risk group, in which case the lamp assessment is not transferrable to the lamp system. Results may not be transferrable if multiple lamps are used in a lamp system.

The requirements in this application-specific (vertical) standard are for the risk group that can be used in some specific applications. Examples include unrestricted-use products which can be used in the home or uncontrolled environments. Performance features are based upon the risk group specifications and application-specific control measures. Basic guidance, based on the likelihood of direct source viewing, is provided in Clause 7. The hierarchy of applicable safety measures follow the internationally accepted priority ranking of manufacturer safety measures. That is, engineering controls (e.g., filters, shielding, interlocks, relevant proximity sensing, etc.) are the highest priority, followed by administrative measures (such as warnings and labels, see 7.3) and then personal protective equipment as the last resort.

An underlying assumption of this document is that it is not necessary to reduce optical radiation exposure to as low as reasonably achievable; however, as a general guideline, needless emissions that would produce unnecessary human exposure should be minimized.

## 5 Measurements to determine applicable risk group

### 5.1 General

This document addresses those lamps and lamp products for which more than half of the optical radiation (radiant power) emitted between 180 nm and 3 000 nm is in the spectral region 180 nm to 400 nm. Examples generally include low and medium pressure mercury lamps, UV LED lamps, excimer lamps and deuterium lamps.

For other lamp types, it is not intended that a spectral measurement be performed to verify this condition for emission. Prior knowledge of the spectral emission regions of the lamp or the spectral transmittance/ reflectance properties of optics used in the lamp product is sufficient to determine whether or not a product falls within the scope.

In case of doubt, a simple test to determine whether a particular lamp meets this criterion could be performed using a thermal detector and a long wavelength pass filter having a cut-on around 400 nm (UV blocking).

Measurements of irradiance in the UV are limited to a full cone angle of 80° (i.e.  $\pm 40^\circ$ ) field of view (FOV).

NOTE Due to the large reduction factor for skin, it is appropriate to apply the 80° FOV that applies for ocular risks (ICNIRP, 2004). Normally the 80° FOV will capture all of the significant radiation. However, if a detector with a wider FOV (e.g., a cosine-response detector) is used, the assessment will over-estimate the exposure.

- The specified output shall be determined for foreseeable variations in the environment (temperature, air pressure, humidity, outdoor-use, etc.).