



Designation: F3179/F3179M – 18

Standard Specification for Performance of Aircraft¹

This standard is issued under the fixed designation F3179/F3179M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers the airworthiness design standards associated with general aeroplane performance. The material was developed through open consensus of international experts in general aviation. This information was created by focusing on Normal Category aeroplanes. The content may be more broadly applicable; it is the responsibility of the Applicant to substantiate broader applicability as a specific means of compliance. The topics covered within this specification are: Stalling, Takeoff and Landing Speeds; Takeoff Performance, Distances and Path; Climb; Landing Performance and Distances; Balked Landing.

1.2 An applicant intending to propose this information as Means of Compliance for a design approval must seek guidance from their respective oversight authority (for example, published guidance from applicable CAAs) concerning the acceptable use and application thereof. For information on which oversight authorities have accepted this standard (in whole or in part) as an acceptable Means of Compliance to their regulatory requirements (hereinafter “the Rules”), refer to ASTM Committee F44 webpage (www.astm.org/COMMITTEE/F44.htm).

1.3 *Units*—This specification may present information in either SI units, English Engineering units, or both. The values stated in each system may not be exact equivalents. Each system shall be used independently of the other; combining values from the two systems may result in nonconformance with the standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recom-*

mendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

2. Referenced Documents

- 2.1 *ASTM Standards*:²
 - F3060 Terminology for Aircraft
 - F3083/F3083M Specification for Emergency Conditions, Occupant Safety and Accommodations
 - F3173/F3173M Specification for Aircraft Handling Characteristics
 - F3174/F3174M Specification for Establishing Operating Limitations and Information for Aeroplanes

3. Terminology

3.1 Refer to Terminology F3060.

3.2 In addition, the following definitions apply only in the context of this standard:

3.2.1 *Loss of Thrust*—For conventional aeroplanes (reciprocating or turbine engine-powered), loss of thrust means one engine inoperative. For other aeroplanes, the amount of thrust loss shall be proposed by the applicant and accepted by the CAA.

4. General

4.1 Unless otherwise prescribed, the performance requirements of this specification shall be met for:

- 4.1.1 Still air and standard atmosphere;
- 4.1.2 Ambient atmospheric conditions within the operating envelope for Level 1 and 2 high-speed aeroplanes and all Level 3 and 4 aeroplanes.

4.2 Performance data shall be determined over not less than the following conditions for all aeroplanes, except for aeroplanes with $V_{S0} \leq 45$ KCAS:

- 4.2.1 Airport altitude from sea level to 3084 m [10 000 ft];
- 4.2.2 The temperature from standard to 30°C [54°F] above standard or the maximum ambient atmospheric temperature at which compliance with the cooling provisions of is shown, if lower;

¹ This specification is under the jurisdiction of ASTM Committee F44 on General Aviation Aircraft and is the direct responsibility of Subcommittee F44.20 on Flight.

Current edition approved May 1, 2018. Published May 2018. Originally approved in 2016. Last previous edition approved in 2016 as F3179/F3179M – 16. DOI: 10.1520/F3179_F3179M-18.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

4.3 Performance data shall be determined with any means for controlling the engine cooling air supply in the position used in the engine cooling tests;

4.4 The available propulsive thrust shall correspond to engine power, not exceeding the approved power, less:

4.4.1 Installation losses.

4.4.2 The power absorbed by the accessories and services appropriate to the particular ambient atmospheric conditions and the particular flight condition.

4.5 The performance, as affected by engine power or thrust, shall be based on a relative humidity:

4.5.1 Of 80 % at and below standard temperature.

4.5.2 From 80 % at the standard temperature, varying linearly down to 34 % at the standard temperature plus 28°C [plus 50°F].

4.6 Unless otherwise prescribed in determining the takeoff and landing distances, changes in the aeroplane's configuration, speed, and power shall be made in accordance with procedures established by the applicant for operation in service. These procedures shall be able to be executed consistently by pilots of average skill in atmospheric conditions reasonably expected to be encountered in service.

4.7 Takeoff and landing distances shall be determined on a smooth, dry, hard-surfaced runway.

4.7.1 The effect on these distances of operation on other types of surfaces (for example, grass and gravel) when dry, may be determined or derived, and these surfaces listed in the aeroplane flight manual in accordance with Specification **F3174/F3174M**.

4.8 For Level 3 and Level 4 high-speed multiengine aeroplanes, the following also apply:

4.8.1 Unless otherwise prescribed, the applicant shall select the takeoff, en route, approach, and landing configurations for the aeroplane;

4.8.2 The aeroplane configuration may vary with weight, altitude, and temperature to the extent they are compatible with the operating procedures required by **4.8.3**;

4.8.3 Unless otherwise prescribed, in determining the take-off performance, takeoff flight path, and the accelerate-stop distance, all with a critical loss of thrust, changes in the aeroplane's configuration, speed, and power shall be made in accordance with procedures established by the applicant for operation in service;

4.8.4 Procedures for the execution of discontinued approaches and balked landings associated with the conditions prescribed in **15.3.4** and **20.3** shall be established;

4.8.5 The procedures established under **4.8.3** and **4.8.4** shall:

4.8.5.1 Be able to be consistently executed by a crew of average skill in atmospheric conditions reasonably expected to be encountered in service,

4.8.5.2 Use methods or devices that are safe and reliable;

4.8.5.3 Include allowance for any reasonably expected time delays in the execution of the procedures.

5. Stalling Speed

5.1 V_{S0} and V_{S1} are the stalling speeds or the minimum steady flight speeds in knots (KCAS) at which the aeroplane is controllable with:

5.1.1 The propulsive thrust not greater than zero at the stalling speed, or, if the resultant thrust has no appreciable effect on the stalling speed, with engine(s) at minimum flight thrust and throttle(s) closed with:

5.1.1.1 The propeller(s) in the takeoff position;

5.1.1.2 The aeroplane in the configuration existing in the test, in which V_{S0} and V_{S1} are being used;

5.1.1.3 The center of gravity in the position that results in the highest value of V_{S0} and V_{S1} ;

5.1.1.4 The weight used when V_{S0} or V_{S1} are being used as a factor to determine compliance with a required performance standard.

5.2 V_{S0} and V_{S1} shall be determined by flight tests using the procedure and meeting the flight characteristics specified in the appropriate stall handling characteristics testing.

6. Takeoff Speeds

6.1 For single-engine aeroplanes and Levels 1, 2, and 3 low-speed multiengine aeroplanes, the rotation speed, V_R , is the speed at which the pilot makes a control input with the intention of lifting the aeroplane out of contact with the runway or water surface.

6.1.1 For Levels 1, 2, and 3 low-speed multiengine landplanes, V_R shall not be less than the greater of $1.05 V_{MC}$ or $1.10 V_{S1}$.

6.1.2 For single-engine landplanes, V_R shall not be less than V_{S1} .

6.1.3 For seaplanes and amphibians taking off from water, V_R shall be any speed that is shown to be safe under all reasonably expected conditions, including turbulence and a critical loss of thrust.

6.2 For single-engine aeroplanes and Levels 1, 2, and 3 low-speed multiengine aeroplanes, the speed at 15 m [50 ft] above the takeoff surface level shall not be less than:

6.2.1 For Level 1 low-speed aeroplanes with $V_{S0} \leq 45$ knots, not less than $1.3 V_{S1}$;

6.2.2 For Levels 1, 2, and 3 low-speed multiengine aeroplanes, the highest of:

6.2.2.1 A speed that is shown to be safe for continued flight (or emergency landing, if applicable) under all reasonable expected conditions, including turbulence and a critical loss of thrust;

6.2.2.2 $1.10 V_{MC}$; or

6.2.2.3 $1.20 V_{S1}$.

6.2.3 For Level 1 aeroplanes with a $V_{S0} > 45$ knots and all Levels 2, 3, and 4 single-engine aeroplanes, the higher of:

6.2.3.1 A speed that is shown to be safe under all reasonably expected conditions, including turbulence and a critical loss of thrust, or

6.2.3.2 $1.20 V_{S1}$.

6.3 For Levels 1, 2, and 3 high-speed multiengine aeroplanes, and all Level 4 multiengine aeroplanes, the following apply:

6.3.1 The value, V_1 , shall be established in relation to V_{EF} as follows:

6.3.1.1 The value, V_{EF} , is the calibrated airspeed at which the critical loss of thrust is assumed to occur. The value, V_{EF} , shall be selected by the applicant but shall not be less than $1.05 V_{MC}$ determined under Specification **F3173/F3173M** or, at the option of the applicant, not less than V_{MCG} determined under Specification **F3173/F3173M**.

6.3.1.2 The takeoff decision speed, V_1 , is the calibrated airspeed on the ground at which, as a result of engine failure or other reasons, the pilot is assumed to have made a decision to continue or discontinue the takeoff. The takeoff decision speed, V_1 , shall be selected by the applicant but shall not be less than V_{EF} plus the speed gained with the critical loss of thrust during the time interval between the instant at which the critical loss occurs and the instant at which the pilot recognizes and reacts to the thrust loss, as indicated by the pilot's application of the first retarding means during the accelerate-stop determination of Section 8.

6.3.2 The rotation speed, V_R , in terms of calibrated airspeed, shall be selected by the applicant and shall not be less than the greatest of the following:

6.3.2.1 V_1 ;

6.3.2.2 $1.05 V_{MC}$ determined under Specification **F3173/F3173M**;

6.3.2.3 $1.10 V_{S1}$; or

6.3.2.4 The speed that allows attaining the initial climb-out speed, V_2 , before reaching a height of 11 m [35 ft] above the takeoff surface in accordance with **9.1.3.2**.

6.3.3 For any given set of conditions, such as weight, altitude, temperature, and configuration, a single value of V_R shall be used to show compliance with both the takeoff after a critical loss of thrust and all-engines-operating takeoff requirements.

6.3.4 The takeoff safety speed, V_2 , in terms of calibrated airspeed, shall be selected by the applicant so as to allow the gradient of climb required in Section 15 but shall not be less than $1.10 V_{MC}$ or less than $1.20 V_{S1}$.

6.3.5 The takeoff distance after a critical loss of thrust, using a normal rotation rate at a speed 5 knots less than V_R , established in accordance with **6.3.2**, shall be shown not to exceed the corresponding takeoff distance after a critical loss of thrust, determined in accordance with Sections 9 and 10, using the established V_R . The takeoff, otherwise performed in accordance with Section 9, shall be continued safely from the point at which the aeroplane is 11 m [35 ft] above the takeoff surface and at a speed not less than the established V_2 minus 5 knots.

6.3.6 The applicant shall show, with all engines operating, that marked increases in the scheduled takeoff distances, determined in accordance with **10.1**, do not result from over-rotation of the aeroplane or out-of-trim conditions.

7. Takeoff Performance

7.1 For Level 1 low-speed single engine aeroplanes with $V_{S0} \leq 45$ knots, the distance required to takeoff from a dry, level, hard surface and climb over a 15 m [50 ft] obstacle shall not exceed 500 m [1640 ft] in still air and a standard

atmosphere using speeds determined in accordance with **6.1** and **6.2** at sea level with:

7.1.1 The engine(s) operating within approved operating limitations;

7.1.2 The cowl flaps in the normal takeoff position.

7.2 For all other single engine aeroplanes and Levels 1, 2, and 3 low-speed multiengine aeroplanes, the distance that is required to takeoff and climb to a height of 15 m [50 ft] above the takeoff surface shall be determined for each weight, altitude, and temperature within the operational limits established for takeoff using speeds determined in accordance with **6.1** and **6.2** with:

7.2.1 Takeoff power on each engine;

7.2.2 Wing flaps in the takeoff position(s);

7.2.3 Landing gear extended.

7.3 For Levels 1, 2, and 3 high-speed multiengine aeroplanes and all Level 4 multiengine aeroplanes, takeoff performance, as required by **8.1** through **10.1**, shall be determined with the operating engine(s) within approved operating limitations.

8. Accelerate-Stop Distance

8.1 For Levels 1, 2, and 3 high-speed multiengine aeroplanes and all Level 4 multiengine aeroplanes, the accelerate-stop distance shall be determined as follows:

8.1.1 The accelerate-stop distance is the sum of the distances necessary to:

8.1.1.1 Accelerate the aeroplane from a standing start to V_{EF} with all engines operating;

8.1.1.2 Accelerate the aeroplane from V_{EF} to V_1 , assuming a critical loss of thrust at V_{EF} ;

8.1.1.3 Come to a full stop from the point at which V_1 is reached.

8.1.2 Means other than wheel brakes may be used to determine the accelerate-stop distances if that means it is:

8.1.2.1 Safe and reliable,

8.1.2.2 Used so that consistent results can be expected under normal operating conditions,

8.1.2.3 Such that exceptional skill is not required to control the aeroplane.

9. Takeoff Path

9.1 For Levels 1, 2, and 3 high-speed multiengine aeroplanes and all Level 4 multiengine aeroplanes, the takeoff path is as follows:

9.1.1 The takeoff path extends from a standing start to a point in the takeoff at which the aeroplane is 457 m [1500 ft] above the takeoff surface at or below which height the transition from the takeoff to the en-route configuration shall be completed.

9.1.1.1 The takeoff path shall be based on the procedures prescribed in Section 4;

9.1.1.2 The aeroplane shall be accelerated on the ground to V_{EF} at which point the critical loss of thrust occurs and remains lost for the rest of the takeoff;

9.1.1.3 After reaching V_{EF} , the aeroplane shall be accelerated to V_2 .