

## TECHNICAL REPORT

Information technology – Generic cabling for customer premises –  
Part 9905: Guidelines for the use of installed cabling to support 25GBASE-T  
application  
(standards.iteh.ai)

[ISO/IEC TR 11801-9905:2018](https://standards.iteh.ai/catalog/standards/sist/e7d2c979-b898-4caa-8bfb-31a2273639fb/iso-iec-tr-11801-9905-2018)

<https://standards.iteh.ai/catalog/standards/sist/e7d2c979-b898-4caa-8bfb-31a2273639fb/iso-iec-tr-11801-9905-2018>



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2018 ISO/IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

**IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)**

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

**IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)**

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch)

ISO/IEC TR 11801-9905-2018  
<https://standards.iteh.ai/catalog/standards/sist/7a2e59-6898-4caa-8bf6-31a2273639fb/iso-iec-tr-11801-9905-2018>



# TECHNICAL REPORT

---

Information technology – Generic cabling for customer premises –  
Part 9905: Guidelines for the use of installed cabling to support 25GBASE-T  
application

[ISO/IEC TR 11801-9905:2018  
https://standards.iteh.ai/catalog/standards/sist/e7d2c979-b898-4caa-8bf6-31a2273639fb/iso-iec-tr-11801-9905-2018](https://standards.iteh.ai/catalog/standards/sist/e7d2c979-b898-4caa-8bf6-31a2273639fb/iso-iec-tr-11801-9905-2018)

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references .....	8
3 Terms, definitions and abbreviations .....	8
4 Cabling channel specifications for 25 GBASE-T.....	9
4.1 General.....	9
4.2 25GBASE-T application specifications .....	9
4.2.1 Return loss .....	9
4.2.2 Insertion loss/attenuation.....	10
4.2.3 NEXT.....	11
4.2.4 Attenuation to crosstalk ratio at the near-end (ACR-N) .....	13
4.2.5 Attenuation to crosstalk ratio at the far-end (ACR-F).....	13
4.2.6 Propagation delay.....	15
4.2.7 Delay skew .....	15
4.2.8 Unbalance attenuation and coupling attenuation .....	15
4.2.9 Alien crosstalk .....	16
4.3 Associated risk of 25GBASE-T operation over installed cabling .....	17
4.4 Characterization of balanced channels using Category 7 <sub>A</sub> components .....	17
4.4.1 General .....	17
4.4.2 Selection of channels for qualification.....	18
4.4.3 Return loss .....	18
4.4.4 Insertion loss.....	19
4.4.5 Near-end crosstalk loss (NEXT).....	19
4.4.6 Attenuation to crosstalk loss ratio near-end (ACR-N).....	21
4.4.7 Attenuation to crosstalk ratio far-end (ACR-F) .....	22
4.4.8 Alien (exogenous) crosstalk .....	24
4.4.9 Propagation delay.....	25
4.4.10 Delay skew .....	25
4.4.11 Coupling attenuation.....	25
4.4.12 Alien crosstalk and coupling attenuation .....	26
4.5 Characterization of balanced channels using Category 7 components.....	26
4.5.1 General .....	26
4.5.2 Selection of channels for qualification.....	27
4.5.3 Return loss .....	27
4.5.4 Insertion loss.....	28
4.5.5 Near-end crosstalk loss (NEXT).....	28
4.5.6 Attenuation to crosstalk loss ratio near-end (ACR-N) .....	30
4.5.7 Attenuation to crosstalk ratio far-end (ACR-F) .....	31
4.5.8 Alien (exogenous) crosstalk .....	33
4.5.9 Propagation delay.....	34
4.5.10 Delay skew .....	34
4.5.11 Coupling attenuation.....	34
4.5.12 Alien crosstalk and coupling attenuation .....	35
4.6 Characterization of balanced channels using Category 6 <sub>A</sub> components .....	35
4.6.1 General .....	35
4.6.2 Selection of channels for qualification.....	36

4.6.3	Test specifications for channels made out of Category 6 <sub>A</sub> components .....	36
5	Guidance for mitigation procedures to improve the cabling of existing installations .....	36
5.1	General.....	36
5.2	Mitigation procedures related to internal noise .....	36
5.3	Mitigation procedures related to exogenous noise (alien crosstalk) .....	36
6	Guidance for cabling for new installations.....	37
	Bibliography.....	38
	Table 1 – Return loss for a channel .....	9
	Table 2 –Return loss values for a channel at key frequencies .....	10
	Table 3 – Insertion loss for a channel .....	10
	Table 4 – Insertion loss values for a channel at key frequencies .....	11
	Table 5 – NEXT for a channel.....	11
	Table 6 – NEXT values for a channel at key frequencies.....	12
	Table 7 – PS NEXT for a channel .....	12
	Table 8 – PS NEXT values for a channel at key frequencies .....	13
	Table 9 – ACR-F for a channel.....	13
	Table 10 – ACR-F values for a channel at key frequencies .....	14
	Table 11 – PS ACR -F for a channel.....	14
	Table 12 – PS ACR-F values for a channel at key frequencies.....	14
	Table 13 – Propagation delay for a channel .....	15
	Table 14 – Propagation delay values for a channel at key frequencies.....	15
	Table 15 – Delay skew for a channel.....	15
	Table 16 – PS ANEXT for a channel .....	16
	Table 17 – PS ANEXT values for a channel at key frequencies .....	16
	Table 18 – PS AACR-F for a channel.....	17
	Table 19 – PS AACR-F values for a channel at key frequencies .....	17
	Table 20 – Risk of 25GBASE-T operation over installed cabling channels.....	17
	Table 21 – Formulae for return loss limits for a channel.....	18
	Table 22 – Return loss limits for a channel at key frequencies .....	18
	Table 23 – Formula for insertion loss limits for a channel.....	19
	Table 24 – Insertion loss limits for a channel at key frequencies .....	19
	Table 25 – Formulae for pair-to-pair NEXT limits for a channel .....	19
	Table 26 – Pair-to-pair NEXT limits for a channel at key frequencies .....	20
	Table 27 – Formulae for PS NEXT limits for a channel.....	20
	Table 28 –PS NEXT limits for a channel at key frequencies .....	20
	Table 29 – ACR-N limits for a channel at key frequencies .....	21
	Table 30 – PS ACR-N limits for a channel at key frequencies .....	22
	Table 31 – Formulae for ACR-F limits for a channel.....	22
	Table 32 – ACR-F limits for a channel at key frequencies .....	23
	Table 33 – Formulae for PS ACR-F limits for a channel .....	23
	Table 34 – PS ACR-F limits for a channel at key frequencies.....	23
	Table 35 – Formulae for PS ANEXT limits for a channel .....	24
	Table 36 – PS ANEXT limits for a channel at key frequencies .....	24

Table 37 – Formula for PS AACR-F limits for a channel ..... 24

Table 38 – PS AACR-F limits for a channel at key frequencies ..... 25

Table 39 – Formula for propagation delay limits for a channel..... 25

Table 40 – Propagation delay limits for a channel at key frequencies..... 25

Table 41 – Formula for coupling attenuation limits for a channel ..... 26

Table 42 – Coupling attenuation limits for a channel at key frequencies..... 26

Table 43 – Alien crosstalk and coupling attenuation..... 26

Table 44 – Formulae for return loss limits for a channel ..... 27

Table 45 – Return loss limits for a channel at key frequencies ..... 27

Table 46 – Formula for insertion loss limits for a channel..... 28

Table 47 – Insertion loss limits for a channel at key frequencies ..... 28

Table 48 – Formulae for pair-to-pair NEXT limits for a channel ..... 28

Table 49 – Pair-to-pair NEXT limits for a channel at key frequencies ..... 29

Table 50 – Formulae for PS NEXT limits for a channel..... 29

Table 51 – PS NEXT limits for a channel at key frequencies ..... 29

Table 52 – ACR-N limits for a channel at key frequencies ..... 30

Table 53- PS ACR-N limits for a channel at key frequencies ..... 31

Table 54 – Formulae for ACR-F limits for a channel..... 31

Table 55 – ACR-F limits for a channel at key frequencies ..... 32

Table 56 – Formulae for PS ACR-F limits for a channel..... 32

Table 57 – PS ACR-F limits for a channel at key frequencies ..... 32

Table 58 – Formulae for PS ANEXT limits for a channel ..... 33

Table 59 – PS ANEXT limits for a channel at key frequencies ..... 33

Table 60 – Formula for PS AACR-F limits for a channel ..... 33

Table 61 – PS AACR-F limits for a channel at key frequencies ..... 34

Table 62 – Formula for propagation delay limits for a channel..... 34

Table 63 – Propagation delay limits for a channel at key frequencies..... 34

Table 64 – Formula for coupling attenuation limits for a channel ..... 35

Table 65 – Coupling attenuation limits for a channel at key frequencies..... 35

Table 66 – Alien crosstalk and coupling attenuation for shielded channels ..... 35

iteh STANDARD PREVIEW  
(standards.iteh.ai)  
ISO/IEC TR 11801-9905:2018  
<https://standards.iteh.ai/catalog/standards/sist/e7d2c979-6898-4caa-8b16-71a275391916/iso-iec-11801-9905-2018>

## INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES –

### Part 9905: Guidelines for the use of installed cabling to support 25GBASE-T application

#### FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

The main task of the joint technical committee is to prepare International Standards. However, the joint technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

ISO/IEC TR 11801-9905, which is a Technical Report, was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 11801 series, under the general title *Information technology — Generic cabling for customer premises*, can be found on the IEC website.

This Technical Report has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This Technical Report is to be read in conjunction with ISO/IEC/IEEE 8802.3:2017/AMD3.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

## **iTeh STANDARD PREVIEW (standards.iteh.ai)**

ISO/IEC TR 11801-9905:2018

<https://standards.iteh.ai/catalog/standards/sist/e7d2c979-b898-4caa-8bf6-31a2273639fb/iso-iec-tr-11801-9905-2018>



## INTRODUCTION

This document provides guidance to determine whether and which installed channels will support 25GBASE-T. It takes into account the design goals for 25GBASE-T equipment such as:

- a) the frequency signal range up to 1 250 MHz;
- b) the support of two-connector channels up to 30 m in length.

The requirements of 25GBASE-T are fully defined in ISO/IEC/IEEE 8802-3:2017/AMD3.

Installed two-connector channels which are characterized up to 1 250 MHz and support all the requirements of the ISO/IEC/IEEE 8802-3:2017/AMD3 link segment are expected to support the 25GBASE-T application.

Characterization of channels using Category 7<sub>A</sub> components is described in 4.4.

Characterization of channels using Category 7 components is described in 4.5.

Characterization of channels using Category 6<sub>A</sub> components is described in 4.6.

This document also provides mitigation procedures to improve the performance of installed channels to the point where the 25GBASE-T application is supported. Additionally, this document recommends the use of Class I and Class II channels to support 25GBASE-T in new installations.

Class I and Class II channels according to ISO/IEC 11801-1 will support 25GBASE-T without mitigation.

Component requirements are not provided in this document and should not be inferred from the channel limits provided.

# INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES –

## Part 9905: Guidelines for the use of installed cabling to support 25GBASE-T application

### 1 Scope

This part of ISO/IEC 11801, which is a Technical Report,

- a) provides guidance on how to select and assess installed channels which conform to ISO/IEC 11801-1, and clarify if they also support ISO/IEC/IEEE 8802-3:2017/AMD3 for 25GBASE-T;
- b) specifies the methods to assess whether installed channels constructed with Category 7<sub>A</sub>, 7, or 6<sub>A</sub> components meet the 25GBASE-T requirements;
- c) provides guidance to identify which channels are likely to meet the 25GBASE-T requirements to avoid unnecessary testing;
- d) provides mitigation techniques to improve the performance of installed channels to meet the 25GBASE-T requirements;
- e) provides cabling recommendations for new installations.

NOTE 1 The channel transmission performance specified in this document is derived from the 25GBASE-T requirements in ISO/IEC/IEEE 8802-3:2017/AMD3.

NOTE 2 This document does not re-specify component or channel definitions of ISO/IEC 11801-1.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 11801-1, *Information technology – Generic cabling systems – Part 1: General requirements*

ISO/IEC/IEEE 8802-3:2017/AMD3, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Standard for Ethernet – Amendment 3: Physical layers and management parameters for 25 Gb/s and 40 Gb/s operation, types 25GBASE-T and 40GBASE-T*

### 3 Terms, definitions and abbreviations

For the purposes of this document, the terms, definitions and abbreviations given in ISO/IEC 11801-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

## 4 Cabling channel specifications for 25 GBASE-T

### 4.1 General

This document provides guidelines for the assessment of installed cabling channels for the additional requirements of ISO/IEC/IEEE 8802-3:2017/AMD3 for 25GBASE-T. It is assumed that each installed channel does fulfil the requirements of its appropriate cabling class defined in ISO/IEC 11801-1.

The requirements defined in Clause 4 are a combination of the original class requirements of the installed cabling and the requirements in support of 25GBASE-T.

For a balanced cabling installation covered by this document:

- the channel performance is specified according to ISO/IEC 11801-1 and additionally according to Clause 4 (or appropriate subclause);
- the interfaces to the cabling are specified according to ISO/IEC 11801-1:2017, Clause 10, with respect to mating interfaces;
- local regulations concerning safety and EMC apply.

The test procedures for balanced cabling installations are specified in IEC 61935-1 in accordance with ISO/IEC 11801-1 and ISO/IEC 14763-2.

### 4.2 25GBASE-T application specifications

NOTE 1 These specifications are consistent with the link segment specifications of ISO/IEC/IEEE 8802-3:2017/AMD3.

NOTE 2 All specifications are based on a channel length of 30 m with 2 connections.

#### 4.2.1 Return loss

The return loss (RL) of each pair of a channel is specified in Table 1. The limits shown in Table 2 are derived from the formulae at key frequencies.

The return loss requirement is specified for both ends of the cabling. Return loss (RL) values at frequencies where the insertion loss (IL) is below 3,0 dB are for information only.

**Table 1 – Return loss for a channel**

Class	Frequency MHz	Minimum return loss dB
I	$1 \leq f < 10$	19,0
	$10 \leq f < 40$	$24 - 5\lg(f)$
	$40 \leq f < 130$	16,0
	$130 \leq f < 1\,000$	$35 - 9\lg(f)$
	$1\,000 \leq f \leq 1\,250$	8,0

**Table 2 –Return loss values for a channel at key frequencies**

Frequency MHz	Minimum return loss dB
	Class
	I
1	19,0
16	18,0
100	16,0
250	13,4
500	10,7
600	10,0
1 000	8,0
1 250	8,0

**4.2.2 Insertion loss/attenuation**

The insertion loss (IL) of each pair of a channel is specified in Table 3. The limits shown in Table 4 are derived from the formulae at key frequencies.

**STANDARD PREVIEW**  
**Table 3 – Insertion loss for a channel**  
**(standards.iteh.ai)**

Class	Frequency MHz	Maximum insertion loss <sup>a</sup> dB
I	1 < f ≤ 500	$\left(0,634\sqrt{f} + 0,00156 \times f + \frac{0,078}{\sqrt{f}}\right)^b$
	500 < f ≤ 1250	$\left(0,60698\sqrt{f} + 0,00277 \times f + \frac{0,078}{\sqrt{f}}\right)^c$
<sup>a</sup> Insertion loss (IL) at frequencies that correspond to calculated values of less than 4,0 dB revert to a maximum requirement of 4,0 dB. <sup>b</sup> This formula is derived using: $0,312 \times \left(1,8\sqrt{f} + 0,005 \times f + \frac{0,25}{\sqrt{f}}\right) + 2 \times (0,02 \times \sqrt{f}) + 0,0324 \times \sqrt{f}$ <sup>c</sup> This formula is derived using: $0,312 \times \left(1,8\sqrt{f} + 0,005 \times f + \frac{0,25}{\sqrt{f}}\right) + 2 \times (0,00649 \times \sqrt{f} + 0,000605 \times f) + 0,0324 \times \sqrt{f}$		

**Table 4 – Insertion loss values for a channel at key frequencies**

Frequency MHz	Maximum insertion loss dB
	Class
	I
1	4,0
16	4,0
100	6,5
250	10,4
500	15,0
600	16,5
1 000	22,0
1 250	24,9

#### 4.2.3 NEXT

##### 4.2.3.1 Pair-to-pair NEXT

The NEXT between each pair combination of a channel is specified in Table 5. The limits shown in Table 6 are derived from the formulae at key frequencies.

(standards.iteh.ai)

The NEXT requirement is specified for both ends of the cabling. NEXT values at frequencies where the insertion loss (IL) is below 4.0 dB are for information only.

<https://standards.iteh.ai/catalog/standards/sist/e7d2c979-b898-4caa-8bf6-31a22756591b/iso-iec-tr-11801-9905-2018>  
**Table 5 – NEXT for a channel**

Class	Frequency MHz	Minimum NEXT <sup>a</sup> dB
I	$1 \leq f \leq 500$	$-20 \lg \left( 10^{\frac{75,3 - 15 \lg(f)}{-20}} + 2 \times 10^{\frac{94 - 20 \lg(f)}{-20}} \right)$
	$500 < f \leq 1250$	$-20 \lg \left( 10^{\frac{75,3 - 15 \lg(f)}{-20}} + 2 \times 10^{\frac{40 - 38 \lg(f/500)}{-20}} \right)$

<sup>a</sup> NEXT at frequencies that correspond to calculated values of greater than 65,0 dB revert to a minimum requirement of 65,0 dB.