

INTERNATIONAL STANDARD



**Industrial communication networks – Profiles –
Part 2: Additional fieldbus profiles for real-time networks based on
ISO/IEC/IEEE 8802-3**

Withhold

IEC 61784-2:2019

<https://standards.iteh.ai/standards/iec/61784-2-2019>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC 61784-2:2019

<https://standards.iteh.ai/en/standards/iec/61784-2-2019>

INTERNATIONAL STANDARD



**Industrial communication networks – Profiles –
Part 2: Additional fieldbus profiles for real-time networks based on
ISO/IEC/IEEE 8802-3**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.100.20; 35.240.50

ISBN 978-2-8322-6725-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	17
INTRODUCTION.....	19
1 Scope.....	20
2 Normative references	20
3 Terms, definitions, abbreviated terms, acronyms, and conventions.....	26
3.1 Terms and definitions.....	26
3.2 Abbreviated terms and acronyms	30
3.3 Symbols.....	31
3.3.1 CPF 2 symbols	32
3.3.2 CPF 3 symbols	33
3.3.3 CPF 4 symbols	34
3.3.4 CPF 6 symbols	34
3.3.5 CPF 10 symbols	35
3.3.6 CPF 11 symbols	36
3.3.7 CPF 12 symbols	37
3.3.8 CPF 13 symbols	37
3.3.9 CPF 14 symbols	38
3.3.10 CPF 15 symbols	39
3.3.11 CPF 16 symbols	39
3.3.12 CPF 17 symbols	40
3.3.13 CPF 18 symbols	41
3.3.14 CPF 20 symbols	42
3.3.15 CPF 21 symbols	43
3.4 Conventions.....	43
3.4.1 Conventions common to all layers	43
3.4.2 Physical layer.....	45
3.4.3 Data-link layer.....	45
3.4.4 Application layer.....	46
4 Conformance to communication profiles	46
5 RTE performance indicators	47
5.1 Basic principles of performance indicators	47
5.2 Application requirements.....	48
5.3 Performance indicators	48
5.3.1 Delivery time	48
5.3.2 Number of RTE end-stations.....	49
5.3.3 Basic network topology.....	49
5.3.4 Number of switches between RTE end-stations	49
5.3.5 Throughput RTE	49
5.3.6 Non-RTE bandwidth.....	49
5.3.7 Time synchronization accuracy.....	50
5.3.8 Non-time-based synchronization accuracy.....	50
5.3.9 Redundancy recovery time	50
6 Conformance tests	50
6.1 Concept.....	50
6.2 Methodology	51
6.3 Test conditions and test cases	51

6.4	Test procedure and measuring.....	51
6.5	Test report.....	52
7	Communication Profile Family 2 (CIP™) – RTE communication profiles.....	52
7.1	General overview.....	52
7.2	Profile 2/2.....	53
7.2.1	Physical layer.....	53
7.2.2	Data-link layer.....	53
7.2.3	Application layer.....	53
7.2.4	Performance indicator selection.....	53
7.3	Profile 2/2.1.....	57
7.3.1	Physical layer.....	57
7.3.2	Data-link layer.....	57
7.3.3	Application layer.....	59
7.3.4	Performance indicator selection.....	61
8	Communication Profile Family 3 (PROFIBUS & PROFINET) – RTE communication profiles.....	63
8.1	General overview.....	63
8.1.1	CPF 3 overview.....	63
8.1.2	Administrative numbers.....	63
8.1.3	Node Classes.....	64
8.1.4	Protocol and timing parameters.....	66
8.1.5	Communication classes.....	76
8.1.6	Media redundancy classes.....	79
8.1.7	Media classes.....	80
8.1.8	Application classes.....	81
8.1.9	Records.....	86
8.1.10	Communication feature list.....	94
8.1.11	Conformance class behaviors.....	94
8.2	Profile 3/4.....	101
8.2.1	Physical layer.....	101
8.2.2	Data link layer.....	101
8.2.3	Application layer.....	102
8.2.4	Performance indicator selection.....	110
8.3	Profile 3/5.....	117
8.3.1	Physical layer.....	117
8.3.2	Data link layer.....	117
8.3.3	Application layer.....	118
8.3.4	Performance indicator selection.....	125
8.4	Profile 3/6.....	126
8.4.1	Physical layer.....	126
8.4.2	Data link layer.....	126
8.4.3	Application layer.....	127
8.4.4	Performance indicator selection.....	133
9	Communication Profile Family 4 (P-NET) – RTE communication profiles.....	137
9.1	General overview.....	137
9.2	Profile 4/3, P-NET on IP.....	138
9.2.1	Physical layer.....	138
9.2.2	Data-link layer.....	138
9.2.3	Application layer.....	139

9.2.4	Performance indicator selection	139
10	Communication Profile Family 6 (INTERBUS®) – RTE communication profiles	143
10.1	General overview	143
10.2	Profile 6/4	145
10.2.1	Mapping	145
10.2.2	Type 10 service and protocol selection	146
10.2.3	Type 8 service and protocol selection	146
10.3	Profile 6/5	147
10.3.1	Mapping	147
10.3.2	Type 10 service and protocol selection	148
10.3.3	Type 8 service and protocol selection	148
10.3.4	Performance indicator selection	148
10.4	Profile 6/6	149
10.4.1	Mapping	149
10.4.2	Type 10 service and protocol selection	149
10.4.3	Type 8 service and protocol selection	149
10.4.4	Performance indicator selection	149
11	Communication Profile Family 10 (Vnet/IP) – RTE communication profiles	150
11.1	General overview	150
11.2	Profile 10/1	151
11.2.1	Physical layer	151
11.2.2	Data link layer	151
11.2.3	Application layer	154
11.2.4	Performance indicator selection	155
12	Communication Profile Family 11 (TCnet) – RTE communication profiles	160
12.1	General overview	160
12.2	Profile 11/1	160
12.2.1	Physical layer	160
12.2.2	Data-link layer	160
12.2.3	Application layer	164
12.2.4	Performance indicator selection	165
12.3	Profile 11/2	171
12.3.1	Physical layer	171
12.3.2	Data-link layer	172
12.3.3	Application layer	176
12.3.4	Performance indicator selection	176
12.4	Profile 11/3	181
12.4.1	Physical layer	181
12.4.2	Data-link layer	181
12.4.3	Application layer	185
12.4.4	Performance indicator selection	185
13	Communication Profile Family 12 (EtherCAT®) – RTE communication profiles	192
13.1	General overview	192
13.2	Profile CP 12/1	192
13.2.1	Physical layer	192
13.2.2	Data-link layer	194
13.2.3	Application layer	198
13.2.4	Performance indicator selection	200

13.3	Profile CP 12/2	203
13.3.1	Physical layer	203
13.3.2	Data-link layer	203
13.3.3	Application layer	207
13.3.4	Performance indicator selection	209
14	Communication Profile Family 13 (Ethernet POWERLINK) – RTE communication profiles	211
14.1	General overview	211
14.2	Profile 13/1	212
14.2.1	Physical layer	212
14.2.2	Data-link layer	212
14.2.3	Application layer	212
14.2.4	Performance indicator selection	213
15	Communication Profile Family 14 (EPA)- RTE communication profiles	218
15.1	General overview	218
15.2	CPF 14 (EPA) communication concept	219
15.2.1	General	219
15.2.2	Network Topology	219
15.2.3	EPA devices	220
15.3	Profile 14/1	220
15.3.1	Physical layer	220
15.3.2	Data-link layer	221
15.3.3	Network Layer	221
15.3.4	Transport Layer	221
15.3.5	Application layer	221
15.3.6	Performance indicator selection	222
15.4	Profile 14/2	225
15.4.1	Physical layer	225
15.4.2	Data-link layer	225
15.4.3	Network Layer	226
15.4.4	Transport Layer	226
15.4.5	Application layer	227
15.4.6	Performance indicator selection	228
15.5	Profile 14/3	230
15.5.1	Physical layer	230
15.5.2	Data-link layer	230
15.5.3	Network Layer	231
15.5.4	Transport Layer	231
15.5.5	Application layer	232
15.5.6	Performance indicator selection	233
15.6	Profile 14/4	236
15.6.1	Physical layer	236
15.6.2	Data-link layer	236
15.6.3	Network layer	237
15.6.4	Transport layer	238
15.6.5	Application layer	238
15.6.6	Performance indicator selection	239
16	Communication Profile Family 15 (MODBUS-RTPS) – RTE communication profiles	241
16.1	General overview	241

16.2	Profile 15/1	242
16.2.1	Physical layer	242
16.2.2	Data-link layer	242
16.2.3	Application layer	242
16.2.4	Performance indicator selection	242
16.3	Profile 15/2	247
16.3.1	Physical layer	247
16.3.2	Data-link layer	247
16.3.3	Application layer	247
16.3.4	Performance indicator selection	248
17	Communication Profile Family 16 (SERCOS)- RTE communication profiles	252
17.1	General overview	252
17.2	Profile 16/3 (SERCOS III)	253
17.2.1	Physical layer	253
17.2.2	Data-link layer	253
17.2.3	Application layer	253
17.2.4	Performance indicator selection	254
18	Communication Profile Family 17 (RAPIEnet) – RTE communication profiles	261
18.1	General overview	261
18.2	Profile 17/1	261
18.2.1	Physical layer	261
18.2.2	Datalink layer	261
18.2.3	Application layer	262
18.2.4	Performance indicator selection	263
19	Communication Profile Family 18 (SafetyNET p) – RTE communication profiles	268
19.1	General overview	268
19.2	Profile 18/1	268
19.2.1	Physical layer	268
19.2.2	Data link layer	268
19.2.3	Application layer	271
19.2.4	Performance indicator selection	273
19.3	Profile 18/2	276
19.3.1	Physical layer	276
19.3.2	Data link layer	276
19.3.3	Application layer	279
19.3.4	Performance indicator selection	280
20	Communication Profile Family 8 (CC-Link) – RTE communication profiles	282
20.1	General overview	282
20.2	Profile 8/4	282
20.2.1	Physical layer	282
20.2.2	Data link layer	283
20.2.3	Application layer	283
20.2.4	Performance indicator selection	284
20.3	Profile 8/5	289
20.3.1	Physical layer	289
20.3.2	Data link layer	289
20.3.3	Application layer	290
20.3.4	Performance indicator selection	291

21	Communication Profile Family 20 (ADS-net) – RTE communication profiles	297
21.1	General overview	297
21.2	Profile 20/1	297
21.2.1	Physical layer	297
21.2.2	Data link layer	297
21.2.3	Application layer	298
21.2.4	Performance indicator selection	299
21.3	Profile 20/2	303
21.3.1	Physical layer	303
21.3.2	Data link layer	303
21.3.3	Application layer	303
21.3.4	Performance indicator selection	304
22	Communication Profile Family 21 (FL-net) – RTE communication profiles	308
22.1	General overview	308
22.2	Profile 21/1	308
22.2.1	Physical layer	308
22.2.2	Data-link layer	308
22.2.3	Application layer	311
22.2.4	Performance indicator selection	315
Annex A	(informative) Performance Indicator calculation	322
A.1	CPF 2 (CIP) – Performance indicator calculation	322
A.1.1	Profile 2/2 EtherNet/IP	322
A.1.2	Profile 2/2.1 EtherNet/IP with Time Synchronization	323
A.2	CPF 3 – PROFINET – Performance indicator calculation	324
A.2.1	Application Scenario	324
A.2.2	Structural examples used for calculation	324
A.2.3	Principles used for calculation	333
A.3	CPF 4/3 P-NET on IP – Performance indicator calculation	335
A.3.1	Application scenario	335
A.3.2	Delivery time calculation	336
A.3.3	Non-RTE throughput calculation	337
A.3.4	Non time-base synchronization accuracy	338
A.3.5	RTE throughput calculation	339
A.3.6	CPF 4/3, Derivation of delivery time formula	339
A.3.7	CPF 4/3, Ethernet characteristics	340
A.4	CPF 20 – Performance indicator calculation	341
A.4.1	Profile 20/1	341
A.4.2	Profile 20/2	342
	Bibliography	344
	Figure 1 – Example of graphical representation of consistent indicators	48
	Figure 2 – Conformance test overview	50
	Figure 3 – Example of network topology using CP 3/4, CP 3/5, and CP 3/6 components	101
	Figure 4 – Example of network topology with wireless segment	104
	Figure 5 – Calculation basis for delivery time and throughput RTE	113
	Figure 6 – Linking-device communication profiles RTE-network context	144
	Figure 7 – Linking-device mapping principle	145

Figure 8 – Data Mapping.....	145
Figure 9 – CP 11/1: Throughput RTE and non-RTE bandwidth.....	169
Figure 10 – CP 11/2: Throughput RTE and non-RTE bandwidth.....	179
Figure 11 – CP 11/3: Throughput RTE and non-RTE bandwidth.....	189
Figure 12 – EPA system network topology example.....	219
Figure 13 – Protocol stack for Type 26 fieldbus.....	309
Figure A.1 – CP 3/4: Example of line structure.....	324
Figure A.2 – CP 3/4: Example of ring structure.....	325
Figure A.3 – CP 3/4: Example of a wireless segment.....	325
Figure A.4 – CP 3/4: Example of an integrated wireless client.....	326
Figure A.5 – CP 3/5: Example of line structure.....	326
Figure A.6 – CP 3/5: Example of ring structure.....	327
Figure A.7 – CP 3/6: Example of line structure.....	328
Figure A.8 – CP 3/6: Example of line structure.....	329
Figure A.9 – CP 3/6: Example of ring structure.....	330
Figure A.10 – CP 3/6: Example of tree structure.....	331
Figure A.11 – CP 3/6: Example of comb structure.....	332
Figure A.12 – CP 3/6: Example of comb structure (optional).....	333
Figure A.13 – Definition of bridge delay.....	334
Figure A.14 – Example of a switch structure.....	335
Figure A.15 – Application configuration.....	336
Figure A.16 – Non-RTE throughput calculation.....	337
Figure A.17 – Non time-base synchronization accuracy.....	338
IEC 61784-2:2019	
Table 1 – Layout of profile (sub)clause selection tables.....	43
Table 2 – Contents of (sub)clause selection tables.....	44
Table 3 – Layout of service selection tables.....	44
Table 4 – Contents of service selection tables.....	45
Table 5 – Layout of parameter selection tables.....	45
Table 6 – Contents of parameter selection tables.....	45
Table 7 – Layout of class attribute selection tables.....	46
Table 8 – Contents of class attribute selection tables.....	46
Table 9 – Basic network topology types.....	49
Table 10 – CP 2/2: PI overview.....	53
Table 11 – CP 2/2: PI dependency matrix.....	54
Table 12 – CP 2/2: Consistent set of PIs for factory automation.....	57
Table 13 – CP 2/2.1: DLL protocol selection.....	58
Table 14 – CP 2/2.1: DLL protocol selection of management objects.....	58
Table 15 – CP 2/2.1: AL service selection.....	59
Table 16 – CP 2/2.1: AL protocol selection.....	60
Table 17 – CP 2/2.1: PI overview.....	61
Table 18 – CP 2/2.1: PI dependency matrix.....	62
Table 19 – CP 2/2.1: Consistent set of PIs for motion control.....	62

Table 20 – Administrative numbers assignment	63
Table 21 – Maximum diagnosis data for one submodule	64
Table 22 – Maximum storage delay	65
Table 23 – Reporting system minimum storage size	65
Table 24 – Reporting system storage	65
Table 25 – Reporting system Timeouts	65
Table 26 – IP layer parameters for IO controller	66
Table 27 – IP layer parameters for IO device	66
Table 28 – Timeout values for name resolution	67
Table 29 – Reaction time for an IO device	67
Table 30 – Maximum time values for MRP	68
Table 31 – Maximum packet size for MRP	68
Table 32 – Maximum time values for PTCP	69
Table 33 – Precision of timers used for PTCP	69
Table 34 – Maximum deviation values for time synchronization	69
Table 35 – Maximum time values for LLDP	70
Table 36 – Required RPC resources	71
Table 37 – Required RPCActivityUUID resources	71
Table 38 – Number of ImplicitARs	71
Table 39 – Data Hold Time deviation	71
Table 40 – RTA Timeout deviation	71
Table 41 – Number of LogBookData entries	72
Table 42 – Community string	72
Table 43 – SNMP timeout values	72
Table 44 – DHCP client	72
Table 45 – System Redundancy times	73
Table 46 – Address parameter	73
Table 47 – AR Parameters	74
Table 48 – PDEV parameters	75
Table 49 – Communication classes applicable in conformance classes	76
Table 50 – Communication performance parameters	77
Table 51 – Parameters for RT_CLASS_3 bridges	77
Table 52 – FrameSendOffset deviation	78
Table 53 – FrameSendOffset deviation for RT_CLASS_1 / RT_CLASS_UDP	78
Table 54 – Minimum FrameSendOffset	78
Table 55 – PTCP control loop	78
Table 56 – Maximum frame size	79
Table 57 – Media redundancy class applicable in conformance classes	80
Table 58 – Media redundancy – additional forwarding rules	80
Table 59 – Media redundancy startup mode	80
Table 60 – Application classes applicable in conformance classes for IO device and IO controller	81
Table 61 – Application classes applicable in conformance classes for network components	82

Table 62 – Application class “isochronous application” AL service selection	82
Table 63 – Application class “isochronous application” AL protocol selection component	82
Table 64 – Application class “high availability” AL service selection	83
Table 65 – Application class “high availability” AL protocol selection component	83
Table 66 – Basis application class for “process automation”	83
Table 67 – Application class “process automation” AL service selection	84
Table 68 – Application class “process automation” AL protocol selection component	84
Table 69 – Application class “High performance” features supported	84
Table 70 – Application class “High performance” parameter values	84
Table 71 – Application class “Controller to Controller” features supported	85
Table 72 – Application class “Functional safety” features supported by IO device	85
Table 73 – Application class “Functional safety” features supported by IO controller	86
Table 74 – Application class “Energy saving” AL service selection	86
Table 75 – Application class “Energy saving” features supported by IO device	86
Table 76 – Application class “Energy saving” features supported by IO controller	86
Table 77 – Index (user specific)	87
Table 78 – Index (subslot specific)	87
Table 79 – Index (slot specific)	89
Table 80 – Index (AR specific)	90
Table 81 – Index (API specific)	91
Table 82 – Index (device specific)	92
Table 83 – PDPortDataAdjust (sub blocks)	93
Table 84 – PDPortDataCheck (sub blocks)	94
Table 85 – Communication feature list	94
Table 86 – Conformance class behaviors	95
Table 87 – IETF RFC 1213-MIB (MIB-2) objects	96
Table 88 – LLDP-MIB objects – range 1	97
Table 89 – LLDP-MIB objects – range 2	97
Table 90 – LLDP-MIB objects – range 3	97
Table 91 – LLDP-EXT-PNO-MIB objects – range 1	98
Table 92 – LLDP-EXT-PNO-MIB objects – range 2	98
Table 93 – LLDP-EXT-DOT3-MIB objects – range 1	98
Table 94 – LLDP-EXT-DOT3-MIB objects – range 2	98
Table 95 – Conformance class behaviors for network components	99
Table 96 – Buffering capacity at 100 Mbit/s	100
Table 97 – Buffering capacity for less than eight ports at 100 Mbit/s	100
Table 98 – Buffering capacity for eight and more ports at 100 Mbit/s	100
Table 99 – Link speed dependent local injection	101
Table 100 – CP 3/4: AL service selection for an IO device	102
Table 101 – CP 3/4: Additional AL service selection for an IO controller	105
Table 102 – CP 3/4: AL protocol selection for an IO device and Network component	105
Table 103 – CP 3/4: AL protocol selection for an IO controller	108

Table 104 – CP 3/4, CP 3/5 and CP 3/6: performance indicator overview.....	110
Table 105 – CP 3/4, CP 3/5 and CP 3/6: performance indicator dependency matrix	111
Table 106 – Manager (MRM) parameters	114
Table 107 – Client (MRC) parameters	115
Table 108 – Manager (MIM) parameters	115
Table 109 – Client (MIC) parameters	115
Table 110 – CP 3/4: Consistent set of PI for MinDeviceInterval=128 ms	116
Table 111 – CP 3/4: Assumed values for consistent set of PI calculation	117
Table 112 – CP 3/5: AL service selection for an IO device	118
Table 113 – CP 3/5: Additional AL service selection for an IO controller	120
Table 114 – CP 3/5: AL protocol selection for an IO device and Network component	120
Table 115 – CP 3/5: AL protocol selection for an IO controller	122
Table 116 – CP 3/5: Consistent set of PI for MinDeviceInterval=128 ms	125
Table 117 – CP 3/5: Assumed values for consistent set of PI calculation	126
Table 118 – CP 3/6: AL service selection for an IO device	127
Table 119 – CP 3/6: Additional AL service selection for an IO controller	129
Table 120 – CP 3/6: AL protocol selection for an IO device and network component.....	129
Table 121 – CP 3/6: AL protocol selection for an IO controller	131
Table 122 – CP 3/6: Consistent set of PI for MinDeviceInterval=1 ms and NumberOfSwitches=20	134
Table 123 – CP 3/6: Consistent set of PI for MinDeviceInterval=1 ms and NumberOfSwitches=63	135
Table 124 – CP 3/6: Assumed values for consistent set of PI calculation	135
Table 125 – CP 3/6: Consistent set of PI for MinDeviceInterval=31,25 µs and NumberOfSwitches=10	136
Table 126 – CP 3/6: Assumed values for consistent set of PI calculation	137
Table 127 – CP 4/3: DLL service selection.....	138
Table 128 – CP 4/3: DLL protocol selection	139
Table 129 – CP 4/3: AL service selection.....	139
Table 130 – CP 4/3: AL protocol selection	139
Table 131 – CP 4/3: PI overview	140
Table 132 – CP 4/3: PI dependency matrix	140
Table 133 – CP 4/3: Consistent set of PIs.....	143
Table 134 – Parameters for calculation of consistent set of PIs.....	143
Table 135 – CPF 6: device CP identifier assignment.....	144
Table 136 – Linking-device Type 10 network PI overview.....	147
Table 137 – OSI layers and CPF 10 layers	150
Table 138 – Overview of CPF 10 profile.....	151
Table 139 – CP 10/1: DLL service selection.....	152
Table 140 – CP 10/1: DLL protocol selection	153
Table 141 – Transport Layer Parameter selection	153
Table 142 – CP 10/1: AL service selection.....	154
Table 143 – CP 10/1: AL protocol selection	155
Table 144 – CP 10/1: PI overview	155

Table 145 – CP 10/1: PI dependency matrix	156
Table 146 – CP 10/1: Consistent set of PIs for the communication between two end-stations belonging to the same domain	158
Table 147 – CP 10/1: Consistent set of PIs for the communication between two end-stations belonging to different domains	159
Table 148 – CP 10/1: Consistent set of PIs for the communication between two end-stations belonging to the same domain with one lost flame	159
Table 149 – CP 10/1: Consistent set of PIs for the communication between two end-stations belonging to different domains with one lost flame	159
Table 150 – CPF 11: Overview of profile sets	160
Table 151 – CP 11/1: DLL service selection	161
Table 152 – CP 11/1: DLL protocol selection	162
Table 153 – CP 11/1: DLL protocol selection of Clause 5	163
Table 154 – CP 11/1: DLL protocol selection of Clause 6	163
Table 155 – CP 11/1: AL service selection	165
Table 156 – CP 11/1: AL protocol selection	165
Table 157 – CP 11/1: PI overview	166
Table 158 – CP 11/1: PI dependency matrix	166
Table 159 – CP 11/1: TCC data service selection	167
Table 160 – CP 11/1: Consistent set of PIs preferential for RTE communications	171
Table 161 – CP 11/1: Consistent set of PIs both for RTE and non-RTE communications	171
Table 162 – CP 11/2: DLL protocol selection	173
Table 163 – CP 11/2: DLL protocol selection of Clause 5	174
Table 164 – CP 11/2: DLL protocol selection of Clause 6	174
Table 165 – CP 11/2: PI overview	176
Table 166 – CP 11/2: PI dependency matrix	177
Table 167 – CP 11/2: TCC data service selection	178
Table 168 – CP 11/2: Consistent set of PIs preferential for RTE communications	181
Table 169 – CP 11/2: Consistent set of PIs both for RTE and non-RTE communications	181
Table 170 – CP 11/3: DLL protocol selection	182
Table 171 – CP 11/3: DLL protocol selection of Clause 5	183
Table 172 – CP 11/3: DLL protocol selection of Clause 6	184
Table 173 – CP 11/3: PI overview	186
Table 174 – CP 11/3: PI dependency matrix	186
Table 175 – CP 11/3: TCC data service selection	187
Table 176 – CP 11/3: Consistent set of PIs preferential for RTE communications	191
Table 177 – CP 11/3: Consistent set of PIs both for RTE and non-RTE communications	191
Table 178 – CP 12/1: PhL selection of preferred physical layer from ISO/IEC/IEEE 8802-3:2017	193
Table 179 – CP 12/1: PhL selection of an optimized physical layer from IEC 61158-2	194
Table 180 – CP 12/1: DLL service selection	194
Table 181 – CP 12/1: DLL protocol selection	195
Table 182 – CP 12/1: DLL service selection	196