



## Standard Test Method for Determining Mass and Moment of Inertia of Alpine Skis<sup>1,2</sup>

This standard is issued under the fixed designation F 1722; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reappraisal.

### 1. Scope

1.1 This test method covers test measurement methods for mass and moment of inertia of adult Alpine skis.<sup>2</sup>

1.2 No limitation to ski size is proposed. This test method is applicable to all adult Alpine skis.

1.3 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

### 2. Referenced Documents

#### 2.1 ISO Standards:<sup>3</sup>

ISO 554 Standard Atmospheres for Conditioning and/or Testing—Specifications

ISO 6003 Alpine Skis—Determination of Mass and Polar Moment of Inertia—Laboratory Measurement Method

### 3. Terminology

#### 3.1 Definitions of Terms Specific to This Standard:

3.1.1 *mass of ski, m*—the mass of a finished, manufactured ski without any mounted parts, expressed in kilograms.

3.1.2 *moment of inertia, I*—the mass moment of inertia of the ski about its center of gravity, expressed in kilogram-metres squared.

### 4. Significance and Use

4.1 This test method provides a means for determining the mass and moment of inertia of adult Alpine skis. It is not intended to evaluate data with regard to the quality of the ski.

### 5. Apparatus

5.1 *Weighing Device*, accurate to  $\pm 0.02$  kg.

5.2 *Fulcrum*, for locating the center of gravity of the ski.

5.3 *Time Measurement Device* (stopwatch), accurate to at least 0.1 s.

5.4 *Measuring Device*, in accordance with Fig. 1, consisting of the following parts:

5.4.1 *Clamping Device, A*, consisting of two clamping fixtures. The top clamping fixture has a hole with a mark to locate the center of gravity and two additional holes at a distance,  $d_f$ , from the center mark for fixation of the filaments, B. The recommended dimension for  $d_f$  is 25 mm, and the mass of the clamping device shall be less than 0.1 kg.

5.4.2 *Top Plate, C*, with two holes separated by the distance  $2d_f$  for the fixation of filaments, B. The plate, C, shall be fixed on a stiff, horizontal beam.

5.4.3 *Two Filaments, B*, with equal lengths,  $l$ , that connect the top plate with the clamping device. The ratio  $d_f:l$  shall be approximately 1:40. With the recommended dimension  $d_f = 25$  mm, and the length,  $l = 1000$  mm. The filaments shall be made of materials with low elongation and high strength (for example, tennis racket string and fishing line). The diameter of the filaments shall be not more than 1.0 mm.

### 6. Sampling and Conditioning

6.1 In order to ensure comparability, it is recommended that one of the following ski sizes be used if the data measured are to be published: 150, 180, or 200 cm. From these three sizes, choose the one that is most representative of the tested model.

6.2 All measurements shall be taken from a finished, manufactured ski without any mounted parts.

6.3 All measurements shall be taken from a ski that has been conditioned in a standard atmosphere 20/65 (ISO 554) (that is, the ski shall be placed in this atmosphere for at least 24 h prior to measurements being taken).

### 7. Calibration of Measuring Device

7.1 Differences in construction between the different measuring devices can lead to different measurement results, which deviate from the theoretical value of the polar moment of inertia. In order to reduce such deviations, it is recommended that a test equipment validation factor,  $c$ , be determined for each measuring device.

7.2 The test equipment validation factor is determined from the ratio of the calculated moment of inertia to the measured moment of inertia of a bar of steel with dimensions 1 to 8 by

<sup>1</sup> This test method is under the jurisdiction of ASTM Committee F-27 on Snow Skiing and is the direct responsibility of Subcommittee F27.30 on Alpine and Nordic Skis.

Current edition approved July 10, 1996. Published September 1996.

<sup>2</sup> This test method is meant to conform in all significant aspects to the test method for determining mass and polar moment of inertia of Alpine skis as set forth in ISO 6003.

<sup>3</sup> Available from American National Standards Institute, 11 W. 42nd St., 13th Floor, New York, NY 10036.