

# INTERNATIONAL STANDARD

**ISO**  
**4250-2**

Second edition  
1991-04-01

---

---

## Narrow and wide base off-road tyres and rims

### Part 2: Loads and inflation pressures

**iTeh STANDARD PREVIEW**

*Pneumatiques et jantes à base étroite et à base large pour engins de génie civil —  
Partie 2: Charges et pressions de gonflage*

[ISO 4250-2:1991](https://standards.iteh.ai/catalog/standards/sist/ade2d978-7d21-4966-80fa-37bf13ab74b6/iso-4250-2-1991)

<https://standards.iteh.ai/catalog/standards/sist/ade2d978-7d21-4966-80fa-37bf13ab74b6/iso-4250-2-1991>



Reference number  
ISO 4250-2 : 1991 (E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

**iTeh STANDARD PREVIEW**

International Standard ISO 4250-2 was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Sub-Committee SC 6, *Off-the-road tyres and rims*.

This second edition cancels and replaces the first edition (ISO 4250-2 : 1987), incorporating draft Addendum 1.

<https://standards.iteh.ai/catalog/standards/sist/ade2d978-7d21-4966-80fa-iso-4250-2:1991>

ISO 4250 consists of the following parts, under the general title *Narrow and wide base off-road tyres and rims*:

- *Part 1: Tyre designations and dimensions*
- *Part 2: Loads and inflation pressures*
- *Part 3: Rims*

© ISO 1991

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization

Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

# Narrow and wide base off-road tyres and rims —

## Part 2:

### Loads and inflation pressures

#### 1 Scope

ISO 4250 consists of three parts (see the Foreword) and provides technical details on the designation and dimensions of off-road tyres and rims, as well as load ratings for these types of tyres.

This part of ISO 4250 gives working definitions of masses and load cycles, and sets out tyre loads and reference inflation pressures for narrow and wide base tyres primarily intended for off-road machines.

NOTE — Terms used are in accordance with ISO 3877-1 : 1978, *Tyres, valves and tubes — List of equivalent terms — Part 1: Tyres*.

#### 2 Definitions

##### 2.1 Definitions of masses

**2.1.1 maximum load:** Maximum loads of individual tyres determined by manufacturer's rated gross machine mass (GMM) distribution assigned to each axle, divided by the number of tyres for that axle.

NOTE — The maximum GMM includes masses calculated in 2.1.1.1 to 2.1.1.6 inclusive.

**2.1.1.1 operating mass; net weight** (deprecated): Actual mass of the base machine with equipment specified by the manufacturer, operator (75 kg), full fuel tank, and full lubricating, hydraulic and cooling systems.

**2.1.1.2 optional equipment mass:** Difference in operating mass between the optional item and standard item replaced (such as engine, brakes, tyres, etc.). This includes the operating mass of additional items offered by the manufacturer which are not replacements for standard items (such as cabs, body-liners, side-boards, air conditioners, etc.).

**2.1.1.3 mass of special modifications:** Difference in the operating mass of the machine due to modifications not previously covered in optional equipment mass (such as additional reinforcements, etc.).

**2.1.1.4 payload:** Total mass of the material being carried.

**2.1.1.5 tyre ballast:** (If used, this is also included in determination of GMM.)

**2.1.1.6 field modifications:** Operating mass change due to machine alterations made other than by the original manufacturer (such as modifications for additional capacity, reinforcements, etc.).

##### 2.2 Definitions of operating conditions

**2.2.1 maximum speed:** Peak velocity attained by the machine.

**2.2.2 earth-moving haulage cycle:** Cycle where machine self-loads or receives a load from loading equipment, transports it elsewhere and returns unloaded. Transportation usually occurs over unimproved surfaces at medium speeds, up to 65 km/h, and short distances, up to 4 km away.

NOTE — Machines in this category are mainly haulage trucks (dumpers) and tractor-scrapers.

**2.2.3 loader cycle:** Cycle where the machine is used to pick up material and move it a short distance away. Tyre loads fluctuate depending on the conditions involved when the equipment picks up the load. Transportation speeds are low, up to 10 km/h, and distances are short, usually less than 75 m away.

**2.2.4 load carry cycle:** Cycle where the machine, primarily intended for loader service, picks up a load, transports it elsewhere and returns unloaded. Transportation usually occurs over unimproved surfaces at low speeds, up to 25 km/h, and rather short distances, up to 600 m.

NOTE — Machines in this category consist mainly of loaders, log stackers and material-handling equipment. Tyre manufacturers should be consulted for specific conditions.

**2.2.5 dozer (tractor) cycle:** Condition where a machine is used to move materials (usually earth) by pushing, dragging or grading. Tyre loads are relatively constant and speeds are low, up to 10 km/h. Travel distances vary depending on work situations.

**2.2.6 grader cycle:** Condition where a machine is used in construction and road maintenance. Tyre loads are relatively constant during the work cycles. Grader speeds are slower

during working periods with typical transportation speeds reaching about 40 km/h. Travel distances vary depending on work situations.

**2.2.7 creep:** Movement of equipment at a very low speed (commonly not over 120 m in 60 min). During creep motion, loads on the tyres are usually very high and consideration needs to be given to the type of surface over which the equipment is travelling. Tyre manufacturers should be consulted for specific conditions.

**2.2.8 drive-away:** Movement of a machine from one location to another under non-working conditions. This movement occurs during transportation of a machine from site to site. Tyre manufacturers should be consulted for specific conditions.

NOTE — Load/speed/distance tables in this part of ISO 4250 do not apply to drive-away conditions.

### 3 Special conditions

For longer hauls and/or speeds in excess of those indicated in the tables, the tyre manufacturers should be consulted for instructions regarding permissible loads and the required inflation pressures.

### 4 Selection for new machine design

Selection of size and strength index of the tyre used on each axle shall be based on the highest individual wheel load (determined by GMM distribution, including load transfer) and the machine application.

Maximum load per tyre shall not be greater than specified in the applicable tables.

The performance of machines fitted with off-road tyres depends on the operating conditions, and more particularly on the specific ground pressure which is governed by the inflation pressure. It is therefore advisable to select tyre size on the basis of low inflation pressure.

## 5 Inflation pressures — General

**5.1** Rim and wheel manufacturers should be consulted to determine if the rim and wheel are of sufficient strength for the intended service conditions (inflation pressure and load).

**5.2** Inflation pressures shown in the load inflation tables are reference pressures and do not include any pressure build-up due to vehicle operation.

**5.3** In agreement with tyre manufacturers, inflation pressures may be varied to compensate for extremes of atmospheric temperatures or special operating conditions.

**5.4** For all tables the inflation pressures are given for guidance only; in actual practice they may vary according to the operating conditions, in agreement with the tyre manufacturers.

## 6 Load/inflation tables

Load/inflation relations for diagonal ply rating tyres are given in tables 1 to 6: those for symbol-marked radial tyres are given in tables 7 to 9.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/ade2d978-7d21-4966-80fa-37bf13ab74b6/iso-4250-2-1991>

**Table 1 — Diagonal ply rating marked narrow base tyres for earth-moving slow speed service, reference speed 10 km/h (loaded conditions)**

Tyre size designation	Ply rating	Load <sup>1)</sup> kg	Inflation kPa
12.00 — 20/21	14	5 000	600
	16	5 450	700
12.00 — 24/25	8	4 000	325
	14	5 600	575
	16	6 150	675
	18	6 500	750
13.00 — 24/25	20	6 900	825
	8	4 375	300
	12	5 600	450
	18	7 100	675
14.00 — 24/25	20	7 500	750
	22	8 000	825
	8	4 875	275
	10	5 600	350
14.00 — 24/25	12	6 300	425
	16	7 300	550
	20	8 500	700
	24	9 500	850
14.00 — 24/25	28	10 000	925
	12	7 100	325
	16	8 250	425
	20	9 750	550
16.00 — 24/25	24	10 600	650
	28	11 500	750
	32	12 500	875
	36	13 600	975
18.00 — 24/25	12	8 250	275
	16	10 000	375
	20	11 500	475
	24	12 500	550
	28	13 600	650
	32	15 000	750
	36	16 000	850
	40	17 000	950
18.00 — 33	28	16 000	650
	32	17 500	750
	36	18 500	850
18.00 — 49	24	18 500	550
	28	20 000	650
	32	21 800	750
21.00 — 24/25	16	11 800	325
	20	13 200	400
	24	15 000	500
	28	16 500	575
21.00 — 35	28	19 500	575
	32	21 200	650
	36	23 000	750
	40	24 300	825
21.00 — 35	44	25 000	900
	28	23 600	575
	32	25 000	650
	36	27 250	750
21.00 — 49	40	29 000	825
	44	30 750	900
	24	18 000	425
	30	20 000	525
24.00 — 25	24	19 000	425
	30	21 800	525
24.00 — 29	24	19 000	425
	30	21 800	525
	36	26 500	650
	42	29 000	750
24.00 — 35	48	31 500	850
	54	34 500	975
	36	30 000	650
	42	32 500	750
24.00 — 43	48	34 500	850
	36	32 500	650
24.00 — 49	42	34 500	750
	48	37 500	850
	24	22 400	350
27.00 — 33	30	25 750	450
	36	29 000	550
	36	36 500	575
27.00 — 49	42	40 000	675
	48	43 750	775
	40	45 000	575
30.00 — 51	46	48 750	650
	52	53 000	750
	42	51 500	550
33.00 — 51	50	56 000	650
	58	61 500	750
	42	58 000	500
36.00 — 51	50	65 000	600
	58	71 000	675
	52	80 000	550
40.00 — 57	60	87 500	650
	68	92 500	725

1) For stationary service conditions, the loads in this table may be increased up to 60 % with no increase in inflation pressure.

For special equipment with a high centre of gravity, consult the tyre manufacturer.

Table 2 — Diagonal ply rating marked narrow base tyres for earth-moving service for relatively short hauls, reference speed 50 km/h

Tyre size designation	Ply rating	Load <sup>1)</sup> kg	Inflation kPa
12.00 — 20/21	14	2 800	425
	16	3 000	475
12.00 — 24/25	8	2 180	225
	14	3 000	375
	16	3 250	450
	18	3 550	500
	20	3 750	550
13.00 — 24/25	8	2 360	200
	12	3 000	300
	18	3 875	450
	20	4 000	500
14.00 — 24/25	8	2 575	175
	10	3 000	225
	12	3 350	275
	16	4 000	375
	20	4 625	475
	24	5 150	575
16.00 — 24/25	12	3 875	225
	16	4 875	325
	20	5 450	400
	24	6 000	475
	28	6 700	575
	32	7 300	650
	36	7 750	725
18.00 — 24/25	12	4 750	200
	16	5 600	275
	20	6 500	350
	24	7 300	425
	28	8 000	500
	32	8 750	575
	36	9 250	625
	40	9 750	700
18.00 — 33	28	9 250	500
	32	10 000	575
	36	10 600	625
18.00 — 49	24	10 600	425
	28	11 800	500
	32	12 850	575
21.00 — 24/25	16	6 900	250
	20	7 750	300
	24	8 750	375
	28	9 500	425
21.00 — 35	28	11 200	425
	32	12 150	500
	36	12 850	550
	40	14 000	625
	44	14 500	675
21.00 — 49	28	13 600	425
	32	15 000	500
	36	15 500	550
	40	17 000	625
	44	17 500	675

Tyre size designation	Ply rating	Load <sup>1)</sup> kg	Inflation kPa
24.00 — 25	24	10 300	325
	30	11 800	400
24.00 — 29	24	11 200	325
	30	12 500	400
24.00 — 35	36	15 500	475
	42	16 500	550
	48	18 500	650
	54	19 500	725
24.00 — 43	36	17 000	475
	42	19 000	575
	48	20 600	650
24.00 — 49	36	18 500	475
	42	20 000	550
	48	21 800	650
27.00 — 33	24	13 200	275
	30	15 500	350
	36	16 500	400
27.00 — 49	36	21 200	425
	42	23 000	500
	48	25 000	575
30.00 — 33	28	16 000	275
	34	18 500	350
	40	21 200	425
30.00 — 51	40	25 750	425
	46	29 000	500
	52	30 000	550
33.00 — 51	42	30 000	425
	50	33 500	500
	58	35 500	575
36.00 — 51	42	34 500	375
	50	37 500	450
	58	41 250	525
40.00 — 57	52	46 250	425
	60	50 000	475
	68	54 500	550

1) Load adjustment for maximum speed 65 km/h :  
load × 0,85  
Load adjustment for maximum speed 15 km/h :  
load × 1,12  
Values so calculated to be rounded off to the nearest :  
25 kg for loads up to 4 999 kg;  
50 kg for loads from 5 000 kg to 9 999 kg;  
100 kg for loads equal to or above 10 000 kg.

**Table 3 — Diagonal ply rating marked wide base tyres for earth-moving slow speed service, reference speed 10 km/h (loaded conditions)**

Tyre size designation	Ply rating	Load <sup>1)</sup> kg	Inflation kPa	Tyre size designation	Ply rating	Load <sup>1)</sup> kg	Inflation kPa	
15.5 — 25	8	4 250	250	33.25 — 29	26	20 600	350	
	10	4 875	325		32	23 600	450	
	12	5 600	400		38	25 750	525	
17.5 — 25	8	4 750	225	33.25 — 35	26	22 400	350	
	12	6 150	350		32	25 750	450	
	16	7 300	475		38	28 000	550	
	20	8 250	575	33.5 — 33	26	22 400	350	
20.5 — 25	12	6 700	250		32	25 750	425	
	16	8 250	350		38	29 000	525	
	20	9 500	450	33.5 — 39	26	24 300	350	
	24	10 300	525		32	27 250	425	
28	11 500	625	38		30 750	525		
23.5 — 25	12	8 000	225	37.25 — 35	30	28 000	375	
	16	9 500	300		36	30 750	450	
	20	10 900	375		42	33 500	525	
	24	12 500	475	37.5 — 33	30	28 000	375	
28	13 600	550	36		31 500	450		
26.5 — 25	16	11 500	275		42	34 500	525	
	20	13 200	350	37.5 — 39	28	29 000	350	
	24	14 000	400		36	33 500	450	
	28	15 500	475		44	37 500	550	
26.5 — 29	18	12 850	300	37.5 — 51	28	33 500	350	
	22	14 500	375		36	38 750	450	
	26	16 000	450		44	42 500	525	
	30	17 500	525	40.5/75 — 39	30	31 500	325	
29.5 — 25	16	12 850	250		38	37 500	425	
	22	15 000	325		46	42 500	525	
	28	17 500	425	29.5 — 29	16	14 000	250	
	22	16 000	325		22	16 000	425	
28	19 000	425	28		19 000	525		
34	21 200	525	34		21 200	625		
29.5 — 35	40	23 600	625	29.5 — 35	22	17 500	325	
	29.5 — 29	16	14 000		250	28	20 600	425
		22	16 000		325	34	23 000	525
28		19 000	425	29.5 — 35	22	17 500	325	
34		21 200	525		28	20 600	425	
40	23 600	625	34		23 000	525		
29.5 — 35	22	17 500	325		29.5 — 35	22	17 500	325
	28	20 600	425	28		20 600	425	
	34	23 000	525	34		23 000	525	

1) For stationary service conditions, the loads in this table may be increased up to 60 % with no increase in inflation pressure. For special equipment with a high centre of gravity, consult the tyre manufacturer.

Table 4 — Diagonal ply rating marked wide base tyres for earth-moving service for relatively short hauls, reference speed 50 km/h

Tyre size designation	Ply rating	Load <sup>1)</sup> kg	Inflation kPa	Tyre size designation	Ply rating	Load <sup>1)</sup> kg	Inflation kPa
15.5 — 25	8	2 575	175	33.25 — 35	26	14 500	275
	10	3 000	225		32	16 000	325
	12	3 250	250		38	18 000	400
17.5 — 25	8	2 800	150	33.5 — 33	26	15 000	275
	12	3 650	225		32	16 500	325
	16	4 250	300		38	18 500	400
	20	5 000	400	33.5 — 39	26	16 000	275
20.5 — 25	12	4 500	200		32	18 000	325
	16	5 450	275		38	20 000	400
	20	6 000	325	37.25 — 35	30	17 500	275
	24	6 700	400		36	19 500	325
28	7 500	475	42		21 800	400	
23.5 — 25	12	5 300	175	37.5 — 33	30	18 000	275
	16	6 150	225		36	20 000	325
	20	7 300	300		42	22 400	400
	24	8 000	350	37.5 — 39	28	18 500	250
	28	8 750	400		36	21 200	325
26.5 — 25	16	7 300	200		44	24 300	400
	20	8 250	250	52	26 500	475	
	24	9 250	300	37.5 — 51	28	20 600	250
	28	10 000	350		36	24 300	325
	32	11 200	425		44	27 250	400
26.5 — 29	18	8 250	225	40.5/75 — 39	30	20 600	250
	22	9 250	275		38	24 300	325
	26	10 300	325		46	27 250	400
	30	11 200	375	<p>1) Load adjustment for maximum speed 65 km/h : load × 0,83</p> <p>Load adjustment for maximum speed 15 km/h : load × 1,12</p> <p>Values so calculated to be rounded off to the nearest : 25 kg for loads up to 4 999 kg; 50 kg for loads from 5 000 kg to 9 999 kg; 100 kg for loads equal to or above 10 000 kg.</p>			
29.5 — 25	16	8 000	175				
	22	10 000	250				
	28	11 500	325				
29.5 — 29	16	8 500	175				
	22	10 600	250				
	28	12 150	325				
	34	14 000	400				
	40	15 000	475				
29.5 — 35	22	11 500	250				
	28	13 600	325				
	34	15 000	400				
33.25 — 29	26	13 600	275				
	32	15 000	325				
	38	17 000	400				



Table 5 – Diagonal ply rating marked 65 series tyres for earth-moving service

Tyre size designation	Ply rating	Earth-moving service for relatively short hauls, reference speed 50 km/h		Earth-moving slow speed service, reference speed 10 km/h (loaded conditions)	
		Load kg	Inflation kPa	Load kg	Inflation kPa
25/65 – 25	12	4 375	175	7 300	250
	16	5 150	225	8 500	325
	20	5 800	275	9 750	400
30/65 – 25	16	6 700	200	10 900	275
	20	7 500	250	12 500	350
30/65 – 29	16	7 100	200	11 500	275
	20	8 250	250	13 200	350
	24	9 000	300	15 000	425
35/65 – 33	24	11 500	250	19 000	350
	30	12 850	300	21 200	425
	36	14 500	375	23 600	525
40/65 – 39	30	—	—	27 250	375
	36	—	—	30 000	450
45/65 – 45	38	—	—	40 000	450
50/65 – 51	46	—	—	51 500	450

Table 6 – Diagonal ply rating marked narrow base, wide base and 65 series tyres in grader service, reference speed 40 km/h

Tyre size designation <sup>1)</sup>	Ply rating	Load kg	Inflation kPa	Tyre size designation <sup>1)</sup>	Ply rating	Load kg	Inflation kPa
10.00 – 24 TG	8	1 700	250	17.5 – 25	8	2 120	125
12.00 – 24 TG	6	1 600	150		12	2 900	200
	8	1 900	225		14	3 000	225
	12	2 430	325		16	3 350	275
13.00 – 24 TG	8	2 060	200	20	3 650	325	
	10	2 360	250	20.5 – 25	12	3 550	175
	12	2 725	300		16	4 000	225
	14	3 000	350		20	4 500	275
14.00 – 24 TG	8	2 500	175	23.5 – 25	12	4 000	150
	10	2 800	225		16	4 750	200
	12	3 075	275		20	5 450	250
	14	3 450	325	25/65 – 25	12	3 350	125
	16	3 650	375		16	4 125	175
16.00 – 24 TG	12	3 650	225	1) "TG" is a designation to be used to identify tyres mounted on SDC rims.			
	14	4 000	275				
	16	4 500	325				
18.00 – 25	12	4 125	200				
	16	5 000	275				
15.5 – 25	8	1 950	150				
	10	2 180	175				
	12	2 650	225				