

INTERNATIONAL STANDARD

Information technology – Underwater acoustic sensor network (UWASN) –
Part 1: Overview and requirements

(standards.iteh.ai)

ISO/IEC 30140-1:2018

<https://standards.iteh.ai/catalog/standards/sist/cf94ceb7-77e0-45cf-a39f-868a3023bd63/iso-iec-30140-1-2018>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2018 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch

<https://standards.iteh.ai/catalog/standards/sist/cb4-icc7-77/cb-45cf-a39f-868a3023bd63/iso-iec-30140-1-2018>



ISO/IEC 30140-1

Edition 1.0 2018-02

INTERNATIONAL STANDARD

Information technology – Underwater acoustic sensor network (UWASN) –
Part 1: Overview and requirements
ITeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 30140-1:2018](https://standards.iteh.ai/catalog/standards/sist/cf94ceb7-77e0-45cf-a39f-868a3023bd63/iso-iec-30140-1-2018)

<https://standards.iteh.ai/catalog/standards/sist/cf94ceb7-77e0-45cf-a39f-868a3023bd63/iso-iec-30140-1-2018>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.110

ISBN 978-2-8322-5372-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

| | |
|---|----|
| FOREWORD..... | 5 |
| INTRODUCTION..... | 6 |
| 1 Scope..... | 7 |
| 2 Normative references | 7 |
| 3 Terms and definitions | 7 |
| 4 Abbreviated terms | 9 |
| 5 UWASN overview and applications | 9 |
| 5.1 Overview..... | 9 |
| 5.2 Application domain of UWASN..... | 11 |
| 6 Characteristics of UWASN in terms of the effects of propagation variability | 12 |
| 6.1 Underwater acoustic communication | 12 |
| 6.2 Acoustic signal strength attenuation..... | 12 |
| 6.3 High propagation delay | 12 |
| 6.4 Multipath..... | 13 |
| 6.5 Propagation loss | 13 |
| 6.6 Noise | 14 |
| 7 Differences between UWASN and terrestrial sensor network | 14 |
| 7.1 Types of underwater communication technologies..... | 14 |
| 7.2 Housing case | 16 |
| 7.3 Costs associated with sensor nodes | 16 |
| 7.4 Omni-directional and directional transducers for data transmission and reception..... | 16 |
| 7.5 Underwater object and event localization and 3D relay node..... | 17 |
| 7.6 Energy harvesting technology for UWASN | 18 |
| 8 Specificities of UWASN and related requirements..... | 18 |
| 8.1 Three structural scales of UWASN network..... | 18 |
| 8.2 Deployments of 2D and 3D topology | 21 |
| 8.2.1 General | 21 |
| 8.2.2 Two-dimensional UWASN architecture..... | 21 |
| 8.2.3 Three-dimensional UWASN architecture | 22 |
| 8.3 Cross layering..... | 24 |
| 8.4 Underwater acoustic modem | 25 |
| 8.5 Doppler spread | 25 |
| 8.6 Deployment considering water depths | 26 |
| 8.7 Underwater wired and wireless communication | 26 |
| 8.8 Time synchronization | 27 |
| 8.9 Data transmission period for energy saving..... | 28 |
| 8.10 Routing | 29 |
| 8.11 Network coding | 31 |
| 8.12 Data compression | 31 |
| 8.13 Delay and disruption tolerant network (DTN)..... | 31 |
| 9 UWASN further general requirements | 32 |
| 9.1 General..... | 32 |
| 9.2 General requirements for UWASN – Cross layering | 32 |
| 9.3 General requirements for the UWASN – Communication technology | 32 |
| 9.4 General requirements for the UWASN – Other system requirements | 33 |

| | |
|---|----|
| Annex A (informative) Selected applications of UWASN..... | 34 |
| A.1 Environmental monitoring – Chemical and biological changes..... | 34 |
| A.1.1 Description | 34 |
| A.1.2 Physical entities | 35 |
| A.1.3 Normal flow | 35 |
| A.1.4 Conditions | 35 |
| A.2 Detection of pipeline leakages | 35 |
| A.2.1 Description | 35 |
| A.2.2 Physical entities | 36 |
| A.2.3 Normal flow | 36 |
| A.2.4 Conditions | 37 |
| A.3 Exploration of natural resources..... | 37 |
| A.3.1 Description | 37 |
| A.3.2 Physical entities | 38 |
| A.3.3 Normal flow | 38 |
| A.3.4 Conditions | 39 |
| A.4 Fish farming..... | 39 |
| A.4.1 Description | 39 |
| A.4.2 Physical entities | 40 |
| A.4.3 Normal flow | 40 |
| A.4.4 Conditions | 40 |
| A.5 Harbour security | 40 |
| A.5.1 Description | 40 |
| A.5.2 Physical entities | 41 |
| A.5.3 Normal flow | 41 |
| A.5.4 Conditions | 42 |
| Bibliography..... | 43 |
| | |
| Figure 1 – Overview of a UWASN | 10 |
| Figure 2 – Omni-directional and directional transducers for data transmission and reception | 17 |
| Figure 3 – Underwater cluster network..... | 18 |
| Figure 4 – Underwater ad-hoc network..... | 19 |
| Figure 5 – UWA-UN communication network..... | 19 |
| Figure 6 – UWA-UN communication network using fixed gateway | 20 |
| Figure 7 – UWA-EUN communication network | 21 |
| Figure 8 – Two-dimensional UWASN architecture | 22 |
| Figure 9 – Three-dimensional UWASN architecture | 23 |
| Figure 10 – UWA-cross layer protocol stack..... | 25 |
| Figure 11 – Underwater wired and wireless communication | 27 |
| Figure 12 – Time synchronization for data transmission | 28 |
| Figure 13 – Using active and sleep modes for energy saving | 29 |
| Figure 14 – UWASN routing..... | 30 |
| Figure A.1 – Illustration of the environmental monitoring use case | 34 |
| Figure A.2 – Oil and gas pipeline leakage monitoring use case | 36 |
| Figure A.3 – Flow – Oil and gas pipeline leakage monitoring | 37 |

| | |
|--|----|
| Figure A.4 – Underwater resource exploration use case | 38 |
| Figure A.5 – Fish farming and monitoring use case | 39 |
| Figure A.6 – Harbour security monitoring use case | 41 |
| Table 1 – UWASN market segments and their current and future applications list | 11 |
| Table 2 – Summary of the features of acoustic, radio, and optical waves in seawater environments | 15 |
| Table 3 – Differences between underwater communication technologies [10][12] | 15 |
| Table 4 – Comparison between 2D and 3D UWASNs | 24 |

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

[ISO/IEC 30140-1:2018](https://standards.iteh.ai/catalog/standards/sist/cf94ceb7-77e0-45cf-a39f-868a3023bd63/iso-iec-30140-1-2018)

<https://standards.iteh.ai/catalog/standards/sist/cf94ceb7-77e0-45cf-a39f-868a3023bd63/iso-iec-30140-1-2018>

INFORMATION TECHNOLOGY – UNDERWATER ACOUSTIC SENSOR NETWORK (UWASN) –

Part 1: Overview and requirements

FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.
- 3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
<https://standards.itec.ai/catalog/standards/sist/cd4ecb7-77e0-45cf-a39f-8683023bd67/iso-iec-30140-1-2018>
- 7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 30140-1 was prepared by subcommittee 41: Internet of Things and related technologies, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 30140 series, under the general title *Information technology – Underwater acoustic sensor network (UWASN)*, can be found on the IEC and ISO websites.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

INTRODUCTION

Water covers approximately 71 % of the surface of the Earth. Modern technologies introduce new methods to monitor the body of water, for example pollution monitoring and detection. Underwater data gathering techniques require exploring the water environment, which can be most effectively performed by underwater acoustic sensor networks (UWASNs). Applications developed for the UWASNs can record underwater climate, detect and control water pollution, monitor marine biology, discover natural resources, detect pipeline leakages, monitor and locate underwater intruders, perform strategic surveillance, and so on.

The ISO/IEC 30140 series provides general requirements, reference architecture (RA) including the entity models and high-level interface guidelines supporting interoperability among UWASNs in order to provide the essential UWASN construction information to help and guide architects, developers and implementers of UWASNs.

Additionally, the ISO/IEC 30140 series provides high-level functional models related to underwater sensor nodes and relationships among the nodes to construct architectural perspective of UWASNs. However, the ISO/IEC 30140 series is an application agnostic standard. Thus, ISO/IEC 30140 series specifies neither any type of communication waveforms for use in UWASNs nor any underwater acoustic communication frequencies. Specifying communication waveforms and/or frequencies are the responsibility of architects, developers and implementers.¹

Acoustical data communication in sensor networks necessitates the introduction of acoustical signals that overlap biologically important frequency bands into the subject environment. These signals may conflict with regional, national, or international noise exposure regulations. Implementers of acoustical communication networks should consult the relevant regulatory agencies prior to designing and deployment of these systems to ensure compliance with regulations and avoid conflicts with the agencies.

<https://standards.iteh.ai/catalog/standards/sist/cf94ceb7-77e0-45cf-a39f-140135615638/iso-iec-30140-1-2018>

The purpose of the ISO/IEC 30140 series is to provide general requirements, guidance and facilitation in order for the users of the ISO/IEC 30140 series to design and develop the target UWASNs for their applications and services.

The ISO/IEC 30140 series comprises four parts as shown below.

Part 1 provides a general overview and requirements of the UWASN reference architecture.

Part 2 provides reference architecture models for UWASN.

Part 3 provides descriptions for the entities and interfaces of the UWASN reference architecture.

Part 4 provides information on interoperability requirements among the entities within a UWASN and among various UWASNs.

¹ Architects, developers and implementers need to be aware of the submarine emergency frequency band, near and below 12 kHz, and it is recommended to provide a provision for such submarine emergency band in their UWASN design and applications.

INFORMATION TECHNOLOGY – UNDERWATER ACOUSTIC SENSOR NETWORK (UWASN) –

Part 1: Overview and requirements

1 Scope

This part of ISO/IEC 30140 provides a general overview of underwater acoustic sensor networks (UWASN). It describes their main characteristics in terms of the effects of propagation variability and analyses the main differences with respect to terrestrial networks. It further identifies the specificities of UWASN and derives some specific and general requirements for these networks.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 29182-2, *Information technology – Sensor networks: Sensor Network Reference Architecture (SNRA) – Part 2: Vocabulary and terminology*

3 Terms and definitions

ISO/IEC 30140-1:2018

[https://standards.iteh.ai/catalog/standards/sist/cf94ceb7-77e0-45cf-a39f-](https://standards.iteh.ai/catalog/standards/sist/cf94ceb7-77e0-45cf-a39f-868a3023bd63/iso-iec-30140-1-2018)

[868a3023bd63/iso-iec-30140-1-2018](https://standards.iteh.ai/catalog/standards/sist/cf94ceb7-77e0-45cf-a39f-868a3023bd63/iso-iec-30140-1-2018)

For the purposes of this document, the terms and definitions given in ISO/IEC 29182-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

ad-hoc node

device in a wireless ad-hoc network

Note 1 to entry: A wireless ad-hoc network is defined in ISO/IEC 27033-6:2016[1],² 3.12, as a “decentralized wireless network which does not rely on a pre-existing infrastructure”.

3.2

cross-layer

technology that permits communication between different layers by allowing one layer to access data of another layer to exchange information and enable interaction

3.3

management cross-layer

technology that provides a system-level management service to all or selected OSI layers in a wireless network system

² Numbers in square brackets refer to the Bibliography.

Note 1 to entry: Examples of management cross-layer are device management cross-layer, network management cross-layer, QoS management cross-layer, security management cross-layer, localization management cross-layer, power management cross-layer, etc.

3.4 underwater acoustic fundamental network UWA-FN

wireless communication network that is built either exclusively using one or more cluster networks or exclusively using one or more ad-hoc networks for underwater environment using acoustic modems

Note 1 to entry: Fundamental network consists of only one network type, either cluster network or ad-hoc network.

Note 2 to entry: Wireless acoustic communication and data links are realized using an acoustic modem.

Note 3 to entry: A modem is defined in ISO/IEC 2382:2015[2], 2124386, as a “functional unit that modulates and demodulates signals”.

3.5 underwater acoustic united network UWA-UN

wireless communication network that is made of two or more underwater acoustic fundamental networks (3.4) and relay nodes

Note 1 to entry: A relay node is, for example, an unmanned underwater vehicle, communication node, beacon, etc.

3.6 underwater acoustic extended united network UWA-EUN

wireless communication network that is made of two or more underwater acoustic united networks (3.5)

3.7 underwater acoustic sensor node UWA-SNode

sensor network element that includes at least one sensor and, optionally actuators with communication capabilities and data processing capabilities, which is built for underwater applications using acoustic modem as a communication unit internal to this element

Note 1 to entry: Wireless acoustic communication and data links are realized using an acoustic modem.

Note 2 to entry: A modem is defined in ISO/IEC 2382:2015, 2124386, as a “functional unit that modulates and demodulates signals”.

[SOURCE: ISO/IEC 29182-2:2013, 2.1.8 – modified: the original definition of sensor node is adapted to an underwater acoustics context.]

3.8 underwater acoustic cluster head UWA-CH

unit that receives data from underwater acoustic sensor nodes (3.7) and transmits the data to one or more relay nodes or a nearby underwater acoustic gateway (3.9)

3.9 underwater acoustic gateway UWA-GW

unit connecting different underwater networks or parts of one underwater network and performing any necessary protocol translation in underwater environment using acoustic modem

[SOURCE: ISO/IEC TR 29108:2013, 3.1.88.3 – modified: the original definition is adapted to an underwater acoustics context.]

4 Abbreviated terms

| | |
|------------|---|
| 2D | two dimensional |
| 3D | three dimensional |
| BER | bit error rate |
| DG | distance group |
| DTN | delay and disruption tolerant network |
| EM | electromagnetic wave |
| EMI | electromagnetic interference |
| GPS | global positioning system |
| kbps | kilobits per second |
| LED | light emitting diode |
| μPa | Micropascal |
| Mbps | megabits per second |
| MCCP | minimum cost clustering protocol |
| QoS | quality of service |
| RF | radio frequency |
| RSS | received signal strength |
| UUV | unmanned underwater vehicle |
| UWASN | underwater acoustic sensor network |
| UWA-CH | underwater acoustic cluster head |
| UWA-DTN | underwater delay tolerant network |
| UWA-DTN-GW | underwater DTN gateway |
| UWA-EUN | underwater acoustic extend united network |
| UWA-FN | underwater acoustic fundamental network |
| UWA-GW | underwater acoustic gateway |
| UWA-SNode | underwater acoustic sensor node |
| UWA-UN | underwater acoustic united network |

5 UWASN overview and applications

5.1 Overview

Figure 1 shows the basic topology of UWASN. In a cluster-based network, the data sensed by underwater acoustic sensor nodes (UWA-SNodes) are transmitted via acoustic communication to an underwater acoustic gateway (UWA-GW) using an underwater acoustic cluster head (UWA-CH), unmanned underwater vehicle (UUV), or relay nodes. Users receive the transmitted data through various externally connected networks (e.g. radio frequency (RF) or satellite communication). During these processes, underwater communication is implemented by acoustic communication. In general, UWA-GWs are either moving nodes or fixed nodes. Topologies and communication configuration models could be adaptively modified according to the application domain's needs at any given time.

UWA-SNodes and UUVs positioned so as to perform collective underwater monitoring. UWA-SNodes and UUVs are organized autonomously into a network that should adapt to changing ocean environments over time.[4]

UWA-SNodes are applicable to pollution monitoring, oceanographic information gathering, strategic observation, assisted navigation, offshore examination, and disaster prevention. Several UUVs with equipped sensors explore underwater resources and gather precise location information. To make this possible, reliable underwater communication between UWA-SNodes and UUVs is required.

UWA-SNodes and UUVs should have self-configuration capabilities that allow them to network themselves. They should manage the operations by sharing location information, configurations, and movements, in order to send monitored data to an on-shore location.

5.2 Application domain of UWASN

A UWASN can realize unexplored underwater applications, increasing the capacity for detecting and forecasting changes in time-varying oceanic environments. Table 1 shows the UWASN market segments and their current and future potential applications.

Annex A provides a description of the selected application of UWASN.

Table 1 – UWASN market segments and their current and future applications list

| Market segment | Description |
|-------------------------|--|
| Scientific applications | Early warning system for detection of disasters and tsunamis, and providing warnings Studying the effects of oceanic earthquakes (seaquakes) Climate recording Pollution control Oil/gas fields exploration Detecting climate change Improving weather forecasting Studying marine biology Ocean circulation studies |
| Business applications | Discovery of natural resources Temperature monitoring in runtime Chemical and biological changes Detection of pipeline leakages Seismic monitoring allowing reservoir management approaches |
| Civilian applications | Assisted navigation Identifying hazards in the seabed Identifying submerged wrecks Identify the mooring positions Underwater hazard avoidance Defining seabed pipeline routes Identifying underwater oilfields Defining paths for the layering of underwater cables |
| Aqua applications | Aquaculture and farming Remote control-monitoring of costly devices |