

Designation: D4890 - 13 D4890 - 18

Standard Test Methods for Polyurethane Raw Materials: Determination of Gardner and APHA Color of Polyols¹

This standard is issued under the fixed designation D4890; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope*

- 1.1 These test methods measure visually the color of clear polyester and polyether liquids. They apply only to materials whose colors have light-absorption characteristics similar to those of the standards. An alternative method is Test Method D1209 (see
- 1.2 Units—The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.
- 1.3 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

Note 1—Test Method A of this standard is equivalent to ISO 6271-1. Test Method B of this standard is equivalent to ISO 4630-1.

1.4 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

2. Referenced Documents

2.1 ASTM Standards:²

D883 Terminology Relating to Plastics

D1103 Specification for Reagant Water D1193 Specification for Reagent Water

D1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)

D5386 Test Method for Color of Liquids Using Tristimulus Colorimetry

D6166 Test Method for Color of Pine Chemicals and Related Products (Instrumental Determination of Gardner Color)

E177 Practice for Use of the Terms Precision and Bias in ASTM Test Methods

E308 Practice for Computing the Colors of Objects by Using the CIE System

E691 Practice for Conducting an Interlaboratory Study to Determine the Precision of a Test Method

E1164 Practice for Obtaining Spectrometric Data for Object-Color Evaluation

2.2 ISO Standards:³

ISO 4630-1 Clear Liquids—Estimation of Colour by the Gardner Colour Scale—Part 1: Visual Method

ISO 4630-2 Clear Liquids—Estimation of Colour by the Gardner Colour Scale—Part 2: Spectroscopic Method

ISO 6271-1 Clear Liquids—Estimation of ColorColour by the Platinum-Cobalt Scale—Part 1: Visual Method

ISO 6271-2 Clear Liquids—Estimation of Color by the Platinum-Cobalt Scale—Part 2: Spectroscopic Method

3. Terminology

3.1 For definitions of terms used in these test methods see Terminology D883.

¹ These test methods are under the jurisdiction of Committee D20 on Plastics and are the direct responsibility of Subcommittee D20.22 on Cellular Materials - Plastics and Elastomers.

Current edition approved April 1, 2013Aug. 1, 2018. Published April 2013August 2018. Originally approved in 1988. Last previous edition approved in 20062013 as D4890 - 06.D4890 - 13. DOI: 10.1520/D4890-13.10.1520/D4890-18.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, http://www.ansi.org.



4. Summary of Test Method

- 4.1 In Test Method A, the color of the material to be tested is compared to a series of color standards with defined chromicitychromaticity coordinates, prepared onin one of three ways. The results are reported as the color standard, which best matches the sample.
- 4.2 In Test Method B, the color of the material to be tested is compared to a series of platinum-cobalt color standards, designated by mg of Pt/mL of standard solution. The results are reported as the color standard, which best matches the sample (see Note 2).

Note 2—Color of liquids are also measured by visible spectroscopy and the results converted to any of several color scales. These results are converted to the APHA scale by appropriate manipulations, as for example in Test Method D5386 and ISO 6271-2. These results are converted to the Gardner scale by appropriate manipulations, as for example in Test Method ISO 4630-2.

5. Significance and Use

5.1 These test methods are suitable for quality control, as specification tests, and for research. Color is an important property of urethane products.

6. Sampling

6.1 Polyesters and polyethers usually contain molecules covering an appreciable range of molecular weights. These have a tendency to fractionate during solidification. Unless the material is a liquid or finely ground solid it is necessary to melt (using no higher temperature than necessary) and mix the resin well before removing a sample for analysis. Many polyols are hygroscopic and care shouldmust be taken to provide minimum exposure to atmospheric moisture during the sampling.

7. Purity of Reagents

- 7.1 Purity of Reagents—Reagent-grade chemicals shall be used in all tests. Unless otherwise indicated, it is intended that all reagents shall conform to the specifications of the Committee on Analytical Reagents of the American Chemical Society, where such specifications are available. Other grades may be used, are acceptable, provided it is first ascertained that the reagent is of sufficiently high purity to permit its use without lessening reducing the accuracy of the determination.
- 7.2 Purity of Water—Unless otherwise indicated, references to water shall be understood to mean reagent water as defined by Type IV or better of Specification D1193.

TEST METHOD A—GARDNER COLOR

8. Apparatus

- 8.1 Gardner-Holdt Tubes, of clear glass, with closed, flat, even bottoms, and having the following approximate dimensions and markings:
 - 8.1.1 A uniform internal length of 112 mm,
 - d9-8flc-b609d4dc5625/astm-d4890-18 8.1.2 A uniform internal diameter throughout the length of the tube of 10.75 mm, and
- 8.1.3 An etched line around the outside of the tube 5 mm from the open end and a second etched line around the outside of the tube 13 mm from the open end.

9. Reagents

- 9.1 Cobalt Chloride Solution—Prepare a solution containing 1 part by weight of cobalt chloride (CoCl₂ × 6H₂O) to 3 parts of HCl (1 to 17).
- 9.2 Ferric Chloride Solution—Prepare a solution containing approximately 5 parts by weight of ferric chloride (FeCl₃ × 6H₂O) and 1.2 parts of HCl (1 to 17). Adjust to exact color equivalence to a freshly prepared solution containing 3 g of K₂Cr₂O₇ in 100 mL of H_2SO_4 (sp gr 1.84).
 - 9.3 Hydrochloric Acid (1 to 17)—Mix 1 volume of concentrated hydrochloric acid (HCl, sp gr 1.19) with 17 volumes of water.
 - 9.4 Hydrochloric Acid (0.1 N)—Prepare 0.1 N HCl.
 - 9.5 Potassium Chloroplatinate (PtCl₆).
 - 9.6 Potassium Dichromate (K₂Cr₂O₇).
 - 9.7 Sulfuric Acid (sp gr 1.84)—Concentrated sulfuric acid (H₂SO₄).

⁴ Reagent Chemicals, American Chemical Society Specifications, American Chemical Society, Washington, DC. For suggestions on the testing of reagents not listed by the American Chemical Society, see Analar Standards for Laboratory Chemicals, BDH Ltd., Poole, Dorset, U.K., and the United States Pharmacopeia and National Formulary, U.S. Pharmacopeial Convention, Inc. (USPC), Rockville, MD.

TABLE 1 Gardner Reference Standard Color Solutions

Gardner Color Standard — Number	Chromaticity Coordinates ^A			Potassium	Iron-Cobalt Solutions			Potassium
	Υ	х	У	 Chloroplatinate, - g/1000 mL of 0.1 N HCl 	Ferric Chloride Solution, mL	Cobalt Chloride Solution, mL	Hydrochloric Acid, mL	Dichromate, g/100 mL Sulfuric Acid ^B
1	80	0.3177	0.3303	0.550				0.0039
2	79	0.3233	0.3352	0.865				0.0048
3	76	0.3329	0.3452	1.330				0.0071
4	75	0.3437	0.3644	2.080				0.0112
5	74	0.3558	0.3840	3.035				0.0205
6	71	0.3767	0.4061	4.225				0.0322
7	67	0.4044	0.4352	6.400				0.0384
8	64	0.4207	0.4498	7.900				0.0515
9	61	0.4343	0.4640		3.8	3.0	93.2	0.0780
10	57	0.4503	0.4760		5.1	3.6	91.3	0.164
11	45	0.4842	0.4818		7.5	5.3	87.2	0.250
12	36	0.5077	0.4638		10.8	7.6	81.6	0.380
13	30	0.5392	0.4458		16.6	10.0	73.4	0.572
14	22	0.5646	0.4270		22.2	13.3	64.5	0.763
15	16	0.5857	0.4089		29.4	17.6	53.0	1.041
16	11	0.6047	0.3921		37.8	22.8	39.4	1.280
17	6	0.6290	0.3701		51.3	25.6	23.1	2.220
18	4	0.6477	0.3521		100.0	0.0	0.0	3.00

^A Chromaticity coordinates for CIE standard illuminant C and the CIE 1931 (2°) standard observer.

10. Gardner Color Reference Standards⁵

- 10.1 The primary standards for color shall consist of solutions defined by their spectral transmittance in 1-cm cell with parallel sides. The chromaticity coordinates of these solutions shall conform to those given in Table 1 when determined on a 1-cm layer of the solution in accordance with Practice E1164 and Test Methods E308 and D6166.
- 10.2 For comparison, permanent solutions of known color are more satisfactory. The approximate composition of solutions giving each of the 18 Gardner colors is also given in Table 1. The solutions shall be made from K₂PtCl₆ in 0.1 N HCl, or, in the darker colors, from stock solutions of FeCl₃, CoCl₂, and HCl (see 9.1, 9.2, and 9.3). Pre-prepared Gardner color standard solutions are commonly available for purchase.
- 10.3 If the solutions in 10.2 are unavailable, solutions of $K_2Cr_2O_7$ (sp gr 1.84) are used as reference standards. The approximate composition of these standards is also given in Table 1. Each solution must be freshly made for the color comparison, using gentle heat, if necessary, to effect solution.
- 10.4 Secondary reference standards may be obtained are available in the form of 18 colored glass disks, which are set into a pair of larger, plastic disks and the latter mounted to rotate in a housing for holding the sample tube and glass disk in close and fixed proximity.

11. Procedure

- 11.1 Fill the tube with sample, free of solid particles or air bubbles, so that the apparent upper edge of the liquid meniscus is even with the lower etched line on the tube.
- 11.2 Determine the color by comparison with the reference standard solutions prescribed in Table 1, by comparing the sample and the standard in Gardner-Holdt viscosity tubes as described. Make the comparison at 25 ± 5 °C by placing tubes close together and looking through them against a white background or by comparison to the standards in a color disk.

12. Report

12.1 Report the color of the sample in terms of the Gardner standard number that is nearest to it in color. If the sample appears exactly halfway between two standards, report the color number of the darker standard.

13. Precision and Bias⁶

13.1 The Table 2 precision of this test method is based on an interlaboratory study conducted in 2011. Six laboratories tested two different polyurethane materials. Every "test result" represents an individual determination. Each laboratory reported three replicate test results for each material. Practice E691 was followed for the design and analysis of the data; the details are given in ASTM Research Report No. D20-1257.

^B The dichromate color standards have been found to be less reliable than chloroplatinate or iron-cobalt color standards. They are included in Table 1 for reference only.

⁵ The sole source of supply of the glass color standards and color standard solutions known to the committee at this time is BYK-Gardner USA, 9104 Guilford Road, Columbia, MD 21046. If you are aware of alternative suppliers, please provide this information to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend.

⁶ Supporting data have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:D20-1257. Contact ASTM Customer Service at service@astm.org.