

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Optical fibres – **iTeh STANDARD PREVIEW**
Part 2-50: Product specifications – Sectional specification for class B single-
mode fibres
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/c729de75-e2b5-44e9-af12-4e4910000000/iec-60793-2-50-2018>
IEC 60793-2-50:2018
Fibres optiques –
Partie 2-50: Spécifications de produits – Spécification intermédiaire pour les
fibres unimodales de classe B





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2018 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 21 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

67 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Optical fibres – iTeh STANDARD PREVIEW
Part 2-50: Product specifications – Sectional specification for class B single-
mode fibres
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/c729de75-e2b5-44e9-af12-284889411c46/iec-60793-2-50>

Fibres optiques –
Partie 2-50: Spécifications de produits – Spécification intermédiaire pour les
fibres unimodales de classe B

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.180.10

ISBN 978-2-8322-6280-1

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references	8
3 Terms and definitions	9
4 Abbreviated terms and symbols	10
5 Specifications	10
5.1 General.....	10
5.2 Dimensional requirements.....	10
5.3 Mechanical requirements	11
5.4 Transmission requirements	12
5.5 Environmental requirements	13
5.5.1 General	13
5.5.2 Optical environmental requirements – Attenuation	14
5.5.3 Mechanical environmental requirements	14
Annex A (normative) Family specification for category B-652 Dispersion unshifted single-mode fibres	16
A.1 General.....	16
A.2 Dimensional requirements.....	16
A.3 Mechanical requirements	17
A.4 Transmission requirements	17
A.5 Hydrogen ageing for sub-category B-652 D.....	19
A.6 Environmental requirements	19
Annex B (normative) Family specification for category B-653 Dispersion shifted single-mode fibres	20
B.1 General.....	20
B.2 Dimensional requirements.....	20
B.3 Transmission requirements	21
B.3.1 General	21
B.3.2 Chromatic dispersion coefficient requirement for sub-category B-653.A fibres	21
B.3.3 Chromatic dispersion coefficient requirement for sub-category B-653.B fibres	22
B.4 Environmental requirements	22
Annex C (normative) Family specification for category B-654 cut-off shifted single-mode fibres.....	23
C.1 General.....	23
C.2 Dimensional requirements.....	23
C.3 Mechanical requirements	23
C.4 Chromatic dispersion parameters for B-654.E fibres	25
C.5 Environmental requirements	25
Annex D (normative) Family specification for category B-655 non-zero dispersion shifted single-mode fibres	26
D.1 General.....	26
D.2 Dimensional requirements.....	26
D.3 Mechanical requirements	26
D.4 Transmission requirements	27
D.4.1 General	27

D.4.2	Chromatic dispersion coefficient limits for sub-category B-655.C fibres.....	27
D.4.3	Chromatic dispersion coefficient limits for sub-category B-655.D fibres.....	28
D.4.4	Chromatic dispersion coefficient limits for sub-category B-655.E fibres.....	28
D.5	Environmental requirements	28
Annex E (normative)	Family specification for category B-656 Wideband non-zero dispersion shifted single-mode fibres	29
E.1	General.....	29
E.2	Dimensional requirements.....	29
E.3	Mechanical requirements	29
E.4	Transmission requirements	30
E.4.1	General	30
E.4.2	Chromatic dispersion coefficient for category B-656 fibres.....	30
E.5	Environmental requirements	31
Annex F (normative)	Family specification for category B-657 Bending loss insensitive single-mode fibres	32
F.1	General.....	32
F.2	Dimensional requirements.....	32
F.3	Mechanical requirements	33
F.4	Transmission requirements	33
F.5	Environmental requirements	35
Annex G (informative)	System design information for category B-655 non-zero dispersion shifted single-mode fibres	36
G.1	General.....	36
G.2	One standard deviation limits for sub-category B-655.D fibres	36
G.3	One standard deviation limits for sub-category B-655.E fibres.....	37
Bibliography.....		39
Figure G.1	– Sub-category B-655.D chromatic dispersion coefficient limits	37
Figure G.2	– Sub-category B-655.E chromatic dispersion coefficient limits	38
Table 1	– Map of IEC designation to ITU-T Recommendations and IEC 60793-2-50:2015 designation.....	8
Table 2	– Dimensional attributes and measurement methods.....	11
Table 3	– Dimensional requirements common to all category B fibres	11
Table 4	– Mechanical attributes and test methods.....	11
Table 5	– Mechanical requirements common to all class B fibres	12
Table 6	– Transmission attributes and measurement methods	12
Table 7	– Transmission, requirements common to all class B fibres	13
Table 8	– Additional transmission attributes required in the family specifications	13
Table 9	– Environmental exposure tests	13
Table 10	– Attributes measured in environmental exposure tests	13
Table 11	– Change in attenuation for environmental tests.....	14
Table 12	– Coating strip force for environmental tests.....	14
Table 13	– Tensile strength for environmental tests	15
Table 14	– Stress corrosion susceptibility for environmental tests.....	15
Table A.1	– Dimensional requirements specific to category B-652.B fibres.....	16
Table A.2	– Dimensional requirements specific to category B-652.D fibres	17

Table A.3 – Mechanical requirements specific to category B-652 fibres	17
Table A.4 – Transmission requirements specific to sub-category B-652.B fibres	18
Table A.5 – Transmission requirements specific to sub-category B-652.D Fibres	18
Table A.6 – Chromatic dispersion properties for sub-category B-652.D fibres	19
Table B.1 – Dimensional requirements specific to category B-653 fibres	20
Table B.2 – Mechanical requirements specific to category B-653 fibres	21
Table B.3 – Transmission requirements specific to category B-653 fibres	21
Table C.1 – Dimensional requirements specific to category B-654 fibres.....	23
Table C.2 – Mechanical requirements specific to category B-654 fibres	24
Table C.3 – Transmission requirements specific to category B-654 fibres	24
Table D.1 – Dimensional requirements specific to category B-655 fibres.....	26
Table D.2 – Mechanical requirements specific to category B-655 fibres	27
Table D.3 – Transmission requirements specific to category B-655 fibres	27
Table E.1 – Dimensional requirements specific to category B-656 fibres.....	29
Table E.2 – Mechanical requirements specific to category B-656 fibres	30
Table E.3 – Transmission requirements specific to category B-656 fibres	30
Table F.1 – Dimensional requirements specific to category B-657 fibres	33
Table F.2 – Mechanical requirements specific to category B-657 fibres.....	33
Table F.3 – Transmission requirements specific to category B-657 fibres	34
Table G.1 – Examples for $\lambda_{\min} = 1\,530\text{ nm}$ and $\lambda_{\max} = 1\,565\text{ nm}$	36

[IEC 60793-2-50:2018](https://standards.iteh.ai/catalog/standards/sist/c729de75-e2b5-44e9-af12-271418494afe/iec-60793-2-50-2018)

<https://standards.iteh.ai/catalog/standards/sist/c729de75-e2b5-44e9-af12-271418494afe/iec-60793-2-50-2018>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

OPTICAL FIBRES –

**Part 2-50: Product specifications –
Sectional specification for class B single-mode fibres**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
<https://standards.iteh.ai/catalog/standards/sist/c729de75-e2b5-44e9-af12->
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60793-2-50 has been prepared by subcommittee 86A: Fibres and cables, of IEC technical committee 86: Fibre optics.

The sixth edition cancels and replaces the fifth edition published in 2015. This edition constitutes a technical revision. This edition includes the following significant technical changes with respect to the previous edition:

- a) Introduction of a revised naming convention which better matches with those found in ITU-T Recommendations G.652, G.653, G.654, G.655, G.656, and G.657. These changes are outlined in the scope of this document along with a cross reference table for the new names. Annexes have been rearranged to improve clarity based on the new naming;
- b) Further details on the requirements for 200 micron coated single-mode fibre;
- c) Harmonization with the following ITU-T Recommendations published in November 2016: G.652, G.654, G.657 including revised chromatic dispersion specifications, new categories and new application spaces for these fibre categories;

d) Descriptions of fibre types have been added to the titles of Annexes A to F.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
86A/1884/FDIS	86A/1898/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 60793 series, published under the general title *Optical fibres*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

OPTICAL FIBRES –

Part 2-50: Product specifications – Sectional specification for class B single-mode fibres

1 Scope

This part of IEC 60793 is applicable to optical fibre categories B-652, B-653, B-654, B-655, B-656 and B-657. A map illustrating the connection of IEC designations to ITU-T designations is shown in Table 1. These fibres are used or can be incorporated in information transmission equipment and optical fibre cables.

Three types of requirements apply to these fibres:

- general requirements, as defined in IEC 60793-2;
- specific requirements common to the class B single-mode fibres covered in this document and which are given in Clause 5;
- particular requirements applicable to individual fibre categories or specific applications, which are defined in Annexes A to F.

For some fibre categories (shown in the relevant family specifications), there are sub-categories that are distinguished on the basis of difference in transmission attribute specifications. The designations for these sub-categories are documented in the individual family specifications.

<https://standards.iteh.ai/catalog/standards/sist/c729dc75-e2b5-44e9-af12-271d1849494e/iec-60793-2-50-2018>

Table 1 shows a map from the IEC designations to the ITU-T recommendations. The table also provides the normative annex in this document that contains the detailed specification as well as the name used to describe this fibre type in IEC 60793-2-50:2015. The ITU-T recommendations as well as the IEC categories/sub-categories within each recommendation are given. In some cases, as for Recommendation G.652, a given IEC designation maps to multiple categories in the ITU-T because the ITU-T categories are distinguished by cabled fibre attribute (PMD_Q) performance which are not distinguished in the IEC fibre specifications.

Table 1 – Map of IEC designation to ITU-T Recommendations and IEC 60793-2-50:2015 designation

Annex	Category	Sub Category	Description	IEC 60793-2-50:2015	ITU-T Rec
	B-652		Dispersion unshifted fibre		G.652
A		B-652.B		B1.1	G.652.B
A		B-652.D		B1.3	G.652.D
	B-653		Dispersion shifted fibre		G.653
B		B-653.A		B2_a	G.653.A
B		B-653.B		B2_b	G.653.B
	B-654		Cut-off shifted fibre		G.654
C		B-654.A		B1.2_a	G.654.A
C		B-654.B		B1.2_b	G.654.B
C		B-654.C		B1.2_c	G.654.C
C		B-654.D		N/A	G.654.D
C		B-654.E		N/A	G.654.E
C	B-655		Non-zero dispersion shifted fibre	B4	G.655
D		B-655.C		B4_c	G.655.C
D		B-655.D		B4_d	G.655.D
D		B-655.E		B4_e	G.655.E
E	B-656		Wideband non-zero dispersion shifted fibre	B5	G.656
F	B-657		Bending loss insensitive fibre	B6	G.657
F		B-657.A1		B6_a1	G.657.A1
F		B-657.A2		B6_a2	G.657.A2
F		B-657.B2		B6_b2	G.657.B2
F		B-657.B3		B6_b3	G.657.B3

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60793-1 (all parts), *Optical fibres*

IEC 60793-1-20, *Optical fibres – Part 1-20: Measurement methods and test procedures – Fibre geometry*

IEC 60793-1-21, *Optical fibres – Part 1-21: Measurement methods and test procedures – Coating geometry*

IEC 60793-1-22, *Optical fibres – Part 1-22: Measurement methods and test procedures – Length measurement*

IEC 60793-1-30, *Optical fibres – Part 1-30: Measurement methods and test procedures – Fibre proof test*

IEC 60793-1-31, *Optical fibres – Part 1-31: Measurement methods and test procedures – Tensile strength*

IEC 60793-1-32, *Optical fibres – Part 1-32: Measurement methods and test procedures – Coating strippability*

IEC 60793-1-33, *Optical fibres – Part 1-33: Measurement methods and test procedures – Stress corrosion susceptibility*

IEC 60793-1-34, *Optical fibres – Part 1-34: Measurement methods and test procedures – Fibre curl*

IEC 60793-1-40, *Optical fibres – Part 1-40: Measurement methods and test procedures – Attenuation*

IEC 60793-1-42, *Optical fibres – Part 1-42: Measurement methods and test procedures – Chromatic dispersion*

IEC 60793-1-44, *Optical fibres – Part 1-44: Measurement methods and test procedures – Cut-off wavelength*

IEC 60793-1-45, *Optical fibres – Part 1-45: Measurement methods and test procedures – Mode field diameter*

IEC 60793-1-46, *Optical fibres – Part 1-46: Measurement methods and test procedures – Monitoring of changes in optical transmittance*

IEC 60793-1-47, *Optical fibres – Part 1-47: Measurement methods and test procedures – Macrobending loss* <https://standards.iteh.ai/catalog/standards/sist/c729de75-e2b5-44e9-af12-271418494afe/iec-60793-2-50-2018>

IEC 60793-1-48, *Optical fibres – Part 1-48: Measurement methods and test procedures – Polarization mode dispersion*

IEC 60793-1-50, *Optical fibres – Part 1-50: Measurement methods and test procedures – Damp heat (steady state) tests*

IEC 60793-1-51, *Optical fibres – Part 1-51: Measurement methods and test procedures – Dry heat (steady state) tests*

IEC 60793-1-52, *Optical fibres – Part 1-52: Measurement methods and test procedures – Change of temperature tests*

IEC 60793-1-53, *Optical fibres – Part 1-53: Measurement methods and test procedures – Water immersion tests*

IEC 60793-2, *Optical fibres – Part 2: Product specifications – General*

IEC 60794-2, *Optical fibre cables – Part 2: Indoor cables – Sectional specification*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60793-2 and the IEC 60793-1 series apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

NOTE General definitions for fibres are provided in IEC 60793-2. The definitions of the specified attributes are contained in the relevant test methods standard of the IEC 60793-1 series, while general definitions for testing are provided in IEC 60793-1-1.

4 Abbreviated terms and symbols

For the purposes of this document, the following abbreviated terms and symbols apply:

F_{avg}	Average strip force
F_{peak}	Peak strip force
λ_0	Zero dispersion wavelength
λ_c	Fibre cut-off wavelength
λ_{cc}	Cable cut-off wavelength
MFD	Mode field diameter
n_d	Stress corrosion parameter – dynamic
PMD	Polarization mode dispersion
PMD_Q	PMD link design value

Iteh STANDARD PREVIEW
(standards.iteh.ai)

5 Specifications

[IEC 60793-2-50:2018](#)

5.1 General <https://standards.iteh.ai/catalog/standards/sist/c729de75-e2b5-44e9-af12-271418494afe/iec-60793-2-50-2018>

The fibre shall consist of a glass core and glass cladding in accordance with the construction of optical fibre class B – single-mode fibre – as given in IEC 60793-2.

The term “glass” usually refers to material consisting of non-metallic oxides. The composition of some fibres may be all glass, or glass and glass/hard polymeric composites.

5.2 Dimensional requirements

Relevant dimensional attributes and measurement methods are given in Table 2.

Requirements common to all categories of class B single-mode fibres are given in Table 3.

Cladding diameter, cladding non-circularity, and core – cladding concentricity error shall be specified in the family specifications

Table 2 – Dimensional attributes and measurement methods

Attribute	Measurement method
Cladding diameter	IEC 60793-1-20
Cladding non-circularity	IEC 60793-1-20
Core – cladding concentricity error	IEC 60793-1-20
Primary coating diameter	IEC 60793-1-21
Primary coating non-circularity	IEC 60793-1-21
Primary coating-cladding concentricity error	IEC 60793-1-21
Fibre length	IEC 60793-1-22

Table 3 – Dimensional requirements common to all category B fibres

Attribute	Unit	Limit
Primary coating diameter – uncoloured	µm	235 to 255 ^a
Primary coating diameter – coloured	µm	235 to 265 ^a
Primary coating-cladding concentricity error	µm	≤ 12,5
Fibre length	km	^b

^a The above limits on primary coating diameter are most commonly used in telecommunications cables. There are other applications, such as fibre for use within optical sub-systems, pigtails, or specialty applications such as for submarines cables or for compact FTTH cables, which use other primary coating diameters, several of which are listed below.

180 µm to 210 µm uncoloured; 180 µm to 220 µm coloured

400 µm ± 40 µm

500 µm ± 50 µm

700 µm ± 70 µm

900 µm ± 90 µm

Alternative coating diameters may impact fibre connectivity such as ribbons, multi-fibre connectors, mechanical splices, and fusion splice protectors; they may also need adjustments to connectivity tools and/or tighter coating tolerances.

^b Length requirements vary and should be agreed between supplier and customer.

5.3 Mechanical requirements

Relevant mechanical attributes and test methods are given in Table 4. The relationship between some of these attributes and mechanical reliability are described in IEC TR 62048 and ITU-T G.Sup.59.

Requirements common to all categories of class B single-mode fibres are given in Table 5.

Table 4 – Mechanical attributes and test methods

Attribute	Test method
Proof test	IEC 60793-1-30
Tensile strength	IEC 60793-1-31
Coating strippability	IEC 60793-1-32
Stress corrosion susceptibility	IEC 60793-1-33
Fibre curl	IEC 60793-1-34

Table 5 – Mechanical requirements common to all class B fibres

Attribute	Unit	Limit
Proof stress level	GPa	$\geq 0,69$ ^a
Coating strip force (average) ^{b, c}	N	$1,0 \leq F_{ave} \leq 5,0$
Coating strip force (peak) ^{b, c}	N	$1,0 \leq F_{peak} \leq 8,9$
Fibre curl radius	m	≥ 2 ^d
Tensile strength (median) for 0,5 m specimen length	GPa	$\geq 3,8$
Stress corrosion susceptibility parameter, n_d	–	≥ 18

^a The proof test value of 0,69 GPa equals about 1 % strain or about 8,8 N force. For the relation between these different units, see IEC TR 62048:2014, clause 8.4.

^b Either average strip force or peak strip force, which are defined in the test procedure, may be specified with agreement between supplier and customer.

^c In case of alternative nominal primary coating diameters (see Table 2), associated alternative coating strip force values need to be agreed between supplier and customer or provided in the detailed specifications provided in Annexes of this document.

^d Depending on splicing methods, a minimum of 4 m may be specified for fibre intended to be used in some cable constructions – such as ribbon cable.

5.4 Transmission requirements

Relevant transmission attributes and measurement methods are given in Table 6.

Requirements common to all categories of class B single-mode fibres are shown in Table 7.

Requirements that shall be specified in the family specifications are listed in Table 8.

Table 6 – Transmission attributes and measurement methods

Attribute	Measurement method
Attenuation coefficient	IEC 60793-1-40 ^a
Chromatic dispersion	IEC 60793-1-42
Cut-off wavelength ^b	IEC 60793-1-44
Mode field diameter	IEC 60793-1-45
Change of optical transmission	IEC 60793-1-46
Macrobending loss	IEC 60793-1-47
Polarization mode dispersion	IEC 60793-1-48

The indicated maximum attenuation values apply to cabled and uncabled optical fibres. Tighter specifications for the fibre may be requested to account for added attenuation in the cabling process; for the maximum cabled attenuation values, reference is made to IEC 60794-2, which can be used in conjunction with this document.

^a The attenuation coefficient at various wavelengths can be calculated using the measured values at a few wavelengths using a spectral model such as that given in IEC 60793-1-40. For example, the attenuation at 1 480 nm can be calculated and used for design of systems that employ remote pumping of optical amplifiers. When using Method C, OTDR, additional guidance information in IEC TR 62316 shall be taken into account. As reported in IEC 60793-1-40:20xx, the spectral attenuation model has been demonstrated on all class B fibres.

^b There are two ways to measure cut-off wavelength, leading to: fibre cut-off wavelength λ_c and to cable cut-off wavelength λ_{cc} , respectively. The correlation of the measured values of λ_c and λ_{cc} depends on the specific fibre and cable design and the test conditions. While in general $\lambda_{cc} < \lambda_c$ a general quantitative relationship cannot be easily established, the importance of ensuring single-mode transmission in the minimum cable length between joints at the minimum operating wavelength is paramount. This may be performed by recommending the maximum cable cut-off wavelength λ_{cc} of a cabled single-mode fibre to be 1 260 nm or for worst case length and bends by recommending a maximum fibre cut-off wavelength λ_c to be 1 260 nm.

Table 7 – Transmission, requirements common to all class B fibres

Attribute	Unit	Limit
Polarization mode dispersion (PMD) coefficient link design value (PMD_Q)	ps/\sqrt{km}	^a
^a A maximum value of PMD_Q on uncabled fibre shall be agreed between supplier and customer to satisfy the primary requirement of cable PMD, given in IEC 60794-3.		

Table 8 – Additional transmission attributes required in the family specifications

Attribute
Attenuation coefficient and wavelengths
Chromatic dispersion characteristics
Nominal mode field diameter (MFD) range and wavelength
Mode field diameter tolerance
Cable cut-off wavelength, λ_{cc}
Macrobending loss including: wavelength, mandrel size, and number of turns
Cladding diameter
Cladding non-circularity
Core – cladding concentricity error

iTech STANDARD PREVIEW
(standards.iteh.ai)

For category B-655 fibre, information for system design is given in Annex G.

5.5 Environmental requirements IEC 60793-2-50:2018

<https://standards.iteh.ai/catalog/standards/sist/c729de75-e2b5-44e9-af12-271418494afe/iec-60793-2-50-2018>

5.5.1 General

Environmental exposure tests and measurement methods are documented in two forms:

- relevant environmental attributes and test methods are given in Table 9;
- measurements of a particular mechanical or transmission attributes that may change on the application of the environment are listed in Table 10.

Table 9 – Environmental exposure tests

Attribute	Test method
Damp heat tests	IEC 60793-1-50
Dry heat tests	IEC 60793-1-51
Change of temperature tests	IEC 60793-1-52
Water immersion tests	IEC 60793-1-53

Table 10 – Attributes measured in environmental exposure tests

Attribute	Test method
Change in optical transmission	IEC 60793-1-46
Attenuation	IEC 60793-1-40
Coating strip force	IEC 60793-1-32
Tensile strength	IEC 60793-1-31
Stress corrosion susceptibility	IEC 60793-1-33