

IEC TR 61948-4

Edition 2.0 2019-03 REDLINE VERSION

TECHNICAL REPORT



Nuclear medicine instrumentation - Routine tests -

Part 4: Radionuclide calibrators
(https://standards.iteh.ai)





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch

www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.



IEC TR 61948-4

Edition 2.0 2019-03 REDLINE VERSION

TECHNICAL REPORT



Nuclear medicine instrumentation – Routine tests –
Part 4: Radionuclide calibrators

Document Preview

IEC TR 61948-4:2019

https://standards.iteh.ai/catalog/standards/iec/2c08c32c-d199-4da4-904b-a3c6d79f9ba7/iec-tr-61948-4-2019

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 11.040.50 ISBN 978-2-8322-6727-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FC	DREWO	RD	3	
1	Scop	e	6	
2	Norm	native references	6	
3	Term	s and definitions	6	
4	Test	methods	8	
	4.1	BACKGROUND RESPONSE	8	
	4.2	Constancy of instrument response	8	
	4.3	SYSTEM LINEARITY	8	
	4.3.1	General	8	
	4.3.2	Decaying source method	9	
	4.3.3	Data analysis	9	
	4.4	Additional checks	9	
	4.5	Frequency of ROUTINE TESTS	9	
Bi	Bibliography1			
In	dex of d	lefined terms1	1	
Ta	ıble 1 –	Frequency of ROUTINE TESTS	9	

(https://standards.iteh.ai) **Document Preview**

IEC TR 61948-4:2019

https://standards.iteh.ai/catalog/standards/iec/2c08c32c-d199-4da4-904h-a3c6d79f9ba7/iec-tr-61948-4-2019

INTERNATIONAL ELECTROTECHNICAL COMMISSION

NUCLEAR MEDICINE INSTRUMENTATION – ROUTINE TESTS –

Part 4: Radionuclide calibrators

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 61948-4, which is a Technical Report, has been prepared by subcommittee 62C: Equipment for radiotherapy, nuclear medicine and radiation dosimetry, of IEC technical committee 62: Electrical equipment in medical practice.

This second edition cancels and replaces the first edition published in 2006. This edition constitutes a technical revision.

This edition includes the following significant technical change with respect to the previous edition: the test method to determine SYSTEM LINEARITY has been updated to reflect the technical developments of RADIONUCLIDE CALIBRATORS.

The text of this Technical Report is based on the following documents:

Draft TR	Report on voting
62C/715/DTR	62C/727/RVDTR

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

Terms used throughout this document that have been defined in Clause 3 appear in SMALL CAPITALS.

A list of all parts in the IEC 61948 series, published under the general title *Nuclear medicine Instrumentation – Routine tests*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

INTRODUCTION

This technical report is based on the German Standard DIN 6855-11, Qualitätsprüfung nuklearmedizinischer Messsysteme – Teil 11: Konstanzprüfung von Aktivimetern, the English document Protocol for Establishing and Maintaining the Calibration of Medical Radionuclide Calibrators and their Quality Control, the Austrian document ÖNORM S 5270, Aktivimeter – Richtlinien für die Konstanzprüfung am Verwendungsort / Radionuclide calibrators – Guidelines for the constancy testing in the field / Calibrateurs de radionucléides – Directives pour l'essai de constance à l'endroit d'utilisation, of 1 April 1998, and the Spanish document Protocolo Nacional del Control de Calidad en la Instrumentación en Medicina Nuclear.

iTeh Standards (https://standards.iteh.ai) Document Preview

EC TR 61948-4:2019

https://standards.iteh.ai/catalog/standards/iec/2c08c32c-d199-4da4-904h-a3c6d79f9ha7/iec-tr-61948-4-2019

NUCLEAR MEDICINE INSTRUMENTATION – ROUTINE TESTS –

Part 4: Radionuclide calibrators

1 Scope and object

This part of IEC 61948 covers the ROUTINE TESTING of RADIONUCLIDE CALIBRATORS used in nuclear medicine. Such devices utilise ionisation chambers of the well type (directly coupled to an appropriate electronic circuitry (IEC 61145)) and a direct readout in units of ACTIVITY. Requirements and specific methods to determine performance parameters are described in IEC 61303 and IEC 61145. These methods are primarily designed for ACCEPTANCE TESTING.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TR 60788:2004, Medical electrical equipment – Glossary of defined terms

IEC 61145:1992, Calibration and usage of ionization chamber systems for assay of radionuclides

IEC 61303:1994, Medical electrical equipment – Radionuclide calibrators – Particular methods for describing performance

IEC 61948-1:2001, Nuclear medicine instrumentation - Routine tests - Part 1: Radiation counting systems

3 Terms and definitions

For the purpose of this document, the terms and definitions given in IEC TR 60788:2004, IEC 61303:1994 and IEC 61145:1992, some of which are repeated here for convenience, and the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

NOTE Defined terms are printed in small capital letters.

2 1

ACCEPTANCE TEST

test carried out at the request and with the participation of the user or his representative to ascertain by determination of proper performance parameters that the instrument meets the specifications claimed by the vendor

NOTE—An ACCEPTANCE TEST should be carried out at the time of installation and when appropriate after major service. During or immediately after acceptance testing, REFERENCE DATA are collected to be used as a standard for comparison with future ROUTINE TESTS.

[IEC 61948-1:2001, definition 3.2.1]

test carried out after new equipment has been installed, or major modifications have been made to existing equipment, in order to verify compliance with contractual specifications

Note 1 to entry: During or immediately after ACCEPTANCE TEST, REFERENCE DATA are collected to be used as a standard for comparison with future ROUTINE TESTS.

[SOURCE: IEC TR 60788:2004, rm-70-01, modified -A note to entry has been added.]

3.2

BACKGROUND RESPONSE

reading of the instrument without intended RADIOACTIVE SOURCE

Note 1 to entry: The BACKGROUND RESPONSE is caused by external radiation fields, but in addition also by electronic noise and contamination.

3.3

CERTIFIED RADIOACTIVE STANDARD SOURCE

RADIOACTIVE SOURCE that has been calibrated by a laboratory recognized as a country's national standardizing laboratory for radioactivity measurements and has been so certified by the aforementioned laboratory

[SOURCE: IEC 61303:1994, 2.1.1]

3.4

IONISATION CHAMBER TEST SOURCE

RADIOACTIVE SOURCE used for the determination of the long-term stability of an ionisation chamber

Note 1 to entry: The half-life of the source shall be greater than five years and the effects of any radioactive contaminants shall be such that the indication of the device over a period of five years would not deviate by more than 0,5 % after decay correction for the known half-life of the principal radionuclide.

[SOURCE: IEC 61303:1994, 2.7, modified – Part of the definition has been moved to a note to entry, and a second note to entry has been added.]

3.5

RADIONUCLIDE CALIBRATOR

device for measuring the ACTIVITY of a radioactive sample

[SOURCE: IEC 61303:1994, 2.11]

3.6

REFERENCE DATA

set of data measured immediately after ACCEPTANCE TESTING, using test methods designed for

[SOURCE: IEC TR 61948-1:2001 2016,3.2.3 3.7]

3.7

ROUTINE TEST

test of a piece of equipment or its components which is repeated at specified intervals, to establish and document changes from the initial status described by REFERENCE DATA

Note 1 to entry: A ROUTINE TEST could be carried out by the user with simple methods and equipment.

[SOURCE: IEC TR 61948-1:2001 2016, 3.2.2 3.8]

3 8

SYSTEM LINEARITY

function relating the observed and predicted ACTIVITY values when the ACTIVITY of a specified RADIOACTIVE SOURCE is varied

[SOURCE: IEC 61303:1994, 2.4]

3.9

TRACEABLE RADIOACTIVE STANDARD SOURCE

RADIOACTIVE SOURCE that has been calibrated by comparing it to a CERTIFIED RADIOACTIVE STANDARD SOURCE or to another TRACEABLE RADIOACTIVE STANDARD SOURCE of the same radionuclide

[SOURCE: IEC 61303:1994, 2.1.2]

3.4

radionuclide factor

factor, dependent on the radionuclide, by which the response of the system must be multiplied in order to obtain the correct ACTIVITY reading of a source which has been placed in the ionization chamber

IEC 61303:1994, definition 2.21

3.7

radioactive standard source

general term used to refer to the standard sources listed below

[IEC 61303:1994, definition 2.1]

Document Preview

4 Test methods

IEC TR 61948-4:2019

4.1 BACKGROUND RESPONSE

The BACKGROUND RESPONSE shall be is obtained with the setting that corresponds to the most often used nuclide. The measurement should be is made with the sample holder in place. The reading of the background is reported.

4.2 Constancy of instrument response

The constancy of instrument response of the RADIONUCLIDE CALIBRATOR and, hence, its calibration—shall be is obtained for a specified radionuclide setting by inserting the IONISATION CHAMBER TEST SOURCE into the measurement position. The instrument reading—shall be is compared to the REFERENCE DATA and reported.

4.3 SYSTEM LINEARITY

4.3.1 General

The test of SYSTEM LINEARITY shall cover all the range of ACTIVITY used in the facility. The sample of the radionuclide used shall be introduced into the measuring position of the device under test. The ACTIVITY shall be measured so that at least one data point is measured per decade of the instrument scale.

The test of SYSTEM LINEARITY covers the range of ACTIVITY from 10 MBq up to 120 % of the maximum ACTIVITY injected into a patient as measured with the device under test and at least up to 1 000 MBq.