

INTERNATIONAL STANDARD

IEC
61121

Third edition
2002-07

Tumble dryers for household use – Methods for measuring the performance

*Sèche-linge à tambour à usage domestique –
Méthodes de mesure de l'aptitude à la fonction*

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

IEC 61121:2002

<https://standards.iteh.ai/catalog/standards/iec/5fe2e3d9-02cb-4b24-aa08-a6f491d6b700/iec-61121-2002>



Reference number
IEC 61121:2002(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/catlg-e.htm) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/JP.htm) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 61121

Third edition
2002-07

Tumble dryers for household use – Methods for measuring the performance

*Sèche-linge à tambour à usage domestique –
Méthodes de mesure de l'aptitude à la fonction*

<https://standards.iteh.ai>
Document Preview

IEC 61121:2002

<https://standards.iteh.ai/catalog/standards/iec/5fe2e3d9-02cb-4b24-aa08-a6f491d6b700/iec-61121-2002>

© IEC 2002 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

U

For price, see current catalogue

CONTENTS

FOREWORD	3
INTRODUCTION	5
1 Scope	6
2 Normative references	6
3 Definitions and symbols	6
4 Dimension	8
5 Rated capacity	9
6 General conditions for measurements	9
6.1 General	9
6.2 Resources and ambient conditions	9
7 Test loads	10
7.1 Composition	10
7.2 Usage	11
7.3 Preparation	12
8 Instrumentation and accuracy	13
8.1 Mass	13
8.2 Water and air temperature	13
8.3 Water volume	13
8.4 Water pressure	13
8.5 Water hardness	13
8.6 Water conductivity	13
8.7 Electrical energy	13
8.8 Time	13
8.9 Ambient humidity	13
9 Performance tests	14
9.1 General	14
9.2 Procedure for drying performance	14
10 Evaluation and calculation	16
10.1 Final moisture content of the load	16
10.2 Electric energy consumption	16
10.3 Water consumption	17
10.4 Time	17
10.5 Condensation efficiency	17
10.6 Evenness of drying	17
11 Reporting of test results	18
Annex A (normative) Nominal and standard exhaust duct for tumble dryer testing	19
Annex B (normative) Cotton test load	22
Annex C (normative) The bone-dry method	24
Annex D (normative) Water preparation	25
Bibliography	26

INTERNATIONAL ELECTROTECHNICAL COMMISSION

TUMBLE DRYERS FOR HOUSEHOLD USE – METHODS FOR MEASURING THE PERFORMANCE

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61121 has been prepared by subcommittee 59D: Home laundry appliances, of IEC technical committee 59: Performance of household electrical appliances.

This third edition cancels and replaces the second edition published in 1997, of which it constitutes a technical revision.

The text of this standard is based on the following documents:

FDIS	Report on voting
59D/219/FDIS	59D/222/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 3.

Annexes A, B, C and D form an integral part of this standard.

In this standard, the following print types are used:

- *test specifications: in italic type;*
- notes: in small roman type;
- other text: in roman type.

Words in **bold** in the text are defined in clause 3.

The committee has decided that the contents of this publication will remain unchanged until 2005. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

The contents of the corrigendum of April 2003 and September 2003 have been included in this copy.

Withdawn

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

IEC 61121:2002

<https://standards.iteh.ai/catalog/standards/iec/5fe2e3d9-02cb-4b24-aa08-a6f491d6b700/iec-61121-2002>

INTRODUCTION

This third edition has been developed in light of experience with use of the second edition of IEC 61121. Other changes include some minor revisions to the test conditions and alterations to the test load to ensure that this remains harmonised with the IEC 60456 load for clothes washers.

In summary, the main changes are as follows.

1) General:

- more terms have been defined and some previous definitions have been streamlined, in addition to the correction of some symbols and equations;
- where possible, definitions and terms have been used in common with IEC 60456;
- the content has been organised into a more logical and simple structure, and repetitive sections have been removed.

2) The conditions of measurement:

- the wording of various sections has been revised to reduce ambiguity;
- limits have been defined for water conductivity for auto-sensing dryers that are sensitive to conductivity, as well as methods to adjust conductivity where necessary;
- specifications of a nominal exhaust duct were included.

3) Reproducibility and repeatability of test results:

- revision of the specification for the cotton test load to include suitable test materials which are currently available on the market;
- more careful definition of the process and conditions for **pre-treatment, conditioning and normalisation**.

4) Test methods:

- accuracy of measurement has been defined for all instruments;
- limits and interpretations of the allowable final moisture content for each type of dryer are now defined;
- practical advice regarding the test procedure has been given with the aim of reducing ambiguity.

TUMBLE DRYERS FOR HOUSEHOLD USE – METHODS FOR MEASURING THE PERFORMANCE

1 Scope

This International Standard is applicable to household electric **tumble dryers** of the **automatic** and **non-automatic** type, with or without a cold water supply and incorporating a heating device.

The object is to state and define the principal performance characteristics of household electric **tumble dryers** of interest to users and to describe standard methods for measuring these characteristics.

This standard is concerned neither with safety nor with performance requirements.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60456, *Clothes washing machines for household use – Methods for measuring the performance*

IEC 60734, *Hard water to be used for testing the performance of some household electrical appliance*

IEC 61036, *Alternating current static watt-hour meters for active energy (Classes 1 and 2)*

IEC 61591:1997, *Household range hoods – Methods for measuring performance*

ISO 5167-1, *Measurement of fluid flow by means of pressure differential devices – Part 1: Orifice plates, nozzles and Venturi tubes inserted in circular cross-section conduits running full*

3 Definitions and symbols

For the purposes of this standard, the following definitions apply.

3.1

tumble dryer

appliance in which textile material is dried by tumbling in a rotating drum, through which heated air is passed

3.2

air vented tumble dryer

tumble dryer with a fresh-air intake which is heated and passed over the textile material and where the resulting moist air is exhausted into the room or vented outside

3.3

condenser tumble dryer

tumble dryer in which the air used for the drying process is dehumidified by cooling

NOTE Combinations of the above-mentioned types are possible.

3.4**automatic tumble dryer**

tumble dryer which switches off the drying process when a certain moisture content of the load is reached

NOTE This may include conductivity or temperature sensing

3.5**non-automatic tumble dryer**

tumble dryer which does not switch off the drying process when a certain moisture content of the load is reached, usually controlled by a timer, but may also be manually controlled

3.6**pre-treatment**

successive washing, rinsing, spinning and drying of a new test load prior to its first use to avoid rapid changes of characteristics during the tests

3.7**normalisation**

successive washing, rinsing, spinning and drying of a test load after a pre-determined number of cycles to bring the test load to a normal state

3.8**conditioning**

treatment of test load to assure homogenous condition

3.9**programme**

series of operations which are pre-defined and which are declared as suitable for drying certain types of textiles

3.10**cycle**

complete drying process, as defined by the **programme** selected, consisting of a series of different operations (heat, cool down etc.)

3.11**rated capacity**

mass in kg of dry textiles of a particular defined type, which the manufacturer declares can be treated in a specific **programme**

3.12 List of symbols

μ_f	actual final moisture content of the test load (%)
μ_{f0}	nominal final moisture content (%) given in table 3, without tolerances
μ_{fi}	actual final moisture content of the test load after the i:th cycle (%)
μ_{fj}	actual final moisture content of the j:th individual piece of textile in a cycle (%)
μ_i	actual initial moisture content (%)
μ_j	arithmetic average of $\mu_{(f, j)}$ for all individual load items
μ_{i0}	nominal initial moisture content (%) given in table 2, without tolerances
μ	arithmetical average of μ_f for all i cycles
C	condensation efficiency (%)
E_m	measured energy consumption kWh
E	corrected energy consumption kWh
L_m	measured water consumption (l)
L	corrected water consumption (l)
n	number of cycles
s_b	standard deviation as a measure of the variability between cycles in one test series
S_w	average drying evenness
s_{wr}	standard deviation for the evenness of drying within a load
W	rated capacity for the programme (g)
W_0	conditioned mass of the test load (g)
W_f	mass of the test load after drying, "the final mass"
W_i	mass of the test load after wetting (but before drying), "the initial mass"
W_w	mass of the condensed water
t_m	measured programme time
t	corrected programme time

4 Dimensions

- Height a_1 = vertical dimension measured from the lower edge (on the floor) to the upper edge of the top, with the door closed. If adjustable levelling feet are provided, they shall be moved up and down to determine minimum and maximum possible heights.
- Height a_2 = maximum vertical dimension measured from the lower edge (on the floor) to a horizontal plane at the maximum height of the tumble dryer with the door open. If adjustable levelling feet are provided, they shall be moved up and down to determine minimum and maximum possible heights.
- Width b = horizontal dimension, between the sides, as measured between two parallel vertical planes against the sides of the tumble dryer, including all projections.
- Depth c_1 = horizontal dimension as measured from a vertical rear plane against the **tumble dryer** and the most prominent part of the front, knobs and handles not being taken into account, with the door closed.
- Depth c_2 = horizontal **dimension** as measured from a vertical rear plane against the **tumble dryer** and the most prominent part of the front knobs and handles not being taken into account, with the door open.
- Drum volume = the volume of the drum in which textiles are placed, determined as the inside volume of the drum, in litres, after subtraction of ribs or other inward protrusions, etc.

5 Rated capacity

If the **rated capacity** is not declared by the manufacturer, the **rated capacity** shall be deduced from the volume of the drum according to the following ratios:

- for cotton textiles: 1 kg / 24 l;
- for easy-care textiles: 1 kg / 60 l.

Where the manufacturer gives a range of values for the **rated capacity** for a particular textile type, the maximum value shall be used.

NOTE For different textiles the **rated capacity** of an appliance may be different.

6 General conditions for measurements

6.1 General

The measurements shall be carried out on a **tumble dryer** installed and used in accordance with the manufacturer's instructions, except as required by this standard.

Where the **tumble dryer** is intended for use without a duct (i.e. the **tumble dryer** is intended to be vented into the room), the **tumble dryer** shall be tested as supplied without a duct.

Where the **tumble dryer** is intended for use with a duct and the duct is supplied with the **tumble dryer** (i.e. not as a separate accessory), the **tumble dryer** is tested with this duct, placed in a configuration consisting of three right angle bends as in figure A.2, as far as possible.

Where the **tumble dryer** is intended for use with a duct and the duct is not supplied with the **tumble dryer**, the **tumble dryer** shall be tested with a duct as specified in annex A.

Where a manufacturer gives the option to use the **tumble dryer** both with and without a duct, the **tumble dryer** shall be tested without a duct.

The test report shall clearly state which duct configuration, if any, is used in each test.

6.2 Resources and ambient conditions

6.2.1 Electricity supply

The supply voltage shall be maintained at the rated voltage ± 2 % throughout the test. If a voltage range is indicated, then the supply voltage shall be the nominal voltage of the country in which the **tumble dryer** is intended to be used.

The supply frequency shall be maintained at the rated frequency ± 1 % throughout the test.

If a frequency range is indicated, the test frequency shall be the nominal frequency of the country in which the **tumble dryer** is intended to be used.

6.2.2 Water supply

For all processes on the test load a water hardness of not higher than $(2,5 \pm 0,2)$ mmol/l shall be used. Water hardness shall be reported. If water hardness needs to be adjusted, IEC 60734 shall be followed.