International Standard



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION+MEXDYHAPODHAR OPFAHUSALUNR TO CTAHDAPTUSALUN+ORGANISATION INTERNATIONALE DE NORMALISATION

Cranes — Wind load assessment

Grues - Charges du vent

First edition - 1981-05-15

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 4302:1981</u> https://standards.iteh.ai/catalog/standards/sist/c969b894-dc5c-4987-882df3de58661799/iso-4302-1981

UDC 621.873 : 624.042.41

Ref. No. ISO 4302-1981 (E)

Descriptors : hoists, cranes (hoists), testing conditions, wind pressure, wind velocity, gust load.

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been set up has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 4302 was developed by Technical Committee ISO/TC 96, *Cranes, lifting appliances and related equipment*, and was circulated to the member bodies in February 1978.

It has been approved by the member bodies of the following countries

https://standards.iteh.ai/catalog/standards/sist/c969b894-dc5c-4987-882d-

| | ÷ | |
|----------------|----------------------|------------------------------------|
| Austria | Mexico | de58661799/jso-4302-1981 Sweden |
| Belgium | Netherlands | Switzerland |
| Czechoslovakia | New Zealand | United Kingdom |
| Finland | Norway | USA |
| India | Poland | USSR |
| Ireland | Romania | Yugoslavia |
| Israel | South Africa, Rep. o | of |
| Japan | Spain | |

The member bodies of the following country expressed disapproval of the document on technical grounds :

France Germany, F. R.

© International Organization for Standardization, 1981 •

Cranes — Wind load assessment

Scope and field of application STANDAR In SPURISE, when p is expressed in kilopascals (kPa) and v_{s} in 1 metres per second (m/s) :

This International Standard relates to wind loads on cranes. ds.iten.ai $p = 0.613 \times 10^{-3} v_s^2$

It gives a simplified method of calculation and assumes that the 02:1981 wind can blow horizontally from any direction, that the wind 3 Design wind conditions blows at a constant velocity and that there is a static reaction to the loadings it applies to the crane structure. It includes built-in allowances for the effects of gusting (rapid changes in wind velocity) and for dynamic response.

A precise method for calculations of the loadings which arise due to the dynamic response of a crane and its load due to gusting will be given in a separate document.

2 Wind pressure

The dynamic wind pressure p is given by the formula

 $p = K v_s^2$

where

K is a factor related to the density of air which for design purposes is assumed to be constant;

 $v_{\rm s}$ is the wind speed, used as a basis of the calculation.

Two design wind conditions are taken into account in calculating wind loads on cranes.

3.1 In-service wind

This is the maximum wind that the crane is designed to withstand under operating conditions. The wind loading is assumed to be applied in the least favourable direction in combination with the appropriate service loads. In-service design wind speeds and corresponding pressures are given in table 1. If the manufacturer uses in-service design wind values which differ from those in table 1, the values used should be stated on the crane certificate.

3.1.1 Action of wind on suspended load

On all cranes, the action of the wind on the load must be taken into account and the method by which this is done shall be clearly described. This may be accomplished by :

a) a method of rated load reduction based upon wind velocity, load area and shape factor;

1) A conversion chart covering v_s in knots, mile/h and m/s, and p in lbf/ft², Pa, and kgf/m² is given in the annex.

b) a limitation of the in-service wind speed for loads exceeding a stipulated surface area;

c) by use of wind forces on load parameters of size and shape. The wind force on the load is calculated as a minimum as follows :

Cranes of type a) in table 1

f = 0,015 mg kN

Cranes of type b) in table 1

 $f = 0.03 \ mg \ kN$

Cranes of type c) in table 1

 $f = 0,06 mg \, kN$

where

f is the wind force due to the wind on the hook load, in kilonewtons;

m is the mass of the hook load, in tonnes;

g is acceleration of free fall equal to 10 m/s².

Where a crane is designed to handle loads of specific size and loads on its composition shape only, the wind force on the suspended load shall be result.

4 Wind load calculations

For most complete and part structures, and individual members used in crane structures, the wind load, F, in kilonewtons, is calculated from the formula

 $F = Ap C_{f}$

where

A is the effective frontal area of the part under consideration, in square metres, i.e. the solid area projection on to a plane perpendicular to the wind direction;

p is the wind pressure corresponding to appropriate design condition, in kilonewtons per square metre;

 $C_{\rm f}$ is the force coefficient in the direction of the wind, for the part under consideration (see clause 5).

For calculating wind loadings for "out-of-service conditions", the wind pressure may be taken as constant for every 10 m vertical interval over the height of the crane. Alternatively the actual design wind pressure at any height may be calculated, or the design wind pressure at the top of the structure may be taken as constant over the entire height.

The total wind load on the structure is taken as the sum of the size and loads on its component parts.

ISO 4302;1981 https://standards.iteh.ai/catalog/standards/sist/c969b894-dc5c-4987-882d

3.2 Out-of-service wind

f3de58661799/iso-4302-1981

This is the maximum (storm) wind blowing from the least favourable direction that a crane is designed to withstand when in an out-of-service condition. The speed varies with the geographical location, and the degree of exposure to prevailing winds.

Out-of-service design wind velocities for use with this International Standard will be given in a further table to be produced when the requisite information becomes available. For the present, out-of-service design wind speeds should be taken from the appropriate national standards.

Mobile cranes with jibs not more than 30 m in length that can be readily lowered to the ground, low pivot cranes with telescoping jibs, and cranes with towers that are readily telescoped by means of self-contained mechanisms, only need to be designed for out-of-service wind in the lowered position. Operating instructions for such cranes shall include the requirement that jibs and/or towers are to be secured from wind exposure when not in service.

The operating instructions for cranes that require the installation of wind stabilizers, or other means not used during operation, in order to resist the specified out-of-service wind speed shall state the wind speed that the crane can safely sustain in its operating configuration; they shall also describe the provisions that must be followed in order that the crane may safely withstand the specified out-of-service wind.

5.1 Individual members, frames, etc.

Force coefficients for individual members, single lattice frames and machinery houses etc., are given in table 2. The values for individual members vary according to the aerodynamic slenderness and, in the case of large box sections, with the section ratio. Aerodynamic slenderness and section ratio are defined in table 2.

Force coefficients obtained by wind tunnel or full scale tests may also be used.

Where a frame is made up of flat-sided and circular sections, or of circular sections in both flow regimes ($D v_s < 6 \text{ m}^2/\text{s}$ and $D v_s \ge 6 \text{ m}^2/\text{s}$, where *D* is the diameter of a circular section, in metres, and v_s is the design wind speed, in metres per second) the appropriate force coefficients are applied to the corresponding frontal areas.

5.2 Shielding factors – Multiple frames or members

Where parallel frames or members are positioned so that shielding takes place, the wind force on the windward frame or member and on the unsheltered parts of those behind it are calculated using the appropriate force coefficients. The force coefficients on the sheltered parts are multiplied by a shielding factor η given in table 3. Values of η vary with the solidity and spacing ratios as defined in table 3.

Where there are a number of identical frames or members spaced equidistantly behind each other in such a way that each frame shields those behind it, it is accepted that the shielding effect increases up to the ninth frame and remains constant thereafter. The wind loads, in newtons, are calculated from the following equations :

On the 1st frame :

$$F_1 = A \ p \ C_{\rm f}$$

On the 2nd frame :

$$F_2 = \eta A p C_f$$

On the *n*th frame (where n is between 3 and 8) :

$$F_n = \eta^{(n-1)} A p C_f$$

On the 9th and subsequent frames :

$$F_9 = \eta^8 A \ p \ C_f$$

The total wind load, in newtons, is thus :

where there are up to 9 frames,

For design purposes the term η^x used in the above formula is taken as 0,10 whenever, numerically, it is less than 0,10.

5.3 Lattice towers

In calculating the "face-on" wind load on square towers, the solid area of the windward face is multiplied by the following overall force coefficients :

for towers composed of flat-sided sections : 1,7 (1 + η)

for towers composed of circular sections,

where $D v_{\rm s} < 6 \,{\rm m^2/s}$: 1,2 (1 + η)

where $D v_{s} > 6 \text{ m}^{2}/\text{s} : 1,4$

The value of η is taken from table 3 for a/b = 1 according to the solidity ratio of the windward face.

The maximum wind load on a square tower occurs when the wind blows into a corner. It may be taken as 1,2 times for "face-on" load.

$F_{\text{total}} = [1 + \eta + \eta^2 + \eta^3 \text{Teh } \eta^n \text{Tuba p CARD PREVIEW}$ (n < 9) $= A p C_f \left(\frac{1 - \eta^n}{1 - \eta}\right)$ (standards. (individual members, frames, etc.)

 $1 - \eta$ where there are more than 9 frames, itch ai/catalog/standards/sist for wind, *F*, in newtons, is obtained from the equation : 130 + 302:19 Where the wind blows at an angle to the longitudinal axis of a member or to the surface of a frame, the force in the direction of the wind, *F*, in newtons, is obtained from the equation : 130 + 302:19 Where the wind blows at an angle to the longitudinal axis of a member or to the surface of a frame, the force in the direction of the wind, *F*, in newtons, is obtained from the equation :

$$F_{\text{total}} = [1 + \eta + \eta^2 + \eta^3 + \dots + \eta^8 + (n > 9)$$

+
$$(n - 9) \eta^{8} \times A p C_{f}$$

where

 $F = A p C_{\rm f} \sin^2 \theta$

F, A, p and C_f are as defined in clause 4;

 $\theta~$ is the angle of the wind ($\theta~<$ 90°) to the longitudinal axis or face.

3

$$= A p C_{f} \left[\left(\frac{1 - \eta^{9}}{1 - \eta} \right) + (n - 9) \eta^{8} \right]$$

| Type of crane | | Wind speed m/s | Wind pressure kPa | |
|---------------|--|----------------------|-------------------------|--|
| a) | Cranes that are easily secured against wind action, and are designed for operation in light winds only (for example cranes of low chassis height with booms that can be readily lowered to the ground) | 14 | 0,125 | |
| b) | All normal types of crane installed in the open | 20 | 0,25 | |
| c) | Transporter type unloaders which must continue to work in high winds | 28,5 | 0,50 | |

Table 1 - In-service design wind speeds and pressures

| Table | 2 – | Force | coefficients |
|-------|-----|-------|--------------|
|-------|-----|-------|--------------|

| | Description | | Aerodynamic slenderness <i>1/b</i> or <i>1/D</i> | | | | | |
|---------------------------|---|--------------------|--|----------------------------|----------------------------|--------------------------|------------|--|
| Туре | | | 10 | 20 | 30 | 40 | 50 | |
| Individual members | Rolled sections, rectangles, hollow sections, flat plates | | 1,35 | 1,6 | 1,65 | 1,7 | 1,9 | |
| | Circular sections where $D v_s < 6 m_s^2/s$ $D v_s \ge 6 m_s^2/s$ Characteristic baseline base | 0,75 0,60 | 0,80 0,65 | 0,90 0,70 | 0,95 0,70 | 1,0 0,75 | 1,1 0,8 | |
| | Box sections over 350 mm square and 1 250 mm, 450 mm rectangular 1 ISO 4300.598 0,255 https://standards.iteh.ai/catalog/standards/255 | 1,40 1,0 0.8 | 1,75 1,55 1,2 0,9 | 1,95 1,75 1,3 0,9 | 2,1 1,85 1,35 1,0 | 2,2 1,9 1,4 1,0 | | |
| | Flat sided sections f3de58661799/iso-43 | |)2-1981 1,7 | | | | | |
| Single lattice frames | Circular sections where $D v_s < 6 m^2/s$ $D v_s \ge 6 m^2/s$ | | 1,2 0,8 | | | | | |
| Machinery houses, etc. | Rectangular clad structures on ground or solid base1,1(air flow beneath structure prevented)1,1 | | | | | | | |



Figure 1 – Aerodynamic slenderness and section ratio

| Spacing ratio | Solidity ratio A/A _e | | | | | |
|---------------|---------------------------------|------|------|------|------|-------|
| a/b | 0,1 | 0,2 | 0,3 | 0,4 | 0,5 | ≥ 0,6 |
| 0,5 | 0,75 | 0,4 | 0,32 | 0,21 | 0,15 | 0,1 |
| 1,0 | 0,92 | 0,75 | 0,59 | 0,43 | 0,25 | 0,1 |
| 2,0 | 0,95 | 0,8 | 0,63 | 0,5 | 0,33 | 0,2 |
| 4,0 | 1 | 0,88 | 0,76 | 0,66 | 0,55 | 0,45 |
| 5,0 | 1 | 0,95 | 0,88 | 0,81 | 0,75 | 0,68 |
| 6,0 | 1 | 1 | 1 | 1 | 1 | 1 |

Table 3 – Shielding factors (η)

a) Solidity ratio



Figure 2 — Solidity ratio and spacing ratio

Annex

Conversion chart for wind speed and pressure

