



Designation: **F1764 – 97 (Reapproved 2012) F1764 – 97 (Reapproved 2018)**

Standard Guide for Selection of Hardline Communication Systems for Confined-Space Rescue¹

This standard is issued under the fixed designation F1764; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This guide covers recommended criteria for the selection of hardwire communication systems for use in permit-required confined-space rescue operations.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.3 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

F1490 [Terminology Relating to Search and Rescue](#) (Withdrawn 2011)³

2.2 *Federal Standards:*

29 Code of Federal Regulations 1910.146 [Permit Required Confined Spaces](#)⁴

29 Code of Federal Regulations 1910.7 [Definition and Requirements for a National Recognized Testing Laboratory](#)⁴

2.3 *National Code:*

[National Electrical Code \(NEC\)/NFPA 70](#)⁵

3. Terminology

3.1 *Definitions of Terms Specific to This Standard:*

3.1.1 *confined space rescue*—rescue operations within spaces that meet the definition of “permit-required confined space” in Fed. Std. 29 CFR 1910.146.

3.1.2 *hardline communication system*—any communication system where all users are connected to the system by a hardline or wire.

4. Significance and Use

4.1 Because of the many unique requirements of permit-required confined space rescue operations and the specific construction and composition of some confined spaces, hardline communications systems may be the only type that will meet the requirements for working within these spaces. Some of these requirements are set forth in Federal Regulation and some by safe operating procedures developed for working in confined spaces by industry.

4.2 This guide is not meant to preclude the use of other types of communication systems in confined-space rescue.

¹ This guide is under the jurisdiction of ASTM Committee F32 on Search and Rescue and is the direct responsibility of Subcommittee F32.01 on Equipment, Testing, and Maintenance.

Current edition approved July 1, 2012; Nov. 1, 2018. Published August 2012; November 2018. Originally approved in 1997. Last previous edition approved in 2007 as F1764 – 97(2007); (2012). DOI: 10.1520/F1764-97R12.10.1520/F1764-97R18.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

⁴ Available from Occupational Safety and Health Administration (OSHA), 200 Constitution Ave., NW, Washington, DC 20210, <http://www.osha.gov>.

⁵ Available from National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA 02169-7471, <http://www.nfpa.org>.



5. System Requirements

5.1 *System Safety*—The system must be safe for use in the atmosphere, or potential atmosphere, within the space.

NOTE 1—See Annex A1.

5.2 The system must have continuous, hands-free voice communications capability.

NOTE 2—See X1.1.

5.3 The system must be dedicated and private so operations cannot be interfered with by outsiders not involved with the rescue.

5.4 The system shall not affect the readings of other safety equipment (that is, gas detectors).

5.5 Systems that are battery powered must have a low-battery warning or a backup power source that provides a minimum of 30 min before communications are lost.

5.6 The system must accommodate a minimum of three users.

NOTE 3—See X1.2.

5.7 The system should allow for communication between all entrants as well as with the attendant.

NOTE 4—See X1.3.

5.8 The system must work in conjunction with the personal protective equipment (PPE) necessary to work in the environment within the space.

NOTE 5—See X1.4.

5.9 The system must be impervious to the chemicals within the space.

6. Keywords

6.1 confined space; hardline

ANNEX

(Mandatory Information)

A1. INHERENT SAFETY

A1.1 Equipment that requires electrical power to operate may be a source of ignition in the presence of flammable gases or vapors, combustible dusts, or ignitable fibers. Equipment that must operate in potentially flammable atmospheres must be unable to cause ignition (inherently safe) in those atmospheres. They can be certified as intrinsically safe or explosion-proof. Rescue teams that only work in known hazards, such as on-site rescue teams, may use equipment approved for only those hazards. Rescue teams that respond to unknown hazards, such as fire departments and other off-site rescue teams, must have equipment with the highest possible level of approval available, that is, equipment approved for atmospheres that are classified as: Class I Division 1 Groups A, B, C, D; Class II Division 1 Groups E, F, G; and Class III Division 1.⁶ (See Note A1.1.) Division 1 locations are more hazardous than Division 2, therefore the test protocols for Division 1 are more stringent. As such, equipment certified for Division 1 is also approved for Division 2. Hardline systems that only have limited approval, when used only in atmospheres for which they are approved, meet this guide. (See Note A1.2.) The NFPA does not certify equipment. Testing and certification must be done by a Nationally Recognized Test Laboratory (NRTL) that has been accredited by OSHA in accordance with 29 CFR 1910.7. All certified equipment must be clearly and permanently marked to show the class, division, and group it is approved for use in and the name or mark of the NRTL that granted the approval. It is insufficient to be simply labeled intrinsically safe.

NOTE A1.1—See X1.5.

NOTE A1.2—See Appendix X2.

⁶ Classifications for hazardous locations are in the National Electrical Code (NEC).