



**IEEE**

**IEC/IEEE 62209-1528**

Edition 1.0 2020-10

# INTERNATIONAL STANDARD

## NORME INTERNATIONALE



**Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices –**

**Part 1528: Human models, instrumentation, and procedures  
(Frequency range of 4 MHz to 10 GHz)**

**Procédure de mesure pour l'évaluation du débit d'absorption spécifique de l'exposition humaine aux champs radiofréquence produits par les dispositifs de communications sans fil tenus à la main ou portés près du corps –  
Partie 1528: Modèles humains, instrumentation et procédures  
(Plage de fréquences comprise entre 4 MHz et 10 GHz)**



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2020 IEC, Geneva, Switzerland

Copyright © 2020 IEEE

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing being secured. Requests for permission to reproduce should be addressed to either IEC at the address below or IEC's member National Committee in the country of the requester or from IEEE.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

Institute of Electrical and Electronics Engineers, Inc.  
3 Park Avenue  
New York, NY 10016-5997  
United States of America  
[stds.ipr@ieee.org](mailto:stds.ipr@ieee.org)  
[www.ieee.org](http://www.ieee.org)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

#### IEC online collection - [oc.iec.ch](http://oc.iec.ch)

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

### A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

### A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

#### Recherche de publications IEC -

[webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

#### Service Clients - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: [sales@iec.ch](mailto:sales@iec.ch).

#### IEC online collection - [oc.iec.ch](http://oc.iec.ch)

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 000 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.



IEEE

IEC/IEEE 62209-1528

Edition 1.0 2020-10

# INTERNATIONAL STANDARD

## NORME INTERNATIONALE



Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices –

Part 1528: Human models, instrumentation, and procedures  
(Frequency range of 4 MHz to 10 GHz)

Procédure de mesure pour l'évaluation du débit d'absorption spécifique de l'exposition humaine aux champs radiofréquence produits par les dispositifs de communications sans fil tenus à la main ou portés près du corps –  
Partie 1528: Modèles humains, instrumentation et procédures  
(Plage de fréquences comprise entre 4 MHz et 10 GHz)

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

ICS 17.220.20

ISBN 978-2-8322-9562-5

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## CONTENTS

FOREWORD.....	14
INTRODUCTION.....	17
1 Scope.....	18
2 Normative references .....	18
3 Terms and definitions .....	18
4 Symbols and abbreviated terms.....	26
4.1 Physical quantities .....	26
4.2 Constants .....	26
4.3 Abbreviated terms.....	27
5 Quick start guide and evaluation plan checklist.....	28
6 Measurement system specifications.....	30
6.1 General requirements for full SAR testing .....	30
6.2 Phantom specifications .....	31
6.2.1 General .....	31
6.2.2 Basic phantom parameters .....	31
6.2.3 Head phantom .....	33
6.2.4 Flat phantom .....	34
6.2.5 Device-specific phantoms .....	35
6.3 Influence of hand on SAR in head.....	35
6.4 Scanning system requirements.....	36
6.5 Device holder specifications.....	36
6.6 Characteristics of the readout electronics.....	37
7 Protocol for SAR assessment.....	37
7.1 General.....	37
7.2 Measurement preparation .....	37
7.2.1 Preparation of tissue-equivalent medium and system check.....	37
7.2.2 Preparation of the wireless communication DUT .....	38
7.2.3 DUT operating mode requirements .....	38
7.2.4 Positioning of the DUT relative to the phantom .....	40
7.2.5 Antenna configurations .....	57
7.2.6 Options and accessories.....	57
7.2.7 DUTs with alternative form factor.....	57
7.2.8 Test frequencies for DUTs .....	58
7.3 Tests to be performed for DUTs .....	58
7.3.1 General .....	58
7.3.2 Basic approach for DUT testing .....	59
7.4 Measurement procedure .....	60
7.4.1 General .....	60
7.4.2 Full SAR testing procedure .....	60
7.4.3 Drift .....	64
7.4.4 SAR measurements of DUTs with multiple antennas or multiple transmitters .....	66
7.5 Post-processing of SAR measurement data .....	72
7.5.1 Interpolation .....	72
7.5.2 Extrapolation .....	72
7.5.3 Definition of the averaging volume.....	72

7.5.4	Searching for the maxima .....	73
7.6	Time-period averaged SAR considerations.....	73
7.6.1	General .....	73
7.6.2	RF conducted power.....	73
7.6.3	Time-period averaged SAR measurement settings for SAR measurement methods .....	73
7.6.4	Exposure condition and test position considerations .....	74
7.6.5	Time-period averaged SAR for simultaneous transmission.....	74
7.6.6	TX factor assessment .....	74
7.6.7	SAR measurements .....	75
7.6.8	Uncertainty in TPAS evaluations.....	75
7.7	Proximity sensors considerations .....	76
7.7.1	General .....	76
7.7.2	Procedures for determining proximity sensor triggering distances .....	77
7.7.3	Procedure for determining proximity sensor coverage area .....	80
7.7.4	SAR measurement procedure involving proximity sensors .....	81
7.8	SAR correction for deviations of complex permittivity from targets .....	81
7.8.1	General .....	81
7.8.2	SAR correction formula.....	82
7.8.3	Uncertainty of the correction formula .....	83
7.9	Minimization of testing time.....	83
7.9.1	General .....	83
7.9.2	Fast SAR testing.....	84
7.9.3	SAR test reductions .....	89
8	Measurement uncertainty estimation.....	100
8.1	General.....	100
8.2	Requirements on the uncertainty evaluation.....	101
8.3	Description of uncertainty models .....	102
8.3.1	General .....	102
8.3.2	SAR measurement of a DUT.....	102
8.3.3	System validation and system check measurement.....	102
8.3.4	System check repeatability and reproducibility.....	102
8.3.5	Fast SAR testing (relative measurement).....	102
8.4	Parameters contributing to uncertainty .....	104
8.4.1	Measurement system errors.....	104
8.4.2	Phantom and device (DUT or validation antenna) errors .....	105
8.4.3	Corrections to the SAR result (if applied).....	107
9	Measurement report .....	108
9.1	General.....	108
9.2	Items to be recorded in the measurement report .....	108
Annex A (normative)	SAR measurement system verification .....	112
A.1	Overview.....	112
A.2	System check .....	112
A.2.1	Purpose.....	112
A.2.2	Phantom set-up .....	113
A.2.3	System check antenna.....	113
A.2.4	System check antenna input power measurement.....	114
A.2.5	System check procedure.....	115
A.2.6	System check acceptance criteria.....	116

A.3	System validation.....	116
A.3.1	Purpose.....	116
A.3.2	Phantom set-up.....	116
A.3.3	System validation antennas.....	116
A.3.4	Input power measurement.....	117
A.3.5	System validation procedure.....	117
A.4	Fast SAR testing system validation and system check.....	119
A.4.1	General.....	119
A.4.2	Fast SAR testing system validation.....	119
A.4.3	Fast SAR testing system check.....	120
Annex B (informative)	SAR test reduction supporting information.....	122
B.1	General.....	122
B.2	Test reduction based on characteristics of DUT design.....	122
B.2.1	General.....	122
B.2.2	Statistical analysis overview.....	122
B.2.3	Analysis results.....	123
B.2.4	Conclusions.....	126
B.2.5	Expansion to multi-transmission antennas.....	126
B.3	Test reduction based on analysis of SAR results on other signal modulations.....	126
B.3.1	General.....	126
B.3.2	Analysis results.....	127
B.4	Test reduction based on SAR level analysis.....	128
B.4.1	General.....	128
B.4.2	Statistical analysis.....	129
B.4.3	Test reduction applicability example.....	132
B.5	Other statistical approaches to search for the high SAR test configurations.....	134
B.5.1	General.....	134
B.5.2	Test reductions based on a DOE.....	134
B.5.3	One factor at a time (OFAT) search.....	134
B.5.4	Analysis of unstructured data.....	134
Annex C (informative)	Measurement uncertainty of results obtained from specific fast SAR testing methods.....	135
C.1	General.....	135
C.2	Measurement uncertainty evaluation – contributing parameters.....	135
C.2.1	General.....	135
C.2.2	Probe calibration and system calibration drift.....	136
C.2.3	Isotropy.....	136
C.2.4	Probe positioning.....	137
C.2.5	Mutual sensor coupling.....	138
C.2.6	Scattering within the probe array.....	139
C.2.7	Sampling error.....	139
C.2.8	Array boundaries.....	139
C.2.9	Probe or probe array coupling with the DUT.....	139
C.2.10	Measurement system immunity / secondary reception.....	139
C.2.11	Deviations in phantom shape.....	140
C.2.12	Spatial variation in dielectric properties.....	140
C.2.13	Reconstruction.....	140
C.3	Uncertainty budget.....	140
Annex D (normative)	SAR system validation antennas.....	143

D.1	General antenna requirements	143
D.2	Standard dipole antenna	143
D.2.1	Mechanical description	143
D.2.2	Numerical target SAR values	146
D.3	Standard waveguide	148
D.3.1	Mechanical description	148
D.3.2	Numerical target SAR values	149
D.4	System validation antennas for below 150 MHz	149
D.4.1	General	149
D.4.2	Confined loop antenna	150
D.4.3	Meander dipole antenna	152
D.5	Orthogonal E-field source – VPIFA	153
D.5.1	Mechanical description	153
D.5.2	Numerical target SAR values	156
Annex E (normative)	Calibration and characterization of dosimetric (SAR) probes	157
E.1	Introductory remarks	157
E.2	Linearity	158
E.3	Assessment of the sensitivity of the dipole sensors	158
E.3.1	General	158
E.3.2	Two-step calibration procedures	158
E.3.3	One-step calibration procedure – reference antenna method	164
E.3.4	One-step calibration procedure – coaxial calorimeter method	168
E.4	Isotropy	170
E.4.1	Axial isotropy	170
E.4.2	Hemispherical isotropy	170
E.5	Lower detection limit	175
E.6	Boundary effect	176
E.7	Response time	176
Annex F (informative)	Example recipes for phantom tissue-equivalent media	177
F.1	General	177
F.2	Ingredients	177
F.3	Tissue-equivalent medium liquid formulas (permittivity/conductivity)	178
Annex G (normative)	Phantom specifications	180
G.1	Rationale for the phantom characteristics	180
G.1.1	General	180
G.1.2	Rationale for the SAM phantom	180
G.1.3	Rationale for the flat phantom	180
G.2	SAM phantom specifications	181
G.2.1	General SAM phantom specifications	181
G.2.2	SAM phantom shell specification	185
G.3	Flat phantom specifications	187
G.4	Justification of flat phantom dimensions	188
G.5	Rationale for tissue-equivalent media	191
G.6	Definition of a phantom coordinate system and a DUT coordinate system	193
Annex H (informative)	Measurement of the dielectric properties of tissue-equivalent media and uncertainty estimation	195
H.1	Overview	195
H.2	Measurement techniques	195
H.2.1	General	195

H.2.2	Instrumentation.....	195
H.2.3	General principles .....	195
H.3	Slotted coaxial transmission line .....	196
H.3.1	General .....	196
H.3.2	Equipment set-up .....	196
H.3.3	Measurement procedure .....	197
H.4	Contact coaxial probe .....	197
H.4.1	General .....	197
H.4.2	Equipment set-up .....	198
H.4.3	Measurement procedure .....	199
H.5	TEM transmission line.....	199
H.5.1	General .....	199
H.5.2	Equipment set-up .....	200
H.5.3	Measurement procedure .....	200
H.6	Dielectric properties of reference liquids .....	201
Annex I (informative)	Studies for potential hand effects on head SAR.....	204
I.1	Overview.....	204
I.2	Background.....	204
I.2.1	General .....	204
I.2.2	Hand phantoms .....	205
I.3	Summary of experimental studies.....	205
I.3.1	Experimental studies using fully compliant SAR measurement systems .....	205
I.3.2	Experimental studies using other SAR measurement systems .....	205
I.4	Summary of computational studies.....	206
I.5	Conclusions.....	206
Annex J (informative)	Skin enhancement factor.....	207
J.1	Background.....	207
J.2	Rationale .....	208
J.3	Simulations .....	208
J.4	Recommendation .....	209
Annex K (normative)	Application-specific phantoms .....	211
K.1	General.....	211
K.2	Phantom basic requirements.....	211
K.3	Examples of specific alternative phantoms.....	211
K.3.1	Face-down SAM phantom.....	211
K.3.2	Head-stand SAM phantom .....	212
K.3.3	Wrist phantom .....	212
K.4	Scanning and evaluation requirements.....	213
K.5	Uncertainty assessment.....	213
K.6	Reporting.....	213
Annex L (normative)	Fast compliance evaluations using a flat-bottom phantom with a curved corner (Uniphantom).....	214
L.1	General.....	214
L.2	Uniphantom .....	214
L.3	Device positions for compliance testing and definitions of handset shapes .....	214
L.3.1	General .....	214
L.3.2	Handsets with a straight form factor.....	215
L.3.3	Handsets with a clamshell form factor.....	215
L.4	Testing procedure.....	215



L.4.1	General .....	215
L.4.2	Handsets with straight form factors .....	215
L.4.3	Handsets with clamshell form factors .....	216
L.5	Uncertainty of SAR measurement results using Uniphantom .....	217
Annex M (informative)	Wired hands-free headset testing .....	218
M.1	Concept .....	218
M.2	Example results .....	219
M.3	Discussion .....	220
Annex N (informative)	Applying the head SAR test procedures .....	221
Annex O (normative)	Uncertainty analysis for measurement system manufacturers and calibration laboratories.....	224
O.1	Probe linearity and detection limits .....	224
O.2	Broadband signal uncertainty .....	225
O.3	Boundary effect.....	225
O.4	Field-probe readout electronics uncertainty.....	226
O.5	Signal step-response time uncertainty.....	226
O.6	Probe integration-time uncertainty .....	227
O.6.1	General .....	227
O.6.2	Probe integration-time uncertainty for periodic pulsed signals.....	227
O.6.3	Probe integration-time uncertainty for non-periodic signals .....	228
O.7	Contribution of mechanical constraints.....	228
O.7.1	Mechanical tolerances of the probe positioner (directions parallel to phantom surface).....	228
O.7.2	Probe positioning with respect to phantom shell surface .....	228
O.7.3	First-order approximation of exponential decay.....	229
O.8	Contribution of post-processing.....	229
O.8.1	General .....	229
O.8.2	Evaluation test functions.....	230
O.8.3	Data-processing algorithm uncertainty evaluations .....	232
O.9	Tissue-equivalent medium properties uncertainty.....	235
O.9.1	General .....	235
O.9.2	Medium density .....	235
O.9.3	Medium conductivity uncertainty .....	235
O.9.4	Medium permittivity uncertainty .....	235
O.9.5	Assessment of dielectric properties measurement uncertainties.....	235
O.9.6	Medium temperature uncertainty.....	237
Annex P (normative)	Post-processing techniques .....	239
P.1	Extrapolation and interpolation schemes .....	239
P.1.1	General .....	239
P.1.2	Extrapolation schemes.....	239
P.1.3	Interpolation schemes.....	239
P.2	Averaging scheme and maximum finding .....	239
P.2.1	Volume average schemes.....	239
P.2.2	Finding the psSAR and estimating the uncertainty .....	240
Annex Q (informative)	Rationale for time-period averaged SAR test procedure .....	241
Annex R (normative)	Measurement uncertainty analysis for testing laboratories .....	242
R.1	RF ambient conditions .....	242
R.2	Device positioning and holder uncertainties .....	242
R.2.1	General .....	242

R.2.2	Device holder perturbation uncertainty.....	243
R.2.3	DUT positioning uncertainty with a specific test device holder: Type A .....	244
R.3	Probe modulation response .....	244
R.4	Time-period averaged SAR .....	245
R.4.1	General .....	245
R.4.2	TX factor uncertainty .....	245
R.5	Measured SAR drift.....	246
R.5.1	General .....	246
R.5.2	Accounting for drift .....	246
R.6	SAR scaling uncertainty .....	247
Annex S (normative)	Validation antenna SAR measurement uncertainty .....	248
S.1	Deviation of experimental antennas .....	248
S.2	Other uncertainty contributions when using system validation antennas.....	248
Annex T (normative)	Interlaboratory comparisons .....	250
T.1	Purpose .....	250
T.2	Phantom set-up .....	250
T.3	Reference devices .....	250
T.4	Power set-up .....	250
T.5	Interlaboratory comparison – procedure .....	251
Annex U (informative)	Determination of the margin for compliance evaluation using the Uniphantom .....	252
U.1	General.....	252
U.2	Deviation of the psSAR measured using the Uniphantom from the psSAR measured using the SAM phantom.....	252
U.3	Determination of margin based on 95 % confidence interval.....	253
U.4	Examples of the determination of the margin factor.....	253
U.4.1	Margin for handsets with straight form factors at flat-bottom position .....	253
U.4.2	Margin for handsets with straight form factors (except smart phones at flat-bottom position).....	255
U.4.3	Margin for smart phones at flat-bottom position .....	257
U.4.4	Margin for smart phones at corner position .....	259
U.4.5	Margin for handsets with clamshell form factors at corner position.....	261
Annex V (informative)	Automatic input power level control for system validation .....	264
V.1	General.....	264
V.2	Operational mechanism of AIPLC .....	264
Annex W (informative)	LTE test configurations supporting information .....	266
W.1	General.....	266
W.2	Study 1 .....	266
W.3	Study 2 .....	268
W.4	Justifications of relative standard deviations .....	269
Bibliography	.....	271
Figure 1	– Quick start guide .....	29
Figure 2	– Dimensions of the elliptical phantom .....	35
Figure 3	– Mounting of the DUT in the device holder using low-permittivity and low-loss foam to avoid changes of DUT performance by the holder material.....	37
Figure 4	– Designation of DUT reference points.....	41

Figure 5 – Measurements performed by shifting a large device over the efficient measurement area of the system including overlapping areas – in this case: six tests performed .....	42
Figure 6 – Test positions for body-worn devices .....	43
Figure 7 – Device with swivel antenna .....	44
Figure 8 – Test positions for body supported devices.....	45
Figure 9 – Test positions for desktop devices .....	47
Figure 10 – Test positions for front-of-face devices.....	48
Figure 11 – Test position for hand-held devices, not used at the head or torso .....	49
Figure 12 – Test position for limb-worn devices .....	49
Figure 13 – Test position for clothing-integrated wireless communication devices.....	50
Figure 14 – Possible test positions for a generic device .....	51
Figure 15 – Vertical and horizontal reference lines and reference points A and B on two example device types: a full touch-screen smart phone (left) and a DUT with a keypad (right) .....	53
Figure 16 – Cheek position of the DUT on the left side of SAM where the device position shall be maintained for the phantom test set-up.....	56
Figure 17 – Tilt position of the DUT on the left side of SAM .....	56
Figure 18 – An alternative form factor DUT with reference points and reference lines .....	57
Figure 19 – Block diagram of the tests to be performed .....	60
Figure 20 – Orientation of the probe with respect to the line normal to the phantom surface, for head and flat phantoms, shown at two different locations .....	64
Figure 21 – Measurement procedure for different types of correlated signals .....	72
Figure 22 – Positioning of the surfaces and edges of the DUT for determining the proximity sensor triggering distance .....	79
Figure 23 – Positioning of the edges of the DUT to determine proximity sensor triggering distance variations with the edge positioned at different angles from the perpendicular position.....	80
Figure 24 – Fast SAR Procedure A .....	87
Figure 25 – Fast SAR Procedure B .....	89
Figure 26 – Modified chart of Figure 19.....	93
Figure 27 – Use of conducted power for LTE mode selection, for Band 1 (1 920 MHz to 1 980 MHz) (MPR values are in dB).....	97
Figure 28 – Use of conducted power for LTE mode selection, for Band 17 (704 MHz to 716 MHz) (MPR values are in dB).....	98
Figure A.1 – Test set-up for the system check .....	114
Figure B.1 – Distribution of Tilt/Cheek.....	124
Figure B.2 – SAR relative to SAR in position with maximum SAR in GSM mode.....	128
Figure B.3 – Two points identifying the minimum distance between the position of the interpolated maximum SAR and the points at $0,6 \times SAR_{max}$ .....	130
Figure B.4 – Histogram for $D_{min}$ in the case of GSM 900 and iso-level at $0,6 \times SAR_{max}$ .....	130
Figure B.5 – Histogram for random variable $Factor_{1g,1800}$ .....	132
Figure D.1 – Mechanical details of the standard dipoles.....	145
Figure D.2 – Standard waveguide (dimensions are according to Table D.3) .....	148
Figure D.3 – Drawing of the CLA that corresponds to a resonant loop integrated in a metallic structure to isolate the resonant structure from the environment .....	150
Figure D.4 – Mechanical details of the meander dipoles for 150 MHz.....	152

Figure D.5 – VPIFA validation antenna .....	155
Figure D.6 – Mask for positioning VPIFAs .....	155
Figure E.1 – Experimental set-up for assessment of the sensitivity (conversion factor) using a vertically-oriented rectangular waveguide .....	162
Figure E.2 – Illustration of the antenna gain evaluation set-up .....	165
Figure E.3 – Schematic of the coaxial calorimeter system.....	169
Figure E.4 – Set-up to assess hemispherical isotropy deviation in tissue-equivalent medium.....	171
Figure E.5 – Alternative set-up to assess hemispherical isotropy deviation in tissue-equivalent medium.....	172
Figure E.6 – Experimental set-up for the hemispherical isotropy assessment.....	173
Figure E.7 – Conventions for dipole position ( $\zeta$ ) and polarization ( $\theta$ ) .....	174
Figure E.8 – Measurement of hemispherical isotropy with reference antenna.....	175
Figure G.1 – Illustration of dimensions in Table G.1 and Table G.2.....	182
Figure G.2 – Close up side view of phantom showing the ear region.....	184
Figure G.3 – Side view of the phantom showing relevant markings .....	185
Figure G.4 – Sagittally bisected phantom with extended perimeter (shown placed on its side as used for device SAR tests) .....	186
Figure G.5 – Picture of the phantom showing the central strip.....	186
Figure G.6 – Cross-sectional view of SAM at the reference plane.....	187
Figure G.7 – Dimensions of the flat phantom set-up used for deriving the minimal phantom dimensions for $W$ and $L$ for a given phantom depth $D$ .....	189
Figure G.8 – FDTD predicted error in the 10 g psSAR as a function of the dimensions of the flat phantom compared with an infinite flat phantom at 800 MHz.....	190
Figure G.9 – Complex permittivity of human tissues compared to the phantom target properties .....	193
Figure G.10 – Example reference coordinate system for the left-ear ERP of the SAM phantom .....	194
Figure G.11 – Example coordinate system on a DUT .....	194
Figure H.1 – Slotted line set-up.....	196
Figure H.2 – An open-ended coaxial probe with inner and outer radii $a$ and $b$ , respectively .....	198
Figure H.3 – TEM line dielectric properties test set-up [85] .....	200
Figure J.1 – SAR and temperature increase ( $\Delta T$ ) distributions simulated for a three-layer (skin, fat, muscle) planar torso model.....	207
Figure J.2 – Statistical approach to protect 90 % of the population .....	209
Figure J.3 – psSAR skin enhancement factors .....	210
Figure K.1 – SAM face-down phantom .....	212
Figure K.2 – SAM head-stand phantom.....	212
Figure K.3 – Wrist phantom .....	213
Figure L.1 – Cross section of the unified phantom (Uniphantom) with its dimensions .....	214
Figure L.2 – Measurement positions of handsets with straight and clamshell form factors .....	215
Figure L.3 – Flow chart of testing procedure for handsets with straight form factors.....	216
Figure L.4 – Flow chart of testing procedure for handsets with clamshell form factors.....	217
Figure M.1 – Configuration of a personal wired hands-free headset.....	218

Figure M.2 – Configuration without a personal wired hands-free headset.....	219
Figure O.1 – Orientation and surface of averaging volume relative to phantom surface.....	235
Figure U.1 – Categories (classes) for comparison of the measured psSAR between the Uniphantom ( $SAR_{uni}$ ) and the SAM phantom ( $SAR_{SAM}$ ) .....	252
Figure U.2 – Histogram of the deviation of the 10 g psSAR of 45 handsets with straight form factors positioned at the flat bottom of the Uniphantom .....	254
Figure U.3 – Histogram of the deviation of the 1 g psSAR of 40 handsets with straight form factors positioned at the flat bottom of the Uniphantom .....	255
Figure U.4 – Histogram of the deviation of the 10 g psSAR of 25 handsets with straight form factors positioned at the flat bottom of the Uniphantom .....	256
Figure U.5 – Histogram of the deviation of the 1 g psSAR from 20 handsets with straight form factors positioned at the flat bottom of the Uniphantom .....	257
Figure U.6 – Histogram of the deviation of the 10 g psSAR of 20 handsets with straight form factors or smart phones positioned at the flat bottom of the Uniphantom .....	258
Figure U.7 – Histogram of the deviation of the 1 g psSAR of 20 handsets with straight form factors or smart phones positioned at the flat bottom of the Uniphantom.....	259
Figure U.8 – Histogram of the deviation of the 10 g psSAR of 20 handsets with straight form factors or smart phones positioned at the corner of the Uniphantom .....	260
Figure U.9 – Histogram of the deviation of the 1 g psSAR of 19 handsets with straight form factors or smart phones positioned at the corner of the Uniphantom .....	261
Figure U.10 – Histogram of the deviation of the 10 g psSAR of 20 handsets with clamshell form factors at the corner of the Uniphantom.....	262
Figure U.11 – Histogram of the deviation of the 1 g psSAR of 19 handsets with clamshell form factors at the corner of the Uniphantom.....	263
Figure V.1 – Generated RF input power variations to operation time without and with application of AIPLC.....	264
Figure V.2 – The system block diagram of the AIPLC.....	265
Figure V.3 – Power variation characteristics by adjusting the amplifier or signal generator outputs.....	265
Figure W.1 – Low, middle, and high channels at 2 GHz band (Band 1) .....	267
Figure W.2 – RF conducted power versus 10 g psSAR .....	268
Figure W.3 – 1 g SAR as a function of RF conducted power in various test conditions .....	269
Table 1 – Evaluation plan checklist.....	28
Table 2 – Dielectric properties of the tissue-equivalent medium .....	32
Table 3 – Area scan parameters .....	63
Table 4 – Zoom scan parameters .....	63
Table 5 – Example method to determine the combined SAR value using Alternative 1 .....	70
Table 6 – Root-mean-squared error SAR correction formula as a function of the maximum change in permittivity or conductivity [28].....	83
Table 7 – Threshold values $TH(f)$ used in this proposed test reduction protocol .....	93
Table 8 – Divisors for common probability density functions (PDFs).....	101
Table 9 – Uncertainty budget template for evaluating the uncertainty in the measured value of 1 g or 10 g psSAR from a DUT or validation antenna (N = normal, R = rectangular) .....	103
Table 10 – Uncertainty of Formula (8) (see 7.8.2) as a function of the maximum change in permittivity or conductivity .....	107
Table B.1 – The number of DUTs used for the statistical study .....	123

Table B.2 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various $x$ values .....	124
Table B.3 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for 1 g and 10 g psSAR .....	124
Table B.4 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various antenna locations .....	125
Table B.5 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various frequency bands .....	125
Table B.6 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various device types .....	126
Table B.7 – Distance $D_{\min}^*$ for various “iso-level” values .....	130
Table B.8 – Experimental thresholds to have a 95 % probability that the maximum measured SAR value from the area scan will also have a psSAR.....	132
Table B.9 – SAR values from the area scan (GSM 900 band): Example 1 .....	133
Table B.10 – SAR values from the area scan (GSM 900 band): Example 2 .....	133
Table C.1 – Measurement uncertainty budget for relative SAR measurements using Class 2 fast SAR testing, for tests performed within one frequency band and modulation.....	141
Table C.2 – Measurement uncertainty budget for system check using Class 2 fast SAR testing .....	142
Table D.1 – Mechanical dimensions of the reference dipoles .....	146
Table D.2 – Numerical target SAR values (W/kg) for standard dipole and flat phantom .....	147
Table D.3 – Mechanical dimensions of the standard waveguide .....	148
Table D.4 – Numerical target SAR values for waveguides.....	149
Table D.5 – Numerical target SAR values for CAs.....	151
Table D.6 – Mechanical dimensions of the reference meander dipole .....	152
Table D.7 – Numerical target SAR value (W/kg) for meander dipole.....	153
Table D.8 – Dimensions for VPIFA antennas at different frequencies.....	154
Table D.9 – Electric properties for the dielectric layers for VPIFA antennas .....	155
Table D.10 – Numerical target SAR values for VPIFAs on the flat phantom.....	156
Table E.1 – Uncertainty analysis for transfer calibration using temperature probes .....	160
Table E.2 – Guidelines for designing calibration waveguides .....	163
Table E.3 – Uncertainty analysis of the probe calibration in waveguide.....	164
Table E.4 – Uncertainty template for evaluation of reference antenna gain .....	166
Table E.5 – Uncertainty template for calibration using reference antenna .....	167
Table E.6 – Uncertainty components for probe calibration using thermal methods .....	170
Table F.1 – Suggested recipes for achieving target dielectric properties, 30 MHz to 900 MHz .....	178
Table F.2 – Suggested recipes for achieving target dielectric properties, 1 800 MHz to 10 000 MHz .....	179
Table G.1 – Dimensions used in deriving SAM phantom from the ARMY 90th percentile male head data (Gordon et al. [61]) .....	183
Table G.2 – Additional SAM dimensions compared with selected dimensions from the ARMY 90th percentile male head data (Gordon et al. [61]) – specialist head measurement section.....	183
Table G.3 – Parameters used for calculation of reference SAR values in Table D.2 .....	190
Table H.1 – Parameters for calculating the dielectric properties of various reference liquids.....	202
Table H.2 – Dielectric properties of reference liquids at 20 °C .....	203
Table J.1 –psSAR correction factors .....	209

Table N.1 – SAR results tables for example test results in GSM 850 band .....	221
Table N.2 – SAR results tables for example test results in GSM 900 band .....	222
Table N.3 – SAR results tables for example test results in GSM 1800 band .....	222
Table N.4 – SAR results tables for example test results in GSM 1900 band .....	223
Table O.1 – Parameters for the reference function $f_1$ in Formula (O.12).....	231
Table O.2 – Reference SAR values from the distribution functions $f_1$ , $f_2$ , and $f_3$ .....	232
Table O.3 – Example uncertainty template and example numerical values for permittivity ( $\epsilon_r'$ ) and conductivity ( $\sigma$ ) measurement.....	237
Table S.1 – Uncertainties relating to the deviations of the parameters of the standard waveguide from theory.....	248
Table S.2 – Other uncertainty contributions relating to the dipole antennas specified in Annex D.....	249
Table S.3 – Other uncertainty contributions relating to the standard waveguides specified in Annex D .....	249
Table U.1 – Summary of information to determine the margin for handsets with straight form factors positioned at the flat bottom of the Uniphantom .....	254
Table U.2 – Summary of information to determine the margin for handsets with straight form factors, including slide-type and bar handsets (except smart phones), positioned at the flat bottom of the Uniphantom .....	256
Table U.3 – Summary of information to determine the margin for the smart phones positioned at the flat bottom of the Uniphantom .....	258
Table U.4 – Summary of information to determine the margin for smart phones positioned at the corner of the Uniphantom .....	260
Table U.5 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various device types .....	261
Table U.6 – Summary of information to determine the margin for handsets with clamshell form factors positioned at the corner of the Uniphantom .....	262
Table W.1 – Relative standard deviation of $\alpha$ found in Study 1 (without MPR) .....	267
Table W.2 – Maximum relative standard deviation of $\alpha$ found in Study 2 (with MPR) .....	269