



IEEE

IEC/IEEE 62209-1528

Edition 1.0 2020-10

INTERNATIONAL STANDARD



Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices –

**Part 1528: Human models, instrumentation, and procedures
(Frequency range of 4 MHz to 10 GHz)**

<https://standards.iteh.ai/catalog/standards/sist/3bb677b3-1842-470d-9649-c245f0b800c0/iec-ieee-62209-1528-2020>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2020 IEC, Geneva, Switzerland
Copyright © 2020 IEEE

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing being secured. Requests for permission to reproduce should be addressed to either IEC at the address below or IEC's member National Committee in the country of the requester or from IEEE.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue
New York, NY 10016-5997
United States of America
stds.ipr@ieee.org
www.ieee.org

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About the IEEE

IEEE is the world's largest professional association dedicated to advancing technological innovation and excellence for the benefit of humanity. IEEE and its members inspire a global community through its highly cited publications, conferences, technology standards, and professional and educational activities.

About IEC/IEEE publications

The technical content of IEC/IEEE publications is kept under constant review by the IEC and IEEE. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and definitions clause of IEC publications issued between 2002 and 2015. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.



IEEE

IEC/IEEE 62209-1528

Edition 1.0 2020-10

INTERNATIONAL STANDARD



**Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices –
Part 1528: Human models, instrumentation, and procedures
(Frequency range of 4 MHz to 10 GHz)**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 17.220.20

ISBN 978-2-8322-8533-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	14
INTRODUCTION.....	17
1 Scope.....	18
2 Normative references	18
3 Terms and definitions	18
4 Symbols and abbreviated terms.....	26
4.1 Physical quantities	26
4.2 Constants	26
4.3 Abbreviated terms.....	27
5 Quick start guide and evaluation plan checklist.....	28
6 Measurement system specifications.....	30
6.1 General requirements for full SAR testing	30
6.2 Phantom specifications	31
6.2.1 General	31
6.2.2 Basic phantom parameters	31
6.2.3 Head phantom	33
6.2.4 Flat phantom	34
6.2.5 Device-specific phantoms	35
6.3 Influence of hand on SAR in head.....	35
6.4 Scanning system requirements.....	36
6.5 Device holder specifications.....	36
6.6 Characteristics of the readout electronics.....	37
7 Protocol for SAR assessment.....	37
7.1 General.....	37
7.2 Measurement preparation	37
7.2.1 Preparation of tissue-equivalent medium and system check.....	37
7.2.2 Preparation of the wireless communication DUT	38
7.2.3 DUT operating mode requirements	38
7.2.4 Positioning of the DUT relative to the phantom	40
7.2.5 Antenna configurations	57
7.2.6 Options and accessories.....	57
7.2.7 DUTs with alternative form factor.....	57
7.2.8 Test frequencies for DUTs	58
7.3 Tests to be performed for DUTs	58
7.3.1 General	58
7.3.2 Basic approach for DUT testing	59
7.4 Measurement procedure	60
7.4.1 General	60
7.4.2 Full SAR testing procedure	60
7.4.3 Drift	64
7.4.4 SAR measurements of DUTs with multiple antennas or multiple transmitters	66
7.5 Post-processing of SAR measurement data	72
7.5.1 Interpolation	72
7.5.2 Extrapolation	72
7.5.3 Definition of the averaging volume.....	72

7.5.4	Searching for the maxima	73
7.6	Time-period averaged SAR considerations.....	73
7.6.1	General	73
7.6.2	RF conducted power.....	73
7.6.3	Time-period averaged SAR measurement settings for SAR measurement methods	73
7.6.4	Exposure condition and test position considerations	74
7.6.5	Time-period averaged SAR for simultaneous transmission.....	74
7.6.6	TX factor assessment	74
7.6.7	SAR measurements	75
7.6.8	Uncertainty in TPAS evaluations.....	75
7.7	Proximity sensors considerations	76
7.7.1	General	76
7.7.2	Procedures for determining proximity sensor triggering distances	77
7.7.3	Procedure for determining proximity sensor coverage area	80
7.7.4	SAR measurement procedure involving proximity sensors	81
7.8	SAR correction for deviations of complex permittivity from targets	81
7.8.1	General	81
7.8.2	SAR correction formula.....	82
7.8.3	Uncertainty of the correction formula	83
7.9	Minimization of testing time.....	83
7.9.1	General	83
7.9.2	Fast SAR testing.....	84
7.9.3	SAR test reductions	89
8	Measurement uncertainty estimation.....	100
8.1	General.....	100
8.2	Requirements on the uncertainty evaluation.....	101
8.3	Description of uncertainty models	102
8.3.1	General	102
8.3.2	SAR measurement of a DUT.....	102
8.3.3	System validation and system check measurement.....	102
8.3.4	System check repeatability and reproducibility.....	102
8.3.5	Fast SAR testing (relative measurement).....	102
8.4	Parameters contributing to uncertainty	104
8.4.1	Measurement system errors.....	104
8.4.2	Phantom and device (DUT or validation antenna) errors	105
8.4.3	Corrections to the SAR result (if applied).....	107
9	Measurement report	108
9.1	General.....	108
9.2	Items to be recorded in the measurement report	108
Annex A (normative)	SAR measurement system verification	112
A.1	Overview.....	112
A.2	System check	112
A.2.1	Purpose.....	112
A.2.2	Phantom set-up	113
A.2.3	System check antenna.....	113
A.2.4	System check antenna input power measurement.....	114
A.2.5	System check procedure.....	115
A.2.6	System check acceptance criteria.....	116

A.3	System validation.....	116
A.3.1	Purpose.....	116
A.3.2	Phantom set-up.....	116
A.3.3	System validation antennas.....	116
A.3.4	Input power measurement.....	117
A.3.5	System validation procedure.....	117
A.4	Fast SAR testing system validation and system check.....	119
A.4.1	General.....	119
A.4.2	Fast SAR testing system validation.....	119
A.4.3	Fast SAR testing system check.....	120
Annex B (informative)	SAR test reduction supporting information.....	122
B.1	General.....	122
B.2	Test reduction based on characteristics of DUT design.....	122
B.2.1	General.....	122
B.2.2	Statistical analysis overview.....	122
B.2.3	Analysis results.....	123
B.2.4	Conclusions.....	126
B.2.5	Expansion to multi-transmission antennas.....	126
B.3	Test reduction based on analysis of SAR results on other signal modulations.....	126
B.3.1	General.....	126
B.3.2	Analysis results.....	127
B.4	Test reduction based on SAR level analysis.....	128
B.4.1	General.....	128
B.4.2	Statistical analysis.....	129
B.4.3	Test reduction applicability example.....	132
B.5	Other statistical approaches to search for the high SAR test configurations.....	134
B.5.1	General.....	134
B.5.2	Test reductions based on a DOE.....	134
B.5.3	One factor at a time (OFAT) search.....	134
B.5.4	Analysis of unstructured data.....	134
Annex C (informative)	Measurement uncertainty of results obtained from specific fast SAR testing methods.....	135
C.1	General.....	135
C.2	Measurement uncertainty evaluation – contributing parameters.....	135
C.2.1	General.....	135
C.2.2	Probe calibration and system calibration drift.....	136
C.2.3	Isotropy.....	136
C.2.4	Probe positioning.....	137
C.2.5	Mutual sensor coupling.....	138
C.2.6	Scattering within the probe array.....	139
C.2.7	Sampling error.....	139
C.2.8	Array boundaries.....	139
C.2.9	Probe or probe array coupling with the DUT.....	139
C.2.10	Measurement system immunity / secondary reception.....	139
C.2.11	Deviations in phantom shape.....	140
C.2.12	Spatial variation in dielectric properties.....	140
C.2.13	Reconstruction.....	140
C.3	Uncertainty budget.....	140
Annex D (normative)	SAR system validation antennas.....	143

D.1	General antenna requirements	143
D.2	Standard dipole antenna	143
D.2.1	Mechanical description	143
D.2.2	Numerical target SAR values	146
D.3	Standard waveguide	148
D.3.1	Mechanical description	148
D.3.2	Numerical target SAR values	149
D.4	System validation antennas for below 150 MHz	149
D.4.1	General	149
D.4.2	Confined loop antenna	150
D.4.3	Meander dipole antenna	152
D.5	Orthogonal E-field source – VPIFA	153
D.5.1	Mechanical description	153
D.5.2	Numerical target SAR values	156
Annex E (normative)	Calibration and characterization of dosimetric (SAR) probes	157
E.1	Introductory remarks	157
E.2	Linearity	158
E.3	Assessment of the sensitivity of the dipole sensors	158
E.3.1	General	158
E.3.2	Two-step calibration procedures	158
E.3.3	One-step calibration procedure – reference antenna method	164
E.3.4	One-step calibration procedure – coaxial calorimeter method	168
E.4	Isotropy	170
E.4.1	Axial isotropy	170
E.4.2	Hemispherical isotropy	170
E.5	Lower detection limit	175
E.6	Boundary effect	176
E.7	Response time	176
Annex F (informative)	Example recipes for phantom tissue-equivalent media	177
F.1	General	177
F.2	Ingredients	177
F.3	Tissue-equivalent medium liquid formulas (permittivity/conductivity)	178
Annex G (normative)	Phantom specifications	180
G.1	Rationale for the phantom characteristics	180
G.1.1	General	180
G.1.2	Rationale for the SAM phantom	180
G.1.3	Rationale for the flat phantom	180
G.2	SAM phantom specifications	181
G.2.1	General SAM phantom specifications	181
G.2.2	SAM phantom shell specification	185
G.3	Flat phantom specifications	187
G.4	Justification of flat phantom dimensions	188
G.5	Rationale for tissue-equivalent media	191
G.6	Definition of a phantom coordinate system and a DUT coordinate system	193
Annex H (informative)	Measurement of the dielectric properties of tissue-equivalent media and uncertainty estimation	195
H.1	Overview	195
H.2	Measurement techniques	195
H.2.1	General	195

H.2.2	Instrumentation.....	195
H.2.3	General principles	195
H.3	Slotted coaxial transmission line	196
H.3.1	General	196
H.3.2	Equipment set-up	196
H.3.3	Measurement procedure	197
H.4	Contact coaxial probe	197
H.4.1	General	197
H.4.2	Equipment set-up	198
H.4.3	Measurement procedure	199
H.5	TEM transmission line.....	199
H.5.1	General	199
H.5.2	Equipment set-up	200
H.5.3	Measurement procedure	200
H.6	Dielectric properties of reference liquids	201
Annex I (informative)	Studies for potential hand effects on head SAR	204
I.1	Overview.....	204
I.2	Background.....	204
I.2.1	General	204
I.2.2	Hand phantoms	205
I.3	Summary of experimental studies	205
I.3.1	Experimental studies using fully compliant SAR measurement systems	205
I.3.2	Experimental studies using other SAR measurement systems	205
I.4	Summary of computational studies.....	206
I.5	Conclusions.....	206
Annex J (informative)	Skin enhancement factor.....	207
J.1	Background.....	207
J.2	Rationale	208
J.3	Simulations	208
J.4	Recommendation	209
Annex K (normative)	Application-specific phantoms	211
K.1	General.....	211
K.2	Phantom basic requirements.....	211
K.3	Examples of specific alternative phantoms	211
K.3.1	Face-down SAM phantom.....	211
K.3.2	Head-stand SAM phantom	212
K.3.3	Wrist phantom	212
K.4	Scanning and evaluation requirements.....	213
K.5	Uncertainty assessment.....	213
K.6	Reporting.....	213
Annex L (normative)	Fast compliance evaluations using a flat-bottom phantom with a curved corner (Uniphantom).....	214
L.1	General.....	214
L.2	Uniphantom	214
L.3	Device positions for compliance testing and definitions of handset shapes	214
L.3.1	General	214
L.3.2	Handsets with a straight form factor.....	215
L.3.3	Handsets with a clamshell form factor.....	215
L.4	Testing procedure	215

L.4.1	General	215
L.4.2	Handsets with straight form factors	215
L.4.3	Handsets with clamshell form factors	216
L.5	Uncertainty of SAR measurement results using Uniphantom	217
Annex M (informative)	Wired hands-free headset testing	218
M.1	Concept	218
M.2	Example results	219
M.3	Discussion	220
Annex N (informative)	Applying the head SAR test procedures	221
Annex O (normative)	Uncertainty analysis for measurement system manufacturers and calibration laboratories.....	224
O.1	Probe linearity and detection limits	224
O.2	Broadband signal uncertainty	225
O.3	Boundary effect.....	225
O.4	Field-probe readout electronics uncertainty.....	226
O.5	Signal step-response time uncertainty.....	226
O.6	Probe integration-time uncertainty	227
O.6.1	General	227
O.6.2	Probe integration-time uncertainty for periodic pulsed signals.....	227
O.6.3	Probe integration-time uncertainty for non-periodic signals	228
O.7	Contribution of mechanical constraints.....	228
O.7.1	Mechanical tolerances of the probe positioner (directions parallel to phantom surface).....	228
O.7.2	Probe positioning with respect to phantom shell surface	228
O.7.3	First-order approximation of exponential decay.....	229
O.8	Contribution of post-processing.....	229
O.8.1	General	229
O.8.2	Evaluation test functions.....	230
O.8.3	Data-processing algorithm uncertainty evaluations	232
O.9	Tissue-equivalent medium properties uncertainty.....	235
O.9.1	General	235
O.9.2	Medium density	235
O.9.3	Medium conductivity uncertainty	235
O.9.4	Medium permittivity uncertainty	235
O.9.5	Assessment of dielectric properties measurement uncertainties.....	235
O.9.6	Medium temperature uncertainty.....	237
Annex P (normative)	Post-processing techniques	239
P.1	Extrapolation and interpolation schemes	239
P.1.1	General	239
P.1.2	Extrapolation schemes.....	239
P.1.3	Interpolation schemes.....	239
P.2	Averaging scheme and maximum finding	239
P.2.1	Volume average schemes.....	239
P.2.2	Finding the psSAR and estimating the uncertainty	240
Annex Q (informative)	Rationale for time-period averaged SAR test procedure	241
Annex R (normative)	Measurement uncertainty analysis for testing laboratories	242
R.1	RF ambient conditions	242
R.2	Device positioning and holder uncertainties	242
R.2.1	General	242

R.2.2	Device holder perturbation uncertainty.....	243
R.2.3	DUT positioning uncertainty with a specific test device holder: Type A	244
R.3	Probe modulation response	244
R.4	Time-period averaged SAR	245
R.4.1	General	245
R.4.2	TX factor uncertainty	245
R.5	Measured SAR drift.....	246
R.5.1	General	246
R.5.2	Accounting for drift	246
R.6	SAR scaling uncertainty	247
Annex S (normative)	Validation antenna SAR measurement uncertainty	248
S.1	Deviation of experimental antennas	248
S.2	Other uncertainty contributions when using system validation antennas.....	248
Annex T (normative)	Interlaboratory comparisons	250
T.1	Purpose	250
T.2	Phantom set-up	250
T.3	Reference devices	250
T.4	Power set-up	250
T.5	Interlaboratory comparison – procedure	251
Annex U (informative)	Determination of the margin for compliance evaluation using the Uniphantom	252
U.1	General.....	252
U.2	Deviation of the psSAR measured using the Uniphantom from the psSAR measured using the SAM phantom.....	252
U.3	Determination of margin based on 95 % confidence interval.....	253
U.4	Examples of the determination of the margin factor.....	253
U.4.1	Margin for handsets with straight form factors at flat-bottom position	253
U.4.2	Margin for handsets with straight form factors (except smart phones at flat-bottom position).....	255
U.4.3	Margin for smart phones at flat-bottom position	257
U.4.4	Margin for smart phones at corner position	259
U.4.5	Margin for handsets with clamshell form factors at corner position.....	261
Annex V (informative)	Automatic input power level control for system validation	264
V.1	General.....	264
V.2	Operational mechanism of AIPLC	264
Annex W (informative)	LTE test configurations supporting information	266
W.1	General.....	266
W.2	Study 1	266
W.3	Study 2	268
W.4	Justifications of relative standard deviations	269
Bibliography	271
Figure 1	– Quick start guide	29
Figure 2	– Dimensions of the elliptical phantom	35
Figure 3	– Mounting of the DUT in the device holder using low-permittivity and low-loss foam to avoid changes of DUT performance by the holder material.....	37
Figure 4	– Designation of DUT reference points.....	41

Figure 5 – Measurements performed by shifting a large device over the efficient measurement area of the system including overlapping areas – in this case: six tests performed	42
Figure 6 – Test positions for body-worn devices	43
Figure 7 – Device with swivel antenna	44
Figure 8 – Test positions for body supported devices.....	45
Figure 9 – Test positions for desktop devices	47
Figure 10 – Test positions for front-of-face devices.....	48
Figure 11 – Test position for hand-held devices, not used at the head or torso	49
Figure 12 – Test position for limb-worn devices	49
Figure 13 – Test position for clothing-integrated wireless communication devices.....	50
Figure 14 – Possible test positions for a generic device	51
Figure 15 – Vertical and horizontal reference lines and reference points A and B on two example device types: a full touch-screen smart phone (left) and a DUT with a keypad (right)	53
Figure 16 – Cheek position of the DUT on the left side of SAM where the device position shall be maintained for the phantom test set-up.....	56
Figure 17 – Tilt position of the DUT on the left side of SAM	56
Figure 18 – An alternative form factor DUT with reference points and reference lines	57
Figure 19 – Block diagram of the tests to be performed	60
Figure 20 – Orientation of the probe with respect to the line normal to the phantom surface, for head and flat phantoms, shown at two different locations	64
Figure 21 – Measurement procedure for different types of correlated signals	72
Figure 22 – Positioning of the surfaces and edges of the DUT for determining the proximity sensor triggering distance	79
Figure 23 – Positioning of the edges of the DUT to determine proximity sensor triggering distance variations with the edge positioned at different angles from the perpendicular position.....	80
Figure 24 – Fast SAR Procedure A	87
Figure 25 – Fast SAR Procedure B	89
Figure 26 – Modified chart of Figure 19.....	93
Figure 27 – Use of conducted power for LTE mode selection, for Band 1 (1 920 MHz to 1 980 MHz) (MPR values are in dB).....	97
Figure 28 – Use of conducted power for LTE mode selection, for Band 17 (704 MHz to 716 MHz) (MPR values are in dB).....	98
Figure A.1 – Test set-up for the system check	114
Figure B.1 – Distribution of Tilt/Cheek.....	124
Figure B.2 – SAR relative to SAR in position with maximum SAR in GSM mode.....	128
Figure B.3 – Two points identifying the minimum distance between the position of the interpolated maximum SAR and the points at $0,6 \times SAR_{max}$	130
Figure B.4 – Histogram for D_{min} in the case of GSM 900 and iso-level at $0,6 \times SAR_{max}$	130
Figure B.5 – Histogram for random variable $Factor_{1g,1800}$	132
Figure D.1 – Mechanical details of the standard dipoles.....	145
Figure D.2 – Standard waveguide (dimensions are according to Table D.3)	148
Figure D.3 – Drawing of the CLA that corresponds to a resonant loop integrated in a metallic structure to isolate the resonant structure from the environment	150
Figure D.4 – Mechanical details of the meander dipoles for 150 MHz.....	152

Figure D.5 – VPIFA validation antenna	155
Figure D.6 – Mask for positioning VPIFAs	155
Figure E.1 – Experimental set-up for assessment of the sensitivity (conversion factor) using a vertically-oriented rectangular waveguide	162
Figure E.2 – Illustration of the antenna gain evaluation set-up	165
Figure E.3 – Schematic of the coaxial calorimeter system.....	169
Figure E.4 – Set-up to assess hemispherical isotropy deviation in tissue-equivalent medium.....	171
Figure E.5 – Alternative set-up to assess hemispherical isotropy deviation in tissue-equivalent medium.....	172
Figure E.6 – Experimental set-up for the hemispherical isotropy assessment.....	173
Figure E.7 – Conventions for dipole position (ζ) and polarization (θ)	174
Figure E.8 – Measurement of hemispherical isotropy with reference antenna.....	175
Figure G.1 – Illustration of dimensions in Table G.1 and Table G.2.....	182
Figure G.2 – Close up side view of phantom showing the ear region.....	184
Figure G.3 – Side view of the phantom showing relevant markings	185
Figure G.4 – Sagittally bisected phantom with extended perimeter (shown placed on its side as used for device SAR tests)	186
Figure G.5 – Picture of the phantom showing the central strip.....	186
Figure G.6 – Cross-sectional view of SAM at the reference plane.....	187
Figure G.7 – Dimensions of the flat phantom set-up used for deriving the minimal phantom dimensions for W and L for a given phantom depth D	189
Figure G.8 – FDTD predicted error in the 10 g psSAR as a function of the dimensions of the flat phantom compared with an infinite flat phantom at 800 MHz.....	190
Figure G.9 – Complex permittivity of human tissues compared to the phantom target properties	193
Figure G.10 – Example reference coordinate system for the left-ear ERP of the SAM phantom	194
Figure G.11 – Example coordinate system on a DUT	194
Figure H.1 – Slotted line set-up.....	196
Figure H.2 – An open-ended coaxial probe with inner and outer radii a and b , respectively	198
Figure H.3 – TEM line dielectric properties test set-up [85]	200
Figure J.1 – SAR and temperature increase (ΔT) distributions simulated for a three-layer (skin, fat, muscle) planar torso model.....	207
Figure J.2 – Statistical approach to protect 90 % of the population	209
Figure J.3 – psSAR skin enhancement factors	210
Figure K.1 – SAM face-down phantom	212
Figure K.2 – SAM head-stand phantom.....	212
Figure K.3 – Wrist phantom	213
Figure L.1 – Cross section of the unified phantom (Uniphantom) with its dimensions	214
Figure L.2 – Measurement positions of handsets with straight and clamshell form factors	215
Figure L.3 – Flow chart of testing procedure for handsets with straight form factors.....	216
Figure L.4 – Flow chart of testing procedure for handsets with clamshell form factors.....	217
Figure M.1 – Configuration of a personal wired hands-free headset.....	218

Figure M.2 – Configuration without a personal wired hands-free headset.....	219
Figure O.1 – Orientation and surface of averaging volume relative to phantom surface.....	235
Figure U.1 – Categories (classes) for comparison of the measured psSAR between the Uniphantom (SAR_{uni}) and the SAM phantom (SAR_{SAM})	252
Figure U.2 – Histogram of the deviation of the 10 g psSAR of 45 handsets with straight form factors positioned at the flat bottom of the Uniphantom	254
Figure U.3 – Histogram of the deviation of the 1 g psSAR of 40 handsets with straight form factors positioned at the flat bottom of the Uniphantom	255
Figure U.4 – Histogram of the deviation of the 10 g psSAR of 25 handsets with straight form factors positioned at the flat bottom of the Uniphantom	256
Figure U.5 – Histogram of the deviation of the 1 g psSAR from 20 handsets with straight form factors positioned at the flat bottom of the Uniphantom	257
Figure U.6 – Histogram of the deviation of the 10 g psSAR of 20 handsets with straight form factors or smart phones positioned at the flat bottom of the Uniphantom	258
Figure U.7 – Histogram of the deviation of the 1 g psSAR of 20 handsets with straight form factors or smart phones positioned at the flat bottom of the Uniphantom.....	259
Figure U.8 – Histogram of the deviation of the 10 g psSAR of 20 handsets with straight form factors or smart phones positioned at the corner of the Uniphantom	260
Figure U.9 – Histogram of the deviation of the 1 g psSAR of 19 handsets with straight form factors or smart phones positioned at the corner of the Uniphantom	261
Figure U.10 – Histogram of the deviation of the 10 g psSAR of 20 handsets with clamshell form factors at the corner of the Uniphantom.....	262
Figure U.11 – Histogram of the deviation of the 1 g psSAR of 19 handsets with clamshell form factors at the corner of the Uniphantom.....	263
Figure V.1 – Generated RF input power variations to operation time without and with application of AIPLC.....	264
Figure V.2 – The system block diagram of the AIPLC.....	265
Figure V.3 – Power variation characteristics by adjusting the amplifier or signal generator outputs.....	265
Figure W.1 – Low, middle, and high channels at 2 GHz band (Band 1)	267
Figure W.2 – RF conducted power versus 10 g psSAR	268
Figure W.3 – 1 g SAR as a function of RF conducted power in various test conditions	269
Table 1 – Evaluation plan checklist.....	28
Table 2 – Dielectric properties of the tissue-equivalent medium	32
Table 3 – Area scan parameters	63
Table 4 – Zoom scan parameters	63
Table 5 – Example method to determine the combined SAR value using Alternative 1	70
Table 6 – Root-mean-squared error SAR correction formula as a function of the maximum change in permittivity or conductivity [28].....	83
Table 7 – Threshold values $TH(f)$ used in this proposed test reduction protocol	93
Table 8 – Divisors for common probability density functions (PDFs).....	101
Table 9 – Uncertainty budget template for evaluating the uncertainty in the measured value of 1 g or 10 g psSAR from a DUT or validation antenna (N = normal, R = rectangular)	103
Table 10 – Uncertainty of Formula (8) (see 7.8.2) as a function of the maximum change in permittivity or conductivity	107
Table B.1 – The number of DUTs used for the statistical study	123

Table B.2 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various x values	124
Table B.3 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for 1 g and 10 g psSAR	124
Table B.4 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various antenna locations	125
Table B.5 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various frequency bands	125
Table B.6 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various device types	126
Table B.7 – Distance D_{\min}^* for various “iso-level” values	130
Table B.8 – Experimental thresholds to have a 95 % probability that the maximum measured SAR value from the area scan will also have a psSAR.....	132
Table B.9 – SAR values from the area scan (GSM 900 band): Example 1	133
Table B.10 – SAR values from the area scan (GSM 900 band): Example 2	133
Table C.1 – Measurement uncertainty budget for relative SAR measurements using Class 2 fast SAR testing, for tests performed within one frequency band and modulation.....	141
Table C.2 – Measurement uncertainty budget for system check using Class 2 fast SAR testing	142
Table D.1 – Mechanical dimensions of the reference dipoles	146
Table D.2 – Numerical target SAR values (W/kg) for standard dipole and flat phantom	147
Table D.3 – Mechanical dimensions of the standard waveguide	148
Table D.4 – Numerical target SAR values for waveguides.....	149
Table D.5 – Numerical target SAR values for CAs.....	151
Table D.6 – Mechanical dimensions of the reference meander dipole	152
Table D.7 – Numerical target SAR value (W/kg) for meander dipole.....	153
Table D.8 – Dimensions for VPIFA antennas at different frequencies.....	154
Table D.9 – Electric properties for the dielectric layers for VPIFA antennas	155
Table D.10 – Numerical target SAR values for VPIFAs on the flat phantom.....	156
Table E.1 – Uncertainty analysis for transfer calibration using temperature probes	160
Table E.2 – Guidelines for designing calibration waveguides	163
Table E.3 – Uncertainty analysis of the probe calibration in waveguide.....	164
Table E.4 – Uncertainty template for evaluation of reference antenna gain	166
Table E.5 – Uncertainty template for calibration using reference antenna	167
Table E.6 – Uncertainty components for probe calibration using thermal methods	170
Table F.1 – Suggested recipes for achieving target dielectric properties, 30 MHz to 900 MHz	178
Table F.2 – Suggested recipes for achieving target dielectric properties, 1 800 MHz to 10 000 MHz	179
Table G.1 – Dimensions used in deriving SAM phantom from the ARMY 90th percentile male head data (Gordon et al. [61])	183
Table G.2 – Additional SAM dimensions compared with selected dimensions from the ARMY 90th percentile male head data (Gordon et al. [61])—specialist head measurement section.....	183
Table G.3 – Parameters used for calculation of reference SAR values in Table D.2	190
Table H.1 – Parameters for calculating the dielectric properties of various reference liquids.....	202
Table H.2 – Dielectric properties of reference liquids at 20 °C	203
Table J.1 –psSAR correction factors	209

Table N.1 – SAR results tables for example test results in GSM 850 band	221
Table N.2 – SAR results tables for example test results in GSM 900 band	222
Table N.3 – SAR results tables for example test results in GSM 1800 band	222
Table N.4 – SAR results tables for example test results in GSM 1900 band	223
Table O.1 – Parameters for the reference function f_1 in Formula (O.12).....	231
Table O.2 – Reference SAR values from the distribution functions f_1 , f_2 , and f_3	232
Table O.3 – Example uncertainty template and example numerical values for permittivity (ϵ_r') and conductivity (σ) measurement.....	237
Table S.1 – Uncertainties relating to the deviations of the parameters of the standard waveguide from theory.....	248
Table S.2 – Other uncertainty contributions relating to the dipole antennas specified in Annex D.....	249
Table S.3 – Other uncertainty contributions relating to the standard waveguides specified in Annex D	249
Table U.1 – Summary of information to determine the margin for handsets with straight form factors positioned at the flat bottom of the Uniphantom	254
Table U.2 – Summary of information to determine the margin for handsets with straight form factors, including slide-type and bar handsets (except smart phones), positioned at the flat bottom of the Uniphantom	256
Table U.3 – Summary of information to determine the margin for the smart phones positioned at the flat bottom of the Uniphantom	258
Table U.4 – Summary of information to determine the margin for smart phones positioned at the corner of the Uniphantom	260
Table U.5 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various device types	261
Table U.6 – Summary of information to determine the margin for handsets with clamshell form factors positioned at the corner of the Uniphantom	262
Table W.1 – Relative standard deviation of α found in Study 1 (without MPR)	267
Table W.2 – Maximum relative standard deviation of α found in Study 2 (with MPR)	269