

Edition 3.0 2021-02

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



## Digital audio – Interface for non-linear PCM Encoded audio bitstreams applying IEC 60958 – Part 1: General (standards.iteh.ai)

Audionumérique – Interface pour les flux de bits audio à codage MIC non linéaire selon l'IEC 60958 – 7d4af2ad9033/iec-61937-1-2021 Partie 1: Généralités





## THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Tel.: +41 22 919 02 11 info@iec.ch www.iec.ch

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a livariety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - www.electropedia.org

IEC Just Published - webstore.iec.ch/justpublished Stay up to date on all new IEC publications. Just Published details all new publications released. Available online\_and)37 once a month by email.

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary

## IEC Customer Service Centre - webstore.iec.ch/cscd9033/icc-01937-1-2021

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

#### A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

#### A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

#### Recherche de publications IEC -

#### webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

#### IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

#### Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

#### IEC online collection - oc.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

#### Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 000 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.



Edition 3.0 2021-02

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



Digital audio – Interface for hon-linear PCM Encoded audio bitstreams applying IEC 60958 – Part 1: General (standards.iteh.ai)

IEC 61937-1:2021

Audionumérique<sub>ps</sub>/Interface.pour les flux/de bits audio à codage MIC non linéaire selon l'IEC 60958 – 7d4af2ad9033/iec-61937-1-2021 Partie 1: Généralités

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 33.160.30

ISBN 978-2-8322-9429-1

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

 Registered trademark of the International Electrotechnical Commission Marque déposée de la Commission Electrotechnique Internationale

## CONTENTS

FOREWORD	4						
1 Scope	6						
2 Normative references	6						
3 Terms, definitions, and presentation	6						
3.1 Terms and definitions	6						
3.2 Presentation convention	8						
4 General description	8						
5 Interface format	8						
6 Mapping of the audio bitstream on to IEC 60958	9						
6.1 Coding of the bitstream	9						
6.2 Burst-payload							
6.3 Stuffing							
7 Format of data-bursts	15						
7.1 General 7.2 Pause data-burst	15						
7.3 Audio data-bursts							
7.4 Null data-burst							
Annex A (normative) Channel status when IEC 60958 is used in consumer							
applications	20						
Annex B (informative) Monaural linear PCM audio sample simultaneous transferred with non-linear PCM encoded audio bitstream <sub>937-12021</sub>	21						
https://standards.iteh.ai/catalog/standards/sist/ce10509c-b263-4899-8e4c-							
Figure 1 – IEC 60958 interface format 20033/iec-61937-1-2021	9						
Figure 2 – Data-burst format	11						
Figure 3 – Burst-preamble	11						
Figure 4 – Burst-preamble with extended preamble	13						
Figure 5 – Length of the burst-payload specified by Pd	14						
Figure 6 – Burst spacing	15						
Figure 7 – Flow chart of transmission of a bitstream	16						
Figure 8 – Bridging gaps in-between data-bursts with three pause data-bursts	17						
Figure 9 – Data-burst format of the data-type pause	18						
Figure 10 – Null data-burst	19						
Figure B.1 – Frame and Block structure	21						
Figure B.2 – Example 1: Frame and Block structure @ 48 kHz IEC 60958 frame rate	22						
Figure B.3 – Example 2: Frame and Block structure @ 192 kHz IEC 60958 frame rate	ə22						
Table 1 – Bit allocation of the IEC 60958 frame	9						
Table 2 – Bit allocation of data-burst in IEC 60958 subframes	10						
Table 3 – Burst-preamble words       12							
Table 4 – Bit map of burst-preambles							
Table 5 – Fields of burst-info							
Table 6 – Burst-preamble words	13						
Table 7 – Fields of Pe (extended data-type)	13						

Table 8 – Fields of Pf	13
Table 9 – Values of data-type-dependent info of the pause data-burst	
Table 10 – Burst-payload of pause data-burst	
Table 11 – Fields of a null data-burst	19
Table A.1 – Allocation of the channel status bits	20
Table B.1 – Relationship between sampling frequency for monaural linear PCM and IEC 60958 frame rate for non-linear PCM	23

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC 61937-1:2021</u> https://standards.iteh.ai/catalog/standards/sist/ce10509c-b263-4899-8e4c-7d4af2ad9033/iec-61937-1-2021

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

### DIGITAL AUDIO – INTERFACE FOR NON-LINEAR PCM ENCODED AUDIO BITSTREAMS APPLYING IEC 60958 –

#### Part 1: General

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61937-1 has been prepared by technical area 20: Analogue and digital audio, of IEC technical committee 100: Audio, video and multimedia systems and equipment. It is an International Standard.

This third edition cancels and replaces the second edition published in 2007, and amendment 1 published in 2011. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Activation of Pe field;
- b) Enhanced usage of channel status bits.
- c) Addition of Annex B.

The text of this International Standard is based on the following documents:

Draft	Report on voting
100/3447/CDV	100/3522/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members\_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The list of all the parts of IEC 61937, under the general title Digital audio - Interface for nonlinear PCM encoded audio bitstreams applying IEC 60958, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed, **iTeh STANDARD PREVIEW**
- withdrawn,
- replaced by a revised edition, or standards.iteh.ai)
- amended.

IEC 61937-1:2021

https://standards.iteh.ai/catalog/standards/sist/ce10509c-b263-4899-8e4c-7d4af2ad9033/iec-61937-1-2021

IMPORTANT - The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

### DIGITAL AUDIO – INTERFACE FOR NON-LINEAR PCM ENCODED AUDIO BITSTREAMS APPLYING IEC 60958 –

## Part 1: General

### 1 Scope

This part of IEC 61937 applies to the digital audio interface using the IEC 60958 series for the conveying of non-linear PCM encoded audio bitstreams.

It describes the way in which this digital interface can be used in consumer applications.

The professional mode is not considered within the scope of this document.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies. (standards.iteh.ai)

IEC 60958-1, Digital audio interface – Part 1: General

https://standards.iteh.ai/catalog/standards/sist/ce10509c-b263-4899-8e4c-IEC 60958-3, Digital audio interface 44a 2art 33 Consumer applications

IEC 60958-5, Digital audio interface – Part 5: Consumer application enhancement

IEC 61937-2, Digital audio – Interface for non-linear PCM encoded audio bitstreams applying IEC 60958 – Part 2: Burst-info

#### 3 Terms, definitions, and presentation

For the purposes of this document, the following terms, definitions, and presentation convention apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

#### 3.1 Terms and definitions

**3.1.1 audio data-burst** data-burst with an encoded audio frame as burst-payload

**3.1.2 audio data-word** 16-bit data word

#### 3.1.3

#### audio frame

fixed number of audio samples

Note 1 to entry: The number of samples in an audio frame is dependent on the particular encoding system that is used to encode the audio frame into the encoded audio frame.

#### 3.1.4

#### audio gap

period in the sequence of baseband audio samples where valid samples of audio are not available

#### 3.1.5

bitstream

non-linear PCM encoded audio source, represented in a sequence of bits

Note 1 to entry: In this interface, the bitstream consists of a sequence of data-bursts.

#### 3.1.6

#### data-burst

packet of data, including the burst-preamble, to be transmitted across the interface

#### 3.1.7

burst-payload

#### information content of the data-burst illeh STANDARD PREVIEW

#### 3.1.8

## (standards.iteh.ai)

burst-preamble (Stantial distribution) header for the data-burst, containing synchronization, and information about the data contained in the burst-payload IEC 61937-1:2021

> https://standards.iteh.ai/catalog/standards/sist/ce10509c-b263-4899-8e4c-7d4af2ad9033/iec-61937-1-2021

## 3.1.9

data-type reference to the type of payload of the data-bursts

#### 3.1.10

#### encoded audio frame

minimum decodable unit of an encoded data sequence

Note 1 to entry: Each encoded audio frame is the encoded representation of a fixed number of audio samples (for each original audio channel). The number of samples that are encoded into an encoded audio frame depends on the particular encoding system that is used to encode the audio frame into the encoded audio frame.

#### 3.1.11

#### idle

state in which the interface is not used to convey any sequence of data-bursts or PCM data

Note 1 to entry: The channel status data is still active (bit b1 is set to '1' when further non-linear PCM encoded audio is anticipated; see Figure 7).

#### 3.1.12

#### length-code

code indicating the length of the data-burst-payload in bits, bytes or 8-byte units

#### 3.1.13

#### repetition period

period between the reference point of the current data-burst and the reference point of the immediately following data-burst of the same data-type

#### 3.1.14

#### sampling frequency

sampling frequency of the encoded PCM audio samples (i.e. before encoding and after decoding)

#### 3.1.15

#### sampling period

time period related to the sampling frequency of the PCM audio samples, represented in the encoded bitstream

#### 3.1.16

stuffing

occupying the unused data capacity of the interface

#### 3.1.17

#### stuffing subframe

occupying the unused data capacity in 16-bit audio data words

#### 3.1.18

#### stream gap

period within the encoded audio bitstream without any audio frame; a discontinuity in the bitstream

Note 1 to entry: Typically, a stream gap will occur between encoded audio frames.

#### 3.2 Presentation convention

## (standards.iteh.ai)

## 3.2.1

F872h value 'F872' in hexadecimal format https://standards.iteh.ai/catalog/standards/sist/ce10509c-b263-4899-8e4c-7d4af2ad9033/iec-61937-1-2021

#### 4 General description

The format of the IEC 60958 interface consists of a sequence of IEC 60958 subframes. Each IEC 60958 subframe is normally used to carry one linear PCM sample, but may also be used to convey data. The non-linear PCM encoded audio bitstreams to be transported over this interface are formed into a sequence of data-bursts.

Each data-burst consists of a 64-bit burst-preamble, followed by the burst-payload. The burst-preamble consists of a sync-word, information about the burst-payload and a bitstream-number.

The interface may convey one or more bitstreams. Each type of bitstream may impose a particular requirement for the repetition period for the data-bursts that make up the bitstream (see Clause 7).

The 16 bits of a data-burst are placed in time-slots 12 to 27 of an IEC 60958 subframe. Both odd and even IEC 60958 subframes (channel 1, channel 2) are simultaneously used to carry 32 bits of data. This allows IEC 60958, in the consumer mode, to convey either two-channel linear PCM audio, or a set of non-linear PCM encoded bitstreams (alternating data words), but not both simultaneously.

#### **5** Interface format

The interface format as defined in IEC 60958-1 and IEC 60958-3 is used.

#### - 8 -

#### 6 Mapping of the audio bitstream on to IEC 60958

#### 6.1 Coding of the bitstream

#### 6.1.1 General

The non-linear PCM encoded audio bitstream is transferred using the basic 16-bit data area of the IEC 60958 subframes, i.e. in time-slots 12 to 27 (see Figure 1 and Table 1). Because the non-linear PCM encoded audio bitstream to be transported is at a lower data rate than that supported by the IEC 60958 interface, the audio bitstream is broken into a sequence of discrete data-bursts, and stuffing between the data-bursts is necessary (see 6.3).

Each data-burst contains data of an encoded audio frame that is the encoded representation of a fixed number of audio samples per PCM audio channel. The number of samples to be encoded into an encoded audio frame depends on the particular encoding system.

It is possible for this interface to simultaneously convey multiple non-linear PCM encoded audio bitstreams. One of the applications of this capability would be to convey both a main audio service and an associated audio service.





Table 1 – Bit allocatior	of the	IEC	60958	frame
--------------------------	--------	-----	-------	-------

Field	IEC 60958 time-slot	Value		
0 to 3	Preamble	IEC 60958 preamble		
4 to 7	Auxiliary field	Not used, all "0" or partial of linear PCM		
8 to 11	Unused data bits	Not used, all "0" or partial of linear PCM		
12 to 27	16-bit data	Sections of the bitstream		
28	Validity flag	According to IEC 60958		
29	User data	According to IEC 60958		
30	Channel status	According to IEC 60958		
31	Parity bit	According to IEC 60958		

#### 6.1.2 Bit map of bitstream

The method of placing the data into the IEC 60958 bitstream is to format the data to be transmitted into data-bursts and to send each data-burst in a continuous sequence of IEC 60958 frames (see Table 2).

		Bit of subframes							
Subframe	MSB				LSB				
	b27	b26	b25 b14	b13	b12				
Frame 0; subframe B or M	0	1		14	15				
Frame 0; subframe W	16	17		30	31				
Frame 1; subframe B or M	32	33		46	47				
Frame 1; subframe W	48	49		62	63				
Frame 2; subframe B or M	64	65		78	79				
Last subframe B or M of data-burst	n – 32	n – 31		n – 18	n – 17				
Last subframe W of data-burst	n – 16	n – 15		n – 2	n – 1				

Table 2 – Bit allocation of data-burst in IEC 60958 subframes

Considering the data within an IEC 60958 subframe as a 16-bit word out of a serial stream of bits, the first bit of the burst-payload in a data-burst would occupy the MSB of subframe 1 (time-slot 27), and the 32<sup>nd</sup> bit would occupy the LSB (or what would be the LSB for 16-bit PCM audio) of subframe 2 (time-slot 12). The next 32 bits of the burst-payload would occupy the next IEC 60958 frame. The last data bits of the audio data-burst might occupy only a fraction of the last frame. Any unused bits in the last frame will be ignored by the receiver. In the case where the audio data-burst contains a multiple of 16 bits, all used IEC 60958 sub-frames are completely filled. When it is not a multiple of 16 bits, the bits of the burst-payload to be conveyed in the last IEC 60958 subframe will be MSB aligned; the remaining bits shall be stuffed with zeros.

#### 6.1.3 IEC 60958 validity flag

It is recommended to set the validity bit to a logical '1'. This is intended to prevent accidental decoding of non-audio data to analogue before a complete channel status block is received.

#### 6.1.4 IEC 60958 channel status bit 1

The purpose of channel status bit 1 is to indicate if IEC 60958 is used to convey linear PCM or to indicate that the interface is used for other purposes (see Annex A). This bit shall be set to '1' when IEC 60958 is used to convey non-linear PCM encoded audio bitstreams.

#### 6.1.5 Symbol frequency

When the IEC 60958 bitstream conveys linear PCM audio, the symbol frequency is 64 times the PCM sampling frequency (32 time-slots per PCM sample, times two channels). When a non-linear PCM encoded audio bitstream is conveyed by the interface, the symbol frequency is normally 64 times the sampling rate of the encoded audio within that bitstream, and other times should be referred to each parts of IEC 61937.

#### 6.1.6 The format of the data-bursts

Each data-burst contains a burst-preamble consisting of four 16-bit words (Pa, Pb, Pc and Pd) followed by the burst-payload that contains data of an encoded audio frame (see Figure 2).





Figure 2 – Data-burst format

The repetition period of these bursts is defined as the length between the reference points R (measured in IEC 60958 frames) of one data-burst and the next data-burst (with the same bit-stream-number). The data representing each individual encoded audio frame is typically specified to be packaged into a single individual data-burst, with a repetition period (measured in IEC 60958 frames) for that data-burst equal to the number of encoded audio samples of each channel contained within that encoded audio frame.

It is possible for a number of data-bursts representing multiple bitstreams to be interleaved on the interface. When more than one non-linear PCM encoded audio bitstreams are transmitted through the same interface, the audio sampling rates of these bitstreams are identical to each other.

## (standards.iteh.ai)

#### 6.1.7 Burst-preamble

The burst-preamble consists of four mandatory fields. Pa and Pb represent a synchronization word. Pc gives information about the type of data, and some information/control for the receiver. Pd gives the length of the burst-payload, limited to 65 535 bits if the length of Pd is given in bits, limited to 65 535 bytes if the length of Pd is given in bytes, or limited to 524 280 bytes if the length of Pd is given in 8-byte units.

The four preamble words are contained in two sequential IEC 60958 frames (see Figure 3). The frame beginning the data-burst contains preamble word Pa in subframe 1, and Pb in subframe 2. The next frame contains Pc in subframe 1 and Pd in subframe 2. When placed into an IEC 60958 subframe, the MSB of a 16-bit burst-preamble word is placed into time-slot 27 and the LSB is placed into time-slot 12 (see Table 3 and Table 4).

Ра	Pb	Pc	Pd	Burst_payload		Pa	Pb	Pc	Pd	Burst_payload
				Length of burst-payload	•					Length of burst-payload
 ■Data-burst					-				Data-burst	
•										IEC



Preamble word	Length of field	Contents	Value MSB LSB
Ра	16-bit	Sync word 1	F872h
Pb	16-bit	Sync word 2	4E1Fh
Pc	16-bit	Burst-info	Table 5
Pd	16-bit	Length-code	Number of bits, number of bytes or number of 8-byte units according to data-type

#### Table 3 – Burst-preamble words

#### Table 4 – Bit map of burst-preambles

IEC 60958 time- slot bit-number	27															12
Preamble bit-number	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
Pa	1	1	1	1	1	0	0	0	0	1	1	1	0	0	1	0
Pb	0	1	0	0	1	1	1	0	0	0	0	1	1	1	1	1
Pc	In a	In accordance with Table 5, burst-info values Pc, bit 15 = MSB														
Pd	Leng	gth-co	de, bi	t 15 =	MSB											

## iTeh STANDARD PREVIEW (standards.iteh.ai)

#### 6.1.8 Burst-info

#### 6.1.8.1 General

#### IEC 61937-1:2021

The 16-bit burst-info contains information about the data that is found in the data-burst.

7d4af2ad9033/iec-61937-1-2021

### Table 5 – Fields of burst-info

Bits of Pc	Value	Contents	Remark		
0 to 6		Data-type	See IEC 61937-2		
7	0	Error flag indicating a valid burst-payload			
	1	Error flag indicating that this burst-payload is not valid			
8 to 12		Data-type-dependent info			
13 to 15	0	Bitstream-number			
NOTE The repetition period of pause data-bursts depends on the application in which IEC 60958 is used to					

NOTE The repetition period of pause data-bursts depends on the application in which IEC 60958 is used to convey encoded audio bitstreams.

#### 6.1.8.2 Data-type

The 7-bit data-type is defined in bits 0 to 6 of the burst-preamble Pc (see Table 5), bit 6 is the MSB. This data-type field indicates the format of the burst-payload, which will be conveyed in the data-burst. Typical properties of a data-type are the reference point and repetition period of the burst, which is the number of sampling periods of the audio between the reference point of the current data-burst and the reference point of the next data-burst. The reference point is inherently defined for each data-type.

The allocation of data-types is defined in IEC 61937-2. The data-types themselves are specified in the other parts of IEC 61937.

#### 6.1.8.3 Extended data-type

#### 6.1.8.3.1 General

When the burst-info Pc is equal to 1Fh (data-type = 31), the burst-preamble is extended with Pe and Pf. Figure 4 shows a burst-preamble with an extended preamble. Pe and Pf are included in the length of the burst-payload. The third frame of the IEC 60958 frames contains Pe in subframe 1 and Pf in subframe 2 (see Table 6, Table 7 and Table 8).



#### Figure 4 – Burst-preamble with extended preamble

Preamble word	length of field	Contents	Value MSB LSB
Pa	1 16-bit SI	Sync word IRD PR	É872h
Pb	16-bit	Sync word 2 sitch	4E1Fh
Pc	16-bit	Burst-info	Table 5
Pd	16-bit https://standards.iteh.a	Length <u>Coode</u> 37-1:2021 i/catalog/standards/sist/ce1050 MatDad9033/iec_61037_1_202	Number of bits, number of bytes or number of 8-byte units according to data-type
Pe (conditional)	16-bit	Extended data-type	Table 7
Pf (conditional)	16-bit	Reserved for future use	Table 8

#### Table 6 – Burst-preamble words

#### 6.1.8.3.2 Fields of Pe

#### Table 7 – Fields of Pe (extended data-type)

Bits of Pe	Value Contents		Remark
0 to 15	0 to 65 535	Extended data-type	See IEC 61937-2

The allocation of extended data-types is defined in IEC 61937-2. The extended data-types themselves are specified in the following parts of IEC 61937.

#### 6.1.8.3.3 Fields of Pf

#### Table 8 – Fields of Pf

Bits of Pf	value	Contents
0 to 15	0 to 65 535	Reserved for future use