



IEC 62271-200

Edition 3.1 2024-06
CONSOLIDATED VERSION

INTERNATIONAL STANDARD



High-voltage switchgear and controlgear –
Part 200: AC metal-enclosed switchgear and controlgear for rated voltages
above 1 kV and up to and including 52 kV

Document Preview

[IEC 62271-200:2021](#)

<https://standards.iteh.ai/catalog/standards/iec/2e245f8f-25f4-47e2-adae-fe0cce1d8a1c/iec-62271-200-2021>





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

International Standards
Document Preview

[IEC 62271-200:2021](https://standards.iteh.ai/catalog/standards/iec/2e245f8f-25f4-47e2-adae-fe0ccea1d8a1c/iec-62271-200-2021)

<https://standards.iteh.ai/catalog/standards/iec/2e245f8f-25f4-47e2-adae-fe0ccea1d8a1c/iec-62271-200-2021>



IEC 62271-200

Edition 3.1 2024-06
CONSOLIDATED VERSION

INTERNATIONAL STANDARD



High-voltage switchgear and controlgear –
Part 200: AC metal-enclosed switchgear and controlgear for rated voltages
above 1 kV and up to and including 52 kV

Document Preview

[IEC 62271-200:2021](https://standards.iteh.ai/catalog/standards/iec/2e245f8f-25f4-47e2-adae-fe0cce1d8a1c/iec-62271-200-2021)

<https://standards.iteh.ai/catalog/standards/iec/2e245f8f-25f4-47e2-adae-fe0cce1d8a1c/iec-62271-200-2021>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.130.10

ISBN 978-2-8322-9349-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	9
INTRODUCTION.....	12
1 Scope.....	13
2 Normative references	13
3 Terms and definitions	14
3.1 General terms and definitions	15
3.2 Assemblies of switchgear and controlgear	16
3.3 Parts of assemblies	16
3.4 Switching devices	16
3.5 Parts of switchgear and controlgear	16
3.6 Operational characteristics of switchgear and controlgear.....	19
3.7 Characteristic quantities	22
3.8 Index of definitions.....	22
4 Normal and special service conditions	24
5 Ratings.....	24
5.1 General.....	24
5.2 Rated voltage (U_r)	24
5.3 Rated insulation level (U_d , U_p , U_s).....	24
5.4 Rated frequency (f_r).....	24
5.5 Rated continuous current (I_r)	24
5.6 Rated short-time withstand currents (I_k , I_{ke}).....	25
5.6.101 Rated short-time withstand current (I_k).....	25
5.6.102 Rated short-time phase-to-earth withstand current (I_{ke})	25
5.7 Rated peak withstand currents (I_p , I_{pe})	25
5.7.101 Rated peak withstand current (I_p).....	25
5.7.102 Rated peak phase-to-earth withstand current (I_{pe})	25
5.8 Rated durations of short-circuit (t_k , t_{ke})	25
5.8.101 Rated duration of short-circuit (t_k)	26
5.8.102 Rated duration of phase-to-earth short-circuit (t_{ke}).....	26
5.9 Rated supply voltage of auxiliary and control circuits (U_a)	26
5.10 Rated supply frequency of auxiliary and control circuits	26
5.11 Rated pressure of compressed gas supply for controlled pressure systems	26
5.101 Classification of earthing function through main switching device.....	26
5.102 Rated cable test voltages (U_{ct} (AC), U_{ct} (DC))	26
5.102.1 General	26
5.102.2 Rated power-frequency cable test voltage U_{ct} (AC)	26
5.102.3 Rated DC cable test voltage U_{ct} (DC) with rated duration t_{ct} (DC).....	26
5.103 Ratings of the internal arc classification (IAC).....	27
5.103.1 General	27
5.103.2 Types of accessibility	27
5.103.3 Classified sides	27
5.103.4 Rated arc fault currents (I_A , I_{Ae}).....	27

5.103.5	Rated arc fault duration (t_A , t_{Ae})	28
6	Design and construction	28
6.1	Requirements for liquids in switchgear and controlgear	28
6.2	Requirements for gases in switchgear and controlgear	28
6.3	Earthing of switchgear and controlgear	28
6.3.101	Earthing of the high-voltage conductive parts	28
6.3.102	Earthing of enclosure(s)	28
6.3.103	Earthing of withdrawable and removable parts	29
6.3.104	Earthing circuit	29
6.4	Auxiliary and control equipment and circuits	29
6.5	Dependent power operation	29
6.6	Stored energy operation	29
6.7	Independent unlatched operation (independent manual or power operation)	30
6.8	Manually operated actuators	30
6.9	Operation of releases	30
6.10	Pressure/level indication	30
6.11	Nameplates	30
6.12	Locking devices	32
6.13	Position indication	33
6.14	Degrees of protection provided by enclosures	33
6.14.1	General	33
6.14.2	Protection of persons against access to hazardous parts and protection of the equipment against ingress of solid foreign objects (IP coding)	33
6.14.3	Protection against ingress of water (IP coding)	33
6.14.4	Protection of equipment against mechanical impact under normal operating conditions (IK coding)	33
6.15	Creepage distances for outdoor insulators	33
6.16	Gas and vacuum tightness	33
6.17	Tightness for liquid systems	34
6.18	Fire hazard (flammability)	34
6.19	Electromagnetic compatibility (EMC)	34
6.20	X-ray emission	34
6.21	Corrosion	34
6.22	Filling levels for insulation, switching and/or operation	34
6.101	General requirements for assemblies	34
6.102	Metal enclosure	35
6.102.1	General	35
6.102.2	Covers and doors	35
6.102.3	Partition or shutter being part of the enclosure	36
6.102.4	Inspection windows	37
6.102.5	Ventilating openings, vent outlets	37
6.103	High-voltage compartments	37
6.103.1	General	37
6.103.2	Fluid-filled compartments (gas or liquid)	38
6.103.3	Partitions and shutters	39
6.104	Removable parts	41
6.105	Provisions for dielectric tests on cables	41
6.106	Internal arc fault	41
7	Type tests	42

7.1	General.....	42
7.1.1	Basics	42
7.1.2	Information for identification of test objects.....	43
7.1.3	Information to be included in type-test reports	43
7.2	Dielectric tests	43
7.2.1	General	43
7.2.2	Ambient air conditions during tests	43
7.2.3	Wet test procedure	43
7.2.4	Arrangement of the equipment.....	43
7.2.5	Criteria to pass the test	43
7.2.6	Application of the test voltage and test conditions.....	43
7.2.7	Tests of switchgear and controlgear of $U_r \leq 245$ kV	45
7.2.8	Tests of switchgear and controlgear of $U_r > 245$ kV	46
7.2.9	Artificial pollution tests for outdoor insulators.....	46
7.2.10	Partial discharge tests	46
7.2.11	Dielectric tests on auxiliary and control circuits.....	46
7.2.12	Voltage test as condition check	46
7.2.101	Dielectric tests on cable testing circuits	46
7.3	Radio interference voltage (RIV) test	46
7.4	Resistance measurement.....	47
7.4.1	Measurement of the resistance of auxiliary contacts class 1 and class 2	47
7.4.2	Measurement of the resistance of auxiliary contacts class 3	47
7.4.3	Electrical continuity of earthed metallic parts test	47
7.4.4	Resistance measurement of contacts and connections in the main circuit as a condition check.....	47
7.5	Continuous current tests	47
7.5.1	Condition of the test object	47
7.5.2	Arrangement of the equipment.....	47
7.5.3	Test current and duration.....	47
7.5.4	Temperature measurement during test	48
7.5.5	Resistance of the main circuit.....	48
7.5.6	Criteria to pass test	48
7.5.101	Test report.....	48
7.6	Short-time withstand current and peak withstand current tests.....	49
7.6.1	General	49
7.6.2	Arrangement of the equipment and of the test circuit	50
7.6.3	Test current and duration.....	50
7.6.4	Conditions of the test object after test.....	51
7.7	Verification of the protection	51
7.7.1	Verification of the IP coding	51
7.7.2	Verification of the IK coding	51
7.8	Tightness tests	51
7.9	Electromagnetic compatibility tests (EMC)	51
7.10	Additional tests on auxiliary and control circuits	52
7.10.1	General	52
7.10.2	Functional tests	52
7.10.3	Verification of the operational characteristics of auxiliary contacts	52
7.10.4	Environmental tests	52

7.10.5	Dielectric test	52
7.11	X-radiation test for vacuum interrupters	52
7.101	Verification of making and breaking capacities	52
7.101.1	General	52
7.101.2	Test requirements for main switching devices	53
7.101.3	Test requirements for earthing function	53
7.102	Mechanical operation tests	53
7.102.1	Switching devices and removable parts	53
7.102.2	Mechanical and electromechanical interlocks and locking devices	54
7.103	Pressure withstand test for gas-filled compartments	55
7.103.1	Pressure withstand test for gas-filled compartments with pressure relief devices	55
7.103.2	Pressure withstand test for gas-filled compartments without pressure-relief devices	57
7.104	Tests to verify the protection of persons against dangerous electrical effects	57
7.104.1	General	57
7.104.2	Dielectric tests	58
7.104.3	Measurements of leakage currents	58
7.105	Internal arc test	58
7.105.1	General	58
7.105.2	Test conditions	58
7.105.3	Arrangement of the equipment	60
7.105.4	Test procedure	60
7.105.5	Criteria to pass the test	60
7.105.6	Test report	61
7.105.7	Extension of validity of test results	62
8	Routine tests	62
8.1	General	62
8.2	Dielectric test on the main circuit	63
8.3	Tests on auxiliary and control circuits	63
8.3.1	Inspection of auxiliary and control circuits, and verification of conformity to the circuit diagrams and wiring diagrams	63
8.3.2	Functional tests	63
8.3.3	Verification of protection against electrical shock	63
8.3.4	Dielectric tests	63
8.4	Measurement of the resistance of the main circuit	63
8.5	Tightness test	64
8.6	Design and visual checks	64
8.101	Partial discharge measurement	64
8.102	Mechanical operation tests	64
8.103	Pressure tests of gas-filled compartments	64
8.104	Tests after erection on site	65
8.105	Measurement of fluid condition after filling on site	65
9	Guide to the selection of switchgear and controlgear (informative)	65
9.1	General	65
9.2	Selection of rated values	66
9.3	Cable-interface considerations	66
9.4	Continuous or temporary overload due to changed service conditions	66
9.5	Environmental aspects	66

9.101	Selection of design and construction	66
9.101.1	General	66
9.101.2	Architecture and accessibility to high-voltage compartments	67
9.101.3	Service continuity of the switchgear	68
9.101.4	Partition classes	70
9.102	Ratings related to earthing circuits	71
9.103	Internal arc fault	71
9.103.1	General	71
9.103.2	Causes and preventive measures	71
9.103.3	Supplementary protective measures	72
9.103.4	Considerations for the selection and installation	73
9.103.5	Internal arc test	74
9.104	Summary of technical requirements, ratings and optional tests	77
10	Information to be given with enquiries, tenders and orders (informative)	79
10.1	General	79
10.2	Information with enquiries and orders	79
10.3	Information with tenders	80
11	Transport, storage, installation, operating instructions and maintenance	81
11.1	General	81
11.2	Conditions during transport, storage and installation	81
11.3	Installation	81
11.4	Operating instructions	81
11.5	Maintenance	82
12	Safety	82
12.101	Procedures	82
12.102	Internal arc aspects	82
13	Influence of the product on the environment	83
Annex A (normative)	Internal arc fault – Method to verify the internal arc classification (IAC)	84
A.1	Room simulation	84
A.1.1	Room simulation for indoor assemblies	84
A.1.2	Room simulation for outdoor assemblies	86
A.2	Indicators (for assessing the thermal effects of the gases)	86
A.2.1	General	86
A.2.2	Arrangement of indicators	86
A.3	Tolerances for geometrical dimensions of test arrangements	88
A.4	Test parameters	88
A.4.1	General	88
A.4.2	Voltage	88
A.4.3	Current	88
A.4.4	Frequency	89
A.5	Test procedure	89
A.5.1	Supply circuit	89
A.5.2	Arc initiation	90
Annex B (normative)	Partial discharge measurement	101
B.1	General	101
B.2	Application	101
B.3	Test circuits and measuring instruments	101

B.4	Test procedure.....	102
B.5	Maximum permissible partial discharge quantity	103
Annex C (informative)	List of notes concerning certain countries	107
Annex D (normative)	Flowchart categorization procedure for LSC for a given functional unit FU1 with connection compartment	108
Annex E (informative)	Pressure coordination chart for gas-filled compartments	109
Bibliography.....		110
Figure 1 – LSC1.....		70
Figure 2 – LSC2.....		70
Figure 3 – LSC2.....		70
Figure 4 – LSC2.....		70
Figure 5 – LSC2A		70
Figure 6 – LSC2B		70
Figure 7 – LSC2B		70
Figure 8 – LSC1 No LSC assigned.....		70
Figure 9 – No LSC assigned		70
Figure A.1 – Mounting frame for vertical indicators		92
Figure A.2 – Horizontal indicator.....		92
Figure A.3 – Position of the indicators.....		93
Figure A.4 – Room simulation and indicator positioning for accessibility type A, classified rear side, ceiling above 2 000 mm, functional unit of any height		94
Figure A.5 – Room simulation and indicator positioning for accessibility type A, non-accessible rear side, ceiling at 2 000 mm, so functional unit ≤ 1 800 mm high.....		95
Figure A.6 – Room simulation and indicator positioning for accessibility type B, classified rear side, functional unit ≥ 1 900 mm high		96
Figure A.7 – Room simulation and indicator positioning for accessibility type B, classified rear side, functional unit < 1 900 mm high		97
Figure A.8 – Ceiling height stated from the floor or false floor level where the assembly is actually placed		98
Figure A.9 – Indicator positioning in case of protrusion at < 2 000 mm height, at classified side		99
Figure A.10 – Indicator positioning in case a bottom exhaust duct belonging to the assembly is defined as a walkable integrated part of the false floor		100
Figure B.1 – Partial discharge test circuit (three-phase arrangement)		105
Figure B.2 – Partial-discharge test circuit (system without earthed neutral).....		106
Figure D.1 – Flowchart categorization procedure for LSC for a given functional unit FU1 with connection compartment		108
Figure E.1 – Example of pressure coordination chart		109
Table 1 – Nameplate information		30
Table 2 – Locations, causes and examples of measures to decrease the probability of internal arc faults		73
Table 3 – Single-phase-to-earth arc fault current depending on the network neutral earthing		75
Table 4 – Summary of technical requirements, ratings and optional tests for assemblies		77

Table A.1 – Parameters for internal arc test according to compartment construction 91

Table B.1 – Test circuits and procedures 104

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 62271-200:2021](https://standards.iteh.ai/catalog/standards/iec/2e245f8f-25f4-47e2-adae-fe0cce1d8a1c/iec-62271-200-2021)

<https://standards.iteh.ai/catalog/standards/iec/2e245f8f-25f4-47e2-adae-fe0cce1d8a1c/iec-62271-200-2021>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

Part 200: AC metal-enclosed switchgear and controlgear for rated voltages above 1 kV and up to and including 52 kV

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 62271-200 edition 3.1 contains the third edition (2021-05) [documents 17C/782/FDIS and 17C/792/RVD] and its amendment 1 (2024-06) [documents 17C/933/FDIS and 17C/938/RVD].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

IEC 62271-200 has been prepared by subcommittee 17C: Assemblies, of IEC technical committee 17: High-voltage switchgear and controlgear. It is an International Standard.

This third edition cancels and replaces the second edition published in 2011. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) clause numbering aligned with IEC 62271-1:2017, including the adoption of the subclause names of Clause 3;
- b) in Clause 3 specific definitions are added for "in service", "normal operating condition" and "normal use";
- c) internal arc testing on pole-mounted switchgear is taken out of this document, as it is now covered by the specific standard IEC 62271-214:2019;
- d) a more precise description of earthing circuit is given with the inclusion of ratings and test requirements;
- e) number of mechanical tests on interlocks is reduced for type testing; a more precise description of forces to apply during type testing is given (refer to 7.102);
- f) resistance measuring on main circuit is only needed before continuous current tests (as reference for routine tests) and no longer needed after this continuous current test. Rationale for this deletion is that this measured resistance does not mean anything; as the temperature rise test was just finished, a new temperature rise test will not give new information;
- g) IEC 62271-100:2021, IEC 62271-103:2021, IEC 62271-105:2021 and IEC 62271-106:2021 are referred to in the document;
- h) IEC 62271-107:2019 and IEC IEEE 62271-37-013:2015 are also considered in 7.101.2;
- i) a more precise description of LSC category is given with the inclusion of an explanatory flowchart (Annex D);
- j) examples not covered by the IAC test are transferred from Clause 6 to 9.103;
- k) the term "assembly" is defined in Clause 3 and used as synonym for "metal-enclosed switchgear and controlgear" in this document;
- l) "metallic" is replaced by "metal" where applicable;
- m) 6.105 is now covered by 7.7;
- n) a 1 s rule was introduced for Criterion 4 during IAC tests regarding hot gases versus glowing particles as cause of ignition;
- o) a more precise description of internal arc tests for switchgear with protrusions is given in Annex A.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

This document should be read in conjunction with IEC 62271-1:2017, to which it refers and which is applicable unless otherwise specified. In order to simplify the indication of corresponding requirements, the same numbering of clauses and subclauses is used as in IEC 62271-1:2017. Amendments to these clauses and subclauses are given under the same numbering, whilst additional subclauses, are numbered from 101.

The reader's attention is drawn to the fact that Annex C lists all of the "in-some-country" clauses on differing practices of a less permanent nature relating to the subject of this document.

A list of all parts in the IEC 62271 series, published under the general title *High-voltage switchgear and controlgear*, can be found on the IEC website.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 62271-200:2021](https://standards.iteh.ai/catalog/standards/iec/2e245f8f-25f4-47e2-adae-fe0cce1d8a1c/iec-62271-200-2021)

<https://standards.iteh.ai/catalog/standards/iec/2e245f8f-25f4-47e2-adae-fe0cce1d8a1c/iec-62271-200-2021>

INTRODUCTION

High-voltage (IEC 60050-601:1985, 601-01-27) switchgear refers to rated voltages above 1 kV. However, medium-voltage is commonly used for distribution systems with rated voltages above 1 kV and generally applied up to and including 52 kV; refer to IEC 60050-601:1985, 601-01-28 [1]¹.

Although primarily dedicated to three-phase systems, this document can also be applied to single-phase and two-phase systems.

Switchgear and controlgear assemblies having a solid-insulation enclosure are covered by IEC 62271-201.

Generally, gas-filled medium-voltage designs have design pressures below 500 kPa, as mentioned for example in the introduction of EN 50187.

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[IEC 62271-200:2021](https://standards.iteh.ai/catalog/standards/iec/2e245f8f-25f4-47e2-adae-fe0cce1d8a1c/iec-62271-200-2021)

<https://standards.iteh.ai/catalog/standards/iec/2e245f8f-25f4-47e2-adae-fe0cce1d8a1c/iec-62271-200-2021>

¹ Numbers in square brackets refer to the Bibliography.