



Edition 4.1 2024-05 CONSOLIDATED VERSION

INTERNATIONAL STANDARD



Specifications for particular types of winding wires – Part 12: Polyvinyl acetal enamelled round copper wire, class 120

Document Preview

IEC 60317-12:2020

https://standards.iteh.ai/catalog/standards/iec/e6df404f-4ab8-4a13-9ded-71816c03102d/iec-60317-12-2020





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.







Edition 4.1 2024-05 CONSOLIDATED VERSION

INTERNATIONAL STANDARD



Specifications for particular types of winding wires – Part 12: Polyvinyl acetal enamelled round copper wire, class 120

Document Preview

IEC 60317-12:2020

https://standards.iteh.ai/catalog/standards/iec/e6df404f-4ab8-4a13-9ded-71816c03102d/iec-60317-12-2020

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.060.10

ISBN 978-2-8322-9004-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FO	REWORD	3
INT	RODUCTION	5
1	Scope	6
2	Normative references	6
3	Terms, definitions, general notes and appearance	6
3	3.1 Terms and definitions	6
3	3.2 General notes	6
	3.2.1 Methods of test	6
	3.2.2 Winding wire	7
3	3.3 Appearance	7
4	Dimensions	7
5	Electrical resistance	7
6	Elongation	7
7	Springiness	7
8	Flexibility and adherence	7
9	Heat shock	
ç	9.1 Nominal conductor diameters up to and including 1,600 mm	
	9.2 Nominal conductor diameters over 1,600 mm	
10	Cut-through	
11	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm)	
12	Resistance to solvents	
13	Breakdown voltage	9
14	Continuity of insulation	9
/sta 15	Continuity of insulation <u>IEC 60317-12:2020</u> n and step al catalog/standards/iec/e6di4041-4ab8-4a13-9ded-71816c03102d/iec Temperature index	c-60317-1
16	kesistance to refrigerants	
17	Solderability	
18	Heat or solvent bonding	
19	Dielectric dissipation factor	
20	Resistance to transformer oil	
21	Loss of mass	
23	Pin hole test	
30 Dib	Packaging	
RID	liography	11
Tah	le 1 – Heat shock	R
	ble 2 – Resistance to abrasion	
ial		J

INTERNATIONAL ELECTROTECHNICAL COMMISSION

- 3 -

SPECIFICATIONS FOR PARTICULAR TYPES OF WINDING WIRES -

Part 12: Polyvinyl acetal enamelled round copper wire, class 120

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies. [2:2000]
- 6) All users should ensure that they have the latest edition of this publication. 71816c03102d/acc-60317-12-2020
 - 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
 - 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
 - 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60317-12 edition 4.1 contains the fourth edition (2020-06) [documents 55/1841/FDIS and 55/1854/RVD] and its amendment 1 (2024-05) [documents 55/1982/CDV and 55/2018/RVC].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication. International Standard IEC 60317-12 has been prepared by IEC technical committee 55: Winding wires.

This fourth edition of IEC 60317-12 cancels and replaces the third edition published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) modification of the Scope;
- b) addition of reference to transformer oil resistance test method in Clause 20.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

This International Standard is to be used in conjunction with IEC 60317-0-1:2013 and its Amendment 1:2019.

A list of all parts in the IEC 60317 series, published under the general title *Specifications for particular types of winding wires*, can be found on the IEC website.

The numbering of clauses in this document is not continuous from Clauses 21 through 30 in order to reserve space for possible future wire requirements prior to those for wire packaging.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

reconfirmed,

- withdrawn, or
- revised.

IEC 60217 12:2020

ttps://standards.iteh.ai/catalog/standards/iec/e6df404f-4ab8-4a13-9ded-71816c03102d/iec-60317-12-2020

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

- 5 -

This Part of IEC 60317 forms an element of a series of standards which deals with insulated wires used for windings in electrical equipment. It is composed of the following series:

- 1) Winding wires Test methods (IEC 60851 series);
- 2) Specifications for particular types of winding wires (IEC 60317 series);
- 3) Packaging of winding wires (IEC 60264 series).

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 60317-12:2020

https://standards.iteh.ai/catalog/standards/iec/e6df404f-4ab8-4a13-9ded-71816c03102d/iec-60317-12-2020

SPECIFICATIONS FOR PARTICULAR TYPES OF WINDING WIRES –

- 6 -

Part 12: Polyvinyl acetal enamelled round copper wire, class 120

1 Scope

This part of IEC 60317 specifies the requirements of enamelled round copper winding wires of class 120 with a sole coating based on polyvinyl acetal or polyvinyl formal resin, which can be modified provided it retains the chemical identity of the original resin and meets all specified wire requirements.

NOTE 1 A modified resin is a resin that has undergone a chemical change, or contains one or more additives to enhance certain performance or application characteristics.

NOTE 2 Polyvinyl acetal is a general name for a family of thermoplastic vinyl resins produced by the condensation of polyvinyl alcohol with an aldehyde. Examples are polyvinyl acetal, polyvinyl formal and polyvinyl butyral.

The range of nominal conductor diameters covered by this document is:

- Grade 1: 0,040 mm up to and including 2,500 mm;
- Grade 2: 0,040 mm up to and including 5,000 mm;
- Grade 3: 0,080 mm up to and including 5,000 mm.

The nominal conductor diameters are specified in Clause 4 of IEC 60317-0-1:2013.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition 2020 cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60317-0-1:2013, Specifications for particular types of winding wires – Part 0-1: General requirements – Enamelled round copper wire IEC 60317-0-1:2013/AMD1:2019

3 Terms, definitions, general notes and appearance

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60317-0-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.2 General notes

3.2.1 Methods of test

Subclause 3.2.1 of IEC 60317-0-1:2013 and IEC 60317-0-1:2013/AMD1:2019 applies. In case of inconsistencies between IEC 60317-0-1 and this document, IEC 60317-12 shall prevail.

IEC 60317-12:2020+AMD1:2024 CSV - 7 - © IEC 2024

3.2.2 Winding wire

Class 120 is a thermal class that requires a minimum temperature index of 120 and a heat shock temperature of at least 155 $^{\circ}$ C.

The temperature in degrees Celsius corresponding to the temperature index is not necessarily that at which it is recommended that the wire be operated and this will depend on many factors, including the type of equipment involved.

3.3 Appearance

Subclause 3.3 of IEC 60317-0-1:2013 applies.

4 Dimensions

Clause 4 of IEC 60317-0-1:2013 applies.

5 Electrical resistance

Clause 5 of IEC 60317-0-1:2013 and IEC 60317-0-1:2013/AMD1:2019 applies.

6 Elongation

iTeh Standards

Clause 6 of IEC 60317-0-1:2013 applies.

7 Springiness

Clause 7 of IEC 60317-0-1:2013 applies.

<u>EC 60317-12:2020</u>

https:/81a Flexibility and adherence

Clause 8 of IEC 60317-0-1:2013 applies, where the constant K used for the calculation of the number of revolutions for the peel test shall be 175 mm.

9 Heat shock

Clause 9 of IEC 60317-0-1:2013 applies. The minimum heat shock temperature shall be 155 $^\circ\text{C}.$

9.1 Nominal conductor diameters up to and including 1,600 mm

The coating shall show no crack. The mandrel diameter shall be as specified in Table 1.

	Nominal condu		Elongation before winding on mandrel %	Mandrel diameter ^b		
	Over	Up to and including	70			
	_	0,050	20 ^a	0,150 mm		
	0,050	1,600	_	D		
а	Or until it breaks, whichever is less.					
b	D is the overall di	D is the overall diameter of the wire.				

Table 1 – Heat shock

9.2 Nominal conductor diameters over 1,600 mm

Subclause 9.2 of IEC 60317-0-1:2013 applies.

10 Cut-through

No failure shall occur within 2 min at 170 °C.

11 Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm)

The wire shall meet the requirements given in Table 2.

For intermediate nominal conductor diameters, the value of the next larger nominal conductor diameter shall be taken.

<u>IEC 60317-12:2020</u>

https://standards.iteh.ai/catalog/standards/iec/e6df404f-4ab8-4a13-9ded-71816c03102d/iec-60317-12-2020