

INTERNATIONAL STANDARD

IEC 61158-4

Second edition
2000-01

**Digital data communications for
measurement and control –
Fieldbus for use in industrial control systems –**

**Part 4:
Data Link protocol specification**

(<https://standards.iteh.ai>)
Document Preview

<https://standards.iteh.ai>
IEC 61158-4:2000

<https://standards.iteh.ai/standards/iec/1311ed3b8-2573-46ab-9a3d-2688d8990a46/iec-61158-4-2000>



Reference number
IEC 61158-4:2000(E)

Numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series.

Consolidated publications

Consolidated versions of some IEC publications including amendments are available. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Validity of this publication

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology.

Information relating to the date of the reconfirmation of the publication is available in the IEC catalogue.

Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is to be found at the following IEC sources:

- **IEC web site***
- **Catalogue of IEC publications**
Published yearly with regular updates
(On-line catalogue)*
- **IEC Bulletin**
Available both at the IEC web site* and as a printed periodical

Terminology, graphical and letter symbols

For general terminology, readers are referred to IEC 60050: *International Electrotechnical Vocabulary (IEV)*.

For graphical symbols, and letter symbols and signs approved by the IEC for general use, readers are referred to publications IEC 60027: *Letter symbols to be used in electrical technology*, IEC 60417: *Graphical symbols for use on equipment. Index, survey and compilation of the single sheets* and IEC 60617: *Graphical symbols for diagrams*.

* See web site address on title page.

INTERNATIONAL STANDARD

IEC 61158-4

Second edition
2000-01

Digital data communications for measurement and control – Fieldbus for use in industrial control systems –

Part 4: Data Link protocol specification

(<https://standards.iteh.ai>)
Document Preview

<https://standards.iteh.ai> IEC 61158-4:2000

<https://standards.iteh.ai/catalog/standards-iec/131ed3b8-2573-46ab-9a3d-2688d8990a46/iec-61158-4-2000>

© IEC 2000 – Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission
Telefax: +41 22 919 0300

3, rue de Varembé Geneva, Switzerland
e-mail: inmail@iec.ch IEC web site <http://www.iec.ch>



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE **XH**

For price, see current catalogue

CONTENTS

| | Page |
|---|------|
| FOREWORD | 28 |
| INTRODUCTION | 30 |
| Clause | |
| 1 Scope and object | 31 |
| 1.1 Specifications | 32 |
| 1.2 Procedures | 34 |
| 1.3 Applicability..... | 34 |
| 1.4 Conformance | 34 |
| 2 Normative references | 35 |
| 2.1 Common normative references..... | 35 |
| 2.2 Type 1: additional normative references | 35 |
| 2.3 Type 2: additional normative references | 36 |
| 2.4 Type 3: additional normative references | 36 |
| 2.5 Type 4: additional normative references | 36 |
| 2.6 Type 5: additional normative references | 36 |
| 2.7 Type 6: additional normative references | 36 |
| 2.8 Type 7: additional normative references | 36 |
| 2.9 Type 8: additional normative references | 37 |
| 3 Definitions..... | 38 |
| 3.1 Reference model definitions..... | 38 |
| 3.2 Service convention definitions | 40 |
| 3.3 Common terms and definitions..... | 41 |
| 3.4 Type 1: additional terms and definitions | 42 |
| 3.5 Type 2: additional terms and definitions..... | 51 |
| 3.6 Type 3: additional terms and definitions..... | 58 |
| 3.7 Type 4: additional terms and definitions..... | 60 |
| 3.8 Type 5: additional terms and definitions..... | 61 |
| 3.9 Type 6: additional terms and definitions..... | 61 |
| 3.10 Type 7: additional terms and definitions..... | 71 |
| 3.11 Type 8: additional terms and definitions..... | 74 |
| 4 Symbols and abbreviations..... | 75 |
| 4.1 Common symbols and abbreviations | 75 |
| 4.2 Type 1: additional symbols and abbreviations | 75 |
| 4.3 Type 2: additional symbols and abbreviations | 79 |
| 4.4 Type 3: additional symbols and abbreviations | 80 |
| 4.5 Type 4: additional symbols and abbreviations | 84 |
| 4.6 Type 5: additional symbols and abbreviations | 84 |
| 4.7 Type 6: additional symbols and abbreviations | 84 |
| 4.8 Type 7: additional symbols and abbreviations | 86 |
| 4.9 Type 8: additional symbols and abbreviations | 87 |
| 5 DL-protocol elements common to multiple DL-protocol Types | 90 |
| 5.1 Frame check sequence | 90 |
| 6 Type 1: Overview of the DL-protocol..... | 94 |
| 6.1 Three-level model of the DLL | 94 |

| | | |
|------|---|-----|
| 6.2 | Service provided by the DLL..... | 97 |
| 6.3 | Structure and definition of DL-addresses..... | 104 |
| 6.4 | Service assumed from the PhL..... | 116 |
| 6.5 | Functions of the DLL..... | 119 |
| 6.6 | Functional classes..... | 121 |
| 6.7 | Local parameters, variables, counters, timers and queues..... | 123 |
| 7 | Type 1: General structure and encoding of PhIDUs and DLPDUs, and related elements of procedure..... | 138 |
| 7.1 | PhIDU structure and encoding..... | 138 |
| 7.2 | Common DLPDU structure, encoding and elements of procedure..... | 139 |
| 8 | Type 1: DLPDU-specific structure, encoding and elements of procedure..... | 148 |
| 8.1 | Establish Connection (EC) DLPDU..... | 150 |
| 8.2 | Disconnect Connection (DC) DLPDU..... | 152 |
| 8.3 | Reset Connection (RC) DLPDU..... | 155 |
| 8.4 | Compel Acknowledgement (CA) DLPDU..... | 157 |
| 8.5 | Compel Data (CD) DLPDU..... | 164 |
| 8.6 | Exchange Data (ED) DLPDU..... | 172 |
| 8.7 | Data (DT) DLPDU..... | 182 |
| 8.8 | Status Response (SR) DLPDU..... | 191 |
| 8.9 | Compel Time (CT) DLPDU..... | 194 |
| 8.10 | Time Distribution (TD) DLPDU..... | 196 |
| 8.11 | Round-Trip-Delay Query (RQ) DLPDU..... | 198 |
| 8.12 | Round-Trip-Delay Reply (RR) DLPDU..... | 200 |
| 8.13 | Probe Node DL-address (PN) DLPDU..... | 202 |
| 8.14 | Probe Response (PR) DLPDU..... | 205 |
| 8.15 | Pass Token (PT) DLPDU..... | 206 |
| 8.16 | Execute Sequence (ES) DLPDU..... | 216 |
| 8.17 | Return Token (RT) DLPDU..... | 224 |
| 8.18 | Request Interval (RI) DLPDU..... | 225 |
| 8.19 | Claim LAS (CL) DLPDU..... | 226 |
| 8.20 | Transfer LAS (TL) DLPDU..... | 228 |
| 8.21 | Wakeup (WK) DLPDU..... | 232 |
| 8.22 | Idle (IDLE) DLPDU..... | 233 |
| 8.23 | Spare DLPDUs..... | 235 |
| 8.24 | Reserved (not to be used) DLPDUs..... | 236 |
| 9 | Type 1: DLPDU-parameter structure and encoding..... | 238 |
| 9.1 | Structure and encoding of EC-PARAMETERS..... | 238 |
| 9.2 | Structure and encoding of DC-PARAMETERS..... | 243 |
| 9.3 | Structure and encoding of RC-PARAMETERS..... | 244 |
| 9.4 | Structure and encoding of SD-Parameters..... | 246 |
| 9.5 | Structure and encoding of SR-parameters..... | 254 |
| 9.6 | Structure and encoding of TD-parameters..... | 254 |
| 9.7 | Structure and encoding of RQ-parameters..... | 257 |
| 9.8 | Structure and encoding of RR-parameters..... | 258 |
| 9.9 | Structure and encoding of PN-parameters..... | 259 |
| 9.10 | Structure and encoding of DD-parameters..... | 260 |
| 10 | Type 1: DL-service elements of procedure..... | 262 |
| 10.1 | Operation of the DL(SAP)-address, buffer and queue management services..... | 262 |
| 10.2 | Operation of the connection-mode services..... | 266 |

| | | |
|-------|---|-----|
| 10.3 | Operation of the connectionless-mode services | 315 |
| 10.4 | Operation of the scheduling guidance services | 329 |
| 11 | Type 1: DL-support subprotocol | 341 |
| 11.1 | Scope | 341 |
| 11.2 | Overview of LAS operation | 341 |
| 11.3 | DL-support subprotocol definition | 342 |
| 11.4 | Elements of Procedures for receiving SPDUs | 379 |
| 12 | Type 1: Other DLE elements of procedure | 381 |
| 12.1 | DLE initialization | 381 |
| 12.2 | LAS behavior and operation | 386 |
| 12.3 | DL-support operation | 395 |
| 12.4 | DL-bridge elements of procedure and bridge sub-protocol | 401 |
| 12.5 | DL-management-information | 433 |
| 12.6 | Implementation profiles | 437 |
| 13 | Type 1: PICS proforma | 444 |
| 13.1 | Introduction | 444 |
| 13.2 | Scope | 444 |
| 13.3 | Normative references | 444 |
| 13.4 | Definitions | 444 |
| 13.5 | Abbreviations | 444 |
| 13.6 | Conformance | 445 |
| 13.7 | Instructions | 445 |
| 13.8 | Identification | 446 |
| 13.9 | Implementation profile | 446 |
| 13.10 | Major low-level capabilities | 451 |
| 13.11 | Major high-level capabilities | 465 |
| 14 | Type 2: Overview of the DL-protocol | 476 |
| 14.1 | General | 476 |
| 14.2 | Services provided by the DL | 478 |
| 14.3 | Structure and definition of DL-addresses | 479 |
| 14.4 | Services assumed from the PhL | 481 |
| 14.5 | Functional classes | 483 |
| 15 | Type 2: General structure and encoding of PhIDUs and DLPDUs and related elements of procedure | 484 |
| 15.1 | Overview | 484 |
| 15.2 | Media access procedure | 484 |
| 15.3 | Mframe structure and encoding | 488 |
| 15.4 | Lpacket components | 489 |
| 15.5 | General Mframe procedures | 491 |
| 15.6 | Summary of DLL support services and objects | 493 |
| 16 | Type 2: Specific DLPDU structure, encoding and procedures | 495 |
| 16.1 | Modeling language | 495 |
| 16.2 | Use of DLL- prefix | 496 |
| 16.3 | DLS user services | 497 |
| 16.4 | Generic Tag Lpacket | 503 |
| 16.5 | Moderator Lpacket | 503 |
| 16.6 | Time distribution Lpacket | 504 |
| 16.7 | UCMM Lpacket | 507 |
| 16.8 | Keeper UCMM Lpacket | 507 |

| | | |
|-------|--|-----|
| 16.9 | TUI Lpacket | 508 |
| 16.10 | Link parameters Lpacket and tMinus Lpacket | 509 |
| 16.11 | I'm alive Lpacket | 510 |
| 16.12 | Ping Lpackets | 512 |
| 16.13 | WAMI Lpacket | 513 |
| 17 | Type 2: Objects for station management..... | 515 |
| 17.1 | General..... | 515 |
| 17.2 | ControlNet object | 516 |
| 17.3 | Keeper object..... | 526 |
| 17.4 | Scheduler object | 549 |
| 18 | Type 2: Other DLE elements of procedure | 561 |
| 18.1 | Network Attachment Monitor (NAM)..... | 561 |
| 18.2 | Calculating link parameters | 567 |
| 19 | Type 2: Detailed specification of DL components | 575 |
| 19.1 | Access Control Machine (ACM) | 575 |
| 19.2 | TxLLC..... | 592 |
| 19.3 | RxLLC | 596 |
| 19.4 | Transmit Machine (TxM) | 599 |
| 19.5 | Receive Machine (RxM) | 602 |
| 19.6 | Serializer | 608 |
| 19.7 | Deserializer..... | 609 |
| 19.8 | DLL management..... | 610 |
| 20 | Type 3: Overview of the DL-protocol | 613 |
| 20.1 | General..... | 613 |
| 20.2 | Overview of the medium access control and transmission protocol | 613 |
| 20.3 | Transmission modes and DL-entity..... | 614 |
| 20.4 | Service assumed from the PhL..... | 621 |
| 20.5 | Timer operation..... | 622 |
| 20.6 | Cycle and system reaction times | 634 |
| 21 | Type 3: General structure and encoding of PhIDUs and DLPDUs, and related elements of procedure | 637 |
| 21.1 | Overview..... | 637 |
| 21.2 | Frame character..... | 637 |
| 21.3 | Length octet (LE, LEr) | 638 |
| 21.4 | Address octet..... | 639 |
| 21.5 | Control octet (FC) | 641 |
| 21.6 | Frame check sequence (FCS) | 645 |
| 21.7 | Data field (DATA_UNIT) | 646 |
| 21.8 | Error control procedures..... | 648 |
| 22 | Type 3: DLPDU-specific structure, encoding and elements of procedure | 650 |
| 22.1 | Overview of frame correlation to station types..... | 650 |
| 22.2 | Frames of fixed length with no data field..... | 650 |
| 22.3 | Frames of fixed length with data field | 653 |
| 22.4 | Frames with variable data field length..... | 654 |
| 22.5 | Token frame | 657 |
| 22.6 | Transmission procedures | 658 |
| 23 | Type 3: Other DLE elements of procedure | 661 |
| 23.1 | DL-entity initialization | 661 |
| 23.2 | States of the media access control of the DL-entity..... | 661 |

| | | |
|------|---|-----|
| 24 | Type 4: Data Link Protocol Definition | 667 |
| 24.1 | Overview of the DL-protocol | 667 |
| 24.2 | General structure and encoding of PhIDUs and DLPDUs, and related elements of procedure | 678 |
| 24.3 | DLPDU-specific structure, encoding and elements of procedure | 685 |
| 24.4 | DL-service elements of procedure | 689 |
| 24.5 | Route mechanism | 692 |
| 24.6 | Link-access system | 696 |
| 24.7 | Local variables, counters and queues | 697 |
| 25 | Type 5: <placeholder for the Type 5 DL-protocol definition> | 699 |
| 26 | Type 6: Overview of the Connection Oriented Data Transfer, Time and Coordination DL-Protocol | 701 |
| 26.1 | Connection Mode Data Transfer using Time Division Multiple Access (TDMA) Principles | 701 |
| 26.2 | Bus Access and Data Transmission | 701 |
| 26.3 | Other Real-time services | 703 |
| 26.4 | Overview of Bus Synchronization | 705 |
| 26.5 | Overview of Connection mode features | 707 |
| 26.6 | Overview of Connectionless mode | 716 |
| 26.7 | Overview of Node Types and Access Roles | 720 |
| 27 | Type 6: Elements of procedure | 721 |
| 27.1 | Common procedures for data transmission and reception | 721 |
| 27.2 | Connection mode procedures for DLSDU transfers | 724 |
| 27.3 | Procedures related to Bus Startup and Bus Operation | 726 |
| 27.4 | Procedures used in sequencing and synchronizing the Bus-State Machines of all DLEs | 729 |
| 28 | Type 7: Overview of the DL-protocol | 733 |
| 28.1 | Overall description of medium allocation | 733 |
| 28.2 | Types of entities | 735 |
| 28.3 | Addressing | 740 |
| 28.4 | Flow control | 747 |
| 28.5 | Graphical representation | 749 |
| 29 | Type 7: General structure and encoding of PhIDUs and DLPDUs and related elements of procedure | 750 |
| 29.1 | DLPDU formats and components | 750 |
| 29.2 | Description of each DLPDU component | 750 |
| 29.3 | PhIDU structure and encoding | 752 |
| 29.4 | Common DLPDU structure, encoding and elements of procedure | 753 |
| 29.5 | Valid DLPDU types | 753 |
| 29.6 | DLL timers | 756 |
| 30 | Type 7: DLPDU-Specific structure, encoding and element of procedure | 761 |
| 30.1 | Buffer read | 761 |
| 30.2 | Buffer Write | 761 |
| 30.3 | Buffer transfer | 762 |
| 30.4 | Specified Explicit Transfer | 763 |
| 30.5 | Free Explicit request | 768 |
| 30.6 | Messaging | 771 |
| 30.7 | Acknowledged messaging | 776 |
| 30.8 | Numbering of acknowledged messages | 780 |

| | | |
|---------|---|-----|
| 30.9 | Behavior with mismatched parameters | 782 |
| 31 | Type 7: DL-Service elements of procedure, interfaces and conformance..... | 785 |
| 31.1 | Producer/consumer entity..... | 785 |
| 31.2 | Protocol elements by service | 788 |
| 31.3 | Bus Arbitrator operation | 797 |
| 31.4 | Bridges | 805 |
| 31.5 | Interfaces..... | 812 |
| 31.6 | Conformance | 814 |
| 32 | Type 8: DL-protocol..... | 818 |
| 32.1 | Overview..... | 818 |
| 32.2 | Data Link Layer Interface (DLI)..... | 818 |
| 32.3 | Peripherals Data Link (PDL) | 823 |
| 32.4 | Basic Link Layer (BLL) | 860 |
| 32.5 | Medium Access Control (MAC)..... | 878 |
| 32.6 | Peripherals Network Management of the Layer 2 (PNM2) | 911 |
| 32.7 | Parameters and monitoring times of the DLL | 919 |
| Annex A | (informative) – Types 1, 2, 3 (synchronous), 5 (first FCS), 6, 7 and 8: Exemplary FCS implementations | 925 |
| Annex B | (informative) – Type 1: Formal protocol finite state machines | 927 |
| B.1 | Basic reception and transmission FSMs | 927 |
| B.2 | FSMs for DLCs | 939 |
| B.3 | FSMs for scheduling | 945 |
| B.4 | FSMs for bridges..... | 945 |
| Annex C | (informative) – Type 1: DLPDU and DL-addressing short-form summaries..... | 946 |
| C.1 | Fields used in short-form summaries..... | 946 |
| C.2 | DLPDU short-form summary grouped by function | 948 |
| C.3 | DLPDU short-form summary in alphabetic order of DLPDU names..... | 950 |
| C.4 | DLPDU short-form summary in alphabetic order of DLPDU acronyms..... | 951 |
| C.5 | DLPDU FC code-point assignment matrix – overview and detail..... | 952 |
| C.6 | SD-parameters (status and data-description parameters) of CA, CD, ED and DT DLPDUs..... | 955 |
| C.7 | EC parameters of EC DLPDUs | 958 |
| C.8 | Parameters of DC and RC DLPDUs..... | 960 |
| C.9 | Parameters of TD, RQ and RR DLPDUs..... | 962 |
| C.10 | Parameters of PN, PT, ES and RI DLPDUs | 964 |
| C.11 | Addressing summary extracted from figures and tables of 6.3..... | 966 |
| Annex D | (informative) – Type 2: DLPDU and DL-addressing short-form summaries..... | 970 |
| D.1 | Structure and definition of DL-addresses | 970 |
| D.2 | MAC ID address..... | 970 |
| Annex E | (informative) – Type 2: PhL interface considerations | 972 |
| E.1 | Data Link to PhL interface , additional requirements | 972 |
| E.2 | PhL requirements..... | 972 |
| Annex F | (informative) – Type 2: Indicators and Switches..... | 974 |
| F.1 | Purpose | 974 |
| F.2 | General indicator requirements | 974 |
| F.3 | Common indicator requirements | 974 |
| F.4 | Module status indicator | 975 |
| F.5 | Network status indicators | 975 |
| F.6 | Switches | 978 |

| | |
|--|------|
| Annex G (informative) – Type 3: Exemplary token procedure and message cycles..... | 980 |
| G.1 Procedure of token passing..... | 980 |
| G.2 Examples for Token Passing procedure..... | 981 |
| G.3 Examples for message cycles – asynchronous transmission..... | 984 |
| G.4 Examples for message cycles – synchronous transmission..... | 986 |
| Annex H (informative) – Type 3: PhL Considerations..... | 988 |
| H.1 Normative references..... | 988 |
| H.2 Data transmission (Ph-media, Ph-layer)..... | 988 |
| H.3 Electrical characteristics..... | 989 |
| H.4 Connector technique, mechanical and electrical specifications..... | 990 |
| H.5 Transmission method..... | 994 |
| Annex I (Informative) – Type 6: Media Independent PhL..... | 995 |
| I.1 Additional definitions..... | 995 |
| I.2 Additional definitions..... | 996 |
| I.3 Media Independent Ph layer..... | 996 |
| Annex J (Informative) – Type 6: RS-485 Wire – Media dependent PhL..... | 1012 |
| J.1 Normative references..... | 1012 |
| J.2 Transmission method..... | 1012 |
| Annex K (informative) – Type 7: Object Modeling..... | 1019 |
| K.1 Modeling of the IDENTIFIER object..... | 1019 |
| K.2 Description of the IDENTIFIER object attributes..... | 1019 |
| K.3 Modeling of the QUEUE object..... | 1024 |
| K.4 Description of the QUEUE object attributes..... | 1024 |
| K.5 Modeling of the BUFFER object..... | 1025 |
| K.6 Description of the BUFFER object attributes..... | 1025 |
| Annex L (informative) – Type 7: Topology of multi-segment DL-subnetwork..... | 1026 |
| L.1 Introduction..... | 1026 |
| L.2 Global Specification..... | 1026 |
| L.3 Local Specification..... | 1027 |
| L.4 Properties..... | 1028 |
| L.5 Methods..... | 1028 |
| Annex M (informative) – Type 7: Management of transmission errors..... | 1032 |
| M.1 Transmission of RP_DAT_XX..... | 1032 |
| M.2 Transmission of RP_RQ(1/2) FREE..... | 1032 |
| M.3 Transmission of the SPECIFIED RP_RQ1..... | 1033 |
| M.4 Transmission of RP_MSG_NOACK..... | 1034 |
| M.5 Transmission of RP_MSG_ACK..... | 1036 |
| Annex N (informative) – Type 8: Implementation possibilities of definite PNM2 functions..... | 1039 |
| N.1 Acquiring the current configuration..... | 1039 |
| N.2 Comparing the acquired and stored configurations prior to a DL-subnetwork error..... | 1042 |
| Annex O (informative) – Type 8: PhL Considerations..... | 1049 |
| O.1 Normative References..... | 1049 |
| O.2 PhL..... | 1049 |
| O.3 Peripherals Network Management of the Layer 1 (PNM1)..... | 1049 |
| Bibliography..... | 1052 |
| Index..... | 1053 |

Figures

| | Page |
|---|------|
| Figure 1 – Relationship of IEC 61158-4 to other Fieldbus layers and to users of the Fieldbus Data Link Service | 30 |
| Figure 2 – Relationships of DLSAPs, DLSAP-addresses and group DL-addresses Type 1 | 42 |
| Figure 3 – Relationships of DLCEPs and DLCEP-addresses to DLSAPs, DLSAP-addresses and group DL-addresses | 44 |
| Figure 4 – Basic Structure of a DL-address | 104 |
| Figure 5 – Basic Structure of a Sublink Selector | 105 |
| Figure 6 – DL-address Alternative Structures | 105 |
| Figure 7 – Basic Structure of MAC-addresses | 116 |
| Figure 8 – Representation of a DL-address as a MAC-address | 116 |
| Figure 9 – Linear relationships of sending and receiving DLCEP sequence-number variables | 130 |
| Figure 10 – DL-address alternative structures | 141 |
| Figure 11 – SHORT DL-address field – alternative implicit structures | 141 |
| Figure 12 – NODE DL-address field – implicit structure | 142 |
| Figure 13 – State transition diagram for a DLCEP | 267 |
| Figure 14 – Projection of the sending and receiving DLCEP sequence-number variables of Figure 9 onto the cyclic sequence-number parameters of CA, CD, DT, ED and RC DLPDUs, with consequent determination of required actions | 287 |
| Figure 15 – State transitions of a DLE | 382 |
| Figure 16 – Bridged Network Topology | 402 |
| Figure 17 – Spanning Tree Representation | 402 |
| Figure 18 – DLSDU transit delay, DLPDU lifetime and bridge forwarding delay | 407 |
| Figure 19 – Forwarding and delivering a received DLPDU | 412 |
| Figure 20 – Forwarding a locally-originated DLPDU | 412 |
| Figure 21 – Republishing a DLSDU received from another link | 413 |
| Figure 22 – Bridge architecture | 415 |
| Figure 23 – Replacement for [IL] Fig 3-2 Bridge ports | 425 |
| Figure 24 – Replacement for [IL] Fig 3-3 Bridge architecture Type 2 | 425 |
| Figure 25 – Data Link Layer internal architecture | 477 |
| Figure 26 – Basic Structure of a MAC ID address | 479 |

| | |
|---|-----|
| Figure 27 – Basic Structure of a Generic tag address | 479 |
| Figure 28 – Basic Structure of a Fixed tag address | 480 |
| Figure 29 – M_symbols and Manchester encoding at 5MHz (informative) | 481 |
| Figure 30 – NUT structure | 485 |
| Figure 31 – Media access during scheduled time | 486 |
| Figure 32 – Media access during unscheduled time | 487 |
| Figure 33 – Mframe format | 488 |
| Figure 34 – Aborting an Mframe during transmission | 489 |
| Figure 35 – Lpacket format | 490 |
| Figure 36 – Generic tag Lpacket format | 491 |
| Figure 37 – Fixed tag Lpacket format | 491 |
| Figure 38 – goodness parameter of TimeDist_unit | 505 |
| Figure 39 – Example I'm alive processing algorithm | 512 |
| Figure 40 – Keeper CRC algorithm | 532 |
| Figure 41 – Keeper object Power Up State Diagram | 545 |
| Figure 42 – Keeper object operating state diagram | 546 |
| Figure 43 – Synchronized Network Change Processing | 549 |
| Figure 44 – NAM state machine | 562 |
| Figure 45 – Logical Token Passing ring | 616 |
| Figure 46 – PhL(T2) data service | 621 |
| Figure 47 – Idle time T _{ID1} | 625 |
| Figure 48 – Idle time T _{ID2} | 625 |
| Figure 49 – Slot time T _{SL1} | 626 |
| Figure 50 – Slot time T _{SL2} | 626 |
| Figure 51 – Synchronization time T _{SYN} | 627 |
| Figure 52 – Idle time T _{ID1} | 630 |
| Figure 53 – Token cycle | 634 |
| Figure 54 – Message cycle | 635 |
| Figure 55 – DL-frame format | 637 |
| Figure 56 – UART character | 637 |
| Figure 57 – Octet structure | 638 |
| Figure 58 – Length octet coding | 639 |

| | |
|--|--------|
| Figure 59 – Address octet coding | 639 |
| Figure 60 – DAE/SAE octet in the frame | 640 |
| Figure 61 – Address extension octet | 640 |
| Figure 62 – FC octet coding | 642 |
| Figure 63 – FCS octet coding | 645 |
| Figure 64 – Data field | 646 |
| Figure 65 – Ident user data | 647 |
| Figure 66 – DLSAP Status user data | 648 |
| Figure 67 – Frames of fixed length with no data field | 651 |
| Figure 68 – Frames of fixed length with no data field | 652 |
| Figure 69 – Frames of fixed length with data field | 653 |
| Figure 70 – Frames of fixed length with data field | 654 |
| Figure 71 – Frames with variable data field length | 655 |
| Figure 72 – Frames with variable data field length | 656 |
| Figure 73 – Token frame | 657 |
| Figure 74 – Token frame | 657 |
| Figure 75 – Send/request frame of fixed length with no data | 658 |
| Figure 76 – Token frame and send/request frame of fixed length with data including address extension | 659 |
| Figure 77 – Send/request frame with variable data field length | 660 |
| Figure 78 – DL-state diagram | 666 |
| | Type 4 |
| Figure 79 – Relationship of PhE, DLE and DLS-user | 667 |
| Figure 80 – DLE state diagram for Confirmed and Unconfirmed, Unacknowledged DLPDUs | 669 |
| Figure 81 – DLE state diagram for Confirmed, Acknowledged DLPDUs | 670 |
| Figure 82 – DLE state diagram for Unconfirmed, Acknowledged DLPDUs | 671 |
| Figure 83 – Full duplex DLE receive state diagram | 672 |
| Figure 84 – Full duplex DLE transmit state diagram | 672 |
| Figure 85 – Link access example | 675 |
| Figure 86 – Simple P-NET-route format | 681 |
| Figure 87 – Extended P-NET-route format | 682 |
| Figure 88 – Complex P-NET-route format | 682 |
| Figure 89 – Immediate P-NET-route format | 683 |

| | |
|--|-----|
| Figure 90 – Control-status format | 683 |
| Figure 91 – Data-field-format | 684 |
| Figure 92 – Source / Destination designator | 693 |
| Figure 93 – Simple P-NET-route generation | 694 |
| Figure 94 – Extended P-NET-route generation | 694 |
| Figure 95 – Complex P-NET-route generation | 695 |
| Figure 96 – Simple DL-route generation | 695 |
| Figure 97 – Extended DL-route generation | 696 |
| Figure 98 – Complex DL-route generation | 696 |
| Type 6 | |
| Figure 99 – Connection Mode operation using TDMA and showing Slots, Channels Slot Selectors and Channel Identifiers | 701 |
| Figure 100 – Fundamental Access Concepts including Slots, Channels, Bus-Cycles, Scan Classes, and Bus Synchronization | 702 |
| Figure 101 – Architecture of a Synchronizer showing one Upper port Bridge-DLE synchronizing multiple Lower Port Bridge-DLEs | 706 |
| Figure 102 – Architecture of a Forwarding Bridge showing one Upper port Bridge-DLE synchronizing exactly one Lower Port Bridge-DLEs and Data Transfer across the Extended Link | 706 |
| Figure 103 – Transfer frame composition on a UNARY channel, showing transfer of the complete DLSDU within a single DLPDU | 708 |
| Figure 104 – Initial Grain DLPDU composition showing the Initial Grain and the Initial Grain Header | 709 |
| Figure 105 – Initial Grain Header Composition, showing the DLPDU-Type, Final flag, CD-semaphore and QoS-set | 709 |
| Figure 106 – Middle Grain DLPDU Composition showing the Middle Grain and the Middle Grain Header | 710 |
| Figure 107 – Middle Grain Header Composition, showing DLPDU-Type and Transmitted Grain Count | 711 |
| Figure 108 : Final Grain Composition showing the Final Grain and the Final Grain Header | 711 |
| Figure 109: Final Grain Composition, showing DLPDU-Type and Transmitted Grain Count | 712 |
| Figure 110: DL Status Header and DLPDU, which shows DLPDU-Type, Transfer Status and Reason for Failure | 712 |
| Figure 111 – DLPDU Format for 1 WAY or 2 WAY Transmission Method | 714 |
| Figure 112 – Virtual Network Topology which can be configured for connection mode operation | 716 |
| Figure 113 – Connectionless DL-addresses, symbols and their relationships, and Node-Visible-Identification | 716 |
| Figure 114 – General form of Connectionless DL-addresses | 717 |