

INTERNATIONAL STANDARD



Components for low-voltage surge ~~protective devices~~ protection –
Part 331: Performance requirements and test methods for metal oxide varistors
(MOV)

(<https://standards.iteh.ai>)

Document Preview

[IEC 61643-331:2020](#)

<https://standards.iteh.ai/catalog/standards/iec/c12137df-94f0-4536-b70f-6cf8d40d3dba/iec-61643-331-2020>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

[IEC 61643-331:2020](https://standards.iteh.ai/catalog/standards/iec/c12137df-94f0-4536-b70f-6cf8d40d3dba/iec-61643-331-2020)

<https://standards.iteh.ai/catalog/standards/iec/c12137df-94f0-4536-b70f-6cf8d40d3dba/iec-61643-331-2020>



IEC 61643-331

Edition 3.0 2020-03
REDLINE VERSION

INTERNATIONAL STANDARD



Components for low-voltage surge ~~protective devices~~ protection –
Part 331: Performance requirements and test methods for metal oxide varistors
(MOV)

Document Preview

[IEC 61643-331:2020](https://standards.iteh.ai/catalog/standards/iec/c12137df-94f0-4536-b70f-6cf8d40d3dba/iec-61643-331-2020)

<https://standards.iteh.ai/catalog/standards/iec/c12137df-94f0-4536-b70f-6cf8d40d3dba/iec-61643-331-2020>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.040.20

ISBN 978-2-8322-8023-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	5
1 Scope	7
2 Normative references	7
3 Terms, definitions, symbols and abbreviated terms	8
3.1 Terms and definitions	8
3.1.1 Ratings	8
3.1.2 Characteristics	9
3.2 Symbols and abbreviated terms used in this document	11
3.2.1 Symbols	11
3.2.2 Abbreviated terms	11
4 Service conditions	12
4.1 Operating and storage temperature ranges	12
4.2 Altitude or atmospheric pressure range	12
4.3 Relative Humidity	12
5 Mechanical requirements and materials	12
5.1 Robustness of terminations	12
5.2 Solderability	12
5.3 Marking	12
6 General	13
6.1 Failure rates	13
6.2 Test standard atmospheric conditions	13
7 Electrical requirements	13
7.1 Nominal Varistor voltage (V_V)	13
7.2 Maximum AC (DC) continuous operating voltage ($V_{M(AC)} / V_{M(DC)}$)	13
7.3 Standby current I_{DC} (I_D)	13
7.4 Capacitance (C_V)	13
7.5 Clamping voltage (V_C)	13
7.6 Electrostatic discharge (ESD) (for SMD type MOV only)	15
7.7 Rated impulse energy (W_{TM})	15
7.8 Nominal discharge current (I_n)	15
7.9 Endurance	15
7.10 Limited current temporary overvoltage	16
8 Standard design test criteria	16
8.1 General	16
8.2 Ratings	16
8.2.1 Single-impulse maximum current (I_{TM})	16
8.2.2 Next impulse	17
8.2.3 Maximum Continuous rated voltage (V_M)	17
8.3 Electrical Characteristics	17
8.3.1 Clamping voltage (V_C)	17
8.3.2 Standby current (I_D)	17
8.3.3 Nominal Varistor voltage (V_N) (V_V)	18
8.3.4 Capacitance (C_V)	18
8.3.5 Rated energy	18
8.4 Endurance Varistor Rating Assurance Testing	18

8.5	ESD test Method	19
9	Nominal discharge current and limited current temporary overvoltage	19
9.1	Thermally protected varistors – Sequence of tests	19
9.2	Temperature and humidity cycle conditioning	20
9.3	Nominal discharge current I_n (I_n) test description	20
9.3.1	General	20
9.3.2	Pass/fail criteria	22
9.4	Limited current temporary overvoltage test description and procedure for thermally protected varistors	22
9.4.1	General	22
9.4.2	Sample preparation	23
9.4.3	Test conditions	23
9.4.4	Pass/fail criteria	23
9.5	Dielectric testing	24
9.5.1	Test conditions for thermally protected MOV	24
9.5.2	Setup from foil to leads	25
9.5.3	Pass criteria	25
9.6	Insulation Resistance	25
Annex A	(informative) MOV testing according to the IEC 61643-11:2011 Surge protective devices for the Class I, II and III	26
A.1	General	26
A.2	MOV selection	26
A.3	Cross reference list of abbreviations, descriptions and definitions	26
A.4	Operating duty test	27
A.4.1	General	27
A.4.2	Class I and II operating duty tests (8.3.4.3)	32
A.4.3	Additional duty test for test class I	33
A.4.4	Class III operating duty tests	33
A.4.5	Pass criteria for all operating duty tests and for the additional duty test for test class I	34
A.4.6	Preferred parameters of impulse discharge current I_{imp} used for Class I additional duty tests	34
A.4.7	Preferred values of impulse discharge current I_n used for Class I and Class II residual voltage and operating duty tests	35
A.4.8	Preferred values of combination generator waveshape used for Class III tests	36
Annex B	(informative) IEC 61051 Varistors for use in electronic equipment	38
Annex C	(informative normative) Accelerated Endurance screening test	39
C.1	Accelerated endurance screening test	39
C.2	Preparation of sample	39
C.3	Test conditions	39
C.4	Refer to test circuit diagram as shown in Figure C.1.	39
C.5	Pass criteria	40
Annex D	(informative) Proposed test method for determination of MTTF – Mean time to failure (MTTF)	41
D.1	Sampling plans	41
D.2	Total test hours	41
D.3	Samples	41
D.4	Test set-up	42
D.5	Intermediate measurements	42

D.6 Failure criteria.....42
 D.7 Acceptance criteria42

Bibliography.....

Figure 1 – V-I characteristic of an MOV 10
 Figure 2 – Symbol for MOV 11
 Figure 3 – Symbol for thermally protected MOV 11
 Figure 4 – Test circuit for single-impulse maximum current 16
 Figure 5 – Test circuit for measuring leakage standby current..... 17
 Figure 6 – Test circuit for measuring nominal varistor voltage (V_N) (V_V) 18
 Figure 7 – Varistor rating assurance test setup 18
 Figure 8 – Nominal discharge current test flowchart..... 21
 Figure 9 – Sequence of the I_n Test 22
 Figure 10 – Temporary overvoltage limited current test procedure flowchart 24
 Figure A.1 – Flow chart of the operating duty test 28
 Figure A.2 – Test set-up for operating duty test 29
 Figure A.3 – Flow chart of testing to determine the measured limiting voltage..... 31
 Figure A.4 – Operating duty test timing diagram for test classes I and II 32
 Figure A.5 – Additional duty test timing diagram for test class I 33
 Figure A.6 – Operating duty test timing diagram for test class III..... 34
 Figure C.1 – Circuit of accelerated ageing test..... 39
 Figure D.1 – Test Circuit of MTTF 42

Table 1 – Typical Voltage ratings for disc types 14
 Table 2 – Typical Voltage Ratings for SMD types..... 14
 Table 3 – Test voltages for dielectric strength Between Test voltage 25
 Table A.1 – Comparison of IEC 61643-11 and IEC 61643-311 Abbreviations, descriptions and definitions..... 27
 Table A.2 – Preferred parameters for class I test 34
 Table A.3 – Preferred values for class I and class II tests 35
 Table A.4 – Preferred values for class III tests 36
 Table C.1 – Current in V_T measurement..... 39
 Table D.1 – Sampling plans 41

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**COMPONENTS FOR LOW-VOLTAGE SURGE ~~PROTECTIVE DEVICES~~
PROTECTION –****Part 331: Performance requirements and test methods
for metal oxide varistors (MOV)**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

International Standard IEC 61643-331 has been prepared by subcommittee 37B: Components for low-voltage surge protection, of IEC technical committee 37: Surge arresters.

This third edition cancels and replaces the second edition published in 2017. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) a Varistor MCOV rating assurance test;
- b) an energy rating test (2ms);
- c) revised Dielectric strength and insulation resistance tests.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
37B/211/FDIS	37B/214/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 61643 series, under the general title *Components for low-voltage surge protective devices*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

COMPONENTS FOR LOW-VOLTAGE SURGE ~~PROTECTIVE DEVICES~~ PROTECTION –

Part 331: Performance requirements and test methods for metal oxide varistors (MOV)

1 Scope

This part of IEC 61643 is a test specification for metal oxide varistors (MOV), which are used for applications up to 1 000 V AC or 1 500 V DC in power lines, or telecommunication, or signalling circuits. They are designed to protect apparatus or personnel, or both, from high transient voltages.

This document applies to MOVs having two electrodes and hybrid ~~overvoltage~~ surge protection components. This document also does not apply to mountings and their effect on the MOV's characteristics. Characteristics given apply solely to the MOV mounted only in the ways described for the tests.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1:2013, *Environmental testing – Part 1: General and guidance*

IEC 60068-2-6:2007, *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-14:2009, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*

IEC 60068-2-20:2008, *Environmental testing – Part 2-20: Tests – Test T: Test methods for solderability and resistance to soldering heat of devices with leads*

IEC 60068-2-21:2006, *Environmental testing – Part 2-21: Tests – Test U: Robustness of terminations and integral mounting devices*

IEC 60068-2-27:2008, *Environmental testing – Part 2-27: Tests – Test Ea and guidance: Shock*

IEC 60068-2-52:2017 *Environmental testing – Part 2-52: Tests – Test Kb: Salt mist, cyclic (sodium chloride solution)*

~~IEC 60068-2-78:2012, *Environmental testing – Part 2-78: Tests – Test Cab: Damp heat, steady state*~~

IEC 61643-11:2011, *Low-voltage surge protective devices – Part 11: Surge protective devices connected to low-voltage power systems – Requirements and test methods*

IEC 61000-4-2:2008, *Electromagnetic compatibility (EMC) – Part 4-2: Testing and measurement techniques – Electrostatic discharge immunity test*

3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1 Terms and definitions

3.1.1 Ratings

3.1.1.1

absolute maximum ratings

limiting values of operating and environmental conditions applicable to a component, device, equipment or machine as defined by its published specification data, which should not be exceeded under the worst possible conditions

Note 1 to entry: A limiting condition may be either a maximum or a minimum or both.

[SOURCE: ~~MODIFIED~~ IEC 62240-1:2013, 3.1.1, modified ("any semiconductor device of a specific type" replaced by "a component, device, equipment or machine", addition of Note 1 to entry)]

3.1.1.2

single-impulse [transient] maximum current

I_{TM}

rated maximum value of current which may be applied for a single impulse of specified waveform

Note 1 to entry: For power distribution ~~surge protective devices (SPDs)~~, IEC 61643-11, Maximum Discharge Current I_{MAX} is used.

3.1.1.3

nominal discharge current

I_n

crest value of the current through the MOV having a current waveshape of 8/20

3.1.1.4

impulse life characteristic

graphical representation between impulse current peak (I), equivalent rectangular pulse width (T), and impulse numbers (n) ~~for~~ which the ~~varistor~~ MOV can withstand

Note 1 to entry: Unless otherwise specified, the range of T shall be 20 μ s to 10 ms, the range of n shall be 10^6 , 10^5 , 10^4 , 10^3 , 10^2 , 10^1 and 10^0 ~~temperature derating curve~~.

3.1.1.5

temperature derating curve

graphical representation of parameter derating against temperature

Note 1 to entry: Typical parameters are rated voltage, impulse current, energy and average power dissipation.

3.1.1.6

single-pulse [transient] maximum energy

W_{TM}

rated maximum value which may be absorbed for a single pulse of a specified waveform

Note 1 to entry: Unless otherwise specified, 2 ms rectangular pulse is used (IEC 60060).

3.1.1.7 maximum continuous voltage

V_M
voltage that may be applied continuously at a specified temperature

Note 1 to entry: May also be called U_C or ~~maximum continuous operating voltage (MCOV)~~.

Note 2 to entry: See Figure 1.

3.1.1.8 maximum continuous AC voltage

$V_{M(AC)}$
value of RMS power frequency voltage (less than 5 % total harmonic distortion) that may be applied continuously at a specified temperature

3.1.1.9 maximum continuous DC voltage

$V_{M(DC)}$
DC voltage that may be applied continuously at a specified temperature

3.1.1.10 mean time to failure

MTTF
basic measure of reliability for non-repairable items, the total number of life units of an item divided by the total number of failures within that population, during a particular measurement interval under stated conditions

3.1.2 Characteristics

3.1.2.1 characteristic

inherent and measurable ~~property~~ properties of an MOV

3.1.2.2 standby current

I_D
current passing through MOV at maximum continuous voltage V_M

Note 1 to entry: The current passing through the MOV at less than V_M is called leakage current.

3.1.2.3 ~~nominal~~ varistor voltage

V_N V_V
voltage across the MOV measured at a specified current (typically 1 mA) for a specific duration

Note 1 to entry: ~~See Figure 1.~~

3.1.2.4 varistor test current

I_N
test current (typically 1 mA) to determine the varistor voltage V_V

Note 1 to entry: See Figure 1.

3.1.2.5 clamping voltage

V_C
peak voltage across the MOV measured under conditions of a specified peak pulse current (I_P) and specified waveform

Note 1 to entry: See Figure 1.

Note 2 to entry: Unless otherwise specified, a typical value of this parameter is measured with a pulsed current 8/20 waveform.

Note 3 to entry: Clamping voltage, V_C , is referred to as measured limiting voltage in IEC 61643-11.




Figure 1 – V-I characteristic of an MOV

3.1.2.6 capacitance

C_V
capacitance across the MOV measured at a specified frequency, voltage and time

3.1.2.7 metal oxide varistor (MOV)

component whose conductance during static state, at a given temperature, increases rapidly with increasing voltage

Note 1 to entry: This is also known as a voltage dependant resistor (VDR).

3.1.2.8 thermally protected metal oxide varistor

varistor which includes a series non-resettable element that will disconnect the MOV when it is overheated due to excessive dissipation

3.1.2.9 DC standby current

I_{DC}
current passing through MOV at maximum continuous voltage DC $V_{M(DC)}$

3.2 Symbols and abbreviated terms used in this document

3.2.1 Symbols

Figure 2 and Figure 3 represent the IEC 60617 symbols for MOV and thermally protected MOV, respectively.



Figure 2 – Symbol for MOV




Figure 3 – Symbol for thermally protected MOV

NOTE IEC 60027 recommends the letters V and v only as reserve symbols for voltage; however, in the field of MOV components, these are so widely used that in this document they are preferred to U and u.

3.2.2 Abbreviated terms

- CUT Component Under Test
- ~~DUT Device Under Test~~
- ESD Electrostatic Discharge
- MCOV Maximum Continuous Operating Voltage
- MOV Metal Oxide Varistor
- MTTF Mean Time To Failure
- SMD Surface Mount Device
- SPD Surge Protective Device
- VDR Voltage Dependent Resistor

4 Service conditions

4.1 Operating and storage temperature ranges

Operating range

- Normal: –5 °C to +55 °C
- Extended: –40 °C to +85 °C

Storage range MOV

- Normal: –40 °C to +85 °C
- Extended: –40 °C to +125 °C

Storage range Thermally protected MOV

- Normal: –40 °C to +85 °C
- Extended: –40 °C to +85 °C

NOTE Temperature range (operating or storage) could be different than the normal or extended values shown above.

4.2 Altitude or atmospheric pressure range

The altitude of air pressure is within 80 kPa to 106 kPa (refer to IEC 60068-1).

4.3 Relative Humidity

Normal range: 5 % to 95 % at 25 °C (refer to IEC 60068-1 and IEC 60068-2-78).

5 Mechanical requirements and materials

5.1 Robustness of terminations

If applicable, the user shall specify a suitable test from IEC 60068-2-21.

5.2 Solderability

Solder terminations shall meet the requirements of IEC 60068-2-20, test Ta, method 1.

5.3 Marking

Legible and permanent marking shall be applied to the MOV as necessary to ensure that the user can determine the following information by inspection.

Each MOV shall be marked with the following information:

- Date of manufacture or batch number
- Manufacturer name or trademark
- part number
- safety approval markings

NOTE 1 The necessary information can also be coded.

NOTE 2 When the space is not sufficient for printing this data, ~~it should be provided in the technical documentation after agreement between the manufacturer and the purchaser~~ it could be provided on the smallest unit container in which the product is packaged or as agreed upon between the manufacturer and the purchaser.