

Edition 4.0 2020-04

REDLINE VERSION



Fibre optic interconnecting devices and passive components – Fibre optic fixed filters – Generic specification

tps://standards.iten.ai) Document Preview

IEC 61977:2020

https://standards.iteh.ai/catalog/standards/iec/41228219-adc4-437h-9163-6cef4h583d10/iec-61977-2020





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Tel.: +41 22 919 02 11

info@iec.ch www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

TEC 61077:2020

https://standards.iteh.ai/catalog/standards/iec/41228219-adc4-437h-9163-6cef4h583d10/iec-61977-2020



Edition 4.0 2020-04

REDLINE VERSION



Fibre optic interconnecting devices and passive components – Fibre optic fixed filters – Generic specification

Document Preview

IEC 61977:2020

https://standards.iteh.ai/catalog/standards/iec/41228219-adc4-437b-9163-6cef4b583d10/iec-61977-2020

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.180.20 ISBN 978-2-8322-8186-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

F	OREWO	PRD	4
IN	ITRODU	JCTION	6
1	Scop	pe	7
2	•	native references	
3	Term	ns and definitions	8
		Basic terms	
	3.1	Component terms	
	3.2	Performance terms	
4	-	uirements	
	4.1	Classification	
	4.1.1		
	4.1.2		
	4.1.3		
		Normative reference extensions	14
	4.2	Documentation	18
	4.2.1	Symbols	18
		Specification system	
	4.2.2	Drawings	19
	4.2.3	Tests and measurements	19
	4.2.4		
	4.2.5	Instructions for use	20
	4.3	Standardisation system	
	4.3.1		
	/st4.3.2	As ite Performance standards///////////////////////////////////	61.9.7.7.2102
	4.3.3	,	
		Interlinking	
	4.4	Design and construction	
	4.4.1		
	4.4.2	•	
	4.5	Quality	
	4.6	Performance requirements	
	4.7	Identification and marking	
	4.7.1		
	4.7.0	Variant identification number	
	4.7.2		
	4.7.3	3	
	4.8	Packaging	
	4.9 4.10	Storage conditions	
٨		Safety(informative) Example of etalon filter technology	
А			
	A.1	Operating principle of etalon filter	
٨	A.2	Transmission characteristics of etalon filter	
А		(informative) Example of fibre Bragg grating (FBG) filter technology	
	B.1	Operating principle of FBG	
	B.2	Example of usage of an FBG	

Annex C (informative) Example of thin film filter technology	31
C.1 Example of thin film filter technology	31
C.2 Example of application of thin film filters	31
Annex D (informative) Examples of interface style	33
Bibliography	
Figure 1 – Illustration of passband ripple	11
Figure 2 – Illustration of a stopband	12
Figure 3 – Illustration of maximum insertion loss within a passband	13
Figure 4 – Illustration of minimum insertion loss within a passband	13
Figure 5 – Illustration of X dB bandwidth	14
Figure 6 Optic filter style configurations	
Figure 7 – Standards currently under preparation	
Figure A.1 – Schematic diagram of an etalon	27
Figure A.2 – Transmission characteristic of an etalon	28
Figure B.1 – Technology of a fibre Bragg grating	29
Figure B.2 – Application of an optical add/drop module	30
Figure B.3 – Application of an OTDR sensor	30
Figure B.4 – Application of the wavelength stabilizer for a 980 nm pump LD	30
Figure C.1 – Structure of a multilayer thin-film	31
Figure C.2 – Application for a GFF for an optical fibre amplifier	
Figure C.3 – Application for a BPF for an optical fibre amplifier	32
Figure D.1 – Examples of interface style for fibre optic fixed filters	33
Table 1 – Example of a typical fibre optic fixed filter classification	15
Table 2 - The IEC specification structure	//icc-01977-2 020
Table 3 – Standards interlink matrix	
Table 4 – Quality assurance options	

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – FIBRE OPTIC FIXED FILTERS – GENERIC SPECIFICATION

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

DISCLAIMER

This Redline version is not an official Standard and is intended to provide the user with an indication of what changes have been made to the previous version. Only the IEC International Standard provided in this package is to be considered the official Standard.

This Redline version provides you with a quick and easy way to compare all the changes between this standard and its previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

International Standard IEC 61977 has been prepared by subcommittee SC 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee TC 86: Fibre optics.

This fourth edition cancels and replaces the third edition published in 2015. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) change of the title and the scope for the limitation to fibre optic fixed filters;
- b) addition of new terms and definitions reflecting new title;
- c) removal of terms and definitions duplicated in IEC TS 62627-09;
- d) harmonization of the vertical axis of Figures 1 to 5;
- e) restructuration of Clause 4 reflecting the latest technical and market situation.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
86B/4267/FDIS	86B/4286/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed, os://standards/iec/41228219-adc4-437b-9163-6cef4b583d10/iec-61977-2020
 withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

There are two generic specifications for fibre optic filters: fibre optic fixed filters and fibre optic tuneable filters. This document focuses on fibre optic fixed filters. Fibre optic tuneable bandpass filter is standardized in IEC 63032.

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 61977:2020

https://standards.iteh.ai/catalog/standards/iec/41228219-adc4-437b-9163-6cef4b583d10/iec-61977-2020

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – FIBRE OPTIC FIXED FILTERS – GENERIC SPECIFICATION

1 Scope

This document applies to the family of fibre optic filters. These components have all of the following general features:

- they are passive for the reason that they contain no optoelectronic or other transducing elements which can process the optical signal launched into the input port;
- they modify the spectral intensity distribution in order to select some wavelengths and inhibit others;
- they are fixed, i.e. the modification of the spectral intensity distribution is fixed and cannot be tuned;
- they have input and output ports or a common port (having both functions of input and output)
 for the transmission of optical power; the ports are optical fibre or optical fibre connectors;
- they differ according to their characteristics. They can be divided into the following categories:
 - short-wave pass (only wavelengths lower than or equal to a specified value are passed);
 - long-wave pass (only wavelengths greater than or equal to a specified value are passed);
 - band-pass (only an optical window is allowed);
 - notch (only an optical window is inhibited);
 - gain flattening (compensating the spectral profile of the device).

It is also possible to have a combination of the above categories.

This document provides the generic information including terminology of IEC 61753-04x series documents. Published IEC 61753-04x series documents are listed in the Bibliography.

This document establishes uniform requirements for optical, mechanical and environmental properties.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60027 (all parts), Letter symbols to be used in electrical technology

IEC 60050-731, International Electrotechnical Vocabulary (IEV) – Part 731: Optical fibre communication (available at http://www.electropedia.org)

IEC 60617 (all parts), Graphical symbols for diagrams (available at http://std.iec.ch/iec60617)

IEC 60695-11-5, Fire hazard testing - Part 11-5: Test flames - Needle-flame test method - Apparatus, confirmatory test arrangement and guidance

IEC 60825 (all parts), Safety of laser products

IEC 61300 (all parts), Fibre optic interconnecting devices and passive components – Basic test and measurement procedures

IEC TR 61930, Fibre optic graphical symbology

IEC TS 62627-09, Fibre optic interconnecting devices and passive components – Vocabulary for passive optical devices

ISO 129-1, Technical <u>drawings</u> product documentation (TPD) <u>- Indication</u> Presentation of dimensions and tolerances – Part 1: General principles

ISO 286-1, Geometrical product specifications (GPS) – ISO code system for tolerances on linear sizes – Part 1: Basis of tolerances, deviations and fits

ISO 1101, Geometrical product specifications (GPS) – Geometrical tolerancing – Tolerances of form, orientation, location and run-out

ISO 8601, Data elements and interchange formats – Information interchange – Representation of dates and times

ISO 8601-1, Date and time - Representations for information interchange - Part 1: Basic rules

3 Terms and definitions S:/ Standards.iteh.ai

For the purpose of this document, terms and definitions given in IEC 60050-731, IEC TS 62627-09 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses: Make all production databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1 Basic terms

3.1.1

port

optical fibre or optical fibre connector attached to a passive component for the entry and/or exit of the optical power (input and/or output port)

3.1 Component terms

3.1.1

bandpass filter

BPF

band-pass filter fibre optic filter designed to allow signals between two specific wavelengths to pass

Note 1 to entry: This note applies to the French language only.

3.1.2

etalon

device consisting of a transparent plane-parallel plate with two reflecting surfaces, or two parallel reflecting mirrors

Note 1 to entry: The varying transmission function of an etalon is caused by interference between the multiple reflections of light between the two reflecting surfaces.

Note 2 to entry: Annex A describes the outline of etalon technology.

3.1.3

fibre Bragg grating

FBG

fibre optic device which has a short periodic variation to the refractive index of the fibre core along the fibre

Note 1 to entry: An FBG can reflect particular wavelengths of light and transmit other wavelengths.

Note 2 to entry: Annex B describes the outline of FBG technology.

Note 3 to entry: This note applies to the French language only.

3.1.4

fibre optic filter

passive component used in fibre optic transmission system to modify the spectral intensity distribution of a signal in order to transmit or attenuate some wavelengths and block some others

Note 1 to entry: There are two types of fibre optic filters: fibre optic fixed filters and fibre optic tuneable filters.

Note 2 to entry: The wavelength band which transmits or attenuates the signal is called the passband. There may be more than one passband.

3.1.5

fibre optic fixed filter

fibre optic filter which spectral profile is fixed 1977:2020

ttps://standards.iteh.ai/catalog/standards/iec/41228219-adc4-437b-9163-6cef4b583d10/iec-61977-2020

3.1.6

fibre optic tuneable filter

fibre optic filter which spectral profile is changeable

Note 1 to entry: Fibre optic tuneable bandpass filter is standardized in IEC 63032.

3.1.7

gain flattening filter

gain equalizer

GFF

GEQ

device fibre optic filter designed to have the inverse characteristic of the wavelength dependent insertion loss of an optical device

Note 1 to entry: A GFF (GEQ) is used for the purpose of minimizing the wavelength dependent loss of a fibre optic

device.

Note 2 to entry: A GFF (GEQ) is typically used with (in) an optical amplifier.

Note 3 to entry: This note applies to the French language only.

Note 4 to entry: This note applies to the French language only.

3.1.8

long wavelength pass filter

LWPF

fibre optic filter that passes long wavelength signals but reduces the amplitude of short wavelength signals

Note 1 to entry: This note applies to the French language only.

3.1.9

notch filter

fibre optic filter that passes all wavelengths except those in a stop band centred on a particular wavelength

3.1.10

reflecting type fibre optic filter

fibre optic filter in which the input and output ports are coincident

wavelength selective reflecting device having two ports that reflects back the light to the launch port at different wavelength range (OTDR monitoring range)

3.1.11

short wavelength pass filter

SWPF

fibre optic filter that passes short wavelength signals but reduces the amplitude of long wavelength signals

Note 1 to entry: This note applies to the French language only.

3.1.12

thin-film filter

TFF

fibre optic filter which passes particular wavelength band(s) and reflects all other wavelengths by using the interference effect of thin-film

Note 1 to entry: One of the typical TFF is a dielectric multi-layer film filter. Annex C describes the outline of TFF technology.

Note 2 to entry: This note applies to the French language only.

3.1.13

transmitting type fibre optic filter

fibre optic filter in which the input and output ports are separated

3.2 Performance terms

3.2.1

operating wavelength

nominal wavelength λ_h , at which a fibre optic filter operates with the specified performances

Note 1 to entry: The term "operating wavelength" includes the nominally transmitting wavelength, and designated attenuation/isolation wavelength.

3.2.2

operating wavelength range

specified range of wavelengths including all operating wavelengths

Note 1 to entry: It includes all passbands and isolation wavelength ranges.

3.2.3

passband

wavelength range within which a passive optical component is required to operate with optical attenuation less than or equal to a specified optical attenuation value

Note 1 to entry: There may be one or more passbands for a fibre optic filter.

3.2.4

passband ripple

maximum peak-to-peak variation of the insertion loss (absolute value) over the passband

Note 1 to entry: See Figure 1.




Figure 1 - Illustration of passband ripple

Note 2 to entry: For a wide wavelength division multiplexing (WWDM) fibre optic filter which has only one passband, the term "spectral ripple" or "flatness" is used instead of "passband ripple".

3.2.5

insertion loss

attenuation

а

reduction of optical power in a passband, when transmitted between the ports of a two-port through a fibre optic filter

Note 1 to entry: The insertion loss is expressed in decibels and defined as:

$$a = -10\log_{10}\left(\frac{P_{\text{out}}}{P_{\text{in}}}\right)$$

where

 P_{in} is the optical power launched into one of the two ports the fibre optic filter;

 P_{out} is the optical power received from the other port out of the fibre optic filter.

Note 2 to entry: The insertion loss (attenuation) is a function of wavelength.

3.2.6

free spectral range

FSR

difference between two adjacent operating wavelengths, in the case of a periodic spectral response of a fibre optic filter, difference between two adjacent operating wavelengths

Note 1 to entry: This note applies to the French language only.

3.2.7

isolation wavelength

nominal wavelength λ_k (where $\lambda_h \neq \lambda_k$), that is nominally suppressed by a fibre optic filter

3.2.8


isolation wavelength range stopband

specified range of wavelengths from λ_{kmin} to λ_{kmax} around the isolation wavelength λ_k , that are nominally suppressed by a fibre optic filter

Note 1 to entry: There may be one or more isolation wavelength ranges (stopbands) for a fibre optic filter.

Note 2 to entry: The term "stopband" is an antonym of the term passband.

Note 3 to entry: See Figure 2.



ottos://standards.iteh.ai/catalog/standards/iec/41228219-adc4-437b-9163-6cef4b583d10/iec-61977-2020

Figure 2 – Illustration of a stopband

3.2.9

maximum insertion loss within a passband

maximum attenuation within a passband

maximum value of the insertion loss optical attenuation within a passband

Note 1 to entry: Figure 3 shows passband and maximum insertion loss within a passband.