Designation: F3255 - 19

An American National Standard

Standard Specification for Rapid Pull Down Refrigerators (Blast Chillers), Freezers (Blast Freezers), Combination Refrigerator/Freezer (Blast Chiller/Freezers), and Quick Chillers for Commercial Use¹

This standard is issued under the fixed designation F3255; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 This specification covers basic design and function of rapid pull down refrigerators or freezers, or a combination of both, sometimes referred to as "blast chillers," "blast freezers," or "quick chillers."
- 1.2 This equipment is for professional use in commercial and other similar food service establishments for rapid intermediate chilling or freezing of hot food products cooked to a specific temperature within a specified time period and holding the food at a safe temperature when not engaged in the chilling or freezing process.
- 1.3 This standard addresses equipment that is self-contained, manually operated, and has a mechanically refrigerated cabinet(s) of a vertical or horizontal cabinet type. Equipment may be a "reach-in" for stationary or fixed shelving or a "roll-in" for mobile carts. This equipment may also be installed under a service counter.
- 1.4 This standard does not cover blast chilling tunnels, continuous blast-chilling and blast freezing equipment, bakery combined freezing and storage units.
- 1.5 The standard does not cover "shock freezers" or equipment that uses nitrogen or other consumable products in their function.
- 1.6 Equipment covered under this specification may contain a substance (or be manufactured with a substance) that harms public health and environment by destroying ozone in the upper atmosphere. This specification does not purport to address environmental regulations. It is the responsibility of the user of this specification to comply with environmental regulations.
- 1.7 *Units*—The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.
- ¹ This specification is under the jurisdiction of ASTM Committee F26 on Food Service Equipment and is the direct responsibility of Subcommittee F26.03 on Storage and Dispensing Equipment.
- Current edition approved March 1, 2019. Published April 2019. DOI: 10.1520/F3255-19.

- 1.8 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.
- 1.9 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

2. Referenced Documents

2.1 ASTM Standards:²

D3951 Practice for Commercial Packaging

F760 Specification for Food Service Equipment Manuals

2.2 ANSI/UL Standards:³

ANSI/UL 471 Commercial Refrigerators and Freezers ANSI/UL 969 Standard for Marking and Labeling Systems

2.3 NSF/ANSI Standards:4

NSF/ANSI 7 Commercial Refrigerators and Freezers

2.4 Military Standards:⁵

MIL-STD-167/1 Mechanical Vibrations of Shipboard Equipment Type I—Environmental and Type II— Internally Excited

MIL-STD-461 Electromagnetic Interference Characteristics Requirements for Equipment

MIL-STD-461B Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from Underwriters Laboratories (UL), 2600 N.W. Lake Rd., Camas, WA 98607-8542, http://www.ul.com.

⁴ Available from NSF International, P.O. Box 130140, 789 N. Dixboro Rd., Ann Arbor, MI 48105, http://www.nsf.org.

⁵ Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098.

MIL-STD-1399/300B Interface Standards for Shipboard Systems Section 300A, Electric Power, Alternating Current

3. Terminology

- 3.1 Definitions:
- 3.1.1 *automatic defrost, n*—process where heat is automatically introduced into the cooling coils to dissipate any ice or frost buildups on the coil.
- 3.1.2 *batch*, *n*—amount (weight) of similar hot food product inserted into blast chiller equipment at a given time for the purpose of chilling or freezing.
- 3.1.3 *capacity*, *n*—total number of pans in the interior of the cabinet.
- 3.1.4 *chill cycle, n*—refrigeration mode intended to chill hot food from $135^{\circ}F$ ($57^{\circ}C$) to below $41^{\circ}F$ ($5^{\circ}C$) within 4 h in a $100^{\circ}F$ ($38^{\circ}C$) ambient.
- 3.1.5 *chill cycle time, n*—length of time which may be specified by the manufacturer that may be less than 4 h where hot food is chilled from 135 to 41°F (5°C) or lower.
- 3.1.6 *delicate (setting), n*—also known as a "soft chill" (see 3.1.17).
- 3.1.7 *food probe*, *n*—temperature sensor used by the equipment to monitor the temperature of the food(s) being chilled.
- 3.1.8 *hard chill*, *n*—cycle ideal for chilling "standard products" such as cooked meat, pies, lasagna, individually portioned meals etc.
- 3.1.9 *hold cycle, n*—refrigeration mode intended to hold recently chilled foods at safe refrigerated temperature, typically between 32 to 41°F (0 to 5°C).
- 3.1.10 *horizontal cabinet*, *n*—any cabinet of undercounter or counter height design whose width is its greatest dimension.
- 3.1.11 *idle cycle, n*—refrigeration mode intended to keep the refrigerated space at a safe refrigerated temperature, typically between 32 to 41°F (0 to 5°C) and when the refrigerated space is empty/not in use.
- 3.1.12 *label printer*, *n*—printer integrated with the equipment used to print batch information on a label applied to the food finished product.
- 3.1.13 *modular, adj*—particular method of cabinet construction which allows the cabinet and all of its components to be dissembled and reassembled for ease of installation.
 - 3.1.14 *net volume*, *n*—expressed as either:
- (1) surface area of a loading level (that is, a shelf) multiplied by the internal height of the door frame, for reach-in cabinets, the loading height of the door is the clearance height minus approximately 10 in. (250 mm), net volume is expressed in cubic feet (ft³) (cubic meters, m³); or
- (2) surface area of the largest possible rack shelf multiplied by the loading height, for roll-in cabinets, net volume is expressed in cubic feet (ft³) (cubic meters, m³).
- 3.1.15 *positive latching hardware, n*—any latching mechanism that requires that the device be disengaged before the door can be opened.

- 3.1.16 *record printer*, *n*—printer integrated with the equipment used to print batch information for record keeping purposes.
- 3.1.17 *soft chill, n*—for the safe chilling of delicate products, cycle that is ideal for the rapid but gentle chilling of any dish.
- 3.1.17.1 *Discussion*—This cycle brings the temperature of the food down whilst retaining a positive air temperature. This prevents large ice crystals from forming which can damage the structure of delicate foods such as gateaux and patisserie items, and high water content items such as vegetables, rice and pasta. Using this program thereby maintains the texture, consistency and appearance of these foods, with no dehydration or cell damage.
- 3.1.18 *undercounter*, *n*—cabinet which has a maximum height of no more than 36 in. (914 mm) including legs or casters and mounting brackets.
 - 3.1.19 *unitary*, *adj*—single piece cabinet construction.
- 3.1.20 *vertical cabinet, n*—any cabinet with single or multiple door arrangements whose height is its greatest dimension and is in excess of 36 in. (914 mm).

4. Classification

- 4.1 *General*—Equipment covered by this specification use the military specification format of classification and is defined by Type, Style, Class, Group, Mode, Category, Size, and Capacity.
 - 4.2 *Type:*
 - 4.2.1 *Type 1*—Undercounter.
 - 4.2.2 Type 2—Reach in.
 - 4.2.3 *Type 3*—Roll in.
 - 4.2.4 Type 4—Roll through.
 - 4.3.1 *Style A*—Self-contained condensing system.
 - 4.3.2 Style B—Remote condensing system.
 - 4.4 Class:
 - 4.4.1 Class A—Air cooled.
 - 4.4.2 Class B—Water cooled.
 - 4.5 *Group:*
 - 4.5.1 Group I)—115 V, 60 Hz, 1 Ph
 - 4.5.2 Group II)-208-240 V, 60 Hz, 1 Ph
 - 4.5.3 Group III)-208-240 V, 60 Hz, 3 Ph
 - 4.5.4 *Group IV*)—115/208-240 V, 60 Hz, 1 Ph (3-Wire)
 - 4.5.5 Group V)—115/208-240 V, 60 Hz, 3 Ph (4-Wire)
 - 4.5.6 Group VI)-460 V, 60 Hz, 3 Ph
 - 4.6 *Mode*:
 - 4.6.1 *Mode 1*)—Door, left-hand swing.
 - 4.6.2 *Mode 2*)—Door, right-hand swing.
 - 4.7 *Category:*
 - 4.7.1 *Category A*)—2 in. legs.
 - 4.7.2 *Category B*)—3 in. legs.
 - 4.7.3 *Category C*)—4 in. legs.
 - 4.7.4 *Category D*)—6 in. legs.
- 4.7.5 *Category E*)-3 in. casters (minimum of two casters with brakes).

- 4.7.6 *Category F*)—4 in. casters (minimum of two casters with brakes).
- 4.7.7 Category G)—5 in. casters (minimum of two casters with brakes).
 - 4.7.8 *Category H*)—Sealed to floor.
 - 4.8 Size and Capacity:
 - 4.8.1 Capacity a)—Less than 50 lb.
 - 4.8.2 Capacity b)—51 to less than 65 lb.
 - 4.8.3 *Capacity c*)—66 to less than 150 lb.
 - 4.8.4 Capacity d)—151 to less than 225 lb.
 - 4.8.5 Capacity e)—226 lb and above.
- 4.9 Additional letters and characters may be used for optional information agreed upon by the buyer and seller for other specifications such as mounting style, chill cycle needs, etc.

5. Ordering Information

- 5.1 *Ordering Data*—Purchasers shall select rapid pull down refrigerator (blast chillers), freezers (blast freezers), combination (blast chill/freezers) and any preferred options and include the following information in the purchasing document:
 - 5.1.1 Title, number, and date of this specification,
- 5.1.2 Type, Style, Class, Group, Mode, Category Size and Style of unit required,
 - 5.1.3 Desired exterior and interior finishes,
 - 5.1.4 Quantity to be furnished,
- 5.1.5 Number of doors, type (solid or glass), hinging or swing,
- 5.1.6 When hardware and fittings are to be other than as specified (see 5.1.5),
- 5.1.7 Accessory equipment: such as spare parts, maintenance parts required, or other options available by the manufacturer, or a combination thereof,
- 5.1.8 When Federal/Military procurement is required, review and implement the applicable supplementary requirements (see S1 through S8.8.3),
- 5.1.9 When specified, the purchaser shall be furnished certification that samples representing each equipment lot have been either tested or inspected as directed in this specification and the requirements have been met. When specified, a copy of the test results shall be furnished.
- 5.1.10 Level of preservation and packing required if other than as stated in Practice D3951 (see Section 13),
- 5.1.11 Other custom features or requirements desired but not included in 5.1.7 such as batch size, chill or hold cycle, hard or soft chill, etc., and;
 - 5.1.12 Labeling requirements (if different than 11.1).
- 5.2 Equipment Selection and Application—Prior to the use of Section 4 classifications, the purchaser will ensure the user is not restricted by some aspect of the equipment design such as weight or external classifications listed in Section 4.
- 5.3 Equipment Availability—Although Section 4 lists a wide range of sizes, classes, groups and styles for commercial types of equipment, not all combinations may be available.
- 5.4 Supplementary Requirements—The supplementary requirements shall apply only when specified by the purchaser in the contract or order and acknowledged by the seller.

6. Materials and Manufacture

6.1 *General*—Equipment shall conform to the applicable documents listed in Section 2.

7. Chemical Composition

7.1 Ozone Depleting Compounds—"Type One" ozone depleting compounds shall not be used as a refrigerant or as a component of foam insulation and shall be the manufacturer's standard chemicals.

8. Design and Construction

- 8.1 Performance Requirements:
- 8.1.1 Performance test methods will be developed at a future date.
- 8.1.2 Energy performance test methods will be developed at a future date.
- 8.2 When specified in the purchase order or contract, the purchaser shall be furnished certification that samples representing each lot have been either tested or inspected as directed in this specification and the requirements have been met. When specified in the purchase order or contract, a report of the test results shall be furnished.
- 8.3 Modular Installation—Modular units shall be capable of being assembled and installed in the location where they are to be used. A minimum of 3 in. (76 mm) of space, in excess of the finished height and width, is required to accommodate the unit. The total installation of the unit is to be accomplished from the front of the unit without access to the exterior sides, back, or top.
- 8.4 Accessories—If specified, accessories such as built-in trim and locks shall be provided.

9. Workmanship, Finish, and Appearance

9.1 General—The final product including all components and assemblies of the units shall be free from dirt and other extraneous materials, burrs, slivers, tool and grind marks, dents and cracks. Castings, molded parts, and stampings shall be free of voids, sand pits, blowholes, and sprues. External surfaces shall be free from kinks, dents, and other deformities. Forming and welding shall not cause damage to the metal and shall be done neatly and accurately. All aspects of the equipment fabrication, assembly, and construction shall be such as not to cause physical harm to the operator while being able to maintain the designed working temperature. No components which may fall off during normal use will be considered an acceptable part of the design.

10. Certification

- 10.1 General—When specified in the purchase order or contract, the purchaser shall be furnished certification that the samples representing each lot have been either tested or inspected as directed in this specification and the requirements have been met.
- 10.2 *Sanitation*—Acceptable evidence of meeting the requirements of NSF/ANSI 7 shall be one of the following:
- 10.2.1 Current NSF listing and display of the NSF mark on the unit identification plate; or