



Edition 2.0 2020-11 REDLINE VERSION

INTERNATIONAL STANDARD



Residual current operated circuit-breakers for household and similar use – Part 3-1: Particular requirements for RCDs devices with screwless-type terminals for external copper conductors

Document Preview

IEC 62873-3-1:2020

0201-https://standards.iteh.ai/catalog/standards/iec/978dda6f-393b-4b75-9c55-74e8ed8224f9/iec-62873





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Tel.: +41 22 919 02 11

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

info@iec.ch www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublishedStay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.





Edition 2.0 2020-11 REDLINE VERSION

INTERNATIONAL STANDARD



Residual current operated circuit-breakers for household and similar use – Part 3-1: Particular requirements for RCDs devices with screwless-type terminals for external copper conductors

Document Preview

IEC 62873-3-1:2020

https://standards.iteh.ai/catalog/standards/iec/978dda6f-393h-4h75-9c55-74e8ed8224f9/iec-62873-3-1-2020

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.120.50 ISBN 978-2-8322-9114-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOF	REWO	RD	3						
INT	RODU	ICTION	2						
1	Scop	e	6						
2	Norm	native references	6						
3	Term	s and definitions	7						
4	Classification								
5	Characteristics of RCDs devices								
6	Marking and other product information8								
7	Standard conditions for operation in service and for installation								
8	Requirements for construction and operation								
٠ 8	3.1	General							
	3.2	Connection—or and disconnection of conductors	_						
8	3.3	Dimensions of connectable conductors							
8	3.4	Connectable cross-sectional areas							
8	3.5	Insertion and withdrawal of conductors	10						
8	3.6	Design and construction of terminals	10						
8	3.7	Resistance to ageing							
9	Tests	S	11						
g	9.1	General	11						
g	9.2	Test of reliability of screwless-type terminals	11						
	9.2.1	Reliability of screwless system	11						
	9.2.2	Test of reliability of connection	12						
S	9.3	Tests of reliability of terminals for external conductors	12						
	9.3.1	\.Ten.81/c8T8109/ST81108T0\$/1ec/9//Xdd8bT-393b-4b/>-9c>>-/4exedx/./4T9/1ec-	12						
	9.3.2	Cycling test	12						
Bibl	iograp	bhy	16						
Figu	ıre 1 -	- Connecting samples	13						
Figu	ıre 2 -	- Examples of screwless-type terminals	15						
Tab	le 1 –	Connectable conductors Conductors and their theoretical diameters	9						
Table 2 – Cross-sections of copper conductors connectable to screwless-type									
	ninals.	• • • • • • • • • • • • • • • • • • • •	10						
Tab	le 3 –	Pull forces	12						
Table 4 – Test copper conductors corresponding to the rated currents									

INTERNATIONAL ELECTROTECHNICAL COMMISSION

RESIDUAL CURRENT OPERATED CIRCUIT-BREAKERS FOR HOUSEHOLD AND SIMILAR USE –

Part 3-1: Particular requirements for RCDs devices with screwless-type terminals for external copper conductors

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

-4-

International Standard IEC 62873-3-1 has been prepared by subcommittee 23E: Circuit-breakers and similar equipment for household use, of IEC technical committee 23: Electrical accessories.

This second edition cancels and replaces the first edition published in 2016. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Modification of scope to cover screwless-type terminals up to 40 A;
- b) Modification of scope to address other devices in addition to RCDs;
- c) Modification of Table 1 to cover rated currents up to 40 A;
- d) Modification of 8.1 so that IEC 62873-3-1 can be referred to by other product standards in addition to those for RCDs:
- e) Modification of 9.1 so that IEC 62873-3-1 can be referred to by other product standards in addition to those for RCDs.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
23E/1190/FDIS	23E/1200/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document is intended to be referred to by a product standard of subcommittee IEC SC23E (e.g. from the IEC 61008 series, IEC 61009 series, IEC 62606, and IEC 63052).

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 62873 series, published under the general title *Residual current* operated circuit-breakers for household and similar use, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This document is part of the series described in the outline document IEC 62873-1.

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 62873-3-1:2020

https://standards.iteh.ai/catalog/standards/iec/978dda6f-393h-4h75-9c55-74e8ed8224f9/iec-62873-3-1-2020

RESIDUAL CURRENT OPERATED CIRCUIT-BREAKERS FOR HOUSEHOLD AND SIMILAR USE –

Part 3-1: Particular requirements for RCDs devices with screwless-type terminals for external copper conductors

1 Scope

This part of IEC 62873 applies to RCDs equipped with screwless terminals, for current not exceeding 20 A primarily suitable for connecting unprepared (see 3.5) copper conductors of cross-section up to 4 mm².

This part of IEC 62873 cannot be used alone but it is intended to be applied together with an RCD product standard (IEC 61008-1 or IEC 61009-1) if an RCD is equipped with screwless terminals.

NOTE-In AT, CZ, DK, NL, NO, PO, PT and CH, the upper limit of current for use of screwless terminals is 16 A.

This document applies to devices equipped with screwless-type terminals for current not exceeding 40 A, primarily suitable for connecting unprepared copper conductors of cross-section up to 10 mm².

This document cannot be used alone but is intended to be applied together with the applicable product standard in which it is referred to.

NOTE 1 In CZ, DK, NL, PO and CH, the upper limit of current for use of screwless-type terminals is 16 A.

NOTE 2 In JP, the upper limit of current for use of screwless-type terminals is 30 A.

NOTE 3 The manufacturer can declare in its documentation specific conditions permitting the use of prepared conductors.

In this document, screwless-type terminals are referred to as terminals, and copper conductors are referred to as conductors.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61008-1, Residual current operated circuit-breakers without integral overcurrent protection for household and similar uses (RCCBs) – Part 1: General rules

IEC 61009-1, Residual current operated circuit-breakers with integral overcurrent protection for household and similar uses (RCBOs) – Part 1: General rules

IEC 62873-2, Residual current operated circuit-breakers for household and similar use – Part 2: Residual current devices (RCDs) – Vocabulary

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62873-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at http://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1

clamping unit

part of the terminal necessary for mechanical clamping and electrical connection of the conductors including parts necessary to ensure correct contact pressure

3.2

universal terminal

terminal for the connection and disconnection of all types of conductors (rigid and flexible)

Note 1 to entry: In the following countries, only universal screwless-type terminals are accepted: AT, BE, CN, DK, DE, ES, FR, IT, PT, SE and CH.

3.3

non-universal terminal

terminal for the connection and disconnection of a certain kind of conductor only (e.g. rigid-solid conductors only or rigid-[solid or stranded] conductors only)

3.4 Document Preview

push-wire terminal

non-universal terminal (see 3.3) in which the connection is made by pushing in rigid (solid or stranded) conductors

IEC 62873-3-1:2020

023/https://standards.iteh.ai/catalog/standards/iec/978dda6f-393b-4b75-9c55-74e8ed8224f9/iec-62873-3

3.5

unprepared conductor

conductor which has been cut and the insulation of which has been removed for insertion into a terminal

Note 1 to entry: A conductor the shape of which is arranged for introduction into a terminal or the strands of which are twisted to consolidate the end is considered as an unprepared conductor.

[SOURCE: IEC 60050-442:1998, 442-01-26]

3.6

low-current terminal

terminal intended to connect a conductor to a device capable of supplying a voltage signal and/or a current not exceeding 300 mA to the device

Note 1 to entry: This does not apply to special terminal constructions intended to connect to flat or other multiwire cables by performing one "clamping action" only for more than one wire (e.g. bus connections).

4 Classification

Clause 4 of the RCD product standard, in which this document is referred to, applies.

5 Characteristics of RCDs devices

Clause 5 of the RCD product standard, in which this document is referred to, applies.

6 Marking and other product information

In addition to Clause 6 of the RCD product standard, in which this document is referred to, the following requirements markings apply:

Universal terminals:

no marking.

Non-universal terminals:

- terminals declared for rigid-solid conductors shall be marked with the letters "sol";
- terminals declared for rigid (solid and stranded) conductors shall be marked with the letter "r":
- terminals declared for flexible conductors shall be marked with the letter "f".

The markings shall appear on the device or, if the space available is not sufficient, on the smallest package unit or in technical information.

An appropriate marking indicating the length of insulation to be removed before insertion of the conductor into the terminal shall be shown on the RCD product.

The manufacturer shall also provide information, in its literature, on the maximum number of conductors which may be clamped.

7 Standard conditions for operation in service and for installation

Clause 7 of the RCD product standard, in which this document is referred to, applies.

8 Requirements for construction and operation

8.1 General

Clause 8 of the RCD product standard applies, with the following exceptions:

In 8.1.5, only 8.1.5.1, 8.1.5.2, 8.1.5.3, 8.1.5.6 and 8.1.5.7 apply.

Compliance is checked by inspection and by the tests of 9.2 and 9.3 of this standard.

In addition, the following requirements apply.

The requirements of Clause 8 of this document apply in addition to Clause 8 of the product standard, in which this document is referred to.

Compliance is checked by inspection and by the tests of 9.2 and 9.3 of this document.

For low-current terminals, no significant current flow is expected in normal service. Therefore, the tests of 9.3.2 are not performed.

8.2 Connection or and disconnection of conductors

The connection of conductors shall be made:

 by the use of a general-purpose tool or by a convenient device integral with the terminal to open it and to assist the insertion or the withdrawal of the conductors (e.g. for universal terminals);

or, for rigid conductors:

by simple insertion. For the disconnection of the conductors, an operation other than a pull
on the conductor shall be necessary (e.g. for push-wire terminals).

Universal terminals shall accept rigid (solid or stranded) and flexible unprepared conductors. They may also accept prepared conductors according to the manufacturer's declaration.

Non-universal terminals shall accept the types of conductors declared by the manufacturer.

Compliance is checked by inspection and by the tests of 9.2 and 9.3 of this document.

8.3 Dimensions of connectable conductors

The dimensions of connectable conductors are given in Table 1.

The ability to connect these conductors shall be checked by inspection and by the tests of 9.2 and 9.3 of this document.

Table 1 - Connectable conductors Conductors and their theoretical diameters

	Connectable conductors and their theoretical diameter										
	Metric Metric					AWG					
	Rigid			Flexible 62873		3-3-1:2020 Rigid			Flexible		
https:	/standard	s.iteh.ai/ca Solid	talog/stan Stranded	dards/iec/9	978dda6f-	393b-4b′	75-9c55- Solid^a	Class B stranded ^a	14f9/iec-6	Classes I, K, M, stranded ^b	
	mm ²	∅ mm	∅ mm	mm ²	∅ mm	gauge	∅ mm	Ø mm	gauge	Ø mm	
	1,0	1,2	1,4	1,0	1,5	18	1,02	1,16	18	1,28	
	1,5	1,5	1,7	1,5	1,8	16	1,29	1,46	16	1,60	
	2,5	1,9	2,2	2,5	2,3	14	1,63	1,84	14	2,08	
	4,0	2, 4	2,7	4,0	2,9	12	2,05	2,32	12	2,70	

NOTE Diameters of the largest rigid and flexible conductors are based on IEC 60228, and, for AWG conductors, on ASTM B 172-01a.

^a— Nominal diameter + 5 %.

b Largest diameter + 5 % for any of the three classes I, K and M.