

# INTERNATIONAL STANDARD

**ISO**  
**4388**

Second edition  
1991-12-15

---

---

## **Cigarettes — Determination of the smoke condensate retention index of a filter — Direct spectrometric method**

iTeh Standards

(<http://standards.iteh.ai/catalog/standards/iso/fb66aacc0-bb3f-448a-b60d-4e712860188a/iso-4388-1991>)  
*Cigarettes — Détermination de l'indice de rétention du condensat de  
fumée d'un filtre — Méthode spectrométrique directe*

Document Preview

ISO 4388:1991

<https://standards.iteh.ai/catalog/standards/iso/fb66aacc0-bb3f-448a-b60d-4e712860188a/iso-4388-1991>



Reference number  
ISO 4388:1991(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 4388 was prepared by Technical Committee ISO/TC 126, *Tobacco and tobacco products*.

This second edition cancels and replaces the first edition (ISO 4388:1977), of which it constitutes a technical revision.

ISO 4388:1991

<https://standards.iteh.ai/catalog/standards/iso/fb66acc0-bb3f-448a-b60d-4e712860188a/iso-4388-1991>

# Cigarettes — Determination of the smoke condensate retention index of a filter — Direct spectrometric method

## 1 Scope

This International Standard specifies a direct spectrometric method for the determination at 450 nm of the smoke condensate retention index of a cigarette filter.

The method is applicable to filter cigarettes. It is not applicable to cigarettes with coloured filters or to cigarettes with filters containing special additives, for example alkaline additives or absorbents such as active charcoal.

This empirical, quick and practical method relates only to smoke condensate. The results should not be interpreted with respect to any particular constituent of the smoke condensate.

## 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 3308:1991, *Routine analytical cigarette-smoking machine — Definitions and standard conditions*.

ISO 3402:1991, *Tobacco and tobacco products — Atmosphere for conditioning and testing*.

ISO 4387:1991, *Cigarettes — Determination of total and nicotine-free dry particulate matter using a routine analytical smoking machine*.

ISO 8243:1991, *Cigarettes — Sampling*.

## 3 Definition

For the purposes of this International Standard, the following definition applies.

**3.1 smoke condensate retention index ( $R_c$ ) of a cigarette filter:** The ratio, expressed as a percentage by mass, of the crude smoke condensate retained by the filter to that entering the filter (see figure 1):

$$R_c = \frac{F_c}{S_c} \times 100 = \frac{F_c}{F_c + H_c} \times 100$$

where

$F_c$  is the mass of crude smoke condensate retained by the filter;

$S_c$  is the mass of crude smoke condensate entering the filter;

$H_c$  is the mass of crude smoke condensate in the main-stream smoke.




Figure 1

## 4 Principle

Smoking of filter cigarettes in accordance with ISO 4387. Dissolution in methanol of the crude smoke condensate from the main-stream smoke. Removal of the filter material from the remaining tobacco butts; dissolution in methanol of the crude smoke condensate retained by the filters.

Determination of the absorbances at 450 nm of the two methanolic solutions by spectrometric measurement and calculation of the retention index from

the ratio of the absorbances. The absorbances are directly proportional to the masses of crude smoke condensate ( $F_c$  and  $H_c$ ).

## 5 Reagent

**5.1 Methanol**, having a water content lower than 0,05 % (m/m).

## 6 Apparatus

Usual laboratory apparatus not otherwise specified and the following items.

**6.1 Conditioning enclosure**, regulated in accordance with the requirements of ISO 3402.

**6.2 Routine analytical cigarette-smoking machine**, complying with the requirements of ISO 3308 and ISO 4387.

**6.3 Spectrometer**, suitable for carrying out measurements at a wavelength of 450 nm.

**6.4 Matched quartz cells**, having an optical path length of 10 mm, if necessary, 5 mm and/or 20 mm.

**6.5 Volumetric flasks**, of capacities 100 ml or 125 ml, with ground glass stoppers.

**6.6 One-mark pipettes**, of capacities 5 ml and 10 ml.

**6.7 Centrifuge**, capable of producing a relative centrifugal acceleration of 25  $g^{(1)}$ .

## 7 Sampling

Carry out sampling in accordance with the method specified in ISO 8243.

## 8 Procedure

### 8.1 Conditioning of the test sample

Keep the test sample in the conditioning enclosure (6.1) until it attains constant mass.

### 8.2 Test portion

Take, as the test portion, 20 filter cigarettes from the conditioned test sample (8.1).

## 8.3 Determination

### 8.3.1 Smoking of the cigarettes

Using the routine analytical cigarette-smoking machine (6.2), smoke the 20 filter cigarettes constituting the test portion (8.2) in accordance with ISO 4387.

NOTE 1 The number of cigarettes smoked per trap depends on the diameter of the glass-fibre filter and the yield of crude smoke condensate of the cigarette.

For a 44 mm smoke trap this number is in general 5.

For a 92 mm smoke trap this number is in general 20.

Extinguish the butts by separating the burning zone, remove the filter plugs and free them from any adhering tipping and plug wrap material and from any tobacco.

### 8.3.2 Preparation of methanolic crude smoke condensate solution

**8.3.2.1** Combine the cigarette filter plugs from one channel of the smoking machine and put them into 100 ml of methanol (5.1) in a volumetric flask (6.5). Do the same with the filter plugs from the other channels. Stopper the flasks, swirl the contents of each flask and allow them to stand in the dark for about 24 h.

**8.3.2.2** Remove the glass-fibre filter discs from the smoke traps and prepare from each disc a solution of the crude condensate in 100 ml of methanol (5.1) in a volumetric flask (6.5).

Stopper the flasks, swirl the contents of each flask and allow them to stand in the dark for the same time as the methanolic solutions obtained from the cigarette filter plugs (8.3.2.1).

**8.3.2.3** Transfer, by means of a pipette (6.6), 5 ml to 10 ml of each of the crude smoke condensate solutions, prepared as described in 8.3.2.1 and 8.3.2.2, to the centrifuge (6.7) and centrifuge for approximately 1 min to remove suspended matter.

### 8.3.3 Measurement

Check that the absorbance of each cell (6.4) is the same before and after each measurement.

Matched quartz cells with an optical path length of 10 mm (6.4) are generally suitable for the spectrometric measurement, but see 10.3.

Using the spectrometer (6.3), measure the optical absorbances of the clear supernatant crude smoke condensate solutions at 450 nm against a methanol blank.

1)  $1 g = 9,81 ms^{-2}$