INTERNATIONAL STANDARD



Second edition 1989-08-15

Hydraulic fluid power — Determination of characteristics of motors —

Part 2 :

Startability iTeh STANDARD PREVIEW

> standards iteh ai Transmissions hydrauliques – Détermination des caractéristiques des moteurs –

Partie 2 : Essai de démarrage

https://standards.iteh.ai/catalog/standards/sist/de8c2d5f-e744-4230-bcc6-7cec5bab3398/iso-4392-2-1989



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at VIEW least 75 % approval by the member bodies voting.

International Standard ISO 4392-2 was prepared by Technical Committee ISO/TC 131, *Fluid power systems.*

ISO 4392-2:1989

This second edition cancels and replaces the first edition (ISO 4392-2 ar1988) of which e744-4230-bcc6it constitutes a minor revision. 7cec5bab3398/iso-4392-2-1989

ISO 4392 will consist of the following parts, under the general title *Hydraulic fluid* power – Determination of characteristics of motors:

- Part 1: At constant low speed and at constant pressure
- Part 2: Startability
- Part 3: Slow speed running

Annexes A, B and C form an integral part of this part of ISO 4392. Annex D is for information only.

© ISO 1989

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization

Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Introduction

In hydraulic fluid power systems power is transmitted and controlled through a fluid under pressure within an enclosed circuit.

Hydraulic motors are units which transform hydraulic energy into mechanical energy, usually with a rotary output. Startability, the ability of a motor to start, is an important property of hydraulic motors, when used for specific applications.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 4392-2:1989 https://standards.iteh.ai/catalog/standards/sist/de8c2d5f-e744-4230-bcc6-7cec5bab3398/iso-4392-2-1989

iTeh STANDARD PREVIEW (standards.iteh.ai) This page intentionally left blank

ISO 4392-2:1989 https://standards.iteh.ai/catalog/standards/sist/de8c2d5f-e744-4230-bcc6-7cec5bab3398/iso-4392-2-1989

Hydraulic fluid power — Determination of characteristics of motors —

Part 2: Startability

1 Scope

This part of ISO 4392 specifies two test methods for determining the startability of rotary hydraulic motors. It describes two comparable methods of measurement, namely the constant torque method (see clause 6) and the constant pressure method (see clause 7). Since the results obtained by these two methods are equivalent no preference is given to either.

(standards.iteh.ai)

3.1 startability: The ability of a hydraulic motor to start against a stated load.

3.2 start at constant torque: That point at which there is an abrupt change in the slope of the angular displacement versus pressure characteristic, when the angular displacement of the motor shaft is measured between the motor and the load.

The accuracy of measurement is divided into three classes A, B and C, which are explained in annex B. https://standards.iteh.ai/catalog/standards/sixversus2pressure.4torque_(characteristic, when the angular 7cec5bab3398/iso-4392isplacement of the motor shaft is measured between the motor and the load.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 4392. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 4392 are encouraged to investigate the possibility of applying the most recent editions of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 3448 : 1975, Industrial liquid lubricants – ISO viscosity classification.

ISO 4391 : 1983, Hydraulic fluid power — Pumps, motors and integral transmissions — Parameter definitions and letter symbols.

ISO 5598 : 1985, Fluid power systems and components – Vocabulary.

3 Definitions

For the purposes of this part of ISO 4392, the definitions given in ISO 4391 and ISO 5598, and the following definitions, apply.

4 Symbols

4.1 The physical quantity letter symbols and their suffixes used in this part of ISO 4392 are fully explained either in ISO 4391 or annex A and are given in table 1.

Table	1	_	Sym	bols	and	units
-------	---	---	-----	------	-----	-------

Quantity	Symbol	Dimension ¹⁾	SI unit ²⁾				
Pressure, differential pressure	<i>p</i> , Δ <i>p</i>	ML-1T-2	Pa				
Torque	Т	ML ² T ⁻²	N∙m				
Instantaneous displacement	v	L3	m ³				
Time	t	Т	s				
Swept volume	V	L3	m ³				
1) $M = mass; L = length; T = time.$ 2) The practical units which may be used for the presentation of							

2) The practical units which may be used for the presentation of results are given in annex C.

4.2 The graphical symbols used in figure 1 are in accordance with ISO 1219.

5 Test installation

5.1 Hydraulic test circuit

5.1.1 An appropriate hydraulic test circuit similar to that shown in figure 1 shall be used.

NOTES

1 Although figure 1 illustrates a basic circuit to test a unidirectional motor, a similar, symmetrical, but suitably modified, circuit is acceptable for testing bidirectional motors.

2 An additional booster pump circuit may be necessary when testing piston-type motors.

3 The basic circuit shown in figure 1 does not incorporate all the safety devices necessary to protect against damage in the event of component failure. It is important that those responsible for carrying out the tests give due consideration to safeguarding both staff and equipment.

5.1.2 A fluid conditioning circuit shall be installed which provides the filtration necessary to protect the test motor and the other circuit components, and which will maintain the fluid temperature at the motor inlet at either 50 °C or 80 °C to within \pm 2 °C.

5.1.3 The hydraulic ports of the test motor shall be connected A with a confidence level of 95 %. to the hydraulic circuit in such a manner that the motor shaft rotation will oppose the torque loading device. (standar6.2.6) The torque levels shall be kept constant to ± 1 %.

5.1.4 The maximum test pressure shall not exceed that <u>A392-2:1989</u> recommended by the motor manufacturer. https://standards.iteh.ai/catalog/standards/st

5.2 Instrumentation

Measuring instruments shall be selected and installed which provide systematic errors which are consistent with the chosen class of measurement accuracy (see annex B).

6 Constant torque method

6.1 Test apparatus

6.1.1 A test rig shall be set up which makes use of the test circuit specified in 5.1.1 and which provides the equipment shown in figure 1 and described in 6.1.2 and 6.1.3.

6.1.2 A suitable torque loading device, either **12** which will allow limited rotation of the test motor shaft at start-up, e.g. a lever arm and adjustable mass at one end, or **14** which allows continuous opposing rotation by a controlled electrical variable torque loading device shall be provided.

6.1.3 A mechanical stop shall also be provided to prevent the torque loading device rotating the motor shaft in the reverse direction.

6.2 Test conditions

before commencing the test.

6.3.1 Adjust the back pressure on the motor outlet to a constant value (see 6.2.2).

6.2.1 The motor being tested shall be in thermal equilibrium

6.2.2 The constant outlet pressure shall be maintained at the

6.2.3 The rate of increase in inlet pressure per second shall be

less than or equal to 20 % of test pressure and shall not

6.2.4 The differential pressure across the motor shall be

reduced to less than 5 % of the maximum test pressure or

10 bar¹⁾ (1 MPa), whichever is the smaller, before embarking on

NOTE - This requirement is not applicable to motors for special ap-

6.2.5 The number of measurements at different shaft posi-

tions shall be greater than the minimum number necessary for the maximum starting pressure over one revolution to be found

level recommended by the motor manufacturer.

significantly influence the starting pressure.

every subsequent set of measurements.

plications, e.g. winch drives.

6.3.2 Gradually increase the inlet pressure until the motor starts to rotate (see 6.2.3). Simultaneously record the angular displacement of the motor shaft against inlet pressure.

6.3.3 Produce a graph of the recordings obtained in 6.3.2 and note the pressure at which the motor starts to rotate, i.e. the point at which there is an abrupt change in the slope of the characteristic (see 3.2).

6.3.4 Repeat the steps described in 6.3.2 and 6.3.3 at a number of different shaft positions (see 6.2.5).

6.3.5 Repeat the steps described in 6.3.2 to 6.3.4 at a number of different torque levels (see 6.2.6) in order that the characteristics over a representative range of starting conditions can be obtained.

6.3.6 For bidirectional motors, repeat the steps described in 6.3.2 to 6.3.5 in the reverse direction.

⁷cec5bab3398/iso-4392-2-1989

^{1) 1} bar = 10^5 Pa; 1 Pa = 1 N/m²

6.4 Expression of results

 $\ensuremath{\mathsf{NOTE}}$ — Refer to clause 4 for a fuller explanation of letter symbols and suffixes.

Calculate the minimum starting efficiency, $\eta_{hm,min}$, for each test torque level, using the following formulae:

$$\eta_{\rm hm,min} = rac{\Delta p_{
m i,mi}}{\Delta p_{
m e,max}}$$

or

$$h_{\rm hm,min} = \frac{\Delta p_{\rm g,mi}}{\Delta p_{\rm e,max}}$$

where

n

$$\Delta p_{\mathsf{i,mi}} = rac{2\pi}{V_{\mathsf{i}}} imes$$
 applied test torque;

$$\Delta p_{\rm g,mi} = rac{2\pi}{V_{\rm g}} imes$$
 applied test torque;

 $\Delta p_{\rm e,max}$ is the highest differential pressure, measured during the test, at a given test torque level.

7 Constant pressure method

7.1 Test apparatus

7.1.1 A test rig shall be set up which makes use of the test circlards/sist/de8c2d5f-e744-4230-bcc6 cuit in 5.1.1 and which provides the equipment shown in iso-4392-2-1989
 figure 1 and described in 7.1.2.
 7.3.7 For bidirectional motors, repeat the steps described

TANDAR

7.1.2 A suitable loading device (**11** and **12** or **13** and **14**) complying with the requirements of 6.1.2 shall be provided.

7.2 Test conditions

7.2.1 The motor being tested shall be in thermal equilibrium before commencing the test.

7.2.2 The constant outlet pressure shall be maintained at the level recommended by the motor manufacturer.

7.2.3 The rate of decrease of the test torque per second shall be less than or equal to 20 % of test torque and shall not significantly influence the starting torque.

7.2.4 The differential pressure across the motor shall be reduced by less than 5 % of the maximum test pressure or 10 bar (1 MPa), whichever is the smaller, before embarking on every subsequent set of measurements.

NOTE – This requirement is not applicable to motors for special applications, e.g. winch drives.

7.2.5 The number of measurements at different shaft positions at one torque level shall be sufficient for the minimum starting torque to be found with a confidence level of 95 %.

7.3 Test procedure

7.3.1 Adjust the back pressure on the motor outlet to a constant value (see 7.2.2).

7.3.2 Adjust the test torque of the torque loading device to a value just above the maximum theoretical torque of the motor at the appropriate test pressure.

7.3.3 Gradually increase the inlet pressure to the motor until the required test pressure is reached.

NOTE - If the test pressure is exceeded, decrease the pressure and repeat the step described in 7.3.3.

7.3.4 Decrease the load torque smoothly (see 7.2.3) until the motor starts to rotate. Simultaneously record the angular displacement of the motor shaft against torque.

7.3.5 Produce a graph of the recordings obtained in 7.3.4 and note the starting torque at which the motor starts to rotate, i.e. the point at which there is an abrupt change in slope of the characteristic (see 3.3).

Standards. 1.3.61 Repeat the steps described in 7.3.2 to 7.3.5 at a number of different pressure levels and shaft positions (see 7.2.5) in order that the characteristics over a representative range of the starting conditions can be obtained.

7.3.7 For bidirectional motors, repeat the steps described in 7.3.2 to 7.3.6 in the reverse direction.

7.4 Expression of results

KL

NOTE — Refer to clause 4 for a fuller explanation of letter symbols and suffixes.

Calculate the minimum starting torque efficiency, $\eta_{hm,min}$ for each test pressure, using the following formulae:

$$\eta_{\rm hm,min} = \frac{T_{\rm e,min}}{T_{\rm i,mi}}$$

or

$$\eta_{\rm hm,min} = \frac{T_{\rm e,min}}{T_{\rm g,mi}}$$

where

$$T_{i,mi} = \frac{1}{2\pi} \times V_i \times \text{applied test pressure};$$

$$T_{g,mi} = \frac{1}{2\pi} \times V_g \times \text{applied test pressure};$$

 $T_{e,min}$ is the lowest torque measured during the startability test at the given test pressure level.

8 Test report

8.1 General

All the relevant test data at every test pressure, and the information listed in 8.3, shall be recorded in a test report.

8.2 Presentation of test data

All test measurements and the results of the calculations derived from the measurements shall be presented in tabular form and, where appropriate, graphically.

8.3 Test data

The following test data shall be included in the test report:

a) a description of the test motor;

b) the test method used, i.e. constant torque method or constant pressure method;

c) the class of measurement accuracy used (see annex B);

e) a description of the test fluid;

f) the fluid viscosity (determined in accordance with ISO 3448);

g) the fluid temperature (see 5.1.2);

h) the outlet pressure (see 6.2.2 or 7.2.2);

i) the geometric swept volume, $V_{\rm g}$, or the derived swept volume, $V_{\rm i}$;

j) either, according to the test method used,

1) the test pressure level and related minimum and maximum starting torque over one shaft revolution at each pressure level,

or

2) the test torque level and related minimum and maximum starting pressures over one shaft revolution at each torque level;

k) the minimum starting efficiency, $\eta_{\rm hm,min}$ (see 6.4 or 7.4);

d) a description of the hydraulic test circuit and components: I) the direction of starting, viewed at end of the shaft

(standards.iteh.ai)

ISO 4392-2:1989 https://standards.iteh.ai/catalog/standards/sist/de8c2d5f-e744-4230-bcc6-7cec5bab3398/iso-4392-2-1989



14 Electrical torque load

Figure 1 – Typical hydraulic circuit – Constant torque test on unidirectional motor