



SLOVENSKI STANDARD
DSIST EN 301 908-10:2002
01-gYdhYa VYf-2002

9`Y_fca U[bYfbUnXfi y`^j cghfØ A 7 Ł]b`nUXYj Yj`nj Yn]`n`fUX]`g_]a`gdY_fca`fØFAŁ!
 6 UnbY`dcgHUY`f6 GŁ]b`i dcfUVb]ý_UcdfYa Ufl 9Ł`nUW] bc`ca fYj`Y`=AH!&\$\$\$`fYrY
 [YbYfUM]Y`!`%\$`"XY.`<Ufa cb]n]fUb]9B`nU`=AH!&\$\$\$ž: 8 A 5 #H 8 A 5 `fB 9 7 HŁž_]`nUYa U
 V]ghj YbY`nU H]j Y` `YbU` "&`X]fY`h] YF/ HH9

Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS) and User Equipment (UE) for IMT-2000 Third-Generation cellular networks; Part 10: Harmonized EN for IMT-2000 FDMA/TDMA (DECT) covering essential requirements of article 3.2 of the R&TTE Directive

Ta slovenski standard je istoveten z: EN 301 908-10 Version 1.1.1

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

DGIST EN 301 908-10:2002 **en**

ETSI EN 301 908-10 V1.1.1 (2002-01)

Candidate Harmonized European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Base Stations (BS) and User Equipment (UE) for
IMT-2000 Third-Generation cellular networks;
Part 10: Harmonized EN for IMT-2000,
FDMA/TDMA (DECT)
covering essential requirements
of article 3.2 of the R&TTE Directive**



Reference

DEN/DECT-A0175

Keywords3G, DECT, digital, generic, IMT-2000, radio,
regulation, testing**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
All rights reserved.

Contents

Intellectual Property Rights	10
Foreword.....	10
Introduction	12
1 Scope	14
2 References	14
3 Definitions and abbreviations.....	15
3.1 Definitions	15
3.2 Abbreviations	18
4 Technical requirements specifications	19
4.1 Environmental profile.....	19
4.2 Document layout	19
4.2.1 Test suites	19
4.2.2 Test groups.....	19
4.2.3 Test cases	20
4.3 Applicant's declaration	20
4.4 Applicability of essential test suites	20
4.4.1 Introduction.....	20
4.4.2 Equipment that includes only a DECT RF receiver	21
4.4.3 Equipment that includes a radio transmitter	21
4.4.4 CTAs.....	21
4.4.5 Equipment with a synchronization port	21
4.4.6 Equipment incorporating the IPEI (PPs only).....	21
4.4.7 All FP equipment.....	21
4.4.8 Equipment with combined FT and PT functionality.....	21
4.4.8.1 Introduction.....	21
4.4.8.2 Wireless Relay Station	21
4.4.8.3 Direct PP to PP communication	22
4.4.8.4 Distributed Communications.....	22
4.4.9 Provision of 2 Mbit/s services. Equipment that is capable of using 4-level and/or 8-level modulation	22
4.4.10 Dual mode handsets	22
4.5 Conformance requirements	22
4.5.1 General.....	22
4.5.2 Accuracy and stability of RF carriers	23
4.5.2.1 Definition of nominal position of RF carriers	23
4.5.2.2 Limits	23
4.5.2.3 Conformance	23
4.5.3 Accuracy and stability of timing parameters	23
4.5.3.1 Definitions.....	23
4.5.3.1.1 Slot structure.....	23
4.5.3.1.2 Definition of the position of p0	24
4.5.3.2 Limits	24
4.5.3.2.1 Reference timer accuracy and stability	24
4.5.3.2.2 RFP transmission jitter	25
4.5.3.2.3 PP reference timer synchronization	25
4.5.3.3 Conformance	25
4.5.4 Transmission burst.....	26
4.5.4.1 Definitions.....	26
4.5.4.1.1 Introduction	26
4.5.4.1.2 Physical packets.....	26
4.5.4.1.3 Transmitted power.....	26
4.5.4.1.4 Normal Transmitted Power (NTP)	26
4.5.4.1.5 Transmitter attack time.....	26
4.5.4.1.6 Transmitter release time	26

4.5.4.1.7	Minimum power	26
4.5.4.1.8	Maximum power	27
4.5.4.1.9	Maintenance of transmission after packet end.....	27
4.5.4.1.10	Transmitter idle power output	27
4.5.4.2	Limits	27
4.5.4.2.1	Transmitter attack time.....	27
4.5.4.2.2	Transmitter release time	27
4.5.4.2.3	Minimum power	27
4.5.4.2.4	Maximum power	27
4.5.4.2.5	Maintenance of transmission after packet end.....	27
4.5.4.2.6	Transmitter idle power output	27
4.5.4.3	Conformance.....	27
4.5.5	Transmitted power	28
4.5.5.1	Definitions.....	28
4.5.5.1.1	PP and RFP with an integral antenna	28
4.5.5.1.2	PP and RFP with external connections for all antennas	28
4.5.5.1.3	PP and RFP with both integral and external antennas	28
4.5.5.2	Limits	28
4.5.5.3	Conformance.....	28
4.5.6	RF carrier modulation.....	28
4.5.6.1	Definition	28
4.5.6.2	Limits	29
4.5.6.3	Conformance.....	29
4.5.7	Unwanted RF power radiation	29
4.5.7.1	General	29
4.5.7.2	Emissions due to modulation	29
4.5.7.2.1	Definition.....	29
4.5.7.2.2	Limits	30
4.5.7.2.3	Conformance	30
4.5.7.3	Emissions due to transmitter transients	30
4.5.7.3.1	Definition.....	30
4.5.7.3.2	Limits	30
4.5.7.3.3	Conformance	30
4.5.7.4	Emissions due to intermodulation	31
4.5.7.4.1	Definition.....	31
4.5.7.4.2	Limits	31
4.5.7.4.3	Conformance	31
4.5.7.5	Spurious emissions when allocated a transmit channel.....	31
4.5.7.5.1	Definition.....	31
4.5.7.5.2	Limits	31
4.5.7.5.3	Conformance	31
4.5.8	Radio receiver testing	31
4.5.8.1	Radio receiver sensitivity	31
4.5.8.1.1	Definition.....	31
4.5.8.1.2	Limits	32
4.5.8.1.3	Conformance	32
4.5.8.2	Radio receiver reference BER and FER.....	32
4.5.8.2.1	Definition.....	32
4.5.8.2.2	Limits	32
4.5.8.2.3	Conformance	32
4.5.8.3	Radio receiver interference performance	32
4.5.8.3.1	Definition.....	32
4.5.8.3.2	Limits	33
4.5.8.3.3	Conformance	33
4.5.8.4	Radio receiver blocking case 1: owing to signals occurring at the same time but on other frequencies	33
4.5.8.4.1	Definition.....	33
4.5.8.4.2	Limits	33
4.5.8.4.3	Conformance	34
4.5.8.5	Radio receiver blocking case 2: owing to signals occurring at a different time	34
4.5.8.5.1	Definition.....	34
4.5.8.5.2	Limits	34

4.5.8.5.3	Conformance	34
4.5.8.6	Receiver intermodulation performance	34
4.5.8.6.1	Definition.....	34
4.5.8.6.2	Limits	34
4.5.8.6.3	Conformance	34
4.5.8.7	Spurious emissions when the PP has no allocated transmit channel	34
4.5.8.7.1	Definition.....	34
4.5.8.7.2	Limits	35
4.5.8.7.3	Conformance	35
4.5.9	Intersystem synchronization (FP only)	35
4.5.9.1	Description	35
4.5.9.2	Wired synchronization ports	36
4.5.9.2.1	FP as a master	36
4.5.9.2.2	FP as a slave	36
4.5.9.3	GPS synchronization.....	37
4.5.9.3.1	FP with integrated Global Positioning System (GPS) synchronization.....	37
4.5.9.3.2	External GPS synchronization device	37
4.5.10	Equipment identity testing	38
4.5.10.1	PP	38
4.5.10.2	FP	38
4.5.11	Efficient use of the radio spectrum	38
4.5.11.1	Channel selection	38
4.5.11.2	Channel confirmation.....	38
4.5.11.2.1	For the PT.....	38
4.5.11.2.2	For the FT	38
4.5.11.3	Channel release	39
4.5.11.4	General	39
4.5.12	WRS testing	39
4.5.12.1	General requirements	39
4.5.12.2	Testing as a PP	39
4.5.12.3	Testing as an RFP	40
4.5.12.4	Additional requirements.....	40
4.5.12.5	Conformance.....	44
4.5.13	Requirements for PPs with direct PP to PP communication mode	44
4.5.13.1	General requirements	44
4.5.13.2	Setting the EUT in direct communications mode.....	44
4.5.13.3	When the EUT has not initiated a call.....	44
4.5.13.4	When the EUT initiates a call	45
4.5.13.5	Conformance.....	45
4.5.14	Distributed Communications	45
4.5.14.1	General requirements	45
4.5.14.2	Testing as a PP	45
4.5.14.3	Testing as an RFP	46
4.5.14.4	Conformance.....	46
4.5.15	Higher level modulation options.....	46
4.5.15.1	Requirements	46
4.5.15.2	Conformance.....	47
5	Testing for compliance with technical requirements.....	47
5.1	General test requirements	47
5.1.1	Test philosophy.....	47
5.1.2	Standard position	48
5.1.3	Test antenna of the LT.....	48
5.1.4	Substitution antenna.....	49
5.1.5	Test fixture.....	49
5.1.5.1	Description	49
5.1.5.2	Calibration of the test fixture for the measurement of transmitter characteristics.....	49
5.1.5.3	Calibration of the test fixture for the measurement of receiver characteristics	50
5.1.5.4	Mode of use.....	50
5.1.6	Equipment with a temporary or internal permanent antenna connector.....	51
5.1.6.1	General	51
5.1.6.2	Equipment with a temporary antenna connector	51

5.1.7	Lower Tester (LT)	51
5.1.7.1	Description	51
5.1.7.2	Connections between the EUT and the LT	52
5.1.7.3	Functions and abilities.....	52
5.1.7.4	Signal generation uncertainty	52
5.1.7.5	Modulated DECT-like carrier	53
5.1.7.6	CW interferers.....	53
5.1.7.7	DECT RF signal.....	53
5.1.7.8	Test modulation signals.....	53
5.1.8	Upper Tester (UT)	53
5.1.8.1	Description of the UT.....	53
5.1.8.2	The test standby mode.....	53
5.1.8.3	Test messages.....	54
5.1.8.4	Dummy setting when EUT is a RFP and it is in test stand-by mode.....	54
5.1.9	Description of the Lower Tester FT and PT	54
5.1.10	General test methods.....	54
5.1.10.1	General	54
5.1.10.2	Sampling the RF signal	55
5.1.10.2.1	Introduction	55
5.1.10.2.2	Sampling method.....	55
5.1.10.3	Determining the reference position	55
5.1.10.3.1	Case 1: EUTs that cannot transmit	55
5.1.10.3.2	Case 2: EUTs that can transmit	55
5.1.10.4	Bit error rate (BER) and Frame Error Ratio (FER) measurements	55
5.1.11	Test setup	56
5.1.11.1	General	56
5.1.11.2	Test setup 1	56
5.1.11.3	Test setup 2	56
5.1.11.4	Test setup 3	57
5.1.11.5	Test setup 4	57
5.1.11.6	Test setup 5	58
5.1.12	Test arrangements for intermodulation measurements	58
5.1.12.1	PT to PT arrangement	58
5.1.12.2	FT to FT arrangement	59
5.1.12.3	FT to PT arrangement	59
5.1.13	Test conditions, power supply and ambient temperatures	60
5.1.13.1	General	60
5.1.13.2	Nominal test conditions.....	60
5.1.13.3	Extreme test conditions	61
5.1.13.4	Test power source - general requirements.....	62
5.1.13.5	Nominal test power source.....	62
5.1.13.5.1	Mains voltage	62
5.1.13.5.2	Regulated lead acid battery power sources.....	62
5.1.13.5.3	Nickel cadmium battery.....	62
5.1.13.5.4	Other power sources	62
5.1.13.6	Extreme test power source	62
5.1.13.6.1	Mains voltage	62
5.1.13.6.2	Regulated lead acid battery power sources.....	62
5.1.13.6.3	Nickel cadmium battery.....	62
5.1.13.6.4	Other power sources	63
5.1.13.7	Testing of host connected equipment and plug-in cards	63
5.1.13.7.1	Permitted approaches.....	63
5.1.13.7.2	Alternative A: composite equipment	63
5.1.13.7.3	Alternative B: use of a test jig and three hosts	63
5.2	Interpretation of the measurement results	64
5.3	Essential radio test suites.....	64
5.3.1	General.....	64
5.3.2	Accuracy and stability of RF carriers	65
5.3.2.1	Test environment.....	65
5.3.2.2	Method of measurement.....	65
5.3.2.3	Verdict criteria when the EUT is a RFP.....	65
5.3.2.4	Verdict criteria when the EUT is a PP	66