



Designation: **D5347 – 95 (Reapproved 2012) D5347 – 19**

Standard Test Method for Determination of the Ash Content of Fats and Oils¹

This standard is issued under the fixed designation D5347; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers the determination of the ash content of fats and oils used in the softening and stuffing of leather and in the manufacture of fatliquors and other softening and stuffing compounds. This test method was derived from Test Method **D1951**.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate ~~safety~~ safety, health, and ~~health~~ environmental practices and determine the applicability of regulatory limitations prior to use.* See Section 5 for specific hazard statements.

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

D1951 Test Method for Ash in Drying Oils and Fatty Acids (Withdrawn 2003)³

3. Significance and Use

3.1 This test method is intended to determine the ash content of fats and oils used in the softening and stuffing of leather, as well as those used in the manufacture of products for such purpose. The ash content of fats and oils is measured for the purpose of quality assurance.

4. Apparatus

4.1 *Crucible*, porcelain or high-silica glass (**Note 1**), 50-mL capacity.

NOTE 1—Platinum is not recommended. Boiled oils or oils contaminated with driers containing lead may ruin platinum by alloy formation.

4.2 *Electric Muffle Furnace*.

4.3 *Desiccator*, containing an efficient desiccant. Anhydrous calcium sulfate (CaSO_4), phosphorus pentoxide (P_2O_5) or concentrated sulfuric acid (H_2SO_4 , sp gr 1.84) are satisfactory. (**Warning**—See 5.1 and 5.2 for specific hazards.) A silica gel desiccant can also be used as a safe alternative.

NOTE 2—Magnesium perchlorate and barium perchlorate are also efficient desiccators and were previously listed in this section. However because of their explosive danger, and the availability of other safer materials, the recommendation for their use has been discontinued.

4.4 *Oil Sample Bottle*, 4-oz (120-mL).

4.5 *Triangle*, Nichrome or clay.

5. Hazards

5.1 *Phosphorus Pentoxide* is a strong oxidizer and reacts violently with water, reducing agents, and organic matter. Causes burns. Avoid contact with skin or eyes, or clothing, or inhalation as dust. Refer to supplier's Material Safety Data Sheet.

¹ This test method is under the jurisdiction of ASTM Committee D31 on Leather and is the direct responsibility of Subcommittee D31.08 on Fats and Oils. This test method was developed in cooperation with the American Leather Chemists Assn. (Method H 27-1957).

Current edition approved April 1, 2012; April 1, 2019. Published April 2012; May 2019. Originally approved in 1993. Last previous edition approved in 2006 as D5347 – 95(2006); R12. DOI: 10.1520/D5347-95R12.10.1520/D5347-19.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.