

TECHNICAL REPORT



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

**Specification for radio disturbance and immunity measuring apparatus and methods –
Part 3: CISPR technical reports**

Document Preview

[CISPR TR 16-3:2020](#)

<https://standards.iteh.ai/catalog/standards/iec/3bf654d1-bc31-45c3-8833-f7394fb0a3b6/cispr-tr-16-3-2020>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

International
Standards
IEC Standards
Document Preview

[CISPR TR 16-3:2020](https://standards.iteh.ai/catalog/standards/iec/3bf654d1-bc31-45c3-8833-f7394fb0a3b6/cispr-tr-16-3-2020)

<https://standards.iteh.ai/catalog/standards/iec/3bf654d1-bc31-45c3-8833-f7394fb0a3b6/cispr-tr-16-3-2020>

TECHNICAL REPORT



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

**Specification for radio disturbance and immunity measuring apparatus and methods –
Part 3: CISPR technical reports**

Document Preview

[CISPR TR 16-3:2020](https://standards.iteh.ai/catalog/standards/iec/3bf654d1-bc31-45c3-8833-f7394fb0a3b6/cispr-tr-16-3-2020)

<https://standards.iteh.ai/catalog/standards/iec/3bf654d1-bc31-45c3-8833-f7394fb0a3b6/cispr-tr-16-3-2020>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.100.10; 33.100.20

ISBN 978-2-8322-8985-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	16
1 Scope.....	18
2 Normative references	18
3 Terms, definitions and abbreviated terms	19
3.1 Terms and definitions.....	19
3.2 Abbreviated terms.....	23
4 Technical reports.....	24
4.1 Correlation between measurements made with apparatus having characteristics differing from CISPR characteristics and measurements made with CISPR apparatus	24
4.1.1 General	24
4.1.2 Critical interference-measuring instrument parameters	24
4.1.3 Impulse interference – correlation factors	26
4.1.4 Random noise	28
4.1.5 The root mean square (RMS) detector	28
4.1.6 Discussion.....	28
4.1.7 Application to typical noise sources	28
4.1.8 Conclusions.....	29
4.2 Interference simulators	30
4.2.1 General	30
4.2.2 Types of interference signals.....	30
4.2.3 Circuits for simulating broadband interference.....	31
4.3 Relationship between limits for open-area test site and the reverberation chamber	35
4.3.1 General	35
4.3.2 Correlation between measurement results of the reverberation chamber and OATS.....	35
4.3.3 Limits for use with the reverberation chamber method	36
4.3.4 Procedure for the determination of the reverberation chamber limit	36
4.4 Characterization and classification of the asymmetrical disturbance source induced in telephone subscriber lines by AM broadcasting transmitters in the LW, MW and SW bands	37
4.4.1 General	37
4.4.2 Experimental characterization.....	37
4.4.3 Prediction models and classification	47
4.4.4 Characterization of the immunity-test disturbance source	51
4.5 Predictability of radiation in vertical directions at frequencies above 30 MHz	58
4.5.1 Summary	58
4.5.2 Range of application.....	59
4.5.3 General	59
4.5.4 Method used to calculate field patterns in the vertical plane	61
4.5.5 Limitations of predictability of radiation at elevated angles.....	62
4.5.6 Differences between the fields over a real ground and the fields over a perfect conductor.....	90
4.5.7 Uncertainty ranges	96
4.5.8 Conclusions.....	98

4.6	The predictability of radiation in vertical directions at frequencies up to 30 MHz	99
4.6.1	Range of application	99
4.6.2	General	100
4.6.3	Method of calculation of the vertical radiation patterns.....	101
4.6.4	The source models	101
4.6.5	Electrical constants of the ground	103
4.6.6	Predictability of radiation in vertical directions	103
4.6.7	Conclusions.....	111
4.6.8	Figures associated with predictability of radiation in vertical directions	112
4.7	Correlation between amplitude probability distribution (APD) characteristics of disturbance and performance of digital communication systems.....	147
4.7.1	General	147
4.7.2	Influence on a wireless LAN system	147
4.7.3	Influence on a Bluetooth system	150
4.7.4	Influence on a W-CDMA system	154
4.7.5	Influence on Personal Handy Phone System (PHS)	157
4.7.6	Quantitative correlation between noise parameters and system performance	161
4.7.7	Quantitative correlation between noise parameters of repetition pulse and system performance of PHS and W-CDMA (BER)	164
4.8	Background material on the definition of the RMS-average weighting detector for measuring receivers.....	167
4.8.1	General – purpose of weighted measurement of disturbance	167
4.8.2	General principle of weighting – the CISPR quasi-peak detector.....	168
4.8.3	Other detectors defined in CISPR 16-1-1	168
4.8.4	Procedures for measuring pulse weighting characteristics of digital radiocommunications services	169
4.8.5	Theoretical studies	172
4.8.6	Experimental results	174
4.8.7	Effects of spread-spectrum clock interference on wideband radiocommunication signal reception	192
4.8.8	Analysis of the various weighting characteristics and proposal of a weighting detector	193
4.8.9	Properties of the RMS-average weighting detector	195
4.9	Common mode absorption devices (CMAD)	197
4.9.1	General	197
4.9.2	CMAD as a two-port device	199
4.9.3	Measurement of CMAD.....	203
4.10	Background on the definition of the FFT-based receiver.....	213
4.10.1	General	213
4.10.2	Tuned selective voltmeters and spectrum analyzers	214
4.10.3	General principle of a tuned selective voltmeter.....	214
4.10.4	FFT-based receivers – digital signal processing	215
4.10.5	Measurement errors specific to FFT processing.....	219
4.10.6	FFT-based receivers – examples	221
4.11	Parameters of signals at telecommunication ports.....	234
4.11.1	General	234
4.11.2	Estimation of common mode disturbance levels.....	235
4.12	Background on CDNE equipment and measurement method.....	236

4.12.1	General	236
4.12.2	Historical overview	237
4.12.3	From CDN to CDNE	241
4.13	Background on LLAS, validation and measurement method	244
4.13.1	General	244
4.13.2	Historical overview	244
4.13.3	Models and equations for the LLAS method	245
5	Background and history of CISPR	245
5.1	The history of CISPR	245
5.1.1	The early years: 1934-1984	245
5.1.2	The division of work	247
5.1.3	The computer years: 1984 to 1998	248
5.1.4	The people in CISPR	248
5.2	Historical background to the method of measurement of the interference power produced by electrical household and similar appliances in the VHF range	249
5.2.1	Historical detail	249
5.2.2	Development of the method	250
Annex A (informative)	Derivation of the formula	252
Annex B (informative)	The field-strength distribution	256
B.1	General	256
B.2	H_O -field expressions	256
B.3	H_i field expressions	258
B.4	E_O -field expressions	259
Annex C (informative)	The induced asymmetrical open-circuit voltage distribution	260
C.1	General	260
C.2	H -field-based relations	260
C.3	E -field-based relations	262
Annex D (informative)	The outlet-voltage distribution	263
D.1	General	263
D.2	H -field-based relations	263
D.3	E -field-based relations	264
Annex E (informative)	Some mathematical relations	265
E.1	General	265
E.2	The error function	265
E.3	Application to the lognormal distribution	266
Annex F (informative)	Harmonic fields radiated at elevated angles from 27 MHz ISM equipment over real ground	267
Annex G (informative)	Models and equations associated with the LLAS method	273
G.1	General	273
G.2	Response of an LAS to a magnetic field dipole	273
G.2.1	Magnetic field strength model of a disturbance source	273
G.2.2	Response of an LAS to a magnetic field dipole	274
G.2.3	Sensitivity of an LLAS for different diameters	278
G.2.4	Limitation of application of the relative sensitivity curves	279
G.3	Response of LLAS to the LLAS verification dipole	280
G.3.1	Relation of LLA current and voltage applied to the LLAS verification dipole	280

G.3.2	Calculation of mutual inductance: the original method	281
G.3.3	Calculation of mutual inductance: the improved method.....	281
G.3.4	Derivation of the equation for the reference validation factor	281
G.3.5	Replication of the original version of the reference validation factor.....	284
G.3.6	Calculation of the improved reference validation factor.....	284
G.3.7	NEC2 method	286
G.4	Magnetic field strength of a magnetic field dipole above a ground plane	287
G.4.1	Model	287
G.4.2	Replication of Figure C.10	288
G.4.3	Conversion factors for calculating magnetic field strength at other distances	290
G.5	LLAS validation criterion	291
Bibliography.....		292
Figure 1	– Relative response of various detectors to impulse interference	25
Figure 2	– Pulse rectification coefficient $P(\alpha)$	26
Figure 3	– Pulse repetition frequency.....	27
Figure 4	– Block diagram and waveforms of a simulator generating noise bursts	33
Figure 5	– Block diagram of a simulator generating noise bursts according to the pulse principle.....	34
Figure 6	– Details of a typical output stage	35
Figure 7	– Scatter plot of the measured outdoor magnetic field strength H_O (dB μ A/m) versus the calculated outdoor magnetic field strength H_C dB(μ A/m)	39
Figure 8	– Measured outdoor magnetic versus distance, and probability of the building- effect parameter	40
Figure 9	– Normal probability plot of the building-effect parameter A_b dB.....	41
Figure 10	– Scatter plot of the outdoor antenna factor G_O dB(Ω m) versus the indoor antenna factor G_i	42
Figure 11	– Normal probability plots of the antenna factors.....	43
Figure 12	– Normal probability plot of the equivalent asymmetrical resistance R_a dB(Ω)	46
Figure 13	– Examples of the frequency dependence of some parameters	47
Figure 14	– Example of the frequency histogram $\Delta N(E_O, \Delta E_O)$	52
Figure 15	– Example of $n_m(E_O)$, i.e. the distribution of the outlets experiencing a maximum field strength E_O resulting from a given number of transmitters in (or near) the respective geographical region	53
Figure 16	– Example of the number of outlets with an induced asymmetrical open- circuit voltage $U_L \leq U_h \leq U_{max} = 79$ V (see Table 10)	55
Figure 17	– Examples of number (left-hand scale) and relative number (right-hand scale) of outlets with $U_L \leq U_h \leq U_{max}$	56
Figure 18	– Vertical polar patterns of horizontally polarized E_x field strengths emitted around small vertical loop (horizontal magnetic dipole) over three different types of real ground	64
Figure 19	– Height scan patterns of vertically oriented E_z field strengths emitted from small vertical loop (horizontal magnetic dipole) over three different types of real ground	64
Figure 20	– Vertical polar patterns of horizontally polarized E_x field strengths emitted around small vertical loop (horizontal magnetic dipole), over three different types of real ground	66

Figure 21 – Vertical polar patterns of vertically oriented E_z field strengths emitted around small vertical loop (horizontal magnetic dipole) over three different types of real ground	66
Figure 22 – Height scan patterns of vertically oriented E_z field strengths emitted at 1 000 MHz from the small vertical loop (horizontal magnetic dipole), at horizontal distance of 10 m, 30 m and 300 m in the Z-X plane over three different types of real ground	67
Figure 23 – Vertical polar patterns of horizontally polarized E_x and vertically oriented E_z field strengths emitted around small horizontal electric dipole, in Y-Z and Z-X planes respectively	69
Figure 24 – Height scan patterns of horizontally polarized E_x field strengths emitted from small horizontal electric dipole	69
Figure 25 – Vertical polar patterns of horizontally polarized E_x and vertically oriented E_z field strengths emitted around small horizontal electric dipole in Y-Z and Z-X planes respectively	72
Figure 26 – Height scan patterns of horizontally polarized E_x field strengths emitted small horizontal electric dipole	72
Figure 27 – Vertical polar patterns of horizontally polarized E_x and vertically oriented E_z field strengths emitted around small vertical loop (horizontal magnetic dipole) in Y-Z and Z-X planes respectively	73
Figure 28 – Height scan patterns of vertically oriented E_z and horizontally oriented E_x field strengths emitted from small vertical loop (horizontal magnetic dipole).....	73
Figure 29 – Vertical polar patterns of vertically oriented E_z and horizontally oriented E_x field strengths emitted around small vertical electric dipole	76
Figure 30 – Height scan patterns of vertically oriented E_z and horizontally oriented E_x field strengths emitted from small vertical electric dipole.....	76
Figure 31 – Vertical polar patterns of horizontally polarized E_x and vertically oriented E_z field strengths emitted around small vertical loop (horizontal magnetic dipole) in Y-Z and Z-X planes respectively	77
Figure 32 – Height scan patterns of vertically oriented E_z and horizontally oriented E_x field strengths emitted from small vertical loop (horizontal magnetic dipole).....	77
Figure 33 – Vertical polar patterns of horizontally polarized E -field strength emitted around small horizontal loop (vertical magnetic dipole)	78
Figure 34 – Height scan patterns of horizontally polarized E -field strength emitted from small horizontal loop (vertical magnetic dipole)	78
Figure 35 – Vertical polar patterns of vertically oriented E_z and horizontally oriented E_x field strengths emitted around small vertical electric dipole	81
Figure 36 – Height scan patterns of vertically oriented E_z and horizontally oriented E_x field strengths emitted from the small vertical electric dipole	81
Figure 37 – Vertical polar patterns of horizontally polarized E_x and vertically oriented E_z field strengths emitted around small vertical loop (horizontal magnetic dipole) in Y-Z and Z-X planes respectively	82
Figure 38 – Height scan patterns of vertically oriented E_z and horizontally oriented E_x field strengths emitted from small vertical loop (horizontal magnetic dipole).....	82
Figure 39 – Vertical polar patterns of horizontally polarized E -field strength emitted around small horizontal loop (vertical magnetic dipole)	83
Figure 40 – Height scan patterns of horizontally polarized E -field strength emitted from small horizontal loop (vertical magnetic dipole)	83
Figure 41 – Vertical polar patterns of horizontally polarized E -field strength emitted around the small horizontal loop (vertical magnetic dipole)	86
Figure 42 – Height scan patterns of horizontally polarized E -field strength emitted from small horizontal loop (vertical magnetic dipole).....	86

Figure 43 – Height scan patterns of horizontally polarized E -field strength emitted from small horizontal loop (vertical magnetic dipole).....	90
Figure 44 – Height scan patterns of the vertical component of the E -fields emitted from a small vertical electric dipole.....	93
Figure 45 – Height scan patterns of the vertical component of the E -fields emitted from a small vertical electric dipole.....	93
Figure 46 – Height scan patterns of the horizontally polarized E -fields emitted in the vertical plane normal to the axis of a small horizontal electric dipole.....	95
Figure 47 – Height scan patterns of the horizontally polarized E -fields emitted in the vertical plane normal to the axis of a small horizontal electric dipole.....	95
Figure 48 – Ranges of uncertainties in the predictability of radiation in vertical directions from electrically small sources located at a height of 1 m or 2 m above ground.....	97
Figure 49 – Ranges of uncertainties in the predictability of radiation in vertical directions from electrically small sources located at a height of 1 m or 2 m above ground.....	97
Figure 50 – Ranges of uncertainties in the predictability of radiation in vertical directions from electrically small sources located at a height of 1 m or 2 m above ground.....	98
Figure 51 – Geometry of the small vertical electric dipole model.....	102
Figure 52 – Geometry of the small horizontal electrical dipole model.....	102
Figure 53 – Geometry of the small horizontal magnetic dipole model (small vertical loop).....	102
Figure 54 – Geometry of the small vertical magnetic dipole model (small horizontal loop).....	102
Figure 55 – Ranges of errors in the predictability of radiation in vertical directions from electrically small sources located close to the ground, based on measurements of the horizontally oriented H -field near ground at a distance of 30 m from the sources.....	110
Figure 56 – Ranges of errors in the predictability of radiation in vertical directions from electrically small sources located close to the ground, based on measurements of the horizontally oriented H -field at the ground supplemented with measurements of the vertically oriented H -field in a height scan up to 6 m at a distance of 30 m from the sources.....	111
Figure 57 – Vertical radiation patterns of horizontally oriented H -fields emitted by a small vertical electric dipole located close to the ground.....	113
Figure 58 – Vertical radiation patterns of horizontally oriented H -fields emitted by a small vertical electric dipole located close to the ground.....	113
Figure 59 – Vertical radiation patterns of E -fields emitted by a small vertical electric dipole located close to the ground.....	114
Figure 60 – Vertical radiation patterns of the E -fields emitted by a small vertical electric dipole located close to the ground.....	114
Figure 61 – Vertical radiation patterns of the H -fields emitted by a small horizontal electric dipole located close to the ground.....	116
Figure 62 – Influence of a wide range of values of the electrical constants of the ground on the vertical radiation patterns of the horizontally oriented H -fields emitted by a small horizontal electric dipole located close to the ground.....	116
Figure 63 – Vertical radiation patterns of the horizontally oriented H -fields emitted by a small horizontal electric dipole located close to the ground.....	117
Figure 64 – Vertical radiation patterns of the E -fields emitted by a small horizontal electric dipole located close to the ground.....	117

Figure 65 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	118
Figure 66 – Vertical radiation patterns of <i>H</i> -fields emitted by small horizontal magnetic dipole (vertical loop) located close to ground	118
Figure 67 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	119
Figure 68 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	119
Figure 69 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	120
Figure 70 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	120
Figure 71 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	122
Figure 72 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	122
Figure 73 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	123
Figure 74 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	123
Figure 75 – Vertical radiation pattern of the <i>E</i> -field emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	124
Figure 76 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	124
Figure 77 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small vertical electric dipole located close to the ground	125
Figure 78 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	125
Figure 79 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	126
Figure 80 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	126
Figure 81 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	127
Figure 82 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	127
Figure 83 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	129
Figure 84 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	129
Figure 85 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	130
Figure 86 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	130
Figure 87 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	131
Figure 88 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	131
Figure 89 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	132

Figure 90 – Vertical radiation patterns of the H -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground 132

Figure 91 – Vertical radiation patterns of the H -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground 133

Figure 92 – Vertical radiation patterns of the E -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground 133

Figure 93 – Vertical radiation patterns of the horizontally oriented H -fields emitted by a small vertical electric dipole located close to the ground 134

Figure 94 – Vertical radiation patterns of the E -fields emitted by a small vertical electric dipole located close to the ground 134

Figure 95 – Vertical radiation patterns of the E -fields emitted by a small vertical electric dipole located close to the ground 136

Figure 96 – Vertical radiation patterns of the H -fields emitted by a small horizontal electric dipole located close to the ground 136

Figure 97 – Vertical radiation patterns of the E -fields emitted by a small horizontal electric dipole located close to the ground 137

Figure 98 – Vertical radiation patterns of the E -fields emitted by a small horizontal electric dipole located close to the ground 137

Figure 99 – Vertical radiation patterns of the H -field emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground 139

Figure 100 – Vertical radiation patterns of the vertically polarized E -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground 139

Figure 101 – Vertical radiation patterns of the H -field emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground 140

Figure 102 – Vertical radiation patterns of the E -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground 140

Figure 103 – Vertical radiation patterns of the horizontally oriented H -fields emitted by a small vertical electric dipole located close to the ground 141

Figure 104 – Vertical radiation patterns of the vertically polarized E -fields emitted by a small vertical electric dipole located close to the ground 141

Figure 105 – Vertical radiation patterns of the H -fields emitted by a small horizontal electric dipole located close to the ground 142

Figure 106 – Vertical radiation patterns of the horizontally oriented H -fields emitted by a small horizontal electric dipole located close to the ground 142

Figure 107 – Influence of a wide range of values of the electrical constants of the ground on the vertical radiation patterns of the horizontally oriented H -fields emitted by a small horizontal electric dipole located close to the ground 143

Figure 108 – Vertical radiation patterns of the vertically polarized E -fields emitted by a small horizontal electric dipole located close to the ground 143

Figure 109 – Vertical radiation patterns of the H -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground 145

Figure 110 – Vertical radiation patterns of the vertically polarized E -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground 145

Figure 111 – Vertical radiation patterns of the H -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground 146

Figure 112 – Vertical radiation patterns of the E -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground 146

Figure 113 – Set-up for measuring communication quality degradation of a wireless LAN .. 147

Figure 114 – APD characteristics of disturbance 149

Figure 115 – Wireless LAN throughput influenced by noise 150

Figure 116 – Set-up for measuring the communication quality degradation of Bluetooth	151
Figure 117 – APD of disturbance of actual MWO (2 441MHz)	151
Figure 118 – APD characteristics of disturbance (2 460 MHz).....	152
Figure 119 – Throughput of Bluetooth influenced by noise	154
Figure 120 – Set-up for measuring the BER of W-CDMA.....	155
Figure 121 – APD characteristics of disturbance	156
Figure 122 – BER of W-CDMA caused by radiation noise	157
Figure 123 – Set-up for measuring the PHS throughput	158
Figure 124 – Set-up for measuring the BER of PHS	158
Figure 125 – APD characteristics of disturbance	159
Figure 126 – PHS throughput caused by radiation	160
Figure 127 – BER of PHS caused by radiation noise.....	161
Figure 128 – Correlation of the disturbance voltages with the system performance (C/N_0).....	162
Figure 129 – Correlation of the disturbance voltages with the system performance.....	162
Figure 130 – Correlation of the disturbance voltages with the system performance.....	163
Figure 131 – Correlation of the disturbance voltages with the system performance (C/N_0).....	163
Figure 132 – Correlation of the disturbance voltages with the system performance (C/N_0).....	164
Figure 133 – Experimental set-up for measuring communication quality degradation of a PHS or W-CDMA	164
Figure 134 – Simulation set-up for estimating communication quality degradation of a PHS or W-CDMA	165
Figure 135 – APD of pulse disturbance	165
Figure 136 – BER degradation of PHS and W-CDMA caused by repetition pulse (Carrier power, –35 dBm).....	166
Figure 137 – Evaluation method of the correlation between BER and APD.....	166
Figure 138 – Correlation between measured ΔL_{BER} and ΔL_{APD}	167
Figure 139 – Correlation between measured p_{BER} and p_{APD}	167
Figure 140 – Weighting curves of quasi-peak measuring receivers for the different frequency ranges as defined in CISPR 16-1-1.....	168
Figure 141 – Weighting curves for peak, quasi-peak, RMS and linear average detectors for CISPR bands C and D.....	169
Figure 142 – Test setup for the measurement of the pulse weighting characteristics of a digital radiocommunication system.....	170
Figure 143 – Example of an interference spectrum: pulse modulated carrier with a pulse duration of 0,2 μ s and a PRF < 10 kHz	171
Figure 144 – The RMS and peak levels for constant BEP for three $K = 3$, convolutional codes of different rate.....	173
Figure 145 – The RMS and peak levels for constant BEP for two rate $\frac{1}{2}$, convolutional code	174
Figure 146 – Test setup for the measurement of weighting curves for Digital Radio Mondiale (DRM).....	176
Figure 147 – Weighting characteristics for DRM signals for various pulse widths of the pulse-modulated carrier	177

Figure 148 – Weighting characteristics for DRM protection level 0: average of results for two receivers	178
Figure 149 – Weighting characteristics for DRM protection level 1: average of results for two receivers	178
Figure 150 – Weighting characteristics for DVB-T with 64 QAM 2k, <i>CR</i> 3/4 (as used in France and UK)	180
Figure 151 – Weighting characteristics for DVB-T with 64 QAM 8k, <i>CR</i> 3/4 (as used in Spain).....	181
Figure 152 – Weighting characteristics for DVB-T with 16 QAM 8k, <i>CR</i> 2/3 (as used in Germany).....	181
Figure 153 – Average weighting characteristics of 6 receiver types for DVB-T with 16QAM	182
Figure 154 – Average weighting characteristics of 6 receiver types for DVB-T with 64QAM	182
Figure 155 – Weighting characteristics for DAB (signal level -71 dBm) with a flat response down to approximately 1 kHz	183
Figure 156 – Weighting characteristics for DAB: average of two different commercial receiver types	184
Figure 157 – Weighting characteristics for TETRA (signal level – 80 dBm) for a code rate of 1	185
Figure 158 – Weighting characteristics for RBER 1b of GSM (signal level –90 dBm).....	186
Figure 159 – Weighting characteristics for RBER 2 of GSM	186
Figure 160 – Carrier-to-interference improvements with decreasing PRF in dB computed for GSM using COSSAP	187
Figure 161 – RMS and quasi-peak values of pulse level for constant effect on FM radio reception	187
Figure 162 – Weighting characteristics for RBER 1b of GSM (signal level –90 dBm).....	188
Figure 163 – Weighting characteristics for DECT (signal level –83 dBm)	189
Figure 164 – Weighting characteristics for IS-95 (signal level -97 dBm) with comparatively high immunity to interference	190
Figure 165 – Weighting characteristics for J-STD 008 (signal level –97 dBm)	190
Figure 166 – Weighting characteristics for the Frame Error Ratio (FER) of CDMA2000 (measured at a receive signal level of –112 dBm) for a low data rate of 9,6 kb/s.....	191
Figure 167 – Weighting characteristics for the Frame Error Ratio (FER) of CDMA2000 (measured at a receive signal level of –106 dBm) for two different data rates (9,6 kb/s and 76,8 kb/s).....	191
Figure 168 – The proposed RMS-average detector for CISPR Bands C and D with a corner frequency of 100 Hz.....	194
Figure 169 – RMS-average detector function by using an RMS detector followed by a linear average detector and peak reading	194
Figure 170 – RMS-average weighting functions for CISPR Bands A, B, C/D and E for the shortest pulse widths allowed by the measurement bandwidths	195
Figure 171 – Shift of the RMS-average weighting function for CISPR band C/D by using a bandwidth of 1 MHz instead of 120 kHz, if the shortest possible pulse widths are applied.....	196
Figure 172 – Example of a simple EUT model.....	198
Figure 173 – Representation of a CMAD as a two-port device.....	199
Figure 174 – Conformal mapping between <i>z</i> -plane and <i>f</i> -plane.....	202

Figure 175 – Conversion from 50 Ω coaxial system to the geometry of the two-port device-under-test..... 204

Figure 176 – Basic model for the TRL calibration..... 205

Figure 177 – The four calibration configurations necessary for the TRL calibration 206

Figure 178 – Measurement of CMAD characteristics..... 210

Figure 179 – Preliminary measurements of the test set-up..... 212

Figure 180 – Position of the reference planes for the measurement with SOLT calibration and $ABCD$ transformation to Z_{ref} level..... 213

Figure 181 – Superheterodyne EMI receiver 215

Figure 182 – An example spectrogram $Z[m,k]$ 217

Figure 183 – Sidelobe effect due to the finite length of window 219

Figure 184 – Measurement error for a single pulse 220

Figure 185 – IF signal for different overlapping factors for the same sequence of pulses..... 221

Figure 186 – FFT-based baseband system 222

Figure 187 – Real-time FFT-based measuring instrument..... 223

Figure 188 – Digital down-converter..... 223

Figure 189 – Short time fast Fourier transform – An example of implementation 224

Figure 190 – Floating-point analogue-to-digital conversion 224

Figure 191 – Example of a 120 kHz Gaussian filter..... 225

Figure 192 – Essential parts of an FFT-based heterodyne receiver..... 226

Figure 193 – Dynamic range for broadband emission as measured with the peak detector 228

Figure 194 – Set-up of FFT-based system type 2..... 228

Figure 195 – FFT Software (“FFTEmi”) screen shot..... 231

Figure 196 – Example of pulse generator measurement with antenna..... 232

Figure 197 – Radiated emission measurement of a motor – peak detector..... 232

Figure 198 – Angular characterization of a PC..... 233

Figure 199 – Example FFT IF analysis display..... 234

Figure 200 – Equivalent radiated measurement methods (30 MHz to 300 MHz)..... 238

Figure 201 – Measured relationship between field strength E_Z and CM current I_{CM} for various termination resistances R 238

Figure 202 – Modelled relationship between field strength E_Z and CM current I_{CM} using EUT height 0,8 m, measurement distance 3 m, receive antenna height 1 m..... 240

Figure 203 – Limit for the terminal voltage at the CDN 240

Figure 204 – Results of a Philips 11-lab internal CDN RRT using an artificial class 1 EUT – expanded uncertainty nearly 10 dB 242

Figure 205 – Block diagram for CDNE-measurement method..... 243

Figure A.1 – Example plot using the expression $P_t + G = P_q + 2$ 253

Figure A.2 – Examples of a number of microwaves measured for P_q and P_t 255

Figure B.1 – Definition of the ring-shaped area round the transmitter T 257

Figure C.1 – The permissible ranges of U_h and G are within the polygon $\{G_L, U_a\}$, $\{G_L, U_b\}$, $\{G_U, U_d\}$, $\{G_U, U_c\}$ and $\{G_L, U_a\}$. For the given value U_L the double-shaded area represents $pr\{U_h \geq U_L\}$ 261