

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Industrial communication networks – Fieldbus specifications –
Part 5-23: Application layer service definition – Type 23 elements**

**Réseaux de communication industriels – Spécifications des bus de terrain –
Partie 5-23: Définition des services de la couche application – Éléments de
type 23**





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online, and once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC online collection - oc.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 000 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.



INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Industrial communication networks – Fieldbus specifications –
Part 5-23: Application layer service definition – Type 23 elements**

**Réseaux de communication industriels – Spécifications des bus de terrain –
Partie 5-23: Définition des services de la couche application – Éléments de
type 23**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 25.040.40; 35.100.70; 35.110

ISBN 978-2-8322-9269-3

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
1.1 General.....	8
1.2 Specifications	9
1.3 Conformance	9
2 Normative references	9
3 Terms, definitions, symbols, abbreviated terms and conventions	10
3.1 Referenced terms and definitions.....	10
3.1.1 ISO/IEC 7498-1 terms.....	10
3.1.2 ISO/IEC 8822 terms.....	10
3.1.3 ISO/IEC 9545 terms.....	10
3.1.4 ISO/IEC 8824-1 terms.....	11
3.1.5 IEC 61158-1 terms.....	11
3.2 Additional Type 23 terms and definitions.....	11
3.3 Symbols and abbreviated terms	13
3.4 Conventions.....	14
3.4.1 General conventions.....	14
3.4.2 Conventions for class definitions.....	15
3.4.3 Conventions for service definitions.....	16
4 Concept.....	17
5 Data type ASE.....	17
5.1 Overview.....	17
5.2 Fixed length types.....	18
5.2.1 Bitstring types.....	18
5.2.2 Numeric types	19
6 Communication model specification.....	23
6.1 Communication model.....	23
6.1.1 General	23
6.1.2 Cyclic model n:n	23
6.1.3 Cyclic model 1:n	24
6.1.4 Transient model.....	24
6.2 ASE.....	25
6.2.1 Overview type C	25
6.2.2 Overview type F.....	25
6.2.3 Cyclic data ASE type C.....	25
6.2.4 Cyclic data ASE type F	32
6.2.5 Acyclic data ASE type C	37
6.2.6 Acyclic data ASE type F	43
6.2.7 Management ASE.....	56
6.2.8 Synchronization ASE	59
6.2.9 Measurement ASE.....	60
6.3 AR type C	61
6.3.1 Overview	61
6.3.2 Connection Control.....	62
6.3.3 Cyclic transmission type C.....	66

6.3.4	Acyclic transmission type C	68
6.3.5	Common parameter dist.....	70
6.4	AR type F	75
6.4.1	Overview	75
6.4.2	Channel control	75
6.4.3	Cyclic transmission type F	82
6.4.4	Acyclic transmission type F	84
6.4.5	Parameter dist.....	87
6.4.6	Synchronous trigger	90
6.4.7	Measurement transmission	91
	Bibliography.....	94
	Figure 1 – Cyclic model (n:n type distributed shared memory, unconfirmed push model)	24
	Figure 2 – Cyclic model (1:n type distributed shared memory, unconfirmed push model)	24
	Figure 3 – Transient model (Client server model).....	24
	Figure 4 – Transient model (Push model).....	25
	Figure 5 – Structure of ASE type C of FAL type 23	25
	Figure 6 – Structure of ASE type F of FAL Type 23.....	25
	Figure 7 – Structure of AR type C	62
	Figure 8 – Structure of AR type F	75
<p>STANDARD PREVIEW (standards.iteh.ai)</p>		
	Table 1 – Ld service parameters	27
	Table 2 – Set service parameters	27
	Table 3 – Reset service parameters	27
	Table 4 – Read service parameters.....	28
	Table 5 – Write service parameters.....	28
	Table 6 – Ld service parameters	29
	Table 7 – Set service parameters	30
	Table 8 – Reset service parameters	30
	Table 9 – Read service parameters.....	31
	Table 10 – Write service parameters.....	31
	Table 11 – Ld service parameters	33
	Table 12 – Set service parameters.....	34
	Table 13 – Reset service parameters	34
	Table 14 – Read service parameters.....	35
	Table 15 – Write service parameters.....	35
	Table 16 – Get memory access info service parameters	38
	Table 17 – Run service parameters.....	39
	Table 18 – Stop service parameters.....	40
	Table 19 – Read memory service parameters	41
	Table 20 – Write memory service parameters	42
	Table 21 – Get memory access info service parameters	44
	Table 22 – Run service parameters.....	45
	Table 23 – Stop service parameters.....	46

Table 24 – Read memory service parameters	47
Table 25 – Write memory service parameters	48
Table 26 – Vendor command service parameters	49
Table 27 – Distribute node info service parameters	50
Table 28 – Get statistics service parameters	51
Table 29 – Get node info detail service parameters	53
Table 30 – AC data service parameters	55
Table 31 – AC data ND service parameters	56
Table 32 – Get attribute service parameters	57
Table 33 – Set attribute service parameters	58
Table 34 – Synchronization trigger service parameters	59
Table 35 – Start measurement service parameters	60
Table 36 – Get offset service parameters	61
Table 37 – Control cyclic service parameters	66
Table 38 – CT Update service parameters	67
Table 39 – AC Send service parameters	68
Table 40 – AC Param send service parameters	70
Table 41 – CPD Set service parameters	74
Table 42 – Control cyclic service parameters	82
Table 43 – CT Update service parameters	83
Table 44 – AC Send service parameters	84
Table 45 – AC Send ND service parameters	86
Table 46 – Synchronous trigger internal service parameters	90
Table 47 – Measure send service parameters	91
Table 48 – MeasureAck send service parameters	92
Table 49 – Offset send service parameters	92
Table 50 – Update send service parameters	93

ITeH STANDARD PREVIEW
 (standards.iteh.ai)
 IEC 61158-5-23:2019
<https://standards.iteh.ai/catalog/standards/sist/a820113d-4d66-4508-b07c-55c09213ca0e/iec-61158-5-23-2019>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
FIELD BUS SPECIFICATIONS –****Part 5-23: Application layer service definition –
Type 23 elements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

Attention is drawn to the fact that the use of the associated protocol type is restricted by its intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a layer protocol type to be used with other layer protocols of the same type, or in other type combinations explicitly authorized by its intellectual-property-right holders.

NOTE Combinations of protocol types are specified in IEC 61784-1 and IEC 61784-2.

International Standard IEC 61158-5-23 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This second edition cancels and replaces the first edition published in 2014. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- addition of an attribute for Master ID (see 3.2.10, 6.4.3, 6.4.4 and 6.4.5).

The text of this International Standard is based on the following documents:

FDIS	Report on voting
65C/947/FDIS	65C/950/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

A list of all the parts of the IEC 61158 series, published under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 61158-5-23:2019](https://standards.iteh.ai/catalog/standards/sist/a820113d-4d66-4508-b07c-35c092e136a6/iec-61158-5-23-2019)

<https://standards.iteh.ai/catalog/standards/sist/a820113d-4d66-4508-b07c-35c092e136a6/iec-61158-5-23-2019>

INTRODUCTION

This document is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC 61158-1.

The application service is provided by the application protocol making use of the services available from the data-link or other immediately lower layer. This document defines the application service characteristics that fieldbus applications and/or system management may exploit.

Throughout the set of fieldbus standards, the term “service” refers to the abstract capability provided by one layer of the OSI Basic Reference Model to the layer immediately above. Thus, the application layer service defined in this document is a conceptual architectural service, independent of administrative and implementation divisions.

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

[IEC 61158-5-23:2019](https://standards.iteh.ai/catalog/standards/sist/a820113d-4d66-4508-b07c-35c092e136a6/iec-61158-5-23-2019)

<https://standards.iteh.ai/catalog/standards/sist/a820113d-4d66-4508-b07c-35c092e136a6/iec-61158-5-23-2019>

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 5-23: Application layer service definition – Type 23 elements

1 Scope

1.1 General

The Fieldbus Application Layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be viewed as a “window between corresponding application programs”.

This part of IEC 61158 provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to Type 12 fieldbus. The term “time-critical” is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This International Standard defines in an abstract way the externally visible service provided by the different Types of the fieldbus Application Layer in terms of

- a) an abstract model for defining application resources (objects) capable of being manipulated by users via the use of the FAL service;
- b) the primitive actions and events of the service;
- c) the parameters associated with each primitive action and event, and the form which they take; and
- d) the interrelationship between these actions and events, and their valid sequences.

The purpose of this document is to define the services provided to

- a) the FAL user at the boundary between the user and the Application Layer of the Fieldbus Reference Model, and
- b) Systems Management at the boundary between the Application Layer and Systems Management of the Fieldbus Reference Model.

This document specifies the structure and services of the IEC Fieldbus Application Layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498-1) and the OSI Application Layer Structure (ISO/IEC 9545).

FAL services and protocols are provided by FAL application-entities (AE) contained within the application processes. The FAL AE is composed of a set of object-oriented Application Service Elements (ASEs) and a Layer Management Entity (LME) that manages the AE. The ASEs provide communication services that operate on a set of related application process object (APO) classes. One of the FAL ASEs is a management ASE that provides a common set of services for the management of the instances of FAL classes.

Although these services specify, from the perspective of applications, how request and responses are issued and delivered, they do not include a specification of what the requesting and responding applications are to do with them. That is, the behavioral aspects of the applications are not specified; only a definition of what requests and responses they can

send/receive is specified. This permits greater flexibility to the FAL users in standardizing such object behavior. In addition to these services, some supporting services are also defined in this document to provide access to the FAL to control certain aspects of its operation.

1.2 Specifications

The principal objective of this document is to specify the characteristics of conceptual application layer services suitable for time-critical communications, and thus supplement the OSI Basic Reference Model in guiding the development of application layer protocols for time-critical communications.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols. It is this latter objective which gives rise to the diversity of services standardized as the various Types of IEC 61158, and the corresponding protocols standardized in subparts of IEC 61158-6.

This specification may be used as the basis for formal Application Programming-Interfaces. Nevertheless, it is not a formal programming interface, and any such interface will need to address implementation issues not covered by this specification, including

- a) the sizes and octet ordering of various multi-octet service parameters, and
- b) the correlation of paired request and confirm, or indication and response, primitives.

1.3 Conformance

This document does not specify individual implementations or products, nor does it constrain the implementations of application layer entities within industrial automation systems.

There is no conformance of equipment to this application layer service definition standard. Instead, conformance is achieved through implementation of conforming application layer protocols that fulfill any given Type of application layer services as defined in this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE All parts of the IEC 61158 series, as well as IEC 61784-1 and IEC 61784-2 are maintained simultaneously. Cross-references to these documents within the text therefore refer to the editions as dated in this list of normative references.

IEC 61158-1:2019, *Industrial communication networks – Fieldbus specifications – Part 1: Overview and guidance for the IEC 61158 and IEC 61784 series*

IEC 61158-6 (all parts), *Industrial communication networks – Fieldbus specifications – Part 6: Application layer protocol specification*

ISO/IEC 646, *Information technology – ISO 7-bit coded character set for information interchange*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC 8822, *Information technology – Open Systems Interconnection – Presentation service definition*

ISO/IEC 8824-1, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation*

ISO/IEC 9545, *Information technology – Open Systems Interconnection – Application Layer structure*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

3 Terms, definitions, symbols, abbreviated terms and conventions

For the purposes of this document, the following terms, definitions, symbols, abbreviations and conventions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1 Referenced terms and definitions

3.1.1 ISO/IEC 7498-1 terms

For the purposes of this document, the following terms given in ISO/IEC 7498-1 apply:

- application entity
- application process
- application protocol data unit
- application service element
- application entity invocation
- application process invocation
- application transaction
- real open system
- transfer syntax

3.1.2 ISO/IEC 8822 terms

For the purposes of this document, the following terms given in ISO/IEC 8822 apply:

- abstract syntax
- presentation context

3.1.3 ISO/IEC 9545 terms

For the purposes of this document, the following terms given in ISO/IEC 9545 apply:

- application-association
- application-context
- application context name
- application-entity-invocation
- application-entity-type
- application-process-invocation
- application-process-type

- h) application-service-element
- i) application control service element

3.1.4 ISO/IEC 8824-1 terms

For the purposes of this document, the following terms given in ISO/IEC 8824-1 apply:

- a) object identifier
- b) type

3.1.5 IEC 61158-1 terms

For the purposes of this document, the following terms given in IEC 61158-1 apply:

- a) DLL mapping protocol machine
- b) fieldbus application layer
- c) FAL service protocol machine
- d) protocol data unit

3.2 Additional Type 23 terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.2.1

cyclic transmission transmission that is performed periodically used for the link device update

3.2.2

intelligent device station

node capable of performing 1 in bit data and word data cyclic transmission and transient transmission with the master station, and transient transmission with slave stations, excluding remote I/O stations and having client functions and server functions during transient transmission

3.2.3

link bit

link relay bit data that are shared by all the nodes through the cyclic transmission and is used as one bit unit shared memory of the n:n type

3.2.4

link device

link bit, link word, link x and link y or RX, RY, RWr, and RWw

3.2.5

link word

link register two octet unit data that are shared by all the nodes through the cyclic transmission and is used as two octet unit shared memory of the n:n type

3.2.6

link x

link input received bit data that are transmitted from each node through the cyclic transmission and is used as an input shared memory of the 1:n type

3.2.7

link y

link output bit data that are sent to each node through the cyclic transmission and is used as an output shared memory of the 1:n type

3.2.8**local station**

node capable of performing n:n bit data and word data cyclic transmission and transient transmission with the master station and other local stations, and transient transmission with slave stations, excluding remote I/O stations and having server functions and client functions during transient transmission

3.2.9**management node**

node in which parameters are set

3.2.10**master ID**

ID that represents the node number of the master station

3.2.11**master station**

node that has control information (parameters) and manages cyclic transmission

3.2.12**node**

element that forms a network and performs data transmission, reception, and transfer

3.2.13**node-to-node test**

physical layer test between two nodes

3.2.14**normal node**

node other than a management node

[IEC 61158-5-23:2019](http://standards.iteh.ai/catalog/standards/sist/a820113d-4d66-4508-b07c-35c092e136a6/iec-61158-5-23-2019)

<http://standards.iteh.ai/catalog/standards/sist/a820113d-4d66-4508-b07c-35c092e136a6/iec-61158-5-23-2019>

3.2.15**remote device station**

node capable of performing 1:n bit data and word data cyclic transmission and transient transmission with the master station, and transient transmission with slave stations, excluding remote I/O stations and having server functions during transient transmission

3.2.16**remote I/O station**

node capable of performing 1:n bit data cyclic transmission with the master station

3.2.17**reserve node**

node that is not yet connected, but counted in the total node number of the network not performing cyclic transmission, but always regarded as normal from applications

3.2.18**RX**

remote input as viewed from the master station with bit data that are periodically updated by cyclic transmission, slave to master, or in local station as viewed from the master station is RY of the local station

3.2.19**RY**

remote output as viewed from the master station with bit data that are periodically updated by cyclic transmission, master to slave, or in local station as viewed from the master station is RX of the local station

3.2.20**RWr**

remote register (input) as viewed from the master station with word data that are periodically updated by cyclic transmission, slave to master, or in local station as viewed from the master station is RWw of the local station

3.2.21**RWw**

remote register (output) as viewed from the master station with word data that are periodically updated by cyclic transmission, master to slave, or in local station as viewed from the master station is RWr of the local station

3.2.22**slave station**

node other than the master station

3.2.23**station**

node of a network

3.2.24**synchronization manager**

single node in a master station role per network that manages synchronization, distributing synchronization timing to other nodes

3.2.25**transient transmission**

transmission that is performed upon each request

3.2.26**transient transmission client function**

function that issues a transient request

3.2.27**transient transmission server function**

function that receives a transient request and issues a response

3.2.28**transmission control manager**

single node in a master station role per network that performs token passing management

3.2.29**word**

unit representing data, 16 bits in length

3.3 Symbols and abbreviated terms

AE	Application Entity
AL	Application Layer
AP	Application Process
APDU	Application Protocol Data Unit
APO	Application Process Object
AR	Application Relationship
AREP	Application Relationship Endpoint
ASE	Application Service Element
ASN.1	Abstract Syntax Notation 1

iTeh STANDARD PREVIEW

(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/a820113d-4d66-4508-b07c-36a6/iec-61158-5-23-2019>

<https://standards.iteh.ai/catalog/standards/sist/a820113d-4d66-4508-b07c-36a6/iec-61158-5-23-2019>

<https://standards.iteh.ai/catalog/standards/sist/a820113d-4d66-4508-b07c-36a6/iec-61158-5-23-2019>