

# INTERNATIONAL STANDARD



**Determination of RF field strength, power density and SAR in the vicinity of base stations for the purpose of evaluating human exposure**

[IEC 62232:2022](https://standards.iteh.ai/catalog/standards/sist/95db2530-416f-408b-8f6b-639bf649e0cc/iec-62232-2022)

<https://standards.iteh.ai/catalog/standards/sist/95db2530-416f-408b-8f6b-639bf649e0cc/iec-62232-2022>



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2022 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

**IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

**IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)**

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

[IEC 62232:2022](#)

---

<https://standards.iteh.ai/catalog/standards/sist/95db2530-416f-408b-816b-639b1649e0cc/iec-62232-2022>

# INTERNATIONAL STANDARD



---

**Determination of RF field strength, power density and SAR in the vicinity of  
base stations for the purpose of evaluating human exposure**

[IEC 62232:2022](#)

<https://standards.iteh.ai/catalog/standards/sist/95db2530-416f-408b-8f6b-639bf649e0cc/iec-62232-2022>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 13.280; 17.240

ISBN 978-2-8322-5778-4

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	16
INTRODUCTION.....	18
1 Scope.....	19
2 Normative references .....	20
3 Terms and definitions .....	21
4 Symbols and abbreviated terms.....	36
4.1 Physical quantities .....	36
4.2 Constants .....	36
4.3 Abbreviated terms.....	36
5 How to use this document.....	39
5.1 Quick start guide.....	39
5.2 RF evaluation purpose categories.....	42
5.3 Implementation case studies.....	42
6 Evaluation processes for product compliance, product installation compliance and in-situ RF exposure assessments .....	42
6.1 Evaluation process for product compliance .....	42
6.1.1 General .....	42
6.1.2 Establishing compliance boundaries .....	42
6.1.3 Iso-surface compliance boundary definition .....	43
6.1.4 Simple compliance boundaries .....	43
6.1.5 Methods for establishing the compliance boundary .....	45
6.1.6 Uncertainty .....	49
6.1.7 Reporting for product compliance .....	49
6.2 Evaluation process used for product installation compliance .....	50
6.2.1 General .....	50
6.2.2 General evaluation procedure for product installations.....	50
6.2.3 Product installation compliance based on the actual maximum transmitted power or EIRP .....	52
6.2.4 Product installation data collection.....	55
6.2.5 Simplified product installation evaluation process .....	56
6.2.6 Assessment area selection .....	59
6.2.7 Measurements.....	60
6.2.8 Computations .....	62
6.2.9 Uncertainty .....	62
6.2.10 Reporting for product installation compliance.....	63
6.3 In-situ RF exposure evaluation or assessment process .....	64
6.3.1 General .....	64
6.3.2 In-situ measurement process.....	64
6.3.3 Site analysis .....	65
6.3.4 Case A evaluation .....	66
6.3.5 Case B evaluation .....	66
6.3.6 Uncertainty .....	67
6.3.7 Reporting.....	67
6.4 Averaging procedures .....	67
6.4.1 Spatial averaging.....	67
6.4.2 Time averaging.....	68
7 Determining the evaluation method.....	68

7.1	Overview.....	68
7.2	Process to determine the evaluation method.....	68
7.2.1	General .....	68
7.2.2	Establishing the evaluation points in relation to the source-environment plane .....	69
7.2.3	Exposure metric selection.....	70
8	Evaluation methods .....	71
8.1	General.....	71
8.2	Measurement methods.....	72
8.2.1	General .....	72
8.2.2	RF field strength and power density measurements .....	72
8.2.3	SAR measurements .....	73
8.3	Computation methods .....	74
8.4	Methods for assessment based on actual maximum approach .....	76
8.4.1	General requirements .....	76
8.4.2	Actual transmitted power or EIRP monitoring.....	76
8.4.3	Actual transmitted power or EIRP control.....	77
8.5	Methods for the assessment of RF exposure to multiple sources .....	78
8.6	Methods for establishing the BS transmitted power or EIRP.....	79
9	Uncertainty.....	80
10	Reporting.....	80
10.1	General requirements .....	80
10.2	Report format.....	81
10.3	Opinions and interpretations .....	82
Annex A (informative)	Source-environment plane and guidance on the evaluation method selection.....	83
A.1	Guidance on the source-environment plane .....	83
A.1.1	General .....	83
A.1.2	Source-environment plane example .....	83
A.1.3	Source regions .....	84
A.2	Select between computation or measurement approaches .....	90
A.3	Select measurement method.....	91
A.3.1	Selection stages .....	91
A.3.2	Selecting between RF field strength, power density and SAR measurement approaches.....	91
A.3.3	Selecting between broadband and frequency selective measurement .....	92
A.3.4	Selecting RF field strength measurement procedures .....	93
A.4	Select computation method .....	93
A.5	Additional considerations .....	95
A.5.1	Simplicity .....	95
A.5.2	Evaluation method ranking .....	95
A.5.3	Applying multiple methods for RF exposure evaluation .....	95
Annex B (normative)	Evaluation methods.....	96
B.1	Overview.....	96
B.2	General.....	96
B.2.1	Coordinate systems and reference points .....	96
B.2.2	Variables .....	97
B.3	RF exposure evaluation principles .....	98
B.3.1	Simple calculation of RF field strength and power density.....	98

B.3.2	Measurement of RF field strength and power density .....	102
B.3.3	Spatial averaging .....	104
B.3.4	Time averaging .....	107
B.3.5	Comparing measured and computed values .....	109
B.3.6	Personal RF monitors .....	109
B.4	RF field strength and power density measurements .....	109
B.4.1	Applicability of RF field strength and power density measurements .....	109
B.4.2	In-situ RF exposure measurements .....	109
B.4.3	Laboratory based RF field strength and power density measurements .....	121
B.4.4	RF field strength and power density measurement uncertainty .....	131
B.5	SAR measurements .....	136
B.5.1	Overview of SAR measurements .....	136
B.5.2	SAR measurement requirements .....	136
B.5.3	SAR measurement description .....	138
B.5.4	SAR measurement uncertainty .....	143
B.6	Basic computation methods .....	146
B.6.1	General .....	146
B.6.2	Basic computation formulas for RF field strength or power density evaluation .....	146
B.6.3	Basic whole-body SAR and peak spatial-average SAR evaluation formulas .....	153
B.6.4	Basic compliance boundary assessment method for BS using parabolic dish antennas .....	160
B.6.5	Basic compliance boundary assessment method for intentionally radiating cables .....	163
B.7	Advanced computation methods .....	164
B.7.1	General .....	164
B.7.2	Synthetic model and ray tracing algorithms .....	164
B.7.3	Full wave RF exposure computation .....	171
B.7.4	Full wave SAR computation .....	180
B.8	Extrapolation from the evaluated values to the maximum or actual values .....	185
B.8.1	Extrapolation method .....	185
B.8.2	Extrapolation to maximum in-situ RF field strength or power density using broadband measurements .....	187
B.8.3	Extrapolation to maximum in-situ RF field strength / power density using frequency or code selective measurements .....	187
B.8.4	Influence of traffic in real operating network .....	188
B.8.5	Extrapolation for massive MIMO and beamforming BS .....	189
B.8.6	Maximum exposure extrapolation with dynamic spectrum sharing (DSS) .....	191
B.9	Guidance for implementing the actual maximum approach .....	192
B.9.1	BS actual EIRP evaluation assumptions .....	192
B.9.2	Technology duty-cycle factor description .....	193
B.9.3	CDF evaluation using modelling studies .....	195
B.9.4	CDF evaluation using measurement studies on operational BS sites .....	196
B.9.5	Actual transmitted power or EIRP monitoring counters .....	198
B.9.6	Configurations with multiple transmitters .....	198
B.10	Transmitted power or EIRP evaluation .....	200
B.10.1	General .....	200
B.10.2	Measurement of the transmitted power in conducted mode .....	200
B.10.3	Measurement of the transmitted power in OTA conditions .....	201

B.10.4	Measurement of the EIRP in OTA and laboratory conditions .....	201
B.10.5	Measurement of the EIRP in OTA and in-situ conditions .....	202
Annex C (informative)	Guidelines for the validation of power or EIRP control features and monitoring counter(s) related to the actual maximum approach .....	203
C.1	Overview.....	203
C.2	Guidelines for validating control feature(s) and monitoring counters.....	203
C.3	Validation of power or EIRP monitoring counter in laboratory conditions .....	204
C.3.1	Validation of power or EIRP monitoring counter in conducted mode – test procedure .....	204
C.3.2	Validation of power or EIRP monitoring counter in OTA mode – test procedure .....	206
C.3.3	Validation of control feature(s) in laboratory conditions.....	209
C.3.4	Validation of control features using in-situ measurements.....	212
C.4	Validation test report.....	214
C.5	Case studies .....	215
C.5.1	Case study A – In-situ validation.....	215
C.5.2	Case study B – In-situ validation.....	219
C.5.3	Case study C – In-situ validation .....	222
Annex D (informative)	Rationale supporting simplified product installation criteria.....	227
D.1	General.....	227
D.2	Class E2 .....	227
D.3	Class E10 .....	228
D.4	Class E100 .....	229
D.5	Class E+ .....	231
D.6	Simplified formulas for millimetre-wave antennas using massive MIMO or beam steering .....	232
Annex E (informative)	Technology-specific exposure evaluation guidance .....	234
E.1	Overview to guidance on specific technologies .....	234
E.2	Summary of technology-specific information .....	234
E.3	Guidance on spectrum analyser settings.....	235
E.3.1	Overview of spectrum analyser settings.....	235
E.3.2	Detection algorithms .....	236
E.3.3	Resolution bandwidth and channel power processing .....	236
E.3.4	Integration per service .....	239
E.4	Stable transmitted power signals .....	239
E.4.1	TDMA/FDMA technology.....	239
E.4.2	WCDMA/UMTS technology .....	240
E.4.3	OFDM technology .....	241
E.5	WCDMA measurement and calibration using a code domain analyser.....	241
E.5.1	WCDMA measurements – General.....	241
E.5.2	WCDMA decoder characteristics.....	241
E.5.3	Calibration .....	242
E.6	Wi-Fi measurements .....	244
E.6.1	General .....	244
E.6.2	Integration time for reproducible measurements .....	245
E.6.3	Channel occupation .....	245
E.6.4	Some considerations .....	246
E.6.5	Measurement configuration and steps.....	246
E.6.6	Influence of the application layers.....	247

E.6.7	Power control .....	247
E.7	LTE measurements .....	248
E.7.1	Overview .....	248
E.7.2	LTE transmission modes.....	248
E.7.3	LTE-FDD frame structure.....	249
E.7.4	LTE-TDD frame structure.....	250
E.7.5	Maximum LTE exposure evaluation .....	252
E.7.6	Instantaneous LTE exposure evaluation .....	257
E.7.7	MIMO multiplexing of LTE BS .....	258
E.8	NR BS measurements.....	258
E.8.1	General .....	258
E.8.2	Maximum NR exposure evaluation.....	258
E.9	Establishing compliance boundaries using numerical simulations of MIMO array antennas emitting correlated waveforms .....	268
E.9.1	General .....	268
E.9.2	Field combining near base stations for correlated exposure with the purpose of establishing compliance boundaries .....	268
E.9.3	Numerical simulations of MIMO array antennas with densely packed columns.....	269
E.9.4	Numerical simulations of large MIMO array antennas .....	270
E.10	Massive MIMO antennas.....	270
E.10.1	Overview .....	270
E.10.2	Deterministic conservative approach .....	270
E.10.3	Statistical conservative approach.....	270
E.10.4	Example approaches .....	271
Annex F (informative)	Guidelines for the assessment of BS compliance with ICNIRP-2020 brief exposure limits .....	288
F.1	General.....	288
F.2	Brief exposure limits .....	288
F.3	Implications of brief exposure limits on signal modulation and TDD duty cycle.....	290
F.4	Implications of brief exposure limits on the actual maximum approach .....	290
Annex G (informative)	Uncertainty .....	294
G.1	Background.....	294
G.2	Requirement to estimate uncertainty .....	294
G.3	How to estimate uncertainty .....	295
G.4	Guidance on uncertainty and assessment schemes .....	295
G.4.1	General .....	295
G.4.2	Overview of assessment schemes .....	295
G.4.3	Examples of assessment schemes .....	296
G.4.4	Assessment schemes and compliance probabilities .....	299
G.5	Guidance on uncertainty .....	301
G.5.1	Overview .....	301
G.5.2	Measurement uncertainty and confidence levels .....	302
G.6	Applying uncertainty for compliance assessments.....	303
G.7	Example influence quantities for field measurements .....	304
G.7.1	General .....	304
G.7.2	Calibration uncertainty of measurement antenna or field probe.....	304
G.7.3	Frequency response of the measurement antenna or field probe .....	304
G.7.4	Isotropy of the measurement antenna or field probe .....	306



G.7.5	Frequency response of the spectrum analyser .....	306
G.7.6	Temperature response of a broadband field probe .....	306
G.7.7	Linearity deviation of a broadband field probe .....	307
G.7.8	Mismatch uncertainty .....	307
G.7.9	Deviation of the experimental source from numerical source .....	307
G.7.10	Meter fluctuation uncertainty for time-varying signals .....	307
G.7.11	Uncertainty due to power variation in the RF source .....	308
G.7.12	Uncertainty due to field gradients .....	308
G.7.13	Mutual coupling between measurement antenna or isotropic probe and object .....	309
G.7.14	Uncertainty due to field scattering from the surveyor's body .....	310
G.7.15	Measurement device .....	312
G.7.16	Fields out of measurement range .....	312
G.7.17	Noise .....	313
G.7.18	Integration time .....	313
G.7.19	Power chain .....	313
G.7.20	Positioning system .....	313
G.7.21	Matching between probe and the EUT .....	313
G.7.22	Drifts in output power of the EUT, probe, temperature, and humidity .....	313
G.7.23	Perturbation by the environment .....	313
G.8	Example influence quantities for RF field strength computations by ray tracing or full wave methods .....	314
G.8.1	General .....	314
G.8.2	System .....	314
G.8.3	Technique uncertainties .....	315
G.8.4	Environmental uncertainties .....	315
G.9	Influence quantities for SAR measurements .....	316
G.9.1	General .....	316
G.9.2	Post-processing .....	316
G.9.3	EUT holder .....	316
G.9.4	EUT positioning .....	317
G.9.5	Phantom shell uncertainty .....	318
G.9.6	SAR correction depending on target liquid permittivity and conductivity .....	318
G.9.7	Liquid permittivity and conductivity measurements .....	319
G.9.8	Liquid temperature .....	319
G.10	Influence quantities for SAR calculations .....	319
G.11	Spatial averaging .....	319
G.11.1	General .....	319
G.11.2	Small-scale fading variations .....	320
G.11.3	Error on the estimation of local average power density .....	321
G.11.4	Characterization of environment statistical properties .....	322
G.11.5	Characterization of different spatial averaging schemes .....	322
G.12	Influence of human body on measurements of the electric RF field strength .....	327
G.12.1	Simulations of the influence of human body on measurements based on the method of moments (surface equivalence principle) .....	327
G.12.2	Comparison with measurements .....	329
G.12.3	Conclusions .....	330
Annex H (informative)	Guidance on comparing evaluated parameters with a limit value .....	331
H.1	Overview .....	331

H.2	Information recommended to compare evaluated value against limit value .....	331
H.3	Performing a limit comparison at a given confidence level.....	331
H.4	Performing a limit comparison using a process-based assessment scheme .....	332
Bibliography.....		333
Figure 1	– Quick start guide to the evaluation process .....	40
Figure 2	– Example of iso-surface compliance boundary .....	43
Figure 3	– Example of cylindrical and half-pipe compliance boundaries .....	44
Figure 4	– Example of box shaped compliance boundary .....	45
Figure 5	– Example of truncated box shaped compliance boundary .....	45
Figure 6	– Example illustrating the linear scaling procedure.....	46
Figure 7	– Example of massive MIMO antenna and corresponding beams and envelope patterns .....	48
Figure 8	– Example of compliance boundary shape for BS antennas with beam steering .....	48
Figure 9	– Example of dish antenna compliance boundary .....	49
Figure 10	– Flowchart describing the product installation evaluation process .....	51
Figure 11	– Example of a CDF curve representing the normalized actual transmitted power or EIRP .....	53
Figure 12	– Flow chart for product installation compliance based on the actual maximum transmitted power or EIRP threshold(s).....	55
Figure 13	– Simplified compliance assessment process using installation classes .....	56
Figure 14	– Example of DI within a square-shaped assessment domain boundary (ADB) with dimension $L_{ADB}$ .....	60
Figure 15	– In-situ RF exposure evaluation or assessment process flow chart .....	65
Figure 16	– Source-environment plane concept .....	69
Figure 17	– Flow chart of the measurement methods .....	72
Figure 18	– Flow chart of the relevant computation methods .....	75
Figure 19	– Example of segments used for monitoring and control of BS using mMIMO or beam steering.....	77
Figure A.1	– Example source-environment plane regions near a base station antenna on a tower.....	83
Figure A.2	– Example source-environment plane regions near a roof-top antenna that has a narrow vertical (elevation plane) beamwidth (not to scale).....	84
Figure A.3	– Geometry of an antenna with largest linear dimension $L_{eff}$ and largest end dimension $L_{end}$ .....	85
Figure A.4	– Maximum path difference for an antenna with largest linear dimension $L$ .....	89
Figure B.1	– Cartesian, cylindrical and spherical coordinate systems relative to the BS antenna (view from the rear panel) .....	97
Figure B.2	– Typical RF exposure assessment case .....	99
Figure B.3	– Reflection due to the presence of a ground plane .....	100
Figure B.4	– Reflections due to the presence of internal walls of the housing and surrounding asphalt and soil configuring a base station installed underground.....	101
Figure B.5	– General representation of RF field strength or power density measurements .....	102
Figure B.6	– Practical examples of measurement equipment installation.....	103

Figure B.7 – Spatial averaging schemes relative to walking or standing surface and in the vertical plane oriented to offer maximum area in the direction of the source being evaluated .....	105
Figure B.8 – Spatial averaging relative to spatial-peak field strength point height .....	107
Figure B.9 – Evaluation locations .....	119
Figure B.10 – Relationship of separation of remote radio source and evaluation area to separation of evaluation points .....	120
Figure B.11 – Outline of the surface scanning methodology .....	123
Figure B.12 – Block diagram of the antenna measurement system.....	124
Figure B.13 – Minimum radius constraint, where $a$ denotes the minimum radius of a sphere, centred at the reference point, that encompasses the EUT.....	125
Figure B.14 – Maximum angular sampling spacing constraint .....	125
Figure B.15 – Outline of the volume/surface scanning methodology.....	128
Figure B.16 – Block diagram of typical near-field EUT measurement system.....	129
Figure B.17 – Examples of positioning of the EUT relative to the relevant phantom .....	136
Figure B.18 – Phantom liquid volume and measurement volume used for whole-body SAR measurements with the box-shaped phantoms.....	143
Figure B.19 – Reference frame employed for cylindrical formulas for RF field strength computation at a point P (left), and on a line perpendicular to boresight (right) .....	147
Figure B.20 – Views illustrating the three valid zones for field strength computation around an antenna.....	149
Figure B.21 – Enclosed cylinder around collinear array antennas, with and without electrical downtilt.....	150
Figure B.22 – Spherical formulas reference results .....	153
Figure B.23 – Cylindrical formulas reference results .....	153
Figure B.24 – Directions for which SAR estimation expressions are provided.....	154
Figure B.25 – Description of SAR estimation formulas physical parameters .....	155
Figure B.26 – Flow chart for the simplified assessment of RF compliance boundary in the line of sight of a parabolic dish antenna .....	162
Figure B.27 – Radiating cable geometry .....	163
Figure B.28 – Synthetic model and ray tracing algorithms geometry and parameters .....	167
Figure B.29 – Line 4 far-field positions for synthetic model and ray tracing validation example .....	169
Figure B.30 – Antenna parameters for synthetic model and ray tracing algorithms validation example .....	170
Figure B.31 – Generic 900 MHz BS antenna with nine dipole radiators .....	177
Figure B.32 – Line 1, 2 and 3 near-field positions for full wave and ray tracing validation .....	178
Figure B.33 – Generic 1 800 MHz BS antenna with five slot radiators .....	179
Figure B.34 – BS antenna placed in front of a multi-layered lossy cylinder.....	185
Figure B.35 – Time variation over 24 h of the exposure induced by NR, GSM and FM, each normalized to the mean value.....	189
Figure B.36– Generic structure of a base station transmitted RF signal frame.....	194
Figure B.37 – Example of setup for the direct power level measurement for BS equipped with direct access conducted output ports.....	201
Figure C.1 – Example of a laboratory test setup for validation of an actual power control feature intended for use with a 5G BS .....	210

Figure C.2 – Example of a test setup for validation of an actual power control feature implemented in a 5G BS .....	213
Figure C.3 – Ground based in-situ validation setup .....	216
Figure C.4 – In-situ validation measurement setup near the general public compliance boundary in front of the 5G massive MIMO antenna (bore sight position) .....	217
Figure C.5 – Comparison between measured time-averaged EMF and power control feature (5G counter data) for the ground-based measurements .....	218
Figure C.6 – Measured exposure adaptation in time expressed as a percentage of ICNIRP limits [1], [2] for the measurements near the general public compliance boundary .....	218
Figure C.7 – Overview of the measurement site .....	220
Figure C.8 – Ground view of the validation site and measurement setup, located 60 m from the 5G BS, in the line of sight .....	221
Figure C.9 – Power transmitted by the massive MIMO antenna (top trace), channel power (ChP) measurements (middle trace) and transmitted resource blocks (RBs) (bottom trace) .....	221
Figure C.10 – Overview of the test platform .....	223
Figure C.11 – Example of synthetic model simulation of the test area .....	223
Figure C.12 – Examples of traffic load profiles .....	223
Figure C.13 – Example of testing in different segments in the test area .....	224
Figure C.14 – Results of the monitoring validation and baseline test in phase 1 .....	225
Figure C.15 – Example of power density measurements and power density derived from counters .....	225
Figure C.16 – Measured power density and power density derived from counters .....	226
Figure C.17 – Comparisons of both counters and measurements .....	226
Figure D.1 – Measured ER as a function of distance for a BS ( $G = 5$ dBi, $f = 2\ 100$ MHz) transmitting with an EIRP of 2 W (installation class E2) and 10 W (installation class E10) .....	227
Figure D.2 – Minimum installation height as a function of transmitting power corresponding to installation class E10 .....	228
Figure D.3 – Compliance distance in the main lobe as a function of EIRP established in accordance with the far-field formula corresponding to installation class E100 .....	229
Figure D.4 – Minimum installation height as a function of transmitting power corresponding to installation class E100 .....	230
Figure D.5 – Averaged power density at ground level for various installation configurations of equipment with 100 W EIRP (installation class E100) .....	231
Figure D.6 – Compliance distance in the main lobe $CD_m$ as a function of EIRP established in accordance with the far-field formula corresponding to installation class E+ .....	232
Figure D.7 – Minimum installation height $h_m$ as a function of EIRP corresponding to installation class E+ .....	232
Figure D.8 – Power density distribution in watts per square metre in a vertical cut plane for an $8 \times 8$ antenna array at 28 GHz (grid step of 10 cm) .....	233
Figure D.9 – Power density distribution in watts per square metre in a vertical cut plane for an $8 \times 8$ antenna array at 39 GHz (grid step of 10 cm) .....	233
Figure E.1 – Spectral occupancy for GMSK .....	237
Figure E.2 – Spectral occupancy for CDMA .....	238
Figure E.3 – Channel allocation for a WCDMA signal .....	241
Figure E.4 – Example of Wi-Fi frames .....	244

Figure E.5 – Channel occupation versus the integration time for IEEE 802.11b standard .....	245
Figure E.6 – Channel occupation versus nominal throughput rate for IEEE 802.11b/g standards.....	246
Figure E.7 – Wi-Fi spectrum trace snapshot.....	246
Figure E.8 – Frame structure of transmission signal for LTE-FDD downlink .....	250
Figure E.9 – Frame structure LTE-TDD type 2 (for 5 ms switch-point periodicity) .....	251
Figure E.10 – Frame structure of transmission signal for LTE-TDD .....	251
Figure E.11 – LTE-TDD PBCH measurement example .....	254
Figure E.12 – Example of VBW setting for LTE-FDD and LTE-TDD to avoid underestimation .....	255
Figure E.13 – Examples of received waves from LTE-FDD downlink signals using a spectrum analyser using zero span mode .....	256
Figure E.14 – LTE-TDD PBCH measurement example spectrum analyser using zero span mode.....	257
Figure E.15 – Example of VBW setting for NR to avoid underestimation .....	261
Figure E.16 – Examples of measurement accuracy results according to the ratio of VBW and RBW for NR SCS 30 kHz and 1 MHz RBW using various SA types (A to D).....	261
Figure E.17 – Waterfall reconstruction plot of a 1 s long measurement trace of an NR signal with subcarrier spacing (SCS) 30 kHz (along one component of the electric field).....	262
Figure E.18 – Example of NR signal frame measured on SA with SSB signal above PDSCH (data).....	262
Figure E.19 – Example of NR signal frame measured on SA with SSB signal below or equal to PDSCH (data) .....	263
Figure E.20 – Time gating of SS burst signal .....	264
Figure E.21 – Representation of the channel bandwidth (CBW) .....	264
Figure E.22 – An example for one port CSI-RS beam design .....	267
Figure E.23 – Plan view representation of statistical conservative model .....	273
Figure E.24 – Binomial cumulative probability function for $N = 24$ , $PR = 0,125$ .....	281
Figure E.25 – Binomial cumulative probability function for $N = 18$ , $PR = 2/7$ .....	281
Figure E.26 – Binomial cumulative probability function for $N = 100$ , $PR = 0,125$ .....	285
Figure E.27 – Binomial cumulative probability function for $N = 82$ , $PR = 2/7$ .....	285
Figure F.1 – Limits for brief exposure ( $t < 360$ s), see Table F.1, divided by the corresponding time interval $t$ and normalized with the value obtained for $t$ up to 360 s .....	289
Figure F.2 – $F_{PR\_min}$ as a function of the pulse duration assuming a whole-body averaging time of 30 min.....	293
Figure F.3 – $F_{PR\_min}$ as a function of the pulse duration assuming an averaging time of 6 min .....	293
Figure G.1 – Examples of general assessment schemes.....	297
Figure G.2 – Target uncertainty scheme overview.....	298
Figure G.3 – Probability of the true value being above (respectively below) the evaluated value depending on the confidence level assuming a normal distribution .....	302
Figure G.4 – Plot of the calibration factors for $E$ (not $E^2$ ) provided from an example calibration report for an electric field probe .....	305
Figure G.5 – Computational model used for the variational analysis of reflected RF fields from the front of a surveyor .....	311
Figure G.6 – EUT positioning equipment and different positioning errors .....	317

Figure G.7 – Physical model of small-scale fading variations ..... 320

Figure G.8 – Example of E-field strength variations in line of sight of an antenna operating at 2,2 GHz..... 320

Figure G.9 – Error at 95 % on average power estimation ..... 321

Figure G.10 – 343 measurement points building a cube (centre) and different templates consisting of a different number of positions ..... 323

Figure G.11 – Moving a template (Line 3) through the cube ..... 324

Figure G.12 – Standard deviations for GSM 900, DCS 1800 and UMTS ..... 326

Figure G.13 – Simulation arrangement..... 328

Figure G.14 – Body influence..... 328

Figure G.15 – Simulation arrangement..... 329

  

Table 1 – Quick start guide evaluation steps ..... 41

Table 2 – Example of product installation classes where a simplified evaluation process is applicable (based on ICNIRP general public limits [1] and [2])..... 57

Table 3 – Exposure metrics validity for evaluation points in each source region ..... 71

Table 4 – Requirements for RF field strength and power density measurements ..... 73

Table 5 – Whole-body SAR exclusions based on RF power levels..... 73

Table 6 – Requirements for SAR measurements ..... 74

Table 7 – Applicability of computation methods for source-environment regions of Figure 16 ..... 75

Table 8 – Requirements for computation methods..... 75

Table A.1 – Definition of source regions..... 86

Table A.2 – Default source region boundaries..... 86

Table A.3 – Source region boundaries for antennas with maximum dimension less than  $2,5 \lambda$  ..... 87

Table A.4 – Source region boundaries for linear/planar antenna arrays with a maximum dimension greater than or equal to  $2,5 \lambda$  ..... 87

Table A.5 – Source region boundaries for equiphase radiation aperture (e.g. dish) antennas with maximum reflector dimension much greater than a wavelength ..... 88

Table A.6 – Source region boundaries for radiating cables..... 88

Table A.7 – Far-field distance  $r$  measured in metres as a function of angle  $\beta$  ..... 90

Table A.8 – Guidance on selecting between computation and measurement approaches..... 91

Table A.9 – Guidance on selecting between broadband and frequency selective measurement..... 92

Table A.10 – Guidance on selecting RF field strength measurement procedures..... 93

Table A.11 – Guidance on selecting computation methods..... 94

Table A.12 – Guidance on specific evaluation method ranking ..... 95

Table B.1 – Dimension variables ..... 97

Table B.2 – RF power variables ..... 97

Table B.3 – Antenna variables ..... 98

Table B.4 – Exposure metric variables ..... 98

Table B.5 – Broadband measurement system minimum requirements ..... 111

Table B.6 – Frequency selective measurement system minimum requirements ..... 112



Table B.7 – Example template for estimating the expanded uncertainty of an in-situ RF field strength measurement that used a frequency selective equipment .....	132
Table B.8 – Example template for estimating the expanded uncertainty of an in-situ RF field strength measurement that used a broadband equipment.....	133
Table B.9 – Example template for estimating the expanded uncertainty of a laboratory-based RF field strength or power density measurement using the surface scanning method .....	134
Table B.10 – Example template for estimating the expanded uncertainty of a laboratory-based RF field strength or power density measurement using the volume scanning method .....	135
Table B.11 – Numerical reference SAR values for reference dipoles and flat phantom – All values are normalized to a forward power of 1 W .....	140
Table B.12 – Phantom liquid volume and measurement volume used for whole-body SAR measurements [61], [77] .....	143
Table B.13 – Correction factor to compensate for a possible bias in the obtained general public whole-body SAR when assessed using the large box-shaped phantom for child exposure configurations [72].....	143
Table B.14 – Measurement uncertainty evaluation template for EUT whole-body SAR test 144	
Table B.15 – Measurement uncertainty evaluation template for whole-body SAR system validation .....	145
Table B.16 – Definition of boundaries for selecting the zone of computation .....	149
Table B.17 – Input parameters for cylindrical and spherical formulas validation .....	152
Table B.18 – Applicability of SAR estimation formulas .....	154
Table B.19 – Calculation of $A(f, d)$ .....	157
Table B.20 – Antenna parameters for SAR estimation formulas verification .....	159
Table B.21 – Verification data for SAR estimation formulas – front.....	159
Table B.22 – Verification data for SAR estimation formulas – axial and back .....	159
Table B.23 – Example template for estimating the expanded uncertainty of a synthetic model and ray tracing RF field strength computation.....	168
Table B.24 – Synthetic model and ray tracing power density reference results.....	171
Table B.25 – Example template for estimating the expanded uncertainty of a full wave RF field strength / power density computation.....	176
Table B.26 – Validation 1 full wave field reference results.....	178
Table B.27 – Validation 2 full wave field reference results.....	179
Table B.28 – Example template for estimating the expanded uncertainty of a full wave SAR computation.....	183
Table B.29 – Validation reference SAR results for computation method .....	185
Table B.30 – Relevant parameters for performing RF exposure modelling studies of a massive MIMO site or site cluster .....	195
Table B.31 – Measurement campaign parameters for performing RF exposure assessment of a massive MIMO site or site cluster .....	197
Table B.32 – Power combination factors applicable to the normalized actual transmitted power CDF in case of combination of multiple independent identical transmitters.....	199
Table B.33 – Power combination factors applicable to two independent transmitters with a ratio $p$ in amplitude .....	200
Table C.1 – Relative difference between the measured averaged transmitted power and actual power counter value for systems that allow direct power level measurements .....	204