

INTERNATIONAL STANDARD

Fibre optic interconnecting devices and passive components – Performance standard –
Part 085-02: Non-connectorized single-mode pigtailed CWDM devices for category C – Indoor controlled environment

<https://standards.iteh.ai/catalog/standards/sist/614f97b8-1250-4cf8-930e-eeb890f4da0a/iec-61753-085-02-2021>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

[IEC 61753-085-02:2021](https://standards.iteh.ai/catalog/standards/sist/61497b8-1250-4cf8-930e-eeb890f4da0a/iec-61753-085-02-2021)

<https://standards.iteh.ai/catalog/standards/sist/61497b8-1250-4cf8-930e-eeb890f4da0a/iec-61753-085-02-2021>

INTERNATIONAL STANDARD

**Fibre optic interconnecting devices and passive components – Performance standard –
Part 085-02: Non-connectorized single-mode pigtailed CWDM devices for category C – Indoor controlled environment**

<https://standards.iteh.ai/catalog/standards/sist/614f97b8-1250-4cf8-930e-eeb890f4da0a/iec-61753-085-02-2021>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.180.10

ISBN 978-2-8322-9985-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	3
1 Scope	5
2 Normative references	5
3 Terms and definitions	6
4 Test	6
5 Test report	7
6 Performance requirements	7
6.1 Reference components	7
6.2 Dimensions	7
6.3 Sample size	7
6.4 Test details and requirements	7
Annex A (normative) Sample size	13
Bibliography	14
Table 1 – Single-mode spectral bands	7
Table 2 – Test details and requirements for category C	8
Table A.1 – Sample size and grouping of tests	13

ITEH STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/614f97b8-1250-4cf8-930e-eeb890f4da0a/iec-61753-085-02-2021>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**FIBRE OPTIC INTERCONNECTING DEVICES AND
PASSIVE COMPONENTS – PERFORMANCE STANDARD –****Part 085-02: Non-connectorized single-mode pigtailed CWDM
devices for category C – Indoor controlled environment**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61753-085-02 has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics. It is an International Standard.

This first edition cancels and replaces IEC 61753-085-2 published in 2008. This edition constitutes a technical revision.

This edition includes the following specific technical change with respect to IEC 61753-085-2: change of test conditions harmonizing with IEC 61753-1:2018.

The text of this International Standard is based on the following documents:

Draft	Report on voting
86B/4319/CDV	86B/4377B/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 61753 series, published under the general title *Fibre optic interconnecting devices and passive components – Performance standard*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 61753-085-02:2021](https://standards.iteh.ai/catalog/standards/sist/614f97b8-1250-4cf8-930e-eeb890f4da0a/iec-61753-085-02-2021)
<https://standards.iteh.ai/catalog/standards/sist/614f97b8-1250-4cf8-930e-eeb890f4da0a/iec-61753-085-02-2021>

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – PERFORMANCE STANDARD –

Part 085-02: Non-connectorized single-mode pigtailed CWDM devices for category C – Indoor controlled environment

1 Scope

This part of IEC 61753 contains the minimum initial test and measurement requirements and severities which a fibre-optic pigtailed coarse wavelength division multiplexing (CWDM) device satisfies in order to be categorised as meeting the requirements of category C (indoor controlled environment), as defined in Annex A of IEC 61753-1:2018. CWDM is defined in IEC 62074-1.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60793-2-50, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 60794-2-50, *Optical fibre cables – Part 2-50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies*

IEC 61300-2-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)*

IEC 61300-2-4, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-4: Tests – Fibre or cable retention*

IEC 61300-2-5, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-5: Tests – Torsion*

IEC 61300-2-9, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests – Shock*

IEC 61300-2-14, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-14: Tests – High optical power*

IEC 61300-2-17, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-17: Tests – Cold*

IEC 61300-2-18, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-18: Tests – Dry heat – High temperature endurance*

IEC 61300-2-19, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-19: Tests – Damp heat (steady state)*

IEC 61300-2-22, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-22: Tests – Change of temperature*

IEC 61300-2-42, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-42: Tests – Static side load for strain relief*

IEC 61300-2-44, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-44: Tests – Flexing of the strain relief of fibre optic devices*

IEC 61300-3-2, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-2: Examination and measurements – Polarization dependent loss in a single-mode fibre optic device*

IEC 61300-3-6, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-6: Examinations and measurements – Return loss*

IEC 61300-3-7, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-7: Examination and measurements – Wavelength dependence of attenuation and return loss of single mode components*

IEC 61300-3-29, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-29: Examinations and measurements – Spectral transfer characteristics of DWDM devices*

IEC 61753-1:2018, *Fibre optic interconnecting devices and passive components – Performance standard – Part 1: General and guidance*

IEC 62074-1, *Fibre optic interconnecting devices and passive components – Fibre optic WDM devices – Part 1: Generic specification*

IEC TS 62627-09, *Fibre optic interconnecting devices and passive components – Vocabulary for passive optical devices*

ITeh STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/61497b8-1250-4cf8-930e-eeb890f4da0a/iec-61753-085-02-2021>

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62074-1 and IEC TS 62627-09 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

4 Test

All test methods are in accordance with a specific IEC 61300 series standard. The parts applicable to this document are mentioned in 6.4 (see Table 2).

The samples shall be terminated onto single-mode fibres as per IEC 60793-2-50 category B-652.B, B-652.D or B-657 in either coated fibres (primary and secondary) or reinforced cable format as per IEC 60794-2-50.

Table 1 is intended to provide guidance on the wavelength ranges of the various spectral bands. It is not intended for specification. All tests shall be carried out over the wavelength range defined by the customer's application; wavelengths, the complete CWDM wavelength range or a wider wavelength range such as from 1 250 nm to 1 650 nm may be used. Values of operating wavelength used in performance verification shall be as agreed between the customer and supplier or shall be as defined in the manufacturer's specification.

Table 1 – Single-mode spectral bands

Band	Descriptor	Range nm
O-band	Original	1 260 to 1 360
E-band	Extended	1 360 to 1 460
S-band	Short wavelength	1 460 to 1 530
C-band	Conventional	1 530 to 1 565
L-band	Long wavelength	1 565 to 1 625
U-band	Ultralong wavelength	1 625 to 1 675

Source: ITU-T G.Supplement 39.

5 Test report

Fully documented test reports and supporting evidence shall be prepared and be available for inspection as evidence that the tests have been carried out and complied with.

6 Performance requirements

6.1 Reference components

The performance testing in this document does not require the use of reference components.

6.2 Dimensions

Dimensions shall comply with either an appropriate IEC interface standard or with those given in appropriate manufacturers drawings, where the IEC interface standard does not exist or cannot be used.

6.3 Sample size

Sample sizes are defined in Table A.1.

6.4 Test details and requirements

The requirements are given only for pigtailed CWDM devices. For connectorized components, the connector performances shall be in compliance with IEC 61753-1.

A minimum length of fibre or cable of 2,0 m per port shall be used for all tests.

Minimum test details and requirements are shown in Table 2.

Table 2 – Test details and requirements for category C

No.	Test	Requirement	Details	
1	Centre wavelength (CWL) IEC 61300-3-7; IEC 61300-3-29	Centre wavelengths ^a : - channel 1: 1 271nm - channel 2: 1 291nm - channel 3: 1 311nm - channel 4: 1 331nm - channel 5: 1 351nm - channel 6: 1 371nm - channel 7: 1 391nm - channel 8: 1 411nm - channel 9: 1 431nm - channel 10: 1 451nm - channel 11: 1 471nm - channel 12: 1 491nm - channel 13: 1 511nm - channel 14: 1 531nm - channel 15: 1 551nm - channel 16: 1 571nm - channel 17: 1 591nm - channel 18: 1 611nm	Launch patchcord length:	≥ 2 m
			Source type:	Unpolarised
			Launch conditions:	The wavelength of the source shall be longer than cut-off wavelength of the fibre.
			Measurement uncertainty:	0,05 nm
2	Passband IEC 61300-3-7; IEC 61300-3-29	CWL ±6,5 nm Passband is defined as 0,5 dB bandwidth ^b .	Launch patchcord length:	≥ 2 m
			Source type:	Unpolarised broadband light
			Launch conditions:	The wavelength of the source shall be longer than cut-off wavelength of the fibre.
			Measurement uncertainty:	0,05 nm
3	Insertion loss (attenuation) IEC 61300-3-7	Type A: ≤ 1,4 dB (1-channel device) ≤ 2,1 dB (4-channel device) ≤ 2,8 dB (8-channel device) ≤ 3,5 dB (12-channel device) ≤ 4,3 dB (16-channel device) ≤ 4,3 dB (18-channel device) Type B: ≤ 1,7 dB (1-channel device) ≤ 2,7 dB (4-channel device) ≤ 4,0 dB (8-channel device) ≤ 5,3 dB (12-channel device) ≤ 6,1 dB (16-channel device) ≤ 6,1 dB (18-channel device) c d	Launch patchcord length:	≥ 2 m
			Source type:	Unpolarised
			Launch conditions:	The wavelength of the source shall be longer than cut-off wavelength of the fibre.
			Measurement uncertainty:	0,1 dB
4	Total channel isolation IEC 61300-3-7; IEC 61300-3-29	≥ 30 dB	Launch patchcord length:	≥ 2 m
			Source type:	Unpolarised
			Launch conditions:	The wavelength of the source shall be longer than cut-off wavelength of the fibre.
			Measurement uncertainty:	1 dB