

INTERNATIONAL ELECTROTECHNICAL COMMISSION  
COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

IEC 61753-1  
Edition 2.0 2018-08

IEC 61753-1  
Édition 2.0 2018-08

FIBRE OPTIC INTERCONNECTING DEVICES AND  
PASSIVE COMPONENTS – PERFORMANCE  
STANDARD

DISPOSITIFS D'INTERCONNEXION ET  
COMPOSANTS PASSIFS FIBRONIQUES – NORME  
DE PERFORMANCE

Part 1: General and guidance

Partie 1: Généralités et recommandations

## CORRIGENDUM 1

Corrections to the French version appear after the English text.

Les corrections à la version française sont données après le texte anglais.

### Table A.15 – Hardened optical connectors and closures – Category S – Outdoor subterranean environment

Replace the existing row starting by "Change of temperature<sup>b</sup>" by the following new row: -2018-cor1-2019

Change of temperature <sup>b</sup> IEC 61300-2-22	Temperature range: –30 °C to +60 °C Duration at extreme temperatures: 4 h Temperature change rate: 1 °C/min 12 cycles	S,O,V	S,O,V
--	--	-------	-------

### Table A.27 – Category A, G and S single mode sealed closures

Replace the existing title by the following new title:

### Table A.27 – Category C, A, G and S single mode sealed closures