



SLOVENSKI STANDARD
SIST EN 300 609-4 V8.0.2:2003
01-december-2003

8 [[]Hb]`W] b]`h`Y_ca i b]_UW`g_]`g]ghYa `fZhU&]b`ZhU&ZLÈ`GdYVZ]_UW`U
cdfYa Y`g]ghYa UVUhb]`dcghU`f6 GGLÈ("XY.`DcbUj``U b]_]`ffYdYh]hcf`Y`L`f] GA`%`%&` ž
fUh]]WU, "\$`&ž]nXUU%--Ł

Digital cellular telecommunications system (Phase 2 and Phase 2+) (GSM); Base Station System (BSS) equipment specification; Part 4: Repeaters (GSM 11.26 version 8.0.2 Release 1999)

iteh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246ef3b7123/sist-en-300-609-4-v8-0-2-2003>

Ta slovenski standard je istoveten z: EN 300 609-4 Version 8.0.2

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---	--

SIST EN 300 609-4 V8.0.2:2003 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 609-4 V8.0.2:2003

<https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246ef3b7123/sist-en-300-609-4-v8-0-2-2003>

ETSI EN 300 609-4 V8.0.2 (2000-10)

European Standard (Telecommunications series)

**Digital cellular telecommunications system (Phase 2 and Phase 2+);
Base Station System (BSS) equipment specification;
Part 4: Repeaters
(GSM 11.26 version 8.0.2 Release 1999)**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

GSM®

GLOBAL SYSTEM FOR
MOBILE COMMUNICATIONS

[SIST EN 300 609-4 V8.0.2:2003](https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246ef3b7123/sist-en-300-609-4-v8-0-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246ef3b7123/sist-en-300-609-4-v8-0-2-2003>



Reference

REN/SMG-021126Q8

KeywordsDigital cellular telecommunications system,
Global System for Mobile communications (GSM)**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88**iTeh STANDARD PREVIEW**
(standards.iteh.ai)SIST EN 300 609-4 V8.0.2:2003<https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246ef3b7123/sist-en-300-609-4-v8-0-2-2003>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	6
2 References	6
3 Definitions and abbreviations.....	7
3.1 Definitions	7
3.2 Abbreviations	7
4 General	7
4.1 Radio frequency bands	7
4.2 Test environments	8
4.2.1 Normal test environment	8
4.2.2 Extreme test environment	8
4.2.3 Extreme temperature	8
4.3 Manufacturers declarations	9
4.4 Methods of measurement	9
5 Spurious emissions	9
5.1 Test purpose	9
5.2 Test case	9
5.3 Conformance requirement	10
5.4 Reference requirement	11
6 Intermodulation attenuation	11
6.1 Test purpose	11
6.2 Test case	11
6.3 Conformance requirement	11
6.4 Reference requirement	11
7 Out of band gain	12
7.1 Test purpose	12
7.2 Test case	12
7.3 Conformance requirement	12
7.4 Reference requirement	12
8 Frequency error	12
8.1 Test purpose	12
8.2 Test case	13
8.3 Conformance requirement	13
8.4 Reference requirement	13
9 Modulation accuracy at GMSK modulation.....	13
9.1 Test purpose	13
9.2 Test case	13
9.3 Conformance requirement	14
9.4 Reference requirement	14
10 Modulation accuracy at 8-PSK modulation	14
10.1 Test purpose	14
10.2 Test case	14
10.3 Conformance requirement	15
Annex A (informative): Testing of gain for part band repeaters	16
A.1 Rationale for this test.....	16
A.2 Gain outside operating band.....	16
A.2.1 Test purpose	16

A.2.2	Test case	16
A.2.3	Conformance requirement	16
Annex B (informative):	Change history	17
History		18

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 609-4 V8.0.2:2003](https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246ef3b7123/sist-en-300-609-4-v8-0-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246ef3b7123/sist-en-300-609-4-v8-0-2-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Special Mobile Group (SMG).

The present document describes the Radio Frequency (RF) tests for GSM 450, GSM 480, GSM 900 and DCS 1800 repeaters within the digital cellular telecommunications system (Phase 2/Phase 2+).

The contents of the present document may be subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of the present document it will then be re-submitted for formal approval procedures by ETSI with an identifying change of release date and an increase in version number as follows:

Version 8.x.y

where:

- iTeh STANDARD PREVIEW**
(standards.iteh.ai)
- 8 GSM Phase 2+ Release 1999. [SIST EN 300 609-4 V8.0.2:2003](https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246ef3b7123/sist-en-300-609-4-v8-0-2-2003)
 - x the second digit is incremented for changes of substance, i.e. technical enhancements, corrections, updates, etc.;
 - y the third digit is incremented when editorial only changes have been incorporated in the specification.

National transposition dates

Date of adoption of this EN:	22 September 2000
Date of latest announcement of this EN (doa):	31 December 2000
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 June 2001
Date of withdrawal of any conflicting National Standard (dow):	31 June 2001

1 Scope

The present document describes the Radio Frequency (RF) tests for GSM 450, GSM 480, GSM 900 and DCS 1800 repeaters which receive, amplify, and retransmit a received Mobile Station (MS) signal in the GSM MS transmit band and simultaneously receive, amplify and retransmit a received Base Transceiver Station (BTS) RF signal in the GSM BTS transmit band.

The present document is applicable to repeaters meeting the requirements of either GSM Phase 2 or GSM Phase 2+. Unless otherwise stated, all tests are applicable to repeaters meeting Phase 2 and/or Phase 2+ GSM requirements, because the requirements of the Phase 2 and Phase 2+ core GSM specifications which are referenced in the test are consistent. Most differences between Phase 2 and Phase 2+ requirements represent Phase 2+ features which are optional for the BSS to support.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.
- For this Release 1999 document, references to GSM documents are for Release 1999 versions (version 8.x.y).

- ITC STANDARD PREVIEW
 (standards.iteh.ai)
- <https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246e1b9125/sist-en-300-609-4-v8-0-2-2003>
- [1] ETR 350 (GSM 01.04): "Digital cellular telecommunication system (Phase 2+); Abbreviations and acronyms".
 - [2] ETS 300 019-1-0: "Equipment Engineering (EE): Environmental conditions and environmental tests for telecommunications equipment Part 1-0; Classification of environmental conditions; Introduction".
 - [3] ETS 300 019-1-3: "Equipment Engineering (EE): Environmental conditions and environmental tests for telecommunications equipment Part 1-3; Classification of environmental conditions, Stationary use at weather-protected locations".
 - [4] ETS 300 019-1-4: "Equipment Engineering (EE): Environmental conditions and environmental tests for telecommunications equipment Part 1-4; Classification of environmental conditions, Stationary use at non-weather-protected locations".
 - [5] ETS 300 113: "Radio Equipment and Systems (RES); Land mobile service; Technical characteristics and test conditions for radio equipment intended for the transmission of data (and speech) and having an antenna connector".
 - [6] ETS 300 910 (GSM 05.05): "Digital cellular telecommunication system (Phase 2+); Radio transmission and reception".
 - [7] IEC 68-2: "Basic environmental testing procedures: Part 2 Tests".
 - [8] IEC 721: "Classification of environmental conditions".
 - [9] ETS 300 607-1 (GSM 11.10-1): "Digital cellular telecommunication system (Phase 2); Mobile Station (MS) conformance specification; Part 1: Conformance specification".
 - [10] ETS 300 609-1 (GSM 11.21): "Digital cellular telecommunication system (Phase 2); Base Station System (BSS) equipment specification; Part 1: Radio aspects".

- [11] ETR 027: "Methods of measurement for private mobile radio equipment".
- [12] ETR 028: "Uncertainties in the measurement of mobile radio equipment characteristics".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

broadband repeater: repeater which is designed for operation on any combination of ARFCNs (up to a specified maximum number) within the operating band of the repeater.

channelized repeater: repeater which is designed for operation on a specified subset of ARFCNs within the operating band of the repeater. The subset of ARFCNs may be determined during the manufacture of the repeater, or may be programmable.

repeater system using frequency shift: frequency shifting repeater consists of two different elements, a master unit close to the BTS and at least one remote unit close to the area to be covered. The master unit amplifies the channels from the BTS and shifts them to different GSM channels. In the remote unit the shifted channels from the master unit will be transferred back to the original channels and amplified. This is valid for the downlink signals as well as for the uplink signals. **GSM:** Unless otherwise specified, references to GSM include both GSM450, GSM 480, GSM 900 and DCS 1800.

repeater: bi-directional Radio Frequency (RF) amplifier which can amplify and transmit a received Mobile Station (MS) signal in the GSM MS transmit band, simultaneously it can amplify and transmit a received Base Transceiver Station (BTS) RF signal in the GSM BTS transmit band.

spurious emissions: emissions at frequencies other than those of the carrier and sidebands associated with normal modulation and switching.

[SIST EN 300 609-4 V8.0.2:2003](https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246ef3b7123/sist-en-300-609-4-v8-0-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246ef3b7123/sist-en-300-609-4-v8-0-2-2003>

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BTS	Base Transceiver Station
MS	Mobile Station
RF	Radio Frequency

Abbreviations used within the GSM specifications are given in ETR 350 (GSM 01.04) [1].

4 General

A repeater can be designed to amplify the whole transmit RF band or just a part of the band. In the latter case the repeater can be either Broadband, with frequency band selective filtering, or channelized, with channel selective filtering.

4.1 Radio frequency bands

A repeater, as a bi-directional amplifier, can amplify and transmit a received MS signal in the MS transmit band, simultaneously it can amplify and transmit a received BTS signal in the BTS transmit band. The relevant MS and BTS transmit bands for the present document, which is a subset of the MS and BTS transmit bands as defined in GSM 05.05 [6], are given in table 1.

Table 1: MS and BTS transmit RF bands

	MS transmit band	BTS transmit band
GSM 450	450,4 MHz to 457,6 MHz	460,4 MHz to 467,6 MHz
GSM 480	478,8 MHz to 486,0 MHz	488,8 MHz to 496,0 MHz
P-GSM 900	890 MHz to 915 MHz	935 MHz to 960 MHz
E-GSM 900	880 MHz to 915 MHz	925 MHz to 960 MHz
DCS 1800	1 710 MHz to 1 785 MHz	1 805 MHz to 1 880 MHz
R-GSM 900	876 MHz to 915 MHz	921 MHz to 960 MHz

NOTE: In some circumstances, for instance when an operator (or more than one operator who co-ordinate the use of repeaters), is not allocated a complete band as defined in table 1, it may be necessary to restrict the frequency range of operations of repeaters. In these circumstances, the test of "Gain outside operating band" in annex A may be used to verify the performance of the repeater.

4.2 Test environments

For each test in the present document, the environmental conditions under which the repeater is to be tested are defined.

4.2.1 Normal test environment

When a normal test environment is specified for a test, the test should be performed under any combination of conditions between the minimum and maximum limits stated in table 2.

Table 2: Limits of conditions for Normal Test Environment

Condition	Minimum	Maximum
Barometric pressure	86 kPa	106 kPa
Temperature	15°C	30°C
Relative Humidity	20 %	85 %
Power supply	Nominal, as declared by the manufacturer	
Vibration	Negligible	

The ranges of barometric pressure, temperature and humidity represent the maximum variation expected in the uncontrolled environment of a test laboratory. If it is not possible to maintain these parameters within the specified limits, the actual values shall be recorded in the test report.

NOTE: This may, for instance, be the case for measurements of radiated emissions performed on an open field test site.

4.2.2 Extreme test environment

The manufacturer shall declare one of the following:

- the equipment class for the equipment under test, as defined in ETS 300 019-1-3 [3];
- the equipment class for the equipment under test, as defined in ETS 300 019-1-4 [4];
- for equipment that does not comply to an ETS 300 019-1 [2] class, the relevant classes from IEC 721 [8] documentation for temperature, humidity and vibration shall be declared.

NOTE: Reduced functionality for conditions that fall out side of the standard operational conditions are not tested in the present document. These may be stated and tested separately.

4.2.3 Extreme temperature

When an extreme temperature test environment is specified for a test, the test shall be performed at the standard minimum and maximum operating temperatures defined by the manufacturer's declaration for the equipment under test.

Minimum temperature:

- the test shall be performed with the environmental test equipment and methods of inducing the required environmental phenomena into the equipment, conforming to the test procedure of IEC 68-2-1 [7]. The equipment shall be maintained at the stabilized condition for the duration of the test sequence.

Maximum temperature:

- the test shall be performed with the environmental test equipment and methods of inducing the required environmental phenomena into the equipment, conforming to the test procedure of IEC 68-2-2 [7]. The equipment shall be maintained at the stabilized condition for the duration of the test sequence.

NOTE: It is recommended that the equipment is made fully operational prior to the equipment being taken to its lower operating temperature.

4.3 Manufacturers declarations

The manufacturer shall declare:

- a) the operating band or bands of the repeater;
- b) the maximum rated output power per channel;
- c) the number of channels supported by the repeater;
- d) the supported modulation methods.

4.4 Methods of measurement

The general methods of measurement and measurement uncertainty shall be according to ETR 027 [11] and ETR 028 [12] except where they conflict with the present document.

[SIST EN 300 609-4 V8.0.2:2003](https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246e3b7123/sist-en-300-609-4-v8-0-2-2003)

[https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-](https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246e3b7123/sist-en-300-609-4-v8-0-2-2003)

[b835-2246e3b7123/sist-en-300-609-4-v8-0-2-2003](https://standards.iteh.ai/catalog/standards/sist/799d0232-5550-4d70-b835-2246e3b7123/sist-en-300-609-4-v8-0-2-2003)

5 Spurious emissions

5.1 Test purpose

This test measures the conducted spurious emissions (see clause 3.1) at the antenna ports and the effective power of spurious emissions radiated by the cabinet and structure.

5.2 Test case

The repeater shall be set to maximum gain. All measurement steps, as described in this clause, apply to all antenna ports of the repeater.

- a) Spurious emissions from the antenna port:
 - one antenna port of the repeater shall be connected to a selective RF measurement device presenting to the repeater a load with an impedance of 50 ohms. An average power measurement of spurious emissions shall be performed for frequency offsets from the carrier frequency greater than 600 kHz under the following two conditions:
 - i) without any RF input signal. The relevant input antenna port of the repeater shall be terminated with 50 ohms;
 - ii) with an RF input signal. The relevant antenna input port of the repeater shall be connected to an RF signal generator. A continuous sinusoidal RF signal shall be input at a level which will result, when measured, in the maximum rated RF output power per channel, as declared by the manufacturer. The RF input signal shall be set to the centre frequency of the repeaters operating band. In the case of a channelized repeater,