

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Safety of laser products –
Part 12: Safety of free space optical communication systems used for
transmission of information**

**Sécurité des appareils à laser –
Partie 12: Sécurité des systèmes de communication optique en espace libre
utilisés pour la transmission d'informations**



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2022 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 300 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 19 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Safety of laser products –
Part 12: Safety of free space optical communication systems used for
transmission of information

Sécurité des appareils à laser –
Partie 12: Sécurité des systèmes de communication optique en espace libre
utilisés pour la transmission d'informations

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 31.260

ISBN 978-2-8322-6195-8

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	7
4 Assessment of access level.....	12
4.1 General.....	12
4.2 Determination of access level and the use of Condition 2.....	13
4.3 Access level 1 and 1M.....	14
4.4 Access level 2 and 2M.....	15
4.5 Access level 3R.....	16
4.6 Access level 3B.....	16
4.7 Access level 4.....	16
4.8 Time base.....	17
5 Classification and evaluation of access level.....	17
5.1 General.....	17
5.2 Impact of using automatic power reduction features.....	18
5.3 Automatic power reduction mechanisms (APR).....	18
5.3.1 General.....	18
5.3.2 APR performance requirements.....	18
5.4 Installation protection systems (IPS).....	19
6 Access level and classification requirements by location type.....	19
6.1 General.....	19
6.2 Requirements for unrestricted locations.....	22
6.2.1 General.....	22
6.2.2 Use of access level 1M and access level 2M FSOCS equipment in unrestricted locations.....	24
6.2.3 Use of access level 3R FSOCS equipment in unrestricted locations	26
6.2.4 General.....	26
6.2.5 Use of access level 3R FSOCS equipment in restricted locations	27
6.3 Requirements for controlled locations.....	28
6.3.1 General.....	28
6.3.2 Use of access level 3B and access level 4 FSOCS equipment in controlled locations.....	29
6.4 Requirements for inaccessible space.....	29
6.5 Specular reflections.....	29
7 Organizational requirements.....	30
7.1 Requirements for manufacturers of ready-to-use FSOCS transmitter or turn key systems.....	30
7.1.1 General.....	30
7.1.2 Additional manufacturer's requirements.....	31
7.2 Installation and service organization requirements.....	32
7.3 Operating organization requirements.....	33
8 Marking.....	33
8.1 General.....	33
8.2 Marking of aperture for transmitter.....	35
8.3 Durability – Indelibility requirements for safety markings.....	35

8.4	Warning for invisible radiation	35
Annex A (informative)	Rationale.....	36
Annex B (informative)	Clarification of the meaning of "access level"	37
B.1	General.....	37
B.2	Class	37
B.3	Access level.....	37
Annex C (informative)	Examples of applications and calculations.....	38
C.1	Symbols used in the example of this annex.....	38
C.2	Examples of NHZ and ENHZ	38
C.2.1	General	38
C.2.2	Example – Collimated beam access level 1M FSOCS.....	38
C.2.3	Example – Diverging beam access level 1M FSOCS.....	39
C.2.4	Example – Access level 3B FSOCS product	39
C.3	Viewing a specular (mirror-like) reflection	40
C.4	Example of divergent, diffuse IR transmitter	41
C.5	FSOCS link between two restricted locations	42
C.6	Unmanned (uncrewed) Aerial (aircraft) system (UAS)	45
Annex D (informative)	Methods of hazard/safety analysis	48
Annex E (informative)	Guidance for installing, servicing and operating organizations.....	49
E.1	Working practices for FSOCSs.....	49
E.1.1	General	49
E.1.2	General working practices	49
E.1.3	Additional working practices for Class/access level 1M, 2M, 3R, 3B and 4 systems	50
E.2	Education and training	50
Bibliography	51
Figure 1	– Commercial structures	20
Figure 2	– Residential areas	21
Figure 3	– Examples of external location types	23
Figure 4	– Access level 1M or 2M transmitter near edge of unrestricted rooftop.....	25
Figure 5	– Access level 1M transmitter in unrestricted location	25
Figure 6	– Access level 3R transmitter in restricted location	28
Figure C.1	– Link between two widely separated locations.....	42
Figure C.2	– Unmanned (uncrewed) Aerial (aircraft) System with FSOCS	45
Figure C.3	– Grounded FSOCS installed to the ground	46
Figure C.4	– Grounded FSOCS installed to the controlled location.....	46
Table 1	– Measurement aperture diameters and distances for the default (simplified) evaluation	14
Table 2	– Restrictions for the use of FSOCS based on access levels.....	22
Table 3	– Requirements for warning signs	32
Table 4	– Marking requirements.....	34
Table C.1	– Symbols used in the example of Annex C	38
Table C.2	– Allowed access levels and installation requirements	47

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SAFETY OF LASER PRODUCTS –**Part 12: Safety of free space optical communication systems
used for transmission of information**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60825-12 has been prepared by IEC technical committee 76: Optical radiation safety and laser equipment. It is an International Standard.

This third edition cancels and replaces the second edition published in 2019. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition.

- a) Where relevant and appropriate, references to IEC 60825-1 have been changed to a specific dated reference i.e. IEC 60825-1:2014.
- b) Condition 2 has been changed from 7 mm aperture stop and 70 mm distance as follows,
 - For wavelengths less than 1 400 nm, 3,5 mm aperture stop and 35 mm distance,
 - For wavelengths equal to or greater than 1 400 nm, 3,5 mm aperture stop and 14 mm distance.

- c) For wavelengths between 1 200 nm and 1 400 nm, an additional limitation is required equal to the equivalent radiant power of the skin MPE. C₇ has therefore been revised in accordance with IEC 60825-1:2014, but with this additional limitation related to the skin MPE; see 4.2.
- d) Additional detail added regarding time base, see 4.8.
- e) Additional clarification added to Clause 8 regarding the content and formatting of labels.
- f) Annex A has been added, providing a rationale for the differences in approach between this document and IEC 60825-1:2014.
- g) Annex B has been added, providing clarification of the meaning of the term "access level".
- h) Worked examples have been added for a variety of scenarios; see Clauses C.2 to C.5.
- i) Clause C.6 has been added on UAS, unmanned aerial systems.

The text of this International Standard is based on the following documents:

Draft	Report on voting
76/717/FDIS	76/722/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The list of all parts of the IEC 60825 series, published under the title *Safety of laser products*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The objective of this document is to:

- protect people from hazardous optical radiation emitted by FSOCSs;
- provide safety requirements and guidance for the design, manufacture and use of laser products or laser systems, which emit laser radiation for the purpose of free space optical data transmission;
- provide guidance for installation, operation, maintenance and service to assure the safe deployment and use of such laser systems.

This document only addresses the open beam portion of the laser product or laser system.

This document places the responsibility for certain product safety requirements, as well as requirements for providing appropriate information on how to use these systems safely, on the manufacturer of the system or the transmitters. It places the responsibility for the safe deployment and use of these systems on the installer or the operating organization. It places the responsibility for adherence to safety instructions during installation and service operations on the installation and service organizations as appropriate, and during operation and maintenance functions on the operating organization. It is recognized that the user of this document may fall into one or more of the categories of manufacturer, installer, service organization and/or operating organization as mentioned above.

Annex A gives a more detailed rationale for this document, and some examples are given in Annex C.

(standards.iteh.ai)

[IEC 60825-12:2022](https://standards.iteh.ai/catalog/standards/sist/b24eb0b3-8bfc-4abf-97bf-32a820c4161d/iec-60825-12-2022)

<https://standards.iteh.ai/catalog/standards/sist/b24eb0b3-8bfc-4abf-97bf-32a820c4161d/iec-60825-12-2022>

SAFETY OF LASER PRODUCTS –

Part 12: Safety of free space optical communication systems used for transmission of information

1 Scope

This part of IEC 60825 is applicable to products that emit laser radiation for the purpose of free space optical data transmission.

This document does not apply to laser products designed for the purposes of transmitting optical power for applications such as material processing or medical treatment. This document also does not apply to the use of laser products in explosive atmospheres (see IEC 60079-0). Light-emitting diodes employed by free space optical communication systems, used for the purpose of free space optical data transmission, do not fall into the scope of this document.

NOTE If the laser product incorporates an optical fibre that extends from the confinements by a system or enclosed space, the requirements in IEC 60825-2 apply.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60825-12:2022

IEC 60825-1:2014, *Safety of laser products – Part 1: Equipment classification and requirements*

60825-12-2022

IEC 60825-2, *Safety of laser products – Part 2: Safety of optical fibre communication systems (OFCSs)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60825-1:2014 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

access level

potential hazard at any accessible position as a result of the optical emissions from a free space optical communication system (FSOCS) installation

Note 1 to entry: The access level is based on the level of laser radiation which could become accessible in reasonably foreseeable circumstances, e.g. walking into an open beam path. It is closely related to the laser classification procedure in IEC 60825-1. The meaning of access level is clarified in Annex B.

Note 2 to entry: Practically speaking, it takes two or more seconds to fully align an optical aid with a beam (which might occur in an unrestricted location), and this delay is incorporated into the method for determining access level.

3.2

access level 1

assigned hazard at any accessible location within a FSOCS at which, under any reasonably foreseeable event, human access to laser radiation (accessible emission), evaluated by the measurement conditions for access level 1 as defined in Clause 4 of this document, will not exceed the accessible emission limits of Class 1 for the applicable wavelengths and emission duration, with additional constraints as defined in 4.3

Note 1 to entry: The "additional constraints" mentioned above refer to additional and stricter constraints that 4.3 of this document places on the values specified in IEC 60825-1:2014 for the accessible emission limits of Class 1 in the wavelength range 1 200 to 1 400 nm.

3.3

access level 1M

assigned hazard at any accessible location within a FSOCS at which, under any reasonably foreseeable event, human access to laser radiation (accessible emission), evaluated by the measurement conditions for access level 1M as defined in Clause 4 of this document, will not exceed the accessible emission limits of Class 1 for the applicable wavelengths and emission, with additional constraints as defined in 4.3

Note 1 to entry: The "additional constraints" mentioned above refer to additional and stricter constraints that 4.3 of this document places on the values specified in IEC 60825-1:2014 for the accessible emission limits of Class 1 in the wavelength range 1 200 to 1 400 nm.

3.4

access level 2

assigned hazard at any accessible location within a FSOCS at which, under any reasonably foreseeable event, human access to laser radiation (accessible emission), evaluated by the measurement conditions for access level 2 as defined in Clause 4 of this document, will not exceed the accessible emission limits of Class 2 for the applicable wavelengths and emission duration, with additional constraints as defined in 4.4

[IEC 60825-12:2022](#)

3.5

access level 2M

assigned hazard at any accessible location within a FSOCS at which, under any reasonably foreseeable event, human access to laser radiation (accessible emission), evaluated by the measurement conditions for access level 2M as defined in Clause 4 of this document, will not exceed the accessible emission limits of Class 2 for the applicable wavelengths and emission duration, with additional constraint as defined in 4.4

3.6

access level 3R

assigned hazard at any accessible location within a FSOCS at which, under any reasonably foreseeable event, human access to laser radiation (accessible emission), evaluated by the measurement conditions for access level 3R as defined in Clause 4 of this document, will not exceed the accessible emission limits of Class 3R for the applicable wavelengths and emission duration, with additional constraints as defined in 4.5

Note 1 to entry: The "additional constraints" mentioned above refer to additional and stricter constraints that 4.5 of this document places on the values specified in IEC 60825-1:2014 for the accessible emission limits of Class 1 in the wavelength range 1 200 to 1 400 nm.

3.7

access level 3B

assigned hazard at any accessible location within a FSOCS at which, under any reasonably foreseeable event, human access to laser radiation (accessible emission), evaluated by the measurement conditions for access level 3B as defined in Clause 4 of this document, will not exceed the accessible emission limits of Class 3B for the applicable wavelengths and emission duration, with additional constraints as defined in 4.6

3.8

access level 4

assigned hazard at any accessible location within a FSOCS at which, under any reasonably foreseeable event, human access to laser radiation (accessible emission), evaluated by the measurement conditions for access level 4 as defined in Clause 4 of this document, will exceed the accessible emission limits of Class 3B for the applicable wavelengths and emission duration, with additional constraints as defined in 4.7

Note 1 to entry: This document is applicable to the conditions of operation and maintenance of FSOCS. In order to achieve an adequate level of safety for persons who may come into contact with the optical transmission path, access level 4 is not permitted by this document. It is permitted to use protection systems, such as automatic power reduction (APR, see 3.10) or installation protection system (IPS: see 3.17), to achieve the required access level where the transmitted power under any operating conditions (e.g. normal and fault operation) exceeds that permitted for a particular location type. For instance, it is possible for accessible parts of an FSOCS to be access level 1 even though the power transmitted down the free space under normal operating conditions is Class 4.

3.9

aperture for transmitter

the window or laser transmissive port of FSOCS through which the beam is emitted into free space

3.10

automatic power reduction

APR

feature of a transmitter of an FSOCS, provided by the system equipment manufacturer, by which the accessible power in the nominal hazard zone (NHZ) or extended nominal hazard zone (ENHZ) is reduced to a specified value within a specified time

Note 1 to entry: The term "automatic power reduction" (APR) used in this document encompasses the following terms used in the International Telecommunication Union (ITU) Recommendation G.664:

- automatic laser shutdown (ALS);
- automatic power reduction (APR);
- automatic power shutdown (APSD).

3.11

beacon

optical source whose function is to aid in pointing or alignment of an FSOCS transmitter and/or receiver

3.12

end-to-end system

FSOCS that is comprised of at least one transmitter, one receiver, and any peripheral hardware necessary for the effective transfer of data along the transmission path from one position in space to another

3.13

extended nominal hazard zone

ENHZ

volume of space within which, when optical aids are used, the level of eye exposure to direct, reflected or scattered radiation exceeds the applicable maximum permissible exposure (MPE) as defined in IEC 60825-1:2014

Note 1 to entry: Exposure levels outside the boundary of the ENHZ are below the applicable MPE when optical aids are used.

Note 2 to entry: This volume is determined prior to activation of any IPS or APR systems unless the APR is used for classification under the conditions of Clause 5 of this document.

3.14
free space optical communication system
FSOCS

installed, portable, or temporarily mounted, through-the-air system typically used, intended or promoted for voice, data or multimedia communications and/or control purposes via the use of FSOCS transmitter

Note 1 to entry: "Free space" means the volume of air into which the laser radiation is emitted.

Note 2 to entry: Emitting and detecting assemblies are sometimes separated and sometimes not be separated.

3.15
FSOC transmitter
transmitter

optical transmitter emitting radiation through the air and used in an FSOCS

3.16
installation organization
installer

organization or individual who is responsible for the installation of an FSOCS

3.17
installation protection system
IPS

feature of an installation site, provided by the installer or operating organization, that has two functions: (1) it detects human entry into the accessible volume of either the NHZ for restricted or controlled locations or the ENHZ for an unrestricted location, and (2) once such entry is detected, causes reduction of the accessible power of the laser to a specified level within a specified time

3.18
interlock

standards.iteh.ai/catalog/standards/sist/b24eb0b3-8bfc-4abf-97bf-32a820c4161d/iec-60825-12-2022

means either of preventing access to a hazardous zone until the hazard is removed, or of automatically removing the hazardous condition when access is gained

Note 1 to entry: Interlocks should be failsafe (see 60825-1:2014 3.39), that is when the interlock is in the failure mode does not defeat the purpose of the interlock.

3.19
location

position or site occupied or available for occupancy

Note 1 to entry: Other standards may use the same terms for location types (3.20 to 3.23) with somewhat different definitions.

3.20
location of inaccessible space
inaccessible space

volume where a person cannot normally be located, i.e. the space that has a horizontal spacing more than 2,5 m from any unrestricted location and is both greater than 6 m above a surface in any unrestricted location, and more than 3 m above a surface in any restricted location

Note 1 to entry: Inaccessible space may be entered by, for example, aircraft.

Note 2 to entry: All open space that is neither an unrestricted, restricted nor controlled location.

3.21
location with controlled access
controlled location

location where an engineering and administrative control measures are present to make it inaccessible except to authorized personnel with appropriate laser safety training

3.22**location with restricted access**
restricted location

location that is normally inaccessible to the general public (including workers, visitors, and residents in the immediate vicinity) by means of any administrative or engineering control measure but that is accessible to authorized personnel (e.g. maintenance or service personnel including window cleaners in exterior locations) who did not have laser safety training

3.23**location with unrestricted access**
unrestricted location

location where access to the transmission/receiver equipment and open beam is not limited (accessible to the general public)

3.24**manufacturer**

organization or individual who makes or assembles optical devices and other components for the construction or modification of an FSOCS

3.25**nominal hazard zone**
NHZ

volume within which the level of eye exposure to direct, reflected or scattered radiation exceeds the applicable maximum permissible exposure (MPE) as defined in IEC 60825-1:2014

Note 1 to entry: Exposure levels outside the boundary of the NHZ are below the applicable MPE.

Note 2 to entry: This volume is determined prior to activation of any IPS or APR systems unless the APR is used for classification under the conditions of Clause 5 of this document.

3.26**operating organization**
operator

organization or individual who is responsible for the operation and maintenance of an FSOCS

3.27**optically-aided**

use of optical aids to view an emitting source from within the emitted beam

Note 1 to entry: It is possible that telescopic optics, including binoculars, could increase the hazard to the eye by intrabeam viewing of a collimated beam when viewed at a distance.

Note 2 to entry: Optical aids are for example, binoculars or magnifiers.

Note 3 to entry: Prescription eyeglasses and contact lenses are not considered optical aids.

3.28**removable laser system**

laser system that can be removed from its protective housing and operated by simply plugging into electrical mains or connection to a battery

3.29**primary beam**

beam that transmits the modulated data signal

3.30**reasonably foreseeable event**

event (or condition) that is credible and whose likelihood of occurrence (or existence) cannot be disregarded

3.31**service organization**

organization or individual who is responsible for the service of an FSOCS

Note 1 to entry: The term service is defined in IEC 60825-1:2014, 3.79.

3.32**special tool**

tool that is not readily available at retail consumer hardware stores

Note 1 to entry: Typical tools in this category are intended for use with tamper-resistant fasteners.

3.33**spillover**

beam radiant energy that propagates past the receiving terminal

3.34**time base**

emission duration to be considered for determination of access level

3.35**without optical aids****optically unaided**

without using magnifiers or other optical aids, as with the naked eye

Note 1 to entry: Prescription eyeglasses and contact lenses are not considered optical aids.

4 Assessment of access level**4.1 General**

The FSOC transmitter shall comply with the applicable requirement of IEC 60825-1:2014.

If an FSOCS incorporates a removable laser system, that removable laser system shall comply with the applicable requirements of IEC 60825-1.

FSOCSs have limitations imposed by this document that are dependent on the location type(s) in which they are installed. Product classification and access level restrictions by location type are summarized in Table 2.

For each location where emission is transmitted, crosses or is received, respective exposure conditions shall be individually evaluated. Furthermore, potentially occupied locations along the beam path, within the NHZ or ENHZ, shall also be evaluated for acceptable access levels (Table 2) and appropriate controls applied. Locations which could be traversed by reflections, actual or potential, of the beam shall also be evaluated if the emission could exceed access level 1 or 2. At a given location, the installation and operational constraints applied from Clause 6 shall be determined by whichever is the more hazardous: the transmitted or the received optical radiation.

The correct allocation of access levels is the ultimate responsibility of the operating organization. However, the access levels may be determined by the maintenance, installation or service organization; or even by the manufacturer, provided the operating organisation is able to provide the manufacturer with sufficient information regarding the precise environment in which the particular FSOCS is to be deployed. The methods for determining compliance with an access level are the same as those described for classification in IEC 60825-1 except for the following.

- a) The access level within a designated location shall be determined at any position relative to an FSOCS transmitter where the access level is maximized.

NOTE The maximized access level can be driven by many factors such as windows and transmitter orientation (in particular for transmitters with dynamic pointing).

- b) The access level may depend on the activation of an IPS or APR system.
- c) If an IPS or APR system is monitoring the location in question, it shall meet the performance requirements defined in 5.3.2. Otherwise, the same method used for classification is also used for determination of access level. For viewing conditions without optical aids refer to the tables of MPEs in IEC 60825-1.

Verification testing of access levels shall be carried out under reasonably foreseeable fault conditions to ensure that the APR and/or IPS, if used, is operating properly. In circumstances where it is difficult to carry out direct measurements, an assessment of the access level based on calculations is acceptable. Faults which result in the emission of radiation in excess of the applicable AEL for a limited period only and for which it is not reasonably foreseeable that human access to the radiation will occur before the product is taken out of service or adjusted down below the AEL, need not be considered.

4.2 Determination of access level and the use of Condition 2

The access level is determined by the measurement of the optical radiation that could become accessible following any reasonably foreseeable event during operation and maintenance. The methods for the determination of compliance with the specified radiation limit values are the same as those described for classification in IEC 60825-1.

In this document three conditions shall be tested. Condition 1 and Condition 3 shall be tested according to IEC 60825-1 and the condition 2 measurements to establish access levels shall be made with,

- for wavelength less than 1 400 nm, 3,5 mm aperture at a distance of 35 mm
- for wavelength equal or greater than 1 400 nm, 3,5 mm aperture at a distance of 14 mm

from the end of the FSOCS transmitter (this simulates a × 18 magnifier), as described in Table 1.

In addition to the above, if the FSOCS transmitter is access level 3B and is handheld, the total emission at any wavelength shall not exceed the AEL of Class 3B.

In circumstances where it is difficult to carry out direct measurements, an assessment of access level based on calculations is acceptable.

For an FSOCS with automatic power reduction (see 5.3.2 for APR performance requirements), the access level will be determined by the accessible emission (pulsed or continuous wave) after the time interval of 2 s. Additionally the MPE requirement in 5.2 shall be satisfied.