



Designation: D4008 – 19

Standard Guide for Measuring Anti-Soil Deposition Properties of Laundry Detergents¹

This standard is issued under the fixed designation D4008; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This guide provides direction for measuring the ability of detergents to prevent the deposition of soils from detergent solutions onto fabrics. It is intended as a laboratory screening test to aid in the formulation of detergent products, for quality control, and as a basis between the purchaser and seller in standardizing specific products' performance.

1.2 The anti-soil deposition performance of detergent products will vary greatly depending on the type of soils and fabrics used in the test. Therefore, selection of the soils, fabrics, reference detergents, and test conditions shall be made by agreement between the interested parties on the basis of experience.

1.3 There is no single or combination of oily soils or particulate soils, or both, that will precisely predict overall the performance of a product or treatment with respect to anti-redeposition as perceived by a consumer. This guide is intended to assess or compare detergent performance with respect to the anti-redeposition performance for the specific soil chosen.

1.4 The values stated in either inch-pound or SI units are to be regarded separately as the standard. The values given in parentheses are for information only.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.* Material safety data sheets are available for reagents and materials. Review them for hazards prior to usage.

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recom-*

mendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

2. Referenced Documents

2.1 *ASTM Standards:*²

[D1193 Specification for Reagent Water](#)

[E97 Method of Test for Directional Reflectance Factor, 45-Deg 0-Deg, of Opaque Specimens by Broad-Band Filter Reflectometry \(Withdrawn 1991\)](#)³

[E313 Practice for Calculating Yellowness and Whiteness Indices from Instrumentally Measured Color Coordinates](#)

3. Terminology

3.1 *Definitions of Terms Specific to This Standard:*

3.1.1 *reflectance retention*—the change in reflectance between clean fabric and the same fabric after laundering.

3.1.2 *soil deposition*—the soiling of clean fabrics by soil that has been added to the wash bath rather than by soil removed from another fabric.

3.1.3 *soil redeposition*—the soiling of clean, or relatively clean, fabrics during the laundering process by soil that has been removed from another fabric.

4. Summary of Guide

4.1 Swatches of clean fabrics are washed, a minimum of three times, in solutions of the test detergent prepared to contain known amounts of particulate and oily soils.

4.1.1 Identical clean swatches are similarly exposed to prepared solutions of a suitable reference detergent containing an identical soil load. The ability of the test detergent to prevent soil deposition is estimated by comparing the reflectance retention of the swatches washed in the test detergent to the reflectance retention of those washed in the reference detergent.

¹ This guide is under the jurisdiction of ASTM Committee D12 on Soaps and Other Detergents and is the direct responsibility of Subcommittee D12.15 on Physical Testing.

Current edition approved June 1, 2019. Published July 2019. Originally approved in 1981. Last previous edition approved in 2016 as D4008 – 16. DOI: 10.1520/D4008-19.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

5. Significance and Use

5.1 The guide can be used to compare anti-redeposition performance of products; however, there is no confirmed basis for correlation of this controlled laboratory technique with consumers' ranking of anti-redeposition performance.

6. Apparatus

6.1 *Laboratory Washer*—A laboratory-scale, agitator-type washing machine.⁴

6.2 *Reflectometer or Spectrophotometer*.

7. Reagents and Materials

7.1 *Purity of Reagents*—Reagent grade chemicals shall be used in all tests. Unless otherwise indicated, it is intended that all reagents shall conform to the specifications of the Committee on Analytical Reagents of the American Chemical Society, where such specifications are available.⁵ Other grades may be used, provided it is first ascertained that the reagent is of sufficiently high purity to permit its use without lessening the accuracy of the determination.

7.2 *Purity of Water*—Unless otherwise indicated, references to water shall be understood to mean Type IV reagent water conforming to Specification **D1193**.

7.3 *Standard Soils*—Laboratory prepared soils or commercially available soils may be used. For example, vacuum cleaner dirt, air conditioner filter dirt, and colored clay material, or mixtures of two or more of these can be used as particulate soil. Triglyceride, fatty acid, paraffinic hydrocarbon, and fatty alcohol are examples of oily soils that may be used. Mixtures of two or more of these oily soils or a mixture based on the components of human sebum may also be used. The oily soils may be added as emulsions or solvent solutions or they may be added after first mixing with the particulate soil in a solvent solution and subsequent evaporation of the solvent.

NOTE 1—A 1:1 mixture of vacuum cleaner dirt and Bandy Black clay has been found suitable as a particulate soil. A suggested use level of this soil is 0.5 g/1000 mL of wash solutions. The vacuum cleaner dirt can be obtained from domestic or office locations. Before use, it is screened through a 150-mesh screen to remove lint, trash, and coarse particles.

A 1:1 mixture of triolein (technical) and mineral oil (Saybolt viscosity 340 to 350) has also been found satisfactory. A suggested use level is 0.100 g/1000 mL of wash solution.

An artificial sebum composition has also been found suitable as an oily soil. A useful formula for such a composition was reported by Spangler and Schaafsma.⁶ A suggested use level is 0.100 g/1000 mL of wash solution.

7.3.1 The following procedure is a satisfactory method for convenient addition of particulate and oily soils to the wash bath: Thoroughly blend together 20 g of Bandy Black clay and

20 g of vacuum cleaner dirt. Add this mixture to 150 mL of methylene chloride containing 4 g of triolein and 4 g of mineral oil. While constantly stirring this mixture, evaporate the solvent under a heat lamp in a hood. The oily/particulate soil is gently ground in a mortar and pestle to disperse any lumps, that may have formed. Store the soil mixture at refrigerator temperature until use. Recommended use level of this combined soil is 0.600 g/1000 mL of wash solution.

7.4 *Standard Clean Fabrics*—Because different fabrics have different soiling characteristics depending on their surface chemistry and morphology, it is recommended that several fabric types be used. For example, cotton, nylon, polyester, and polyester/cotton blends may be used. These may be cut to 4 by 4½ in. in size with pinked, merrowed, or fused edges to prevent unraveling. Multiple swatches of each fabric should be used for each test. Test each fabric type separately. Pay special attention to the identification of finishes, for example durable-press, soil-release, etc.

NOTE 2—A preliminary laundering of the fabric may be desired to remove any material that might interfere with the test.

7.5 *Reference Detergent*—A comparison detergent suitable to the fabric and conditions shall be included in each run, if desired.

7.6 *Hard-Water Stock Solution*—Prepare a hard-water stock solution by dissolving 2.940 ± 0.002 g of calcium chloride dihydrate ($\text{CaCl}_2 \cdot 2\text{H}_2\text{O}$) and 2.033 ± 0.002 g of magnesium chloride hexahydrate ($\text{MgCl}_2 \cdot 6\text{H}_2\text{O}$) in about 300 mL of water. Dilute to a volume of 1 L with additional water. This solution contains 3000 ppm hardness (expressed as calcium carbonate) with a Ca + Mg molar ratio of 2:1. Other ratios may be used.

7.7 *Calcium/Magnesium Ratio (as CaCO_3)*—It is suggested that this ratio be adjusted for different water hardnesses as follows:

Water Hardness Range, ppm (gpg)	Calcium/ Magnesium Ratio
0 to 60 (0 to 3.5)	4:1
61 to 120 (3.6 to 7.0)	3:1
121 and over (7.1 and over)	2:1

These ratios are based on calculations derived from data included in Public Water Supplies of 100 Largest Cities in the United States, by E. Becker and C. N. Durfor; U. S. Government Printing Office, 1964.

8. Sampling

8.1 Samples of the detergent to be tested and of the reference detergent shall be obtained from homogeneous lots and stored in nearly filled, airtight containers until tested.

9. Reflectance Determinations

9.1 If using a reflectometer, operate the instrument in accordance with the instructions supplied with the instrument for 45°, 0° luminous reflectance using a procedure that avoids fluorescence effects. Standardize the instrument with standard vitreous enamel plaques that have reflectances closest to the reflectances of the swatches being measured. Use sufficient layers of the fabric being read, so that addition of another layer

⁴ The Terg-o-tometer has been found satisfactory.

⁵ *Reagent Chemicals, American Chemical Society Specifications*, American Chemical Society, Washington, DC. For suggestions on the testing of reagents not listed by the American Chemical Society, see *Analar Standards for Laboratory Chemicals*, BDH Ltd., Poole, Dorset, U.K., and the *United States Pharmacopeia and National Formulary*, U.S. Pharmacopeial Convention, Inc. (USPC), Rockville, MD.

⁶ Spangler, W. G., Cross, H. D., and Schaafsma, B. R., "A laboratory method for testing laundry products for detergency," *Journal of the American Oil Chemists' Society*, Vol 42, 1965, p. 723.