

INTERNATIONAL STANDARD



3D display devices – **STANDARD PREVIEW**
Part 1-2: Generic – Terminology and letter symbols
(standards.iteh.ai)

[IEC 62629-1-2:2021](https://standards.iteh.ai/catalog/standards/sist/f86f4832-4d53-461a-afdd-e9db7326bcab/iec-62629-1-2-2021)

<https://standards.iteh.ai/catalog/standards/sist/f86f4832-4d53-461a-afdd-e9db7326bcab/iec-62629-1-2-2021>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

[IEC 62629-1-2:2021](https://standards.iteh.ai/catalog/standards/sist/f86f4832-4d53-461a-afdd-e9db7326bcab/iec-62629-1-2-2021)

<https://standards.iteh.ai/catalog/standards/sist/f86f4832-4d53-461a-afdd-e9db7326bcab/iec-62629-1-2-2021>

INTERNATIONAL STANDARD



3D display devices – Part 1-2: Generic – Terminology and letter symbols
STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/f86f4832-4d53-461a-afdd-e9db7326bcab/iec-62629-1-2-2021>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.120; 31.260

ISBN 978-2-8322-1024-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references.....	5
3 Terms and definitions	5
3.1 General terms	5
3.2 Terms related to components	8
3.3 Terms related to performance specifications	9
Annex A (informative) Definition guidelines for terms which include "image", "view" or "vision".....	10
A.1 General.....	10
A.2 Definition guidelines.....	10
A.2.1 Stereoscopic image and stereoscopic view	10
A.2.2 Convention in using the plural form of stereoscopic image and stereoscopic view.....	11
A.2.3 View and vision.....	12
A.2.4 Imaging and vision	12
Annex B (informative) Classification of 3D display types	13
B.1 General.....	13
B.2 Classification	13
B.2.1 3D display.....	13
B.2.2 Stereoscopic display	13
B.2.3 Autostereoscopic display.....	13
Annex C (informative) Relation between depth perception and 3D display.....	15
C.1 General.....	15
C.2 Depth perception by binocular parallax when viewing a 3D display	15
C.3 Convergence accommodation conflict when viewing a 3D display.....	15
C.4 Horizontal-parallax-only and full-parallax 3D display	16
Annex D (informative) Lobe.....	18
Annex E (informative) Relationship between integral imaging display and light field display.....	19
Bibliography	21
Figure A.1 – Difference between "image" and "view".....	10
Figure A.2 – Structure of multi-view display	11
Figure A.3 – Stereoscopic images and stereoscopic views.....	12
Figure B.1 – Classification of 3D displays.....	14
Figure C.1 – Depth perception by convergence when viewing a 3D display	15
Figure C.2 – Vergence-accommodation conflict	16
Figure C.3 – Horizontal and vertical parallax	17
Figure D.1 – Lobe of autostereoscopic display.....	18
Figure E.1 – Display configurations that reproduce the light field	20

INTERNATIONAL ELECTROTECHNICAL COMMISSION

3D DISPLAY DEVICES –**Part 1-2: Generic – Terminology and letter symbols**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62629-1-2 has been prepared by IEC technical committee 110: Electronic displays. It is an International Standard.

This second edition cancels and replaces the first edition published in 2013. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) added new terms related to holographic display and light field display;
- b) added new terms on the performance specifications used in other IEC 62629 series documents;
- c) added Annex C to explain the depth perception in 3D displays in more detail.

The text of this International Standard is based on the following documents:

Draft	Report on voting
110/1287/CDV	110/1330/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

In this standard, the following print types are used:

- *Terms defined within Clause 3: in italics type.*

A list of all the parts in the IEC 62629 series, under the general title *3D display devices*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, <https://standards.iteh.ai/catalog/standards/sist/f86f4832-4d53-461a-afdd-c9db7326bcab/iec-62629-1-2-2021>
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

3D DISPLAY DEVICES –

Part 1-2: Generic – Terminology and letter symbols

1 Scope

This part of IEC 62629 provides a list of the terminologies that are frequently used in describing 3D display technologies in the IEC 62629 series. Terms for various 3D display technologies on stereoscopic, autostereoscopic, volumetric, and holographic displays are included.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>
<https://standards.iteh.ai/catalog/standards/sist/f86f4832-4d53-461a-afdd-e9db7326bcab/iec-62629-1-2-2021>

3.1 General terms

3.1.1

3D display

display device giving depth perception with physiological depth cues

Note 1 to entry: Physiological depth cues include accommodation, convergence, binocular parallax, and motion parallax. The 3D display provides users with all or some of the physiological depth cues so that they can perceive depth. Physiological depth cues should be distinguished from pictorial depth cues which can also be provided by the usual 2D displays. Pictorial depth cues are features in an image that give a hint of the depth. Examples of pictorial depth cues are texture gradient, shadow, occlusion, and vanishing lines. See Annex C.

3.1.2

stereoscopic display

3D display providing binocular parallax

Note 1 to entry: See *autostereoscopic display* (3.1.3). For classification of the 3D displays, see Annex B.

3.1.3

autostereoscopic display

stereoscopic display that requires no viewing aids

Note 1 to entry: See *stereoscopic display* (3.1.2). For classification of the 3D displays, see Annex B.

3.1.4

two-view display

two-view autostereoscopic display

autostereoscopic display providing one stereoscopic view

Note 1 to entry: See *multi-view display* (3.1.5).

3.1.5**multi-view display****multi-view autostereoscopic display**

autostereoscopic display providing multiple stereoscopic views

Note 1 to entry: See *two-view display* (3.1.4).

3.1.6**integral imaging display****integral imaging autostereoscopic display****light field display**

autostereoscopic display that reproduces ray space

Note 1 to entry: Depending on the light field or ray space that the display reproduces, the display may not be an autostereoscopic display. For example, if the reproduced light field allows the user to recognize information only at a pre-defined authorized condition, then the display is a secure display, not an autostereoscopic display. But in the IEC 62629 series, the light field is limited to the one corresponding to the 3D images such that the display reproducing the light field is an autostereoscopic display.

Note 2 to entry: If the angular range of the light field reconstruction does not cover the two eyes of the user, the display is a monocular 3D display, not an autostereoscopic display. However, in the IEC 62629 series, the light field display is limited to the autostereoscopic display.

Note 3 to entry: An integral imaging display is the same as a light field display. Sometimes, though, it could refer to a subset of the light field display which uses an array of lenslets or pinholes for the reproduction of light field. See Annex E.

3.1.7**voxel**

volume pixel which can be addressed to control its light intensity

Note 1 to entry: Voxel includes not only the physical element that emits or reflects light but also the optical image point to which light from the display converges or diverges from.

3.1.8**volumetric display**

autostereoscopic display which forms a set of voxels distributed in space

3.1.9**stereoscopic image**

pair of images with parallax shown on a stereoscopic display

Note 1 to entry: Stereoscopic images are made by capturing images of an object from slightly different positions and are used as output of a stereoscopic display. See Annex A.

3.1.10**stereoscopic view**

pair of sights provided by a stereoscopic display, which induce stereopsis

Note 1 to entry: Stereoscopic view is generally not the same as stereoscopic image. In some cases, more than a single monocular image is projected on the retina of an eye by crosstalk. See Annex A.

3.1.11**monocular image**

one part of a stereoscopic image

Note 1 to entry: See A.2.2 and Figure A.3.

3.1.12**monocular view**

one part of a stereoscopic view

Note 1 to entry: See A.2.2 and Figure A.3.

3.1.13**designed viewing distance**

viewing distance recommended by the manufacturer of the 3D display

Note 1 to entry: For a detailed measurement procedure, see IEC 62629-22-1 [3]¹.

3.1.14**lobe**

space wherein one or multiple stereoscopic images are projected in correct angular order by an autostereoscopic display

Note 1 to entry: See Annex D.

3.1.15**ray space****light field**

spatial and angular distribution of light rays

Note 1 to entry: Distribution of the light rays in a space can be described by a plenoptic function, also called light field, which represents intensity as a 7D function of spatial position (3D), direction (2D), wavelength (1D), and polarization (1D) of the rays. The 7D plenoptic function can be reduced to a 4D ray space which only represents the ray angular direction (2D) and the spatial position (2D) intercepting a plane. Although the light field originally means the plenoptic function, it is also frequently used in its reduced meaning of ray space. In this document, the ray space and the light field have the same meaning, representing 4D distribution of the light rays.

3.1.16**holographic display**

autostereoscopic display that generates continuous wavefront converging to each point of a 3D image in space by light diffraction

Note 1 to entry: In its broad meaning, holographic display does not require continuity of the wavefront.

Note 2 to entry: For a detailed explanation, see IEC TR 62629-41-1 [4].

Note 3 to entry: If the angular range of the wavefront generation does not cover the two eyes of the user, then the display is a monocular 3D display, not an autostereoscopic display. However, in the IEC 62629 series, the holographic display is limited to the autostereoscopic display.

3.1.17**holographic stereogram display**

autostereoscopic display that provides discrete stereoscopic views by light diffraction

Note 1 to entry: A full parallax holographic stereogram display generates a discrete wavefront converging to each point of a 3D image and can be considered as the holographic display in its broad meaning.

Note 2 to entry: For a detailed explanation, see IEC TR 62629-41-1 [4].

3.1.18**complex amplitude**

complex value representing amplitude and phase of the light wave

Note 1 to entry: For a detailed explanation, see IEC TR 62629-41-1 [4].

3.1.19**wavefront**

locus of spatial points that share the same phase of the light wave

Note 1 to entry: For a detailed explanation, see IEC TR 62629-41-1 [4].

¹ Numbers in square brackets refer to the Bibliography.

3.1.20**aerial display**

display that forms a real image in mid-air by use of an incoherent light source display and a passive optical component to converge diverging light from the light source display

Note 1 to entry: For a detailed explanation, see IECTR 62629-51-1 [5].

3.2 Terms related to components**3.2.1****active glasses, pl.**

glasses whose left and right lenses alternate their optical characteristics, by synchronizing with displayed sequential images on a stereoscopic display (e.g., synchronizing with TV fields, TV frame, etc.) to separate the displayed images into left and right monocular views

Note 1 to entry: Usually left and right images are displayed alternately on a screen. When a left image is displayed, the left lens of the active glasses is turned on to transmit the image and the right lens is turned off to cut off the image. The lenses do not need a function for focusing light.

3.2.2**passive glasses, pl.**

glasses whose left and right lenses have complementary but fixed optical characteristics to separate displayed images on a stereoscopic display into left and right monocular views

Note 1 to entry: Usually left and right images are displayed on a screen with spatial or temporal multiplexing. In the spatial multiplexing, spatially divided left and right images are displayed at the same time on a screen; each divided segment in the screen emits polarized light to display the images, and the left and right segments have orthogonal polarization. The left lens of the passive glasses has a polarization to pass the emitted light of the left images and to cut off that of the right images, while the right lens passes the right images and cuts off the left images. In the temporal multiplexing, left and right images are displayed sequentially on a screen with alternating orthographic polarizations. The left lens of the passive glasses has a polarization to pass the emitted light of the left image frames to cut off that of the right image frames, while the right lens does the opposite.

3.2.3**polarized glasses, pl.**

passive glasses equipped with two polarizers whose polarization properties are opposite to each other

Note 1 to entry: See *linearly polarized glasses* (3.2.4) and *circularly polarized glasses* (3.2.5).

3.2.4**linearly polarized glasses, pl.**

passive glasses equipped with two linear polarizers whose polarizing directions are orthogonal to each other

Note 1 to entry: See *polarized glasses* (3.2.3) and *circularly polarized glasses* (3.2.5).

3.2.5**circularly polarized glasses, pl.**

passive glasses equipped with two circular polarizers whose rotational directions of circular polarization are orthogonal to each other

Note 1 to entry: See *polarized glasses* (3.2.3) and *linearly polarized glasses* (3.2.4).

3.2.6**patterned retarder**

array of two kinds of optical phase retarders arranged alternatively in a plane

3.2.7**parallax barrier**

barrier with an array of slits for providing one or multiple stereoscopic views

3.2.8

lenticular lens **lenticular sheet**

set of semi-cylindrical lenses that are arranged side by side in a plane

3.2.9

fly-eye lens

set of lenslets that are arranged in a plane

3.2.10

spatial light modulator

device that spatially modulates the complex amplitude of light

Note 1 to entry: Depending on the modulation type, the usual spatial light modulators can be classified into amplitude-only and phase-only spatial light modulators.

3.3 Terms related to performance specifications

3.3.1

interocular chromatic difference

difference in chromaticity between left and right monocular views

Note 1 to entry: For a detailed measurement procedure, see IEC 62629-12-1 [2].

3.3.2

interocular contrast difference

difference in contrast between left and right monocular views

Note 1 to entry: For a detailed measurement procedure, see IEC 62629-12-1 [2].

3.3.3

interocular luminance difference

difference in luminance between left and right monocular views

Note 1 to entry: For a detailed measurement procedure, see IEC 62629-12-1 [2].

3.3.4

interocular crosstalk

luminance leakage into the observed monocular view of an eye from the monocular image for the other eye

Note 1 to entry: For a detailed measurement procedure, see IEC 62629-12-1 [2].

3.3.5

3D crosstalk

luminance leakage into an observed monocular view from other monocular images that are not designed to be seen at the observing position

Note 1 to entry: For a detailed measurement procedure, see IEC 62629-22-1 [3].

3.3.6

ghost

image artefact that the observer perceives due to the incomplete image separation of the left and right views

Note 1 to entry: For a detailed measurement procedure, see IEC 62629-13-1 [6].