

9`Y_fca U[bYfbUnXfi y`^j cgh]b`nUXYj Yj`nj Yn]`n`fUX]`g_`ja`gdY_fca`fØFAŁË
BUdfUj Y`fUh_Y[UXcgY[UfGF8 gŁËFUX]`g_UcdfYa Uj`ZY_j Yb bYa`cVa c`f`cX`-
`<n`Xc`&`A<n]`b`g]ghYa]`n]`bXi`_W]`g_c`nUb_c`j`ZY_j Yb bYa`cVa c`f`cX`-`<n`Xc`
'`\$`A<n`Ë`%`r`XY.`HY b] bY`_UFU`Hf]gh]_Y]b`dfYg_i gbYa YrcXY

ElectroMagnetic Compatibility and Radio Spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz; Part 1: Technical characteristics and test methods

STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 330-1 V1.3.1:2003](https://standards.iteh.ai/catalog/standards/sist/44f9d7b5-3d44-44c7-a32e-4130503e474b/sist-en-300-330-1-v1-3-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/44f9d7b5-3d44-44c7-a32e-4130503e474b/sist-en-300-330-1-v1-3-1-2003>

Ta slovenski standard je istoveten z: EN 300 330-1 Version 1.3.1

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

SIST EN 300 330-1 V1.3.1:2003 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 330-1 V1.3.1:2003

<https://standards.iteh.ai/catalog/standards/sist/44f9d7b5-3d44-44c7-a32e-4130503e474b/sist-en-300-330-1-v1-3-1-2003>

ETSI EN 300 330-1 V1.3.1 (2001-06)

European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Short Range Devices (SRD);
Radio equipment in the frequency range
9 kHz to 25 MHz and inductive loop systems
in the frequency range 9 kHz to 30 MHz;
Part 1: Technical characteristics and test methods**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 330-1 V1.3.1:2003](https://standards.iteh.ai/catalog/standards/sist/44f9d7b5-3d44-44c7-a32e-4130503e474b/sist-en-300-330-1-v1-3-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/44f9d7b5-3d44-44c7-a32e-4130503e474b/sist-en-300-330-1-v1-3-1-2003>



Reference

REN/ERM-RP08-0405-1

Keywords

radio, SRD, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 330-1 V1.3.1:2003

<https://standards.iteh.ai/catalog/standards/sist/44f9d7b5-3d44-44c7-a32e-4130503e474b/sist-en-300-330-1-v1-3-1-2003>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.
All rights reserved.

Contents

Intellectual Property Rights	7
Foreword	7
1 Scope	8
2 References	9
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Symbols	10
3.3 Abbreviations	10
4 Technical requirements specifications	11
4.1 General requirements	11
4.1.1 Receiver classification	11
4.1.2 General performance criteria	11
4.2 Presentation of equipment for testing purposes	11
4.2.1 Choice of model for testing	12
4.2.2 Testing of equipment with alternative radiated field or power levels	12
4.2.3 Testing of equipment that does not have an external 50 Ohm RF connector (integral antenna equipment)	12
4.2.3.1 Equipment with an internal permanent or temporary antenna connector	12
4.2.3.2 Equipment with a temporary antenna connector	12
4.2.4 On-site testing	12
4.3 Mechanical and electrical design	13
4.3.1 General	13
4.3.2 Controls	13
4.3.3 Transmitter shut-off facility	13
4.3.4 Receiver mute or squelch	13
4.3.5 Marking (equipment identification)	13
4.3.5.1 Equipment identification	13
4.3.5.2 Regulatory marking	13
4.4 Declarations by the applicant	13
4.5 Auxiliary test equipment	13
4.6 Interpretation of the measurement results	14
5 Test conditions, power sources and ambient temperatures	14
5.1 Normal and extreme test conditions	14
5.2 Test power source	14
5.2.1 External test power source	14
5.2.2 Internal test power source	14
5.3 Normal test conditions	15
5.3.1 Normal temperature and humidity	15
5.3.2 Normal test power source	15
5.3.2.1 Mains voltage	15
5.3.2.2 Regulated lead-acid battery power sources	15
5.3.2.3 Other power sources	15
5.4 Extreme test conditions	15
5.4.1 Extreme temperatures	15
5.4.1.1 Procedure for tests at extreme temperatures	15
5.4.1.1.1 Procedure for equipment designed for continuous operation	16
5.4.1.1.2 Procedure for equipment designed for intermittent operation	16
5.4.1.2 Extreme temperature ranges	16
5.4.2 Extreme test source voltages	16
5.4.2.1 Mains voltage	16
5.4.2.2 Regulated lead-acid battery power sources	16
5.4.2.3 Power sources using other types of batteries	17
5.4.2.4 Other power sources	17

6	General conditions	17
6.1	Normal test signals and test modulation	17
6.1.1	Normal test signals for analogue speech	17
6.1.2	Normal test signals for data	17
6.2	Artificial antenna.....	18
6.2.1	Artificial antenna for inductive transmitters (non 50 Ohm).....	18
6.2.2	Artificial antenna for transmitters with 50 Ohm impedance connector	18
6.3	Test fixture.....	18
6.4	Test sites and general arrangements for radiated measurements	19
6.5	Modes of operation of the transmitter.....	19
6.6	Measuring receiver	19
7	Transmitter requirements	20
7.1	Transmitter definitions	20
7.1.1	The inductive loop coil transmitters.....	20
7.1.2	The large size loop transmitters	20
7.1.3	Other transmitters	20
7.1.4	Product Classes.....	21
7.2	Transmitter carrier output levels	22
7.2.1	H-field (radiated)	22
7.2.1.1	Definition.....	22
7.2.1.2	Methods of measurement.....	22
7.2.1.3	Limits.....	23
7.2.2	RF carrier current.....	23
7.2.2.1	Definition.....	23
7.2.2.2	Methods of measurement.....	24
7.2.2.3	Limits.....	24
7.2.3	Radiated E-field (Product Class 4).....	24
7.2.3.1	Definition.....	24
7.2.3.2	Methods of measurement.....	24
7.2.3.3	Limits.....	25
7.3	Permitted frequency range of the modulation bandwidth.....	25
7.3.1	Definition	25
7.3.2	Method of measurement.....	25
7.3.3	Limits.....	26
7.4	Spurious emissions.....	26
7.4.1	Definition	26
7.4.2	Conducted spurious emissions.....	26
7.4.2.1	Methods of measurement (< 30 MHz).....	26
7.4.2.2	Limits.....	27
7.4.2.3	Methods of measurement (\geq 30 MHz).....	27
7.4.2.4	Limits.....	27
7.4.3	Radiated field strength	27
7.4.3.1	Methods of measurement (< 30 MHz).....	27
7.4.3.2	Limits.....	28
7.4.4	Effective radiated power	28
7.4.4.1	Methods of measurement (\geq 30 MHz).....	28
7.4.4.2	Limits.....	29
7.5	Duty cycle.....	29
7.5.1	Definitions.....	29
7.5.2	Declaration	29
7.5.3	Duty cycle classes.....	29
8	Receiver requirement.....	30
8.1	Adjacent channel selectivity - in band.....	30
8.1.1	Definition	30
8.1.2	Method of measurement.....	30
8.1.3	Limits.....	31
8.2	Blocking or desensitization.....	31
8.2.1	Definition	31
8.2.2	Methods of measurement	31
8.2.3	Limits.....	32

8.3	Receiver spurious radiation.....	33
8.3.1	Definition	33
8.3.2	Methods of measurement	33
8.3.3	Limits.....	33
8.3.3.1	Radiated emissions below 30 MHz.....	33
8.3.3.2	Radiated emissions above 30 MHz.....	33
9	Measurement uncertainty	34
Annex A (normative): Radiated measurements.....		35
A.1	Test sites and general arrangements for measurements involving the use of radiated fields	35
A.1.1	Outdoor test site	35
A.1.1.1	Standard position	36
A.1.2	Test antenna	36
A.1.2.1	Below 30 MHz.....	36
A.1.2.2	Above 30 MHz	36
A.1.3	Substitution antenna	36
A.1.4	Optional additional indoor site.....	37
A.2	Guidance on the use of radiation test sites	38
A.2.1	Measuring distance.....	38
A.2.2	Test antenna.....	38
A.2.3	Substitution antenna	38
A.2.4	Artificial antenna.....	38
A.2.5	Auxiliary cables	38
A.3	Further optional alternative indoor test site using an anechoic chamber	39
A.3.1	Example of the construction of a shielded anechoic chamber.....	39
A.3.2	Influence of parasitic reflections in anechoic chambers	39
A.3.3	Calibration of the shielded RF anechoic chamber.....	40
Annex B (normative): Transmitter carrier limits.....		41
Annex C (normative): Transmitter (RF carrier current × antenna area) limit for large size loop.....		42
Annex D (normative): H-field limit correction factor for generated E-fields		43
Annex E (normative): Spurious limits, radiated H-field at 10 m distances		44
Annex F (normative): Customized loop antennas		45
F.1	Product classes related to the antenna loop	45
F.1.1	Antenna loops below 1 MHz.....	45
F.1.2	Antenna loops above 1 MHz.....	46
Annex G (informative): Test fixture for measuring inductive transmitter carrier and harmonic currents by use of an artificial antenna (Product Class 3 only).....		47
Annex H (informative): E-fields in the near field at low frequencies		49
Annex J (normative): H-field measurements at other distances than 10 m		50
Annex K (normative): Transmitter requirements overview.....		53
Annex L (normative): Low level transmitter spectrum mask measurements		54
Annex M (informative): Clauses of the present document relevant for compliance with the essential requirements of relevant EC Council Directives.....		55
M.1	Compliance with 1999/5/EC (R&TTE Directive) article 3.3e	55
M.2	Compliance with 1999/5/EC (R&TTE Directive) article 3.3f.....	55

Annex N (informative):	Bibliography.....	56
History		57

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 330-1 V1.3.1:2003

<https://standards.iteh.ai/catalog/standards/sist/44f9d7b5-3d44-44c7-a32e-4130503e474b/sist-en-300-330-1-v1-3-1-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document is part 1 of a multi-part deliverable covering the Short Range Devices (SRD); Radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonized EN under article 3.2 of the R&TTE Directive".

National transposition dates

Date of adoption of this EN:	15 June 2001
Date of latest announcement of this EN (doa):	30 September 2001
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2002
Date of withdrawal of any conflicting National Standard (dow):	31 March 2002

1 Scope

The present document applies to Short Range Devices (SRDs) transmitters and receivers:

- a) - transmitters operating in the range from 9 kHz to 25 MHz; and
 - inductive loop transmitters operating from 9 kHz to 30 MHz;
- b) - receivers operating from 9 kHz to 30 MHz.

The present document contains the technical characteristics for radio equipment and is referencing in CEPT/ERC Recommendation 70-03 [3] and ERC Decisions.

The present document does not necessarily include all the characteristics which may be required by a user, nor does it necessarily represent the optimum performance achievable. It is a product family standard which may be completely or partially superseded by specific standards covering specific applications.

The present document applies to generic SRDs:

- inductive loop systems;
- with an antenna connection and/or with an integral antenna;
- for alarms, identification systems, telecommand, telemetry, etc.;
- applications with or without speech.

When selecting parameters for new SRDs, which may have inherent safety of human life implications, manufacturers and users should pay particular attention to the potential for interference from other systems operating in the same or adjacent bands.

The present document covers fixed stations, mobile stations and portable stations. If a system includes transponders, these are measured together with the transmitter.

All types of modulation for radio devices are covered by the present document, provided the requirements of clause 7.3 are met.

The radio equipment, covered by the classification SRD is divided into several power classes based on maximum radiated field strength or output power (see table 1). The power class designation is based on CEPT/ERC Recommendation 70-03 [3] and ERC Decisions.

Table 1: Maximum radiated H-field or power (e.i.r.p)

Power Class	Radiated H-field or power level
1	7 dB μ A/m at 10 m
2	42 dB μ A/m at 10 m
3	72 dB μ A/m at 10 m (at 9 kHz to 30 kHz, descending 3 dB/octave from 30 kHz 135 kHz)
4	37,7 dB μ A/m at 10 (at 135 kHz, descending 3 dB/octave from 135 kHz to 1 MHz)
	29 dB μ A/m at 10 m (at 1,0 MHz descending 9 dB/oct from 1 MHz to 4,642 MHz)
5	9 dB μ A/m at 10 m (4,642 MHz to 30 MHz)

On non-harmonized parameters, national administrations may impose conditions on the type of modulation, frequency, channel/frequency separations, maximum transmitter radiated field strength/maximum output current to a defined antenna, duty cycle, equipment marking and the inclusion of an automatic transmitter shut-off facility, as a condition for the issue of an individual or general licence, or as a condition for use under licence exemption.

Three types of measuring methods are defined in the present document due to the varied nature of the types of equipment used in this band. One method measures the RF carrier current, another measures the radiated H-field and the third the conducted power.

The present document covers requirements for radiated emissions below as well as above 30 MHz.

Additional standards or specifications may be required for equipment such as that intended for connection to the Public Switched Telephone Network (PSTN).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
 - For a specific reference, subsequent revisions do not apply.
 - For a non-specific reference, the latest version applies.
- [1] ETSI EN 300 330-2 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz; Part 2: Harmonized EN under article 3.2 of the R&TTE Directive".
- [2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity.
- [3] CEPT/ERC Recommendation 70-03 (1997): "Relating to the use of Short Range Devices (SRD)".
- [4] ITU-T Recommendation O.153: "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [5] ETSI ETR 028: "Radio Equipment and Systems (RES); Uncertainties in the measurement of mobile radio equipment characteristics".
- [6] ITU-T Recommendation O.41: "Psophometer for use on telephone-type circuits".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

alarm: use of radio communication for indicating an alarm condition at a distant location

artificial antenna: tuned reduced-radiating dummy load equal to the nominal impedance specified by the applicant

assigned frequency band: frequency band within which the device is authorized to operate

conducted measurements: measurements which are made using a direct connection to the equipment under test

customized antenna: antenna build according to manufacturers antenna design rules inside tested limits

dedicated antenna: removable antenna supplied and tested with the radio equipment, designed as an indispensable part of the equipment

fixed station: equipment intended for use in a fixed location

H-field test antenna: electrically screened loop or equivalent antenna, with which the magnetic component of the field can be measured

identification system: equipment consisting of a transmitter(s), receiver(s) (or a combination of the two) and an antenna(s) to identify objects by means of a transponder

integral antenna: permanent fixed antenna, which may be build-in, designed as an indispensable part of the equipment

magnetic dipole moment: product of (Number of coil turns) \times (coil area) \times (coil current)
(Air coils only)

mobile station: equipment normally installed in a vehicle

portable station: equipment intended to be carried, attached or implanted

radiated measurements: measurements which involve the absolute measurement of a radiated field

telecommand: use of radio communication for the transmission of signals to initiate, modify or terminate functions of equipment at a distance

telemetry: use of radio communication for indicating or recording data at a distance

transponder: device, that responds to an interrogation signal

3.2 Symbols

For the purposes of the present document, the following symbols apply:

E	Electrical field strength
E _o	reference electrical field strength, (see annex A)
e.i.r.p	effective isotropic radiated power
f	frequency
H	magnetic field strength
H _o	reference magnetic field strength, (see annex A)
m	magnetic dipole moment
P	Power
PSTN	Public Switched Telephone Network
R	distance
R _o	Reference distance, (see annex A)
t	time

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

EMC	ElectroMagnetic Compatibility
ISM	Industrial, Scientific and Medical
RF	Radio Frequency
R&TTE	Radio and Telecommunications Terminal Equipment
SRD	Short Range Device
VSWR	Voltage Standing Wave Ratio

4 Technical requirements specifications

4.1 General requirements

4.1.1 Receiver classification

The product family of short range radio devices is divided into three Equipment Classes, see table 2, each having its own set of minimum performance criteria. This classification is based upon the impact on persons in case the equipment does not operate above the specified minimum performance level.

Table 2

Receiver class	Relevant receiver clauses	Risk assessment of receiver performance
1	8.1, 8.2, and 8.3	Highly reliable SRD communication media; e.g. serving human life inherent systems (may result in a physical risk to a person)
2	8.2 and 8.3	Medium reliable SRD communication media e.g. causing inconvenience to persons, which cannot simply be overcome by other means
3	8.3	Standard reliable SRD communication media e.g. inconvenience to persons, which can simply be overcome by other means (e.g. manual)

NOTE: With reference to the present document manufacturers are recommended to declare classification of their devices in accordance with table 2 and EN 300 330-2 [1], clause 4.2, as relevant. In particular where an SRD which may have an inherent safety of human life implications, manufacturers and users should pay particular attention to the potential for interference from other systems operating in the same or adjacent bands.

4.1.2 General performance criteria

<https://standards.iteh.ai/catalog/standards/sist/449d7b5-3d44-44c7-a32e-4130502-st74/receiver-200-330-1-v1-3-1-2003>

For the purpose of the receiver performance tests, the receiver will produce an appropriate output under normal conditions as indicated below. Where the indicated performance cannot be achieved or if it defined differently, the manufacturer shall declare and publish the performance criteria used to determine the performance of the receiver:

- a SND/ND ratio of 20 dB, measured at the receiver output through a telephone psophometric weighting network as described in ITU-T Recommendation O.41 [6]; or
- after demodulation, a data signal with a bit error ratio of 10^{-2} ; or
- after demodulation, a message acceptance ratio of 80 %.

4.2 Presentation of equipment for testing purposes

Each equipment submitted for testing where type approval is still in force shall fulfil the requirements of the present document on all frequencies over which it is intended to operate.

The applicant shall declare the frequency ranges, the range of operating conditions and power requirements in consultation with the Administration(s), as applicable, to establish the appropriate test conditions.

Additionally, technical documentation and operating manuals, sufficient to make the test, shall be supplied.

A test fixture for equipment with an integral antenna may be supplied by the applicant (see clauses 6.3). For equipment supplied without an antenna i.e. Product Class 3, the applicant will supply either a tuned reduced radiating load (see clause 6.2.1) or an artificial antenna as defined by annex G.

If an equipment is designed to operate with different radiated field strengths or power level, measurement of each transmitter parameter shall be performed, according to the present document, on samples of equipment defined in clause 4.2.1.

To simplify and harmonize the testing procedures between different testing laboratories, measurements shall be performed, according to the present document, on samples defined in clauses 4.2.1 and 4.2.4

4.2.1 Choice of model for testing

The applicant shall provide one or more samples of the equipment, as appropriate for testing.

Stand alone equipment shall be offered by the applicant complete with any ancillary equipment needed for testing.

If an equipment has several optional features, considered not to affect the RF parameters then the tests need only to be performed on the equipment configured with that combination of features considered to be the most complex, as proposed by the applicant and agreed by the test laboratory.

Where practicable, equipment offered for testing shall provide a 50 Ω connector for conducted RF power level measurements.

In the case of integral antenna equipment, if the equipment does not have a internal permanent 50 Ω connector then it is permissible to supply a second sample of the equipment with a temporary antenna connector fitted to facilitate testing, see clause 4.2.3.

4.2.2 Testing of equipment with alternative radiated field or power levels

If a family of equipment has alternative radiated field strengths or output power levels provided by the use of separate power modules or add on stages, then these shall be declared by the applicant. Each module or add on stage shall be tested in combination with the equipment. As a minimum, measurements of the radiated power, eirp and spurious emissions shall be performed for each combination and shall be stated in the test report.

4.2.3 Testing of equipment that does not have an external 50 Ohm RF connector (integral antenna equipment)

4.2.3.1 Equipment with an internal permanent or temporary antenna connector

The means to access and/or implement the internal permanent or temporary antenna connector shall be stated by the applicant with the aid of a diagram. The fact that use has been made of the internal antenna connection, or of a temporary connection, to facilitate measurements shall be recorded in the test report.

4.2.3.2 Equipment with a temporary antenna connector

The applicant, may submit one set of equipment with the normal antenna connected, to enable radiated measurements to be made. The applicant shall attend the test laboratory at the conclusion of the radiated measurements, to disconnect the antenna and fit the temporary connector. The testing laboratory staff shall not connect or disconnect any temporary antenna connector.

Alternatively, the applicant may submit two sets of equipment to the test laboratory, one fitted with a temporary antenna connector with the antenna disconnected and another equipment with the antenna connected. Each equipment shall be used for the appropriate tests. The applicant shall declare that the two sets of equipment are identical in all aspects except for the antenna connector.

4.2.4 On-site testing

In certain cases it may not be possible to provide representative samples of antennas and/or equipment due to physical constraints. In these cases equivalent measurements to the present document shall be made at a representative installation of the equipment (on-site).

4.3 Mechanical and electrical design

4.3.1 General

The equipment submitted by the applicant should be designed, constructed and manufactured in accordance with sound engineering practice and with the aim of minimizing harmful interference to other equipment and services.

Transmitters and receivers may be individual or combination units.

4.3.2 Controls

Those controls which, if maladjusted, might increase the interfering potentialities of the equipment shall not be easily accessible to the user.

4.3.3 Transmitter shut-off facility

If the transmitter is equipped with an automatic transmitter shut-off facility, it should be made inoperative for the duration of the test.

4.3.4 Receiver mute or squelch

If the receiver is equipped with a mute, squelch or battery-saving circuit, this circuit shall be made inoperative for the duration of the tests.

4.3.5 Marking (equipment identification)

The equipment shall be marked in a visible place. This marking shall be legible and durable. Where this is not possible due to physical constraints, the marking shall be included in the users manual.

[SIST EN 300 330-1 V1.3.1:2003](https://standards.iteh.ai/catalog/standards/sist/449d7b5-3d44-44c7-a32e-4130503e474b/sist-en-300-330-1-v1-3-1-2003)

4.3.5.1 Equipment identification

The marking shall include as a minimum:

- the name of the manufacturer or his trade mark;
- the type designation; and
- equipment classification, see clause 4.1.1.

4.3.5.2 Regulatory marking

The equipment shall be marked, where applicable, in accordance with CEPT/ERC Recommendation 70-03 [3] or the EC Council Directive 1999/5/EC (R&TTE Directive) [2], whichever is applicable. Where this is not applicable the equipment shall be marked in accordance with the National Regulatory requirements.

4.4 Declarations by the applicant

When submitting equipment for type testing, the applicant shall supply the necessary information required by the appropriate application form.

The performance of the equipment submitted for type testing shall be representative of the performance of the corresponding production model.

4.5 Auxiliary test equipment

All necessary test signal sources and set-up information shall accompany the equipment when it is submitted for type testing.