

INTERNATIONAL STANDARD

IEC
61108-4

First edition
2004-07

**Maritime navigation and radiocommunication
equipment and systems –
Global navigation satellite systems (GNSS) –**

**Part 4:
Shipborne DGPS and DGLONASS maritime
radio beacon receiver equipment –
Performance requirements, methods of
testing and required test results**

[IEC 61108-4:2004](https://standards.iteh.ai/catalog/standards/iec/ba3ec145-114b-4a81-a01a-a8991ca38428/iec-61108-4-2004)

<https://standards.iteh.ai/catalog/standards/iec/ba3ec145-114b-4a81-a01a-a8991ca38428/iec-61108-4-2004>



Reference number
IEC 61108-4:2004(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre: custserv@iec.ch

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 61108-4

First edition
2004-07

Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS) –

Part 4: Shipborne DGPS and DGLONASS maritime radio beacon receiver equipment – Performance requirements, methods of testing and required test results

[IEC 61108-4:2004](https://standards.iteh.ai/catalog/standards/iec/ba3ec145-114b-4a81-a01a-a8991ca38428/iec-61108-4-2004)

<https://standards.iteh.ai/catalog/standards/iec/ba3ec145-114b-4a81-a01a-a8991ca38428/iec-61108-4-2004>

© IEC 2004 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

W

For price, see current catalogue

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Terms, definitions and abbreviations	7
3.1 Definitions	7
3.2 Abbreviations	7
4 Performance requirements	7
4.1 Introduction	7
4.2 Composition	8
4.3 Functional requirements	8
4.4 Protection.....	9
4.5 Integrity.....	9
4.6 Interfaces	10
4.7 IEC 61162-1, IEC 61162-2 implementation	10
4.8 IEC 61162-3 implementation	10
4.9 Display and control.....	10
4.10 Installation	10
5 Technical characteristics	11
5.1 Carrier frequency	11
5.2 Frequency tolerance.....	11
5.3 Message types	11
5.4 Data transmission rate	11
5.5 Dynamic range	11
5.6 Maximum bit error ratio	11
5.7 Receiver selectivity and stability.....	11
5.8 Automatic frequency selection.....	12
5.9 Protection ratios	12
6 Methods of testing and required test results	13
6.1 General conditions of measurement and test signals	13
6.2 Operational tests	14
6.3 Protection of external connections.....	18
6.4 Integrity.....	18
6.5 Technical tests	18
6.6 Additional functionality tests	20
 Annex A (normative) Simulation of noise situations for the test of shipborne DGPS maritime radio beacon receiver equipment.....	21
A.1 Parameters describing noise	21
A.2 Noise models	22
A.3 Test procedures	26
 Annex B (informative) Methodology for measuring WER	27
B.1 Recording the RTCM data stream.....	27
B.2 Analysing the RTCM data stream	27
B.3 Caution	27

Annex C (normative) Tests that are specific to integrated equipment that does not provide an output port for testing	30
C.1 General requirements	30
C.2 Test of WER display	30
C.3 Comments to Clause 6, methods of testing	30
Annex D (informative) Installation guidelines to counteract the effect of interference	31
D.1 Introduction	31
D.2 Antennas	31
D.3 General installation requirements	32
D.4 Noise/interference sources	34
D.5 Testing	34
D.6 Troubleshooting.....	35
Annex E (informative) Implementation using a concurrent process.....	36
Annex F (informative) Data interface guidance.....	38
Bibliography.....	39
Figure A.1 – Generating atmospherics according to Feldman.....	24
Figure A.2 – Test set-up using a PC to program a waveform synthesizer	26
Figure B.1 – Word error rate algorithm (first part)	28
Figure B.2 – Word error rate algorithm (second part)	29
Figure E.1 – Station status update	36
Figure E.2 – Navigation process	37
Table 1 – Message types (M823/1.2)	11
Table 2 – Protection ratios	12
Table A.1 – Parameters for different interference situations	23
Table A.2 – Characteristic parameters of the simulated situations.....	25
Table D.1 – Troubleshooting conditions	35

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS –
GLOBAL NAVIGATION SATELLITE SYSTEMS (GNSS) –**

**Part 4: Shipborne DGPS and DGLONASS maritime
radio beacon receiver equipment –
Performance requirements, methods of testing
and required test results**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61108-4 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/394/FDIS	80/398/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

IEC 61108 consists of the following parts, under the general title *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS)*:

Part 1: Global positioning system (GPS) – Receiver equipment – Performance standards, methods of testing and required test results

Part 2: Global navigation satellite system (GLONASS) – Receiver equipment – Performance standards, methods of testing and required test results

Part 3: (To be used at a later date)

A bilingual version of this publication may be issued at a later date.

[iTech Standards
\(https://standards.iteh.ai\)](https://standards.iteh.ai)
Document Preview

[IEC 61108-4:2004](https://standards.iteh.ai/catalog/standards/iec/ba3ec145-114b-4a81-a01a-a8991ca38428/iec-61108-4-2004)

<https://standards.iteh.ai/catalog/standards/iec/ba3ec145-114b-4a81-a01a-a8991ca38428/iec-61108-4-2004>

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS –
GLOBAL NAVIGATION SATELLITE SYSTEMS (GNSS) –**

**Part 4: Shipborne DGPS and DGLONASS maritime
radio beacon receiver equipment –
Performance requirements, methods of testing
and required test results**

1 Scope

This part of IEC 61108 specifies the minimum operational and performance requirements, methods of testing and required test results conforming to performance standards not inferior to those adopted by the IMO in resolution MSC.114(73). In addition, it takes account of IMO resolution A.694(17) and is associated with IEC 60945. When a requirement of this standard is different from IEC 60945, the requirement in this standard shall take precedence.

This standard may be satisfied by equipment integral with GNSS equipment.

This standard is applicable to HSC.

All text of this standard, whose wording is identical to that in IMO resolution MSC.114(73) and ITU-R M.823 is printed in *italics* and the resolution (abbreviated to – 114 and M.823 respectively) and paragraph numbers are indicated in brackets i.e. (114/3.3 or M.823/3.3).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

IEC 61162-2, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 2: Single talker and multiple listeners, high speed transmission*

IMO Resolution MSC.114(73), *Revised recommendation on performance standards for shipborne DGPS and DGLONASS maritime radio beacon receiver equipment*

IMO Resolution A.694(17), *General requirements for shipborne radio equipment forming part of the Global Maritime Distress and Safety System (GMDSS) and for electronic navigational aids*

ITU-R M.823-2, *Technical characteristics of differential transmissions for Global Navigation Satellite Systems (GNSS) from maritime radio beacons in the frequency band 283,5 – 315 kHz in Region 1 and 285 – 325 kHz in Regions 2 and 3*

3 Terms, definitions and abbreviations

For the purposes of this standard the following definitions and abbreviations apply.

3.1 Definitions

3.1.1

Eurofix

the Eurofix datalink is a scheme for modulation of the Loran-C and Chayka signals to establish a broadcast capability that can be used for distribution of GNSS corrections, integrity data and other information. Similar developments in the US are referred to as LORAN-COMM

3.1.2

global navigation satellite system (GNSS)

is a world-wide position, time and velocity radio determination system comprising space, ground and user segments

3.1.3

integrity

is the ability to provide users with warnings within a specified time when the system should not be used for navigation

3.2 Abbreviations

BER	Bit error rate
bps	Bits per second
DGLONASS	Differential GLONASS
DGNSS	Differential GNSS
DGPS	Differential GPS
EGNOS	European Geo-stationary Navigational Overlay System
EPFS	Electronic position fixing system
EUT	Equipment under test
MSAS	Multi-Satellite Augmentation System
MSK	Minimum shift keying
RTK	Real-Time Kinematics
SNR	Signal to noise ratio
UDRE	User defined range error
VTS	Vessel Tracking Services
WAAS	Wide-Area Augmentation System
WER	Word error rate

4 Performance requirements

4.1 Introduction

Differential services broadcast information for augmenting Global Positioning System (GPS) and the Global Navigation Satellite System (GLONASS) to provide the accuracy and integrity required for entrances and harbour approaches and other waters in which the freedom to manoeuvre is limited. Various service providers are broadcasting differential information applicable to localised areas. Different services provide information for augmenting GPS, GLONASS, or both.(114/1.1)

Receiver equipment for the reception and proper de-modulating / decoding of differential GPS and GLONASS maritime radio beacon broadcasts (fully compliant with ITU-R M.823) intended for navigational purposes on ships with maximum speeds not exceeding 70 knots shall, in addition to the general requirements contained in resolution A.694(17), comply with the following minimum performance requirements.(114/1.2) As noted in Clause 1 – Scope: This standard is applicable to HSC.

This standard covers the basic requirements of maritime radio beacon receiver equipment providing augmentation information to position-fixing equipment, including health messages. It does not cover other computational facilities which may be in the equipment.(114/1.3)

Additional functionality (e.g. use of differential corrections and integrity, from multiple beacon reference stations, Eurofix, LORAN-COMM, VTS, FM subcarrier, commercial satellite, WAAS, EGNOS, MSAS and RTK) is permitted if the manufacturer can demonstrate that this does not degrade performance.

4.2 Composition

The words “DGPS and DGLONASS maritime radio beacon receiver equipment” as used in this performance standard includes all the components and units necessary for the system to properly perform its intended functions. The equipment shall include the following minimum facilities:(114/2)

- 1) *antenna capable of receiving DGPS or DGLONASS maritime radio beacon signals;(114/2.1)*
- 2) *DGPS and DGLONASS maritime radio beacon receiver and processor; (114/2.2)*
- 3) *receiver control interface; (114/2.3) (See also 4.3 2))*
- 4) *data output interface (114/2.4) (See also 4.3 5)), and*
- 5) *broadcast station database capable of storing at least the following data for a minimum of 1000 stations. These data elements can be initially downloaded and shall be updated from DGNSS broadcasts:*

ID_{REF1}, ID_{REF2}

BROADCAST STATION ID

BROADCAST STATION NAME

FREQUENCY

REFERENCE STATION POSITION

REFERENCE STATION DATUM

OFFICIAL OPERATION STATUS (operational, test, or not operational)

- 6) *broadcast station database capable of calculating and storing at least the following data for a minimum of 10 closest stations. The receiver shall update these data elements from information included in DGNSS broadcasts:*

TIME/DATE of UPDATE

REFERENCE STATION HEALTH

WORD ERROR RATE (WER)

DISTANCE (user to reference station(s))

4.3 Functional requirements

The DGPS and DGLONASS maritime radio beacon receiver equipment shall: (114/3)

- 1) *operate in the band of 283,5 to 315 kHz in Region 1 and 285 to 325 kHz in Regions 2 and 3 in accordance with ITU-R M.823 (114/3.1). The receiver shall perform to the requirements of this standard while subjected to typical radio frequency interference and noise sources, as follows:*

- atmospheric noise (e.g. local thunderstorms);
- man-made noise (e.g. own ship, shipyard industrial, etc.);
- Gaussian noise;
- interference from LF and MF radio stations outside the band.

The specifications of these are further developed in Annex A.

- precipitation static (especially in the high latitudes) is not specified or tested against, but H-field antennas are recommended to be used on ships that go to the high latitudes that experience this environmental interference; (See Annex D.)
- 2) *provide means of automatically and manually selecting the station;* (114/3.2) When in manual mode, operator action shall be required for a change and the receiver shall provide an indication of other available stations. The database shall be continually updated and utilised to select reference stations;(See Annex E.)
 - 3) *make the data available for use with a delay not exceeding 100 ms after its reception;* (114/3.3) The delay from the first bit of the modulated data to the last bit of the decoded data output from the receiver shall be less than 100 ms plus the transmission time of the message;
 - 4) *be capable of acquiring a signal in less than 45 s in the presence of electrical storms;* (114/3.4);
 - 5) *have an omni-directional antenna in the horizontal plane.* (114/3.6) The difference between the maximum and minimum signal strength shall be less than:
 - .1 5 dB over frequency range
 - .2 3 dB over azimuth
 - .3 3 dB over roll of 20°;
 - 6) and make available the health status, of the station being used, to the system.

4.4 Protection

Precautions shall be taken to ensure that no permanent damage can result from an accidental short circuit or grounding of the antenna or any of its input or output connections or any of the DGPS and DGLONASS maritime radio beacon receiver equipment inputs or outputs for a duration of five minutes. (114/4)

4.5 Integrity

The following functions shall be performed in either an integrated DGNSS receiver or an associated GNSS receiver. As a consequence, there are no tests for these clauses within this standard.

4.5.1 DGNSS integrity status

When in differential mode, the GNSS receiver shall give a DGNSS integrity indication:

- a) if no DGNSS message is received within 10 s;
- b) while in manual station selection mode and the selected station is unhealthy, unmonitored, or signal quality is below threshold;
- c) while in automatic station selection mode and the only available station is unhealthy, unmonitored, or signal quality is below threshold.

4.5.2 GNSS integrity status

If the Range-rate Correction or the Pseudorange Correction of a satellite is out of tolerance, the binary code in the ITU-R M.823-2 types 1, 9, 31 and 34 messages will indicate to the GNSS receiver that the satellite shall not be used.

4.6 Interfaces

The equipment shall *have at least one serial data output that conforms to the relevant international marine interface standard*; (114/3.5) as defined in IEC 61162-1, IEC 61162-2, or IEC 61162-3 as appropriate.

4.7 IEC 61162-1, IEC 61162-2 implementation

Integrated equipment and stand-alone receivers shall use the following IEC 61162-1 messages for control and status reporting:

- MSK – MSK Receiver Interface (input/output)
- MSS – MSK Receiver Signal (output)

The Talker Identifier Mnemonic for stand-alone receivers is:

- COMMUNICATIONS: Data Receiver: CR

Stand-alone receivers shall use GGA, GNS or GLL (as defined in IEC 61162-1) to receive position data from the GNSS receiver for its automatic functions. (input)

The DGNSS receiver shall provide ITU-R M.823 data output to a port for testing. See also Annex F for informative guidance on ITU-R M.823 interface matters.

4.8 IEC 61162-3 implementation

Integrated equipment and stand-alone receivers shall use the following IEC 61162-3 parameter groups for control, status and data reporting:

- GNSS Position Data
- GNSS Differential Correction Receiver Signal Status
- GNSS Differential Correction Receiver Interface
- GNSS Differential Corrections

4.9 Display and control

The selected operational mode (manual or automatic) shall be clearly indicated or available on an appropriate interface

The following information shall be available for display of the selected station and the next two nearest stations (see 5) of 4.2):

- reference Station ID;
- station name;
- frequency;
- calculated distance to the station;
- station health (from message header);
- signal quality (acceptable < 10 % WER, unacceptable > 10 % WER).

4.10 Installation

For information guidance on installation see Annex D.