

TECHNICAL REPORT



Information technology – Generic cabling for customer premises –
Part 9909: Evaluation of balanced cabling in support of 25 Gbit/s for reach
greater than 30 metres (standards.iteh.ai)

[ISO/IEC TR 11801-9909:2020](https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73df61d3/iso-iec-tr-11801-9909-2020)

<https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73df61d3/iso-iec-tr-11801-9909-2020>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2020 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

[ISO/IEC TR 11801-9909:2020](https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73df61d3/iso-iec-tr-11801-9909-2020)

<https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73df61d3/iso-iec-tr-11801-9909-2020>

iTeh STANDARDS (Standards.iteh.ai)

TECHNICAL REPORT



**Information technology – Generic cabling for customer premises –
Part 9909: Evaluation of balanced cabling in support of 25 Gbit/s for reach
greater than 30 metres**

[ISO/IEC TR 11801-9909:2020](https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73df61d3/iso-iec-tr-11801-9909-2020)

<https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73df61d3/iso-iec-tr-11801-9909-2020>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200

ISBN 978-2-8322-8487-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	7
3.1 Terms and definitions.....	7
3.2 Abbreviated terms.....	7
4 Extended reach channel specifications	8
4.1 General.....	8
4.2 Channel performance enhancement methods for increased SNR	8
4.2.1 General	8
4.2.2 Reduced delay and delay skew.....	9
4.2.3 Enhanced cable.....	9
4.2.4 Enhanced connector.....	9
4.3 Example channel specifications with length scaling.....	9
4.3.1 General	9
4.3.2 Return loss (RL)	10
4.3.3 Insertion loss (IL).....	10
4.3.4 Near-end crosstalk loss (NEXT).....	11
4.3.5 Attenuation to crosstalk loss ratio near end (ACR-N).....	11
4.3.6 Attenuation to crosstalk ratio far-end (ACR-F)	12
4.3.7 Alien (exogenous) crosstalk.....	12
4.3.8 DC loop resistance.....	13
4.3.9 Propagation delay.....	13
4.3.10 Delay skew	13
4.3.11 Unbalance attenuation near end (TCL) and far end (ELTCTL), and coupling attenuation	14
Annex A (informative) Reduced delay and delay skew	15
A.1 Reduced delay relation to extended reach	15
A.1.1 General	15
A.1.2 Example reduced delay evaluation.....	15
A.2 Delay relation to insertion loss (IL).....	15
A.2.1 General	15
A.2.2 Relation of variable relative permittivity to attenuation	16
A.2.3 Relation of dissipation factor to attenuation:	16
Annex B (informative) Enhanced capacity	18
B.1 Enhanced cabling components.....	18
B.1.1 General	18
B.1.2 Enhanced cable.....	18
B.1.3 Enhanced connector.....	18
B.2 Channel SNR margin-to-capacity	18
B.2.1 General	18
B.2.2 Margin-to-capacity calculation and comparison.....	18
B.2.3 Margin-to-capacity versus frequency.....	19
B.2.4 Margin-to-capacity versus reach	20
Bibliography.....	21

Figure B.1 – Margin-to-capacity versus frequency for 25 Gbit/s rate for 50 m reach 19

Figure B.2 – Margin-to-capacity versus reach for 25 Gbit/s at 1 000 MHz frequency 20

Table 1 – Enhancement methods for 25 Gbit/s extended reach 9

Table 2 – Formulae for return loss specifications for example 50 m channel 10

Table 3 – Formulae for insertion loss specifications for example 50 m channel 10

Table 4 – Formulae for pair-to-pair NEXT specifications for example 50 m channel 11

Table 5 – Formula for PS NEXT specifications for example 50 m channel 11

Table 6 – Formulae for ACR-F specifications for example 50 m channel 12

Table 7 – Formulae for PS ACR-F specifications for example 50 m channel 12

Table 8 – Formulae for PS ANEXT specifications for example 50 m channel 13

Table 9 – Formulae for PS AACR-F specifications for example 50 m channel 13

Table 10 – Formulae for propagation delay specifications for a 50 m channel 13

Table 11 – Delay skew specifications for a 50 m channel 13

Table 12 – TCL for example 50 m channel 14

Table 13 – ELTCTL for example 50 m channel 14

Table 14 – Coupling attenuation for example 50 m channel for E_1 and E_2 14

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC TR 11801-9909:2020](https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73df61d3/iso-iec-tr-11801-9909-2020)
<https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73df61d3/iso-iec-tr-11801-9909-2020>

INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES –

Part 9909: Evaluation of balanced cabling in support of 25 Gbit/s for reach greater than 30 metres

FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO National bodies.
- 3) IEC and ISO documents have the form of recommendations for international use and are accepted by IEC and ISO National bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC and ISO documents is accurate, IEC and ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC and ISO National bodies undertake to apply IEC and ISO documents transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC and ISO document and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC and ISO do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC and ISO marks of conformity. IEC and ISO are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this document.
- 7) No liability shall attach to IEC and ISO or their directors, employees, servants or agents including individual experts and members of its technical committees and IEC and ISO National bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this ISO/IEC document or any other IEC and ISO documents.
- 8) Attention is drawn to the Normative references cited in this document. Use of the referenced publications is indispensable for the correct application of this document.
- 9) Attention is drawn to the possibility that some of the elements of this ISO/IEC document may be the subject of patent rights. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

The main task of IEC and ISO technical committees is to prepare International Standards. However, a technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

ISO/IEC TR 11801-9909, which is a Technical Report, has been prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 11801 series, under the general title *Information technology – Generic cabling for customer premises*, can be found on the IEC and ISO websites.

The text of this Technical Report is based on the following documents:

DTR	Report on voting
JTC1-SC25/2932/DTR	JTC1-SC25/2948/RVDTR

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC TR 11801-9909:2020](https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73df61d3/iso-iec-tr-11801-9909-2020)
<https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73df61d3/iso-iec-tr-11801-9909-2020>

INTRODUCTION

This document provides an evaluation of balanced cabling in support of 25 Gbit/s data transmission. The evaluation covers enhanced balanced cabling channel specifications, which are based on Category 8.1 and Category 8.2 balanced cabling components. The enhanced channel specifications are intended to support extended reach greater than 30 m.

The extended reach evaluation is intended to support various emerging use-cases including

- 25 Gbit/s LAN,
- extended reach high definition audio/video,
- Wi-Fi®¹ application greater than 10 Gbit/s, and
- 5G intrabuilding sites.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC TR 11801-9909:2020](https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73df61d3/iso-iec-tr-11801-9909-2020)

<https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73df61d3/iso-iec-tr-11801-9909-2020>

¹ Wi-Fi is a registered trademark of Wi-Fi Alliance. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO or IEC.

INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES –

Part 9909: Evaluation of balanced cabling in support of 25 Gbit/s for reach greater than 30 metres

1 Scope

This part of ISO/IEC 11801, which is a Technical Report, covers evaluation and recommendations for achieving extended reach, greater than 30 m, for 25 Gbit/s applications over balanced cabling channels.

This document covers channel reference implementations, based on Category 8.1 and Category 8.2, 2 000 MHz, components.

The channel and component category specifications covered in this document are not intended to be normative.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO/IEC TR 11801-9909:2020](https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73185132/iso-iec-tr-11801-9909-2020)

[https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-](https://standards.iteh.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-8e9c73185132/iso-iec-tr-11801-9909-2020)

ISO/IEC 11801-1, *Information technology – Generic cabling for customer premises – Part 1: General requirements*

3 Terms and definitions

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 11801-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.2 Abbreviated terms

For the purposes of this document, the abbreviated terms given in ISO/IEC 11801-1 and the following apply.

SNR	signal to noise ratio
NVP	nominal velocity of propagation

4 Extended reach channel specifications

4.1 General

Balanced cabling channels in accordance with ISO/IEC 11801-1:2017, Class I and Class II, are intended to support link data rate operating at 25 Gbit/s – for example, ISO/IEC/IEEE 8802-3:2017/AMD3:2017 25GBASE-T – with link reach up to 30 m.

NOTE 1 ISO/IEC/IEEE 8802-3:2017/AMD3:2017 25GBASE-T link segment specifications are referenced, see ISO/IEC TR 11801-9905.

Class I and Class II balanced cabling channels in accordance with ISO/IEC 11801-1:2017 are implemented using Category 8.1 and Category 8.2 balanced screened cabling components, respectively.

NOTE 2 ISO/IEC/IEEE 8802-3:2017/AMD3:2017 25GBASE-T is defined using Category 8.1 and Category 8.2 (Class I and Class II, respectively) up to 1250 MHz.

ISO/IEC 11801-1 allows for variation in channel implementation configurations that maintain conformance to channel specifications.

Enhanced channel reference implementations use two connections, with two 2 m, 20 % derated cords attached to the ends of a permanent link, so that the permanent link length is equal to the channel length (in metres) minus 4 m.

Enhanced channels can provide additional SNR margin-to-capacity, which can potentially support additional reach, see Annex B.

NOTE 3 The possibility of additional reach can be verified with manufacturers of specific equipment before deployment.

Extended reach channel reference implementations, greater than 30 m, are evaluated over four reach ranges: ≤ 40 m, ≤ 50 m, ≤ 67 m, and ≤ 100 m; see Table 1.

Balanced cabling covered by this document:

- a) is specified in accordance with ISO/IEC 11801-1;
- b) is tested in accordance with ISO/IEC 11801-1, i.e. as specified in IEC 61935-1.

4.2 Channel performance enhancement methods for increased SNR

4.2.1 General

Table 1 shows the enhancement method considerations for 25 Gbit/s and 25GBASE-T operation over various extended reach cabling channels using Category 8.1 and Category 8.2 components.

NOTE 25GBASE-T can be supported only by channels which fully conform to the ISO/IEC/IEEE 8802-3:2017/AMD3 25GBASE-T link segment specifications, see 4.2.2.

Table 1 – Enhancement methods for 25 Gbit/s extended reach

	Channel length, L m			
Reach range	$30 < L \leq 40$	$40 < L \leq 50$	$50 < L \leq 67$	$68 < L \leq 100$
Application supported	25 Gbit/s and 25GBASE-T	25 Gbit/s	25 Gbit/s	25 Gbit/s
Recommended channel enhancement method				
Channel component Category 8.1	Reduced delay and delay skew in accordance with 4.2.2.	Reduced delay and delay skew in accordance with 4.2.2, and Enhanced cable in accordance with 4.2.3.	Reduced delay and delay skew in accordance with 4.2.2, Enhanced cable in accordance with 4.2.3, and Enhanced connector in accordance with 4.2.4.	Reduced delay and delay skew in accordance with 4.2.2, Enhanced cable in accordance with 4.2.3, and Enhanced connector in accordance with 4.2.4.
Channel component Category 8.2	Reduced delay and delay skew in accordance with 4.2.2.	Reduced delay and delay skew in accordance with 4.2.2, and Enhanced cable in accordance with 4.2.3.	Reduced delay and delay skew in accordance with 4.2.2, and Enhanced cable in accordance with 4.2.3	Reduced delay and delay skew in accordance with 4.2.2, Enhanced cable in accordance with 4.2.3, and Enhanced connector in accordance with 4.2.4.

iTeh STANDARD PREVIEW
 (standards.itech.ai)

4.2.2 Reduced delay and delay skew

ISO/IEC TR 11801-9909:2020
<https://standards.itech.ai/catalog/standards/sist/bc9add5a-8da6-4465-8a25-ved-propagation-delay-and-delay-skew-performance-compare>

Using components with improved propagation delay and delay skew performance compared to those specified in ISO/IEC 11801-1 for Category 8.1 and 8.2 components can provide longer channel lengths than the reference implementations of 30 m, see Annex A.

NOTE Engineered channels made from cable with higher NVP thus have inherently lower delay and delay skew characteristics; thus they can support more physical length, e.g. more than 30 m, while still conforming to all 25GBASE-T link segment specifications, including maximum delay specifications, i.e. 185 ns.

4.2.3 Enhanced cable

Using cables with enhanced RL, IL, TCL, ELTCTL and coupling attenuation compared to ISO/IEC 11801-1 Category 8.1 and 8.2 components specifications can provide longer channel lengths than the reference implementations of 30 m, see Annex B.

4.2.4 Enhanced connector

Using connecting hardware with enhanced RL, IL, TCL, ELTCTL and coupling attenuation compared to ISO/IEC 11801-1 Category 8.1 and 8.2 components specifications can provide longer channel lengths than the reference implementations of 30 m, see Annex B.

4.3 Example channel specifications with length scaling

4.3.1 General

Two informative example extended-reach enhanced channel transmission parameters specifications are given:

- a) 50 m using Category 8.1; and
- b) 50 m using Category 8.2.