

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 13041:2001

<https://standards.iteh.ai/catalog/standards/sist/d5b34fa6-d25e-4bd5-bc81-fe4029dedb41/sist-en-13041-2001>

EUROPEAN STANDARD

EN 13041

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 1999

ICS 65.080

English version

Soil improvers and growing media - Determination of physical properties - Dry bulk density, air volume, water volume, shrinkage value and total pore space

Amendements du sol et supports de culture -
Détermination des propriétés physiques - Masse volumique
apparente sèche, volume d'air, volume d'eau, valeur de
rétraction et porosité totale

Bodenverbesserungsmittel und Kultursubstrate -
Bestimmung der physikalischen Eigenschaften - Rohdichte
(trocken), Luftkapazität, Wasserkapazität,
Schrumpfungswert und Gesamtporenvolumen

This European Standard was approved by CEN on 23 October 1999.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

fe4029dedb41/sist-en-13041-2001



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

Contents

	Page
Foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 Principle	5
5 Apparatus	5
6 Preparation	6
7 Procedure	6
8. Expression of results	8
9 Number of replicates	10
10 Precision	10
11 Test report	10
Annex A (normative) Construction of sand suction table	11
Annex B (informative) Results of an interlaboratory trial to determine the physical characteristics	18
Bibliography	21

SIST EN 13041:2001

<https://standards.iteh.ai/catalog/standards/sist/d5b34fa6-d25e-4bd5-bc81-fe4029dedb41/sist-en-13041-2001>

Foreword

This European Standard has been prepared by Technical Committee CEN/TC 223 "Soil improvers and growing media", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2000, and conflicting national standards shall be withdrawn at the latest by June 2000.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 13041:2001](https://standards.iteh.ai/catalog/standards/sist/d5b34fa6-d25e-4bd5-bc81-fe4029dedb41/sist-en-13041-2001)

[https://standards.iteh.ai/catalog/standards/sist/d5b34fa6-d25e-4bd5-bc81-
fe4029dedb41/sist-en-13041-2001](https://standards.iteh.ai/catalog/standards/sist/d5b34fa6-d25e-4bd5-bc81-fe4029dedb41/sist-en-13041-2001)

1 Scope

This European Standard describes an instrumental method for the routine determination of the physical properties, dry bulk density, water volume, air volume, shrinkage value and total pore space of soil improvers or growing media.

This European Standard is not suitable for those materials which are very coarse, which do not make proper capillary contact or those which are pre-formed and non-particulate and have closed porosity. It is applicable to materials with particles ≤ 25 mm and/or flexible fibres ≤ 80 mm.

NOTE 1 The method is not applicable to liming materials or sewage sludges and is not suitable for materials like rockwool and foam slabs.

NOTE 2 The method is not applicable to inorganic materials.

NOTE 3 The requirements of the standard may differ from the national legal requirements for the declaration of the products concerned.

2 Normative references

This European Standard incorporates, by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

EN 12579	Soil improvers and growing media - Sampling
EN 13039	Soil improvers and growing media - Determination of organic matter content and ash
EN 13040 : 1999	Soil improvers and growing media - Sample preparation for chemical and physical tests, determination of dry matter content, moisture content and laboratory compacted bulk density.
ISO 11274:1998	Soil quality - Determination of the water retention characteristic - Laboratory methods.

3 Terms and definitions

For the purposes of this standard the terms and definitions in EN 12579 and the following apply.

3.1

air volume

that part of the volume of a sample filled by air measured under the conditions specified in this European Standard, in particular at a defined suction (e.g. minus 10 cm suction).

3.2

dry bulk density

ratio of the dry mass and volume of the sample in grams per litre.

3.3**total pore space**

total volume of voids filled with water and/or air measured under the conditions specified in this European Standard, in particular at a defined suction (e.g. minus 10 cm suction).

3.4**shrinkage value**

loss in volume of the sample after drying a moist sample.

3.5**water volume**

that part of the volume of a sample filled by water measured under the conditions specified in this European Standard, in particular at a defined suction (e.g. minus 10 cm suction).

3.6**particle density**

the ratio of the total mass of oven-dry solid particles (minerals, organic matter) to the volume of these particles. The volume of the internal pores of the particles and the pore spaces between particles are excluded.

4 Principle

The sample is saturated in water and then equilibrated on a sand box at minus 50 cm water pressure head. The sample is then transferred into double ring sample cylinders, re-wetted and equilibrated at minus 10 cm water pressure head. After equilibration the physical properties are calculated from the wet and dry weights of the sample in the lower ring.

iTech STANDARD PREVIEW
(standards.iteh.ai)

5 Apparatus**5.1 Double rings** (figure A.1)

[SIST EN 13041:2001](#)

<https://standards.iteh.ai/catalog/standards/sist/d5b34fa6-d25e-4bd5-bc81-fe4029dedb41/sist-en-13041-2001>

5.1.1 General

The double rings and fixing collars described in this clause, shall be made from any rigid material that will not deform at a temperature of up to 120 °C.

5.1.2 Lower sample ring

5.1.2.1 Sample ring of internal diameter (D_1) 100 ± 1 mm and height 50 ± 1 mm.

As each ring is individually made it is necessary to determine the volume (V_1), record the mass (m_1) and identify each lower sample ring. The volume shall be determined by measuring with a calliper gauge the mean height (at least quadruplicate measurements) (h_1) and mean diameter (d_1) of the sample rings. (At least triplicate measurements; top, middle and bottom).

5.1.2.2 Removable gauze-retaining ring or collar 2 cm high and 0,75 cm to 0,85 cm larger than the outer diameter of the sample ring.

5.1.2.3 Non-biodegradable synthetic gauze with a mesh size of about 0,1 mm.

5.1.3 Upper ring

5.1.3.1 Upper ring having the same internal diameter as the ring prepared in (5.1.2.1) and height $53 \text{ mm} \pm 1 \text{ mm}$.

5.1.3.2 Collar - fixed on the ring permitting the upper cylinder to be secured to the lower cylinder for the duration of the test.

5.2 Plastic tube, of approximately 14 cm diameter and 14 cm high to give a volume of about 2 litres. Tightly stretch and secure the gauze (5.1.2.3) to one end of the tube by means of an elastic band.

5.3 Water bath, capable of holding at least 4 plastic tubes (5.2) standing on a coarse mesh and capable of being filled with water to the top of the plastic tubes.

5.4 Sand suction table (figure A.3)

Prepare the sand suction table for example in accordance with annex A, using the fine sand to obtain the required suction. The pressure head in the plastic tubes (minus 50 cm) is measured from the bottom of the tube. The pressure head in the rings (minus 10 cm and minus 50 cm) is measured from the middle of the lower ring (figure A.3). The setting of the pressure head can be checked with a tensiometer or pressure transducer.

5.5 Ventilated drying oven set at $103\text{ °C} \pm 2\text{ °C}$

5.6 Analytical balance with a scale interval of 0,1 g

5.7 Shallow vessel, spoon or scoop approx. 50 ml capacity

6 Preparation

Prepare the laboratory sample in accordance with clause 8.4 of EN 13040 : 1999.

7 Procedure

7.1 Moistening, saturating and equilibration at minus 50 cm pressure head

7.1.1 Fill at least 2 tubes (5.2) with the test portion taking care to prevent artificial air voids. Cover each tube with synthetic gauze (5.1.2.3) secured with an elastic band. Place the tube on the grid in a dry water bath (5.3).

7.1.2 Slowly, with constant flow, fill the bath with water until the level reaches to within 1 cm below the top of the tube. Filling should take approximately 30 min.

7.1.3 If a tube shows signs of floating, place a weighted disc on the top of the tube allowing air to evacuate and at the same time ensuring that compaction of the sample does not take place, (figure A.4).

7.1.4 Allow to stand maintaining a constant water level until the sample is thoroughly wetted, (up to 36 h).

7.1.5 Remove the tubes and without delay transfer the tubes to the sand suction table. The bottom of the tube should be fully in contact with the sand. Apply a minus 50 cm pressure head, measured from the bottom of the tube, for 48 h.

7.2 Filling tubes

7.2.1 Secure the gauze (5.1.2.3) with the collar (5.1.2.2) to the base of the lower sample ring (5.1.2). Attach and secure the upper sample ring (5.1.3) to the lower sample ring.

7.2.2 Empty the tubes containing the equilibrated (minus 50 cm) wet sample from (7.1.5) onto a clean surface and gently mix taking care not to cause any physical damage to the sample.

7.2.3 Transfer using the shallow vessel (5.7) approximately 50 ml portions of the mixed sample to the prepared sample rings taking care to avoid compaction or artificial air voids and filling the cylinder and removable ring completely.

7.2.4 Fill at least 4 units with the sample. Place the unit on the grid in a dry water bath. Slowly, with constant flow, fill the bath (5.3) with water until the level reaches to within 1 cm below the top of the tube. Filling should take approximately 30 min.

7.2.5 Maintain a constant water level for 24 h. (figure A.5).

NOTE Two different baths may be used, one for minus 10 cm and one for minus 50 cm.

7.3 Suction

7.3.1 Carefully remove the units and without delay transfer to the sand bath (5.4) making sure there is contact between sand and the lower part of the unit. Cover the sand box and apply a minus 10 cm pressure head, measured from the middle of the lower ring.

7.3.2 It is important to regularly check that no air bubbles are present in the suction level regulator tubes.

Apply the suction until equilibrium is reached. A minimum of 48 h and up to 72 h is required.

7.4 Separation of rings

7.4.1 Remove the double ring sample cylinders from the sand box and place on a flat solid surface. Carefully remove the upper ring in a vertical movement. Using a knife or straight edge strike off the material level with the top of the sample ring without causing compaction. The levelling of fibrous materials can best be done by cutting off excess matter with a pair of scissors exercising considerable care to avoid other disturbances.

7.4.2 Remove any materials adhering to the outside of the sample ring and record the mass (m_2) taking care not to turn the ring.

7.4.3 Place in the drying oven (5.5) with out altering the structure and dry at $103\text{ °C} \pm 2\text{ °C}$ to constant mass (m_3).

7.4.4 Remove the ring and measure with a calliper gauge the mean height (quadruplicate measurements) (h_2) and mean diameter (triplicate measurements; top, middle and bottom) (d_2) of the dried samples.

NOTE This procedure cannot be carried out with some granular materials because they do not retain their shape on drying. In these cases, it is recommended to measure the height prior to drying.

7.5 Organic matter (W_{om})

Determine the organic matter content in accordance with EN 13039.

7.6 Ash content (W_{ash})

Determine the mineral matter content in accordance with EN 13039.

8. Expression of results

8.1 Volume of the sample ring

Calculate the volume of the sample ring using the following equation

$$V_1 = \left\{ \pi x (0,5d_1)^2 x h_1 \right\} \quad (1)$$

where

- V_1 is the volume of the ring in cubic centimetres (cm³);
- d_1 is the diameter in centimetres of the sample ring;
- h_1 is the height in centimetres of the sample ring.

8.2 Dry bulk density

$$D_{BD} = \frac{(m_3 - m_1)}{V_1} x 1000 \quad (2)$$

where

- D_{BD} is the dry bulk density in kilograms dry matter per cubic metre (kg/m³);
- m_1 is the mass in grams of the sample ring;
- m_3 is mass in grams of the dried sample plus sample ring;
- V_1 is the volume in cubic centimetres of the sample ring.

8.3 Shrinkage value

Calculate the shrinkage value of the sample after drying using the following equation:

$$S_{\%} = \frac{(V_1 - M_v)}{V_1} x 100 \quad (3)$$

where

- $S_{\%}$ is the shrinkage value of the sample after drying expressed as a percentage by volume;
- V_1 is the volume in cubic centimetres of the sample ring (8.1)
- d_2 is the diameter in centimetres of the dried sample;
- h_2 is the height in centimetres of the dried sample;
- V_m is the mean volume in cubic centimetres of the dried sample $\{\pi(0,5 \times d_2)^2 \times h_2\}$.

8.4 Particle density

Calculate the particle density using the following equation:

$$P_D = \frac{1}{\{W_{om} / (100 \times 1550)\} + \{W_{ash} / (100 \times 2650)\}} \quad (4)$$

where

- P_D is the particle density in kilograms per cubic metre (kg/m^3);
- W_{om} is the organic matter content expressed as a percentage by mass, (100 - ash %);
- W_{ash} is the ash expressed as a percentage by mass;
- 1550 is taken as the density in kilograms per cubic metre of organic matter [1, 2];
- 2650 is taken as the density in kilograms per cubic metre of ash [2].

8.5 Total pore space

Calculate the total pore space of the sample after applying minus 10 centimetre pressure head using the following equation:

$$P_s = \frac{(1 - D_{BD})}{P_D} \times 100 \quad (5)$$

where

- P_s is the total pore space expressed as a percentage by volume, % (V/V), wet sample at minus 10 centimetre pressure head;
- D_{BD} is the dry bulk density in kilograms per cubic metre (kg/m^3);
- P_D is the particle density in kilograms per cubic metre (kg/m^3).

8.6 Water volume

Calculate the water volume content of the sample after applying minus 10 centimetre pressure head using the following equation:

$$W_v = \frac{(m_2 - m_3)}{V_1} \times 100 \quad (10)$$

where

- W_v is the water volume content expressed as a percentage by volume, % (V/V), wet sample at minus 10 centimetre pressure head;
- V_1 is the volume in cubic centimetres of the sample ring;
- m_2 is the mass in grams of the wet sample plus sample ring at minus 10 centimetre pressure head;
- m_3 is the mass in grams of the dried sample plus sample ring at minus 10 centimetre pressure head.