

Edition 4.0 2023-07 REDLINE VERSION

INTERNATIONAL STANDARD



Resin based reactive compounds used for electrical insulation -

Part 2: Methods of test

(https://standards.iteh.ai)
Document Preview

IEC 60455-2:2023

https://standards.iteh.ai/catalog/standards/iec/3b064347-5ef5-4d96-9569-4a22f9726f31/iec-60455-2-2023





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch

www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublishedStay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.



Edition 4.0 2023-07 REDLINE VERSION

INTERNATIONAL STANDARD



Resin based reactive compounds used for electrical insulation – Part 2: Methods of test

Document Preview

IEC 60455-2:2023

https://standards.iteh.ai/catalog/standards/iec/3h064347-5ef5-4d96-9569-4a22f9726f31/iec-60455-2-2023

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 17.220.99, 29.035.01 ISBN 978-2-8322-7342-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

| | | | | _ |
|----|---------|--------|---|-----------|
| IN | TRODI | JCTI | ON | 2 |
| 1 | Scop | ре | | 8 |
| 2 | Norr | nativ | e references | 8 |
| 3 | Tern | ns an | d definitions | 11 |
| 4 | Gen | eral r | notes on methods of test | 11 |
| | 4.1 | | paration and conditioning | |
| | 4.2 | | uence of tests | |
| | 4.3 | | t report | |
| 5 | | | of test for reactive compounds and their components | |
| | 5.1 | | sh point | |
| | 5.2 | | isity | |
| | 5.3 | | cosity | |
| | 5.4 | | cosity after storing at elevated temperature | |
| | 5.5 | | stent of volatile organic components | |
| | 5.6 | | hermal increase of viscosity (processing time) | |
| | 5.7 | | If life | |
| | 5.8 | | | |
| | 5.9 | Soft | tening temperature | 14 |
| | 5.10 | Ash | content | 14 |
| | 5.11 | Fille | er content | 14 |
| | 5.12 | | orine content | |
| | 5.12 | | Total chlorine content of unsaturated polyesters and epoxide resins | |
| | 5.12 | | Inorganic chlorine content of epoxide resins and glycidyl esters | |
| | 5.12 | | Easily saponifiable chlorine content of epoxide resins and related | |
| | standar | | materials | 455-21402 |
| | 5.13 | Ten | dency of crystallisation | |
| | 5.14 | Еро | xide equivalent of epoxide resins | 14 |
| | 5.15 | Con | itent of isocyanate | 14 |
| | 5.16 | Wat | er content (Karl Fischer method) | 15 |
| | 5.17 | Hyd | roxyl value | 15 |
| | 5.17 | .1 | Polyester resins | 15 |
| | 5.17 | .2 | Resins other than polyester | 15 |
| | 5.18 | Acid | d value of polyester resins | 15 |
| | 5.19 | Amo | ount of double bonds of unsaturated polyester and acrylate resins | 15 |
| | 5.20 | Acid | d and acid-anhydride content of acid-anhydride hardeners | 15 |
| | 5.21 | Ami | ne value | 15 |
| | 5.22 | Pot | life | 15 |
| | 5.22 | .1 | General | 15 |
| | 5.22 | .2 | Resinous compounds for cable accessories | 15 |
| | 5.23 | Gel | time | 16 |
| | 5.23 | .1 | Unsaturated polyester based compounds | 16 |
| | 5.23.2 | | Phenolic resin based compounds | 16 |
| | 5.23 | .3 | Other compounds | 16 |
| | 5.24 | Exo | thermic temperature rise | 16 |
| | 5.24 | .1 | Unsaturated polyester based compounds | 16 |
| | 5.24.2 | | Resinous compounds for cable accessories | 16 |

| | | Other compounds | ••••• |
|---|----------------|---|-------|
| | | tal volume shrinkage of epoxide and unsaturated polyester based mpounds | 17 |
| | | iring in presence of water | |
| | 5.26.1 | General | |
| | 5.26.2 | Apparatus and materials | |
| | 5.26.3 | Pouring device | |
| | 5.26.4 | Procedure | |
| | 5.26.5 | Test report | |
| | | etermination of the degree of curing | |
| | | ring in thick layer and emissions during curing | |
| | 5.28.1 | General | |
| | 5.28.2 | Equipment | |
| | 5.28.3 | Test specimen | |
| | 5.28.4 | Procedure | |
| 6 | | s of test for cured reactive compounds | |
| • | | eneral | |
| | | st specimens. | |
| | 6.2.1 | General | |
| | 6.2.2 | Preparation of the reactive compound | |
| | 6.2.3 | Preparation of test specimens | |
| | 6.2.4 | Type and number of test specimens | |
| | - | ensity | |
| | | echanical properties | |
| | 6.4.1 | Tensile properties | 23 |
| | 6.4.2 | Compressive properties | |
| | 6.4.3 | Flexural properties | |
| | 6.4.4 | <u>1LC 00+35-2.2025</u> | |
| | 6.4.5 | Impact strength | |
| | | | |
| | 6.5.1 | ermal properties | |
| | 6.5.2 | Bond strength at elevated temperatureLinear thermal expansion | |
| | 6.5.3 | · | |
| | 6.5.4 | Thermal conductivityGlass transition | |
| | 6.5.5 | | |
| | 6.5.6 | Flammability | |
| | | | |
| | 6.5.7 6.5.8 | Dry heat resistance of resins for cable accessories – Method of test Wet heat resistance of resins for cable accessories | |
| | 6.5.9 | Loss of mass | |
| | | | |
| | 6.5.10 | Temperature index | |
| | | nemical properties | |
| | 6.6.1 | Water absorption | |
| | 6.6.2 | Effect of liquid chemicals | |
| | 6.6.3 | Resistance to mould growth | |
| | 6.6.4 | Water vapour permeability | |
| | | ectrical properties | |
| | 6.7.1 | Effect of water immersion on volume resistivity | |
| | 6.7.2 | Dielectric dissipation factor (tan δ) and relative permittivity | |
| | 6.7.3 | Break down voltage and electric strength | 31 |

| 6.7.4 | Proof tracking index (PTI) | 33 | | |
|--------------|---|----|--|--|
| 6.7.5 | Electrolytic corrosion | 33 | | |
| Annex A (int | formative) Health and safety | 38 | | |
| Bibliography | | | | |
| | | | | |
| Figure 1 - T | est apparatus for curing in presence of water test | | | |
| Figure 2 - T | est set-up for volume resistivity | | | |
| Figure 1 – E | xamination grid | 19 | | |
| Figure 2 – P | osition of examination grid on the specimen | 19 | | |
| Figure 3 – E | xample of electrode arrangement for flexible cured compound | 36 | | |
| Figure 4 – E | xample of electrode arrangement for rigid cured compound | 37 | | |
| | | | | |
| Table 1 – Co | ondition of the top side | 20 | | |
| Table 2 – Co | ondition of the bottom side | 21 | | |
| Table 3 – Co | ondition of the interior | 21 | | |
| Table 4 - V | nide | 21 | | |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

RESIN BASED REACTIVE COMPOUNDS USED FOR ELECTRICAL INSULATION –

Part 2: Methods of test

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 60455-2:2015. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 60455-2 has been prepared by IEC technical committee 15: Solid electrical insulating materials. It is an International Standard.

This fourth edition cancels and replaces the third edition published in 2015. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Introduction of test methods related to IEC 60455-3-8;
- b) Additional and updated test methods for resins.

The text of this International Standard is based on the following documents:

| Draft | Report on voting |
|--------------|------------------|
| 15/1006/FDIS | 15/1015/RVD |

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 60455 series, published under the general title Resin based reactive compounds used for electrical insulation, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of IEC 60455 is one of a series which deals with solvent-free resin based reactive compounds and their components used for electrical insulation.

The series consists of three parts:

- Part 1: Definitions and general requirements;
- Part 2: Methods of test;
- Part 3: Specifications for individual materials.

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 60455-2:2023

https://standards.iteh.ai/catalog/standards/iec/3h064347-5ef5-4d96-9569-4a22f9726f31/iec-60455-2-2023

RESIN BASED REACTIVE COMPOUNDS USED FOR ELECTRICAL INSULATION –

Part 2: Methods of test

1 Scope

This part of IEC 60455 specifies methods of test to be used for testing resin based reactive compounds, their components and cured compounds used for electrical insulation.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050 (all parts), International Electrotechnical Vocabulary (available at http://www.electropedia.org)

IEC 60068-2-10:2005, Environmental testing – Part 2-10: Tests – Test J and guidance: Mould growth

IEC 60093:1980, Methods of test for volume resistivity and surface resistivity of solid electrical insulating materials

IEC 60112:20032020, Method for the determination of the proof and the comparative tracking indices of solid insulating materials

IEC 60216 (all parts), Electrical insulating materials – Thermal endurance properties

IEC 60243-1:19982013, Electrical strength of insulating materials – Test methods – Part 1: Tests at power frequencies

IEC 60250:1969, Recommended methods for the determination of the permittivity and dielectric dissipation factor of electrical insulating materials at power, audio and radio frequencies including metre wavelengths

IEC 60296:20122020, Fluids for electrotechnical applications – Unused Mineral insulating oils for transformers and switchgear electrical equipment

IEC 60426:2007, Electrical insulating materials – Determination of electrolytic corrosion caused by insulating materials – Test methods

IEC 60455-1:1998, Resin based reactive compounds used for electrical insulation – Part 1: Definitions and general requirements

IEC 60455-3 (all parts), Resin based reactive compounds used for electrical insulation – Part 3: Specifications for individual materials

IEC 60455-3-8:20132021, Resin based reactive compounds used for electrical insulation – Part 3-8: Specifications for individual materials – Resins for cable accessories

IEC 60695-11-10:19992013, Fire hazard testing – Part 11-10: Test flames – 50 W horizontal and vertical flame test methods

IEC 60814:1997, Insulating liquids – Oil-impregnated paper and pressboard – Determination of water by automatic coulometric Karl Fischer titration

IEC 61033:1991, Test methods for the determination of bond strength of impregnating agents to an enamelled wire substrate

IEC 61099:2010, Insulating liquids – Specifications for unused synthetic organic esters for electrical purposes

ISO 37:2011, Rubber, vulcanized or thermoplastic – Determination of tensile stress-strain properties

ISO 62:2008, Plastics – Determination of water absorption

ISO 75 (all parts), Plastics and ebonite – Determination of temperature of deflection under load

ISO 175:2010, Plastics – *Methods of test for the determination of the effects of immersion in liquid chemicals*. *including water*

ISO 178:2010, Plastics – Determination of flexural properties

ISO 179-1:2010, Plastics – Determination of Charpy impact properties – Part 1: Non-instrumented impact test

ISO 179-2:1997, Plastics – Determination of Charpy impact properties – Part 2: Instrumented impact test

ISO 291, Plastics – Standard atmospheres for conditioning and testing

ISO 306:20042013, Plastics – Thermoplastic materials – Determination of Vicat softening temperature (VST)

ISO 527 (all parts), Plastics – Determination of tensile properties

ISO 584:1982, Plastics – Unsaturated polyester resins – Determination of reactivity at 80 degrees C (conventional method)

ISO 604:2002, Plastics – Determination of compressive properties

ISO 868:2003, Plastics and ebonite – Determination of indentation hardness by means of a durometer (Shore hardness)

ISO 1183-1:20122019, Plastics – Methods for determining the density of non-cellular plastics – Part 1: Immersion method, liquid pycnometer method and titration method

ISO 1513:2010, Paints and varnishes – Examination and preparation of test samples for testing

ISO 1523:2002, Paints, varnishes, petroleum and related products — Determination of flash point — Closed cup equilibrium method

ISO 1675:1985, Plastics – Liquid resins – Determination of density by the pycnometer method

– 10 **–**

ISO 2039-1:1993, Plastics - Determination of hardness - Part 1: Ball indentation method

ISO 2114:19962000, *Plastics – Unsaturated* (polyester resins) and paints and varnishes (binders) – Determination of partial acid value and total acid value

ISO 2431:1993, Paints and varnishes – Determination of flow time by use of flow cups

ISO 2535:1997, Plastics – Unsaturated polyester resins – Measurement of gel time at 25 degrees C

ISO 2554:1997, Plastics - Unsaturated polyester resins - Determination of hydroxyl value

ISO 2555:1989, Plastics – Resins in the liquid state or as emulsions or dispersions – Determination of apparent viscosity by the Brookfield test using a single cylinder type rotational viscometer method

ISO 2592:1973, Petroleum products – Determination of flash and fire points – Cleveland open cup method

ISO 3001:1997, Plastics – Epoxide Epoxy compounds – Determination of epoxide epoxy equivalent

ISO 3219:1993, Plastics – Polymers/resins in the liquid state or as emulsions or dispersions – Determination of viscosity using a rotational viscometer with defined shear rate

ISO 3451-1:1997, Plastics - Determination of ash - Part 1: General methods

ISO 3521:1997, Plastics – Unsaturated polyester and epoxy resins – Determination of overall volume shrinkage

ISO 3679:1983, Paints, varnishes, petroleum and related products – Determination of flashpoint – Rapid equilibrium method

ISO 4573:1978, Plastics – Epoxide resins and glycidyl esters – Determination of inorganic chlorine

ISO 4583:1998, Plastics – Epoxide resins and related materials – Determination of easily saponifiable chlorine

ISO 4615:1979, Plastics – Unsaturated polyesters and epoxide resins – Determination of total chlorine content

ISO 4625:1980, Binders for paints and varnishes – Determination of softening point – Ring-and-ball method

ISO 4895, Plastics – Liquid epoxy resins – Determination of tendency to crystallize

ISO 7056, Plastics laboratory ware – Beakers

ISO 9396:1997, Plastics – Phenolic resins – Determination of the gel time at a given temperature of resols under specific conditions using automatic apparatus

ISO 11357-2:1999, Plastics – Differential scanning calorimetry (DSC) – Part 2: Determination of glass transition temperature and step height

ISO 11359-2:1999, Plastics – Thermomechanical analysis (TMA) – Part 2: Determination of coefficient of linear thermal expansion and glass transition temperature

ISO 11359-3:2002, Plastics – Thermomechanical analysis (TMA) – Part 3: Determination of penetration temperature

ISO 14896:2009, Plastics – Polyurethane raw materials – Determination of isocyanate content

ISO 15528:2000, Paints, varnishes and raw materials for paints and varnishes - Sampling

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60455-1 and IEC 60050 and the following shall apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1

volume resistance

part of the insulation resistance which is due to conduction through the volume and excluding surface current

3.2

volume resistivity

volume resistance reduced to a cubical unit volume

3.3 <u>IEC 60455-2:202</u>:

dielectric dissipation factor lards/iec/3b064347-5ef5-4d96-9569-4a22f9726f31/iec-60455-2-2023 tan δ

numerical value of the ratio of the imaginary to the real part of the complex permittivity

3.4

relative permittivity

٤r

ratio of the absolute permittivity to the electric constant

Note 1 to entry: In practical engineering, it is usual to employ the term 'permittivity' when referring to relative permittivity

4 General notes on methods of test

4.1 Preparation and conditioning

Unless otherwise specified in the relevant specification standard or in the method of test, all tests shall be carried out at atmospheric conditions in a temperature range of between 21 °C and 29 °C and a relative humidity range of between 45 % and 70 %. Before measurements are made, the sample or test specimen shall be pre-conditioned under these atmospheric conditions for a time sufficient to allow the sample or the test specimen to reach stability. For taking samples in liquid or paste form, ISO 15528 shall be applied. For preparation of such samples for testing, ISO 1513 shall be applied.

NOTE For definitions of terms for standard atmospheres, see ISO 558. The test atmosphere as specified above does not comply with any of the two standard atmospheres as specified in ISO 291 but covers both ranges inclusive of their tolerances

Normally, all requirements for a method of test are given in the description, and diagrams are intended only to illustrate one possible arrangement for conducting the test. In case of inconsistencies between this document and the specification sheets of the IEC 60455-3 series, the latter shall prevail. When another standard is invoked for a test method, reference to that standard shall be included in the report.

4.2 Sequence of tests

To avoid unnecessary efforts, tests shall be carried out on the samples in the following sequence:

- 1) tests on individual components prior to mixing;
- 2) tests on reactive compound just after mixing (ready to use);
- 3) tests on cured compound;
- 4) tests on cured compound after pre treatment (thermal, humidity, water etc.).

If the sample under test fails a test the following tests may become obsolete.

4.3 Test report

If not otherwise specified, the test report shall include the following data:

- 1) resin designation and identification;
- 2) lot number or other identification;
- 3) confirmation of marking and labelling according to the material safety data sheet (MSDS);
- 4) test results;
- 5) major test parameters, including conditioning and calibration, if any;
- 6) processing conditions used to reactive compound;
- 7) copy of the technical data sheet (TDS) and (MSDS).

http 5/s Methods of test for reactive compounds and their components 31/iec-60455-2-2023

5.1 Flash point

For flash point temperatures of 79 °C and above, the method given in ISO 2592 shall be used. For flash point temperatures below 79 °C, the method given in ISO 1523 shall be used with any of the closed-cup apparatus as described in Annex A of ISO 1523:2002. ISO 1523 shall be read in conjunction with ISO 3679. Two measurements shall be made on two separate samples, and the two results of the flash point shall be reported along with reference to the standards applied.

5.2 Density

The method given in ISO 1675 shall be used. Two measurements shall be made, and the two results of the density shall be reported.

5.3 Viscosity

The viscosity shall be determined with a suitable device at (23 ± 0.5) °C if not otherwise specified. If a rotating type of device is used, it shall be in accordance with ISO 2555 (Brookfield type) or with ISO 3219 (a type working at a defined shear rate). If an efflux type of equipment is used, the method of test and the flow cup shall be in accordance with ISO 2431. Two measurements shall be made, and the two results of the viscosity shall be reported, along with reference to the standards applied.

5.4 Viscosity after storing at elevated temperature

This method is not applicable to one-component systems or components containing hardener.