



Designation: D7367 – 19

Standard Test Method for Determining Water Holding Capacity of Fiber Mulches for Hydraulic Planting¹

This standard is issued under the fixed designation D7367; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This quantitative test method determines the water holding capacity of fiber mulches, including wood, paper, and agriculturally derived and blended fiber mulches that are used for hydraulic seeding and planting. Results from this testing can be used as a quality assurance and/or quality control data for manufacturing processes.

1.2 There are no known limitations to this test method.

1.3 *Units*—The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.4 All observed and calculated values shall conform to the guidelines for significant digits and rounding established in Practice D6026.

1.4.1 The procedures used to specify how data are collected/recorded or calculated in the standard are regarded as the industry standard. In addition, they are representative of the significant digits that generally should be retained. The procedures used do not consider material variation, purpose for obtaining the data, special purpose studies, or any considerations for the user's objectives; and it is common practice to increase or reduce significant digits of reported data to be commensurate with these considerations. It is beyond the scope of this standard to consider significant digits used in analysis methods for engineering data.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recom-*

mendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

2. Referenced Documents

2.1 *ASTM Standards:*²

D653 Terminology Relating to Soil, Rock, and Contained Fluids

D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction

D4753 Guide for Evaluating, Selecting, and Specifying Balances and Standard Masses for Use in Soil, Rock, and Construction Materials Testing

D6026 Practice for Using Significant Digits in Geotechnical Data

E11 Specification for Woven Wire Test Sieve Cloth and Test Sieves

3. Terminology

3.1 *Definitions*—For definitions of common technical terms used in this standard, refer to Terminology D653.

4. Summary of Test Method

4.1 A representative sample of a fiber mulch is taken from a packaged bale or bag. The representative sample is thoroughly mixed to obtain 3 test specimens. The test specimens are allowed to condition for 24 h. Then, the mass of each test specimen is determined as is the mass of a sieve and a sieve pan. Test water is then added to the test specimen and mixed. The test water and fiber is then poured over a sieve and evenly distributed. The sieve is then placed in bowl to allow the fiber mulch to saturate. After saturation, the sieve is allowed to drain and the sieve and pan are dried off before the mass of the sieve plus sieve pan plus saturated fiber mulch is determined. This process is repeated for the other 2 test specimens. The water holding capacity is expressed as a percentage of increased mass after saturation.

¹ This test method is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.25 on Erosion and Sediment Control Technology.

Current edition approved June 15, 2019. Published July 2019. Originally approved in 2007. Last previous edition approved in 2014 as D7367 – 14. DOI:10.1520/D7367-19.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

*A Summary of Changes section appears at the end of this standard