

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE

Rotating electrical machines –  
Part 9: Noise limits

ITIH STANDARD PREVIEW  
(standards.iteh.ai)

Machines électriques tournantes –  
Partie 9: Limites de bruit

<https://standards.iteh.ai/catalog/standards/sist/8f64e25c-e19e-4bcd-b96e-9bb4b13e3e3e/iec-60034-9-2021>  
IEC 60034-9:2021





## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

#### IEC online collection - [oc.iec.ch](http://oc.iec.ch)

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

### A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

### A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

#### Recherche de publications IEC -

[webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

#### IEC online collection - [oc.iec.ch](http://oc.iec.ch)

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 000 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

#### Service Clients - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: [sales@iec.ch](mailto:sales@iec.ch).

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE

Rotating electrical machines –  
Part 9: Noise limits

Machines électriques tournantes –  
Partie 9: Limites de bruit

STANDARD PREVIEW  
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/8f64e25c-e19e-4bcd-b96e-9bb4b13e3e3e/iec-60034-9-2021>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

ICS 29.160.01

ISBN 978-2-8322-1034-0

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## CONTENTS

FOREWORD .....	3
INTRODUCTION .....	5
1 Scope .....	6
2 Normative references .....	6
3 Terms and definitions .....	7
4 Methods of measurement .....	8
5 Test conditions .....	8
5.1 Machine mounting .....	8
5.1.1 Precautions .....	8
5.1.2 Resilient mounting .....	9
5.1.3 Rigid mounting .....	9
5.2 Test operating conditions .....	9
6 Sound power level limits .....	9
7 Determination of sound pressure level .....	10
8 Declaration and verification of sound power values .....	10
Annex A (informative) Typical values for measurement surface index .....	16
Annex B (informative) Information on typical noise increments caused by converter supply .....	17
Bibliography .....	20
Figure B.1 – Frequency spectrum of the currents at the output terminals of a 6-pulse block-type current-source converter $f_1 = 50$ Hz .....	17
Figure B.2 – Frequency spectrum of the voltages at the terminals of a type A voltage-source converter (characterized by pronounced spikes close to the switching frequency and its multiples) $f_1 = 50$ Hz, $f_s = 3$ kHz .....	17
Figure B.3 – Frequency spectrum of the voltages of a type B voltage-source converter (characterized by a broad voltage spectrum without pronounced spikes) $f_1 = 50$ Hz, $f_s$ average = 4,5 kHz .....	18
Table 1 – Maximum A-weighted sound power level, $L_{WA}$ in dB, at no-load (excluding motors according to Table 2 and Table 3) (Method of cooling, IC code, see IEC 60034-6, Method of protection, IP code, see IEC 60034-5) .....	12
Table 2 – Maximum A-weighted sound power level, $L_{WA}$ in dB, at no-load, 50 Hz, sinusoidal supply (for single speed three-phase cage induction motors) .....	13
Table 3 – Maximum A-weighted sound power level, $L_{WA}$ in dB, at no-load, 60 Hz, sinusoidal supply (for single speed three-phase cage induction motors) .....	14
Table 4 – Expected increase, over no-load condition, in A-weighted sound power levels, $\Delta L_{WA}$ in dB, for rated load condition (for motors according to Table 2 and Table 3) .....	15
Table A.1 – Typical values for measurement surface index for the conversion from sound power level to sound pressure level based on using parallelepiped measurement surface according to ISO 3744 .....	16
Table B.1 – Resonance frequencies of vibration mode r .....	18
Table B.2 – Increments of A-weighted noise values .....	19

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## ROTATING ELECTRICAL MACHINES –

## Part 9: Noise limits

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60034-9 has been prepared by IEC technical committee 2: Rotating machinery. It is an International Standard.

This fifth edition cancels and replaces the fourth edition, published in 2003 and its amendment 1, published in 2007. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) In Table 2 and Table 3 cooling methods IC01, IC11, IC21 and IC31, IC71, IC81 are now covered.
- b) This edition adds Table 3 for 60 Hz machines, whereas Table 2, which covers only 50 Hz machines, has no change in levels.
- c) In Table 3, grade A is added to harmonize the highest levels seen in IEC and NEMA, whereas grade B was added to harmonize the lowest, more restrictive levels seen in IEC and NEMA.

- d) The clause “Determination of noise increments caused by converter supply” has been shifted to Annex B and renamed “Information on typical noise increments caused by converter supply”

The text of this International Standard is based on the following documents:

FDIS	Report on voting
2/2064/FDIS	2/2069/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

A list of all parts in the IEC 60034 series, published under the general title *Rotating electrical machines*, can be found on the IEC website.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/standardsdev/publications](http://www.iec.ch/standardsdev/publications).

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

STANDARD PREVIEW  
(standards.iteh.ai)  
IEC 60034-9:2021  
<https://standards.iteh.ai/catalog/standards/sist/8f64e25c-e19e-4bcd-b96e-9bb4b13e3e3e/iec-60034-9-2021>

## INTRODUCTION

Acoustic quantities can be expressed in sound pressure terms or sound power terms. The use of a sound power level, which can be specified independently of the measurement surface and environmental conditions, avoids the complications associated with sound pressure levels, which require additional data to be specified. Sound power levels provide a measure of radiated energy and have advantages in acoustic analysis and design.

## **iTeh STANDARD PREVIEW** **(standards.iteh.ai)**

[IEC 60034-9:2021](https://standards.iteh.ai/catalog/standards/sist/8f64e25c-e19e-4bcd-b96e-9bb4b13e3e3e/iec-60034-9-2021)

<https://standards.iteh.ai/catalog/standards/sist/8f64e25c-e19e-4bcd-b96e-9bb4b13e3e3e/iec-60034-9-2021>

# ROTATING ELECTRICAL MACHINES –

## Part 9: Noise limits

### 1 Scope

This part of IEC 60034:

- specifies test methods for the determination of sound power level of rotating electrical machines;
- specifies maximum A-weighted sound power levels for factory acceptance testing of network-supplied, rotating electrical machines in accordance with IEC 60034-1, having methods of cooling according to IEC 60034-6 and degrees of protection according to IEC 60034-5, and having the following characteristics:
  - standard design, either AC or DC, without additional special electrical, mechanical, or acoustical modifications intended to reduce the sound power level
  - rated output from 1 kW (or kVA) up to and including 5 500 kW (or kVA)
  - rated speed not greater than 3 750 min<sup>-1</sup>

Excluded are noise limits for AC motors supplied by converters. For these conditions see Annex B for guidance.

The object of this document is to determine maximum A-weighted sound power levels,  $L_{WA}$  in decibels, dB, for airborne noise emitted by rotating electrical machines of standard design, as a function of power, speed and load, and to specify the method of measurement and the test conditions appropriate for the determination of the sound power level of the machines to provide a standardized evaluation of machine noise up to the maximum specified sound power levels. This document does not provide correction for the existence of tonal characteristics.

Sound pressure levels at a distance from the machine may be required in some applications, such as hearing protection programs. Information is provided on such a procedure in Clause 7 based on a standardized test environment.

NOTE 1 This document recognizes the economic reason for the availability of standard noise-level machines for use in non-critical areas or for use with supplementary means of noise attenuation.

NOTE 2 Where sound power levels lower than those specified in Table 1, Table 2 or Table 3 are required, these are agreed between the manufacturer and the purchaser, as special electrical, mechanical, or acoustical design may involve additional measures.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60034-1, *Rotating electrical machines – Part 1: Rating and performance*

IEC 60034-5, *Rotating electrical machines – Part 5: Degrees of protection provided by the integral design of rotating electrical machines (IP code) – Classification*

IEC 60034-6, *Rotating electrical machines – Part 6: Methods of cooling (IC Code)*



ISO 3741, *Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Precision methods for reverberation test rooms*

ISO 3743-1, *Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Engineering methods for small, movable sources in reverberant fields – Part 1: Comparison method for a hard-walled test room*

ISO 3743-2, *Acoustics – Determination of sound power levels of noise sources using sound pressure – Engineering methods for small, movable sources in reverberant fields – Part 2: Methods for special reverberation test rooms*

ISO 3744, *Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Engineering methods for an essentially free field over a reflecting plane*

ISO 3745, *Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Precision methods for anechoic rooms and hemi-anechoic rooms*

ISO 3746, *Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Survey method using an enveloping measurement surface over a reflecting plane*

ISO 3747, *Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Engineering/survey methods for use in situ in a reverberant environment*

ISO 4871, *Acoustics – Declaration and verification of noise emission values of machinery and equipment*

<https://standards.iteh.ai/catalog/standards/sist/8f64e25c-e19e-4bcd-b96e-9bb4b13e3e3e/iec-60034-9-2021>

ISO 9614-1, *Acoustics – Determination of sound power levels of noise sources using sound intensity – Part 1: Measurement at discrete points*

ISO 9614-2, *Acoustics – Determination of sound power levels of noise sources using sound intensity – Part 2: Measurement by scanning*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

#### 3.1

##### sound power level

$L_W$

ten times the logarithm to the base 10 of the ratio of the sound power radiated by the source under test to the reference sound power [ $W_0 = 1 \text{ pW}$  ( $10^{-12} \text{ W}$ )] expressed in decibels

### 3.2 sound pressure level

$L_p$

ten times the logarithm to the base 10 of the ratio of the square of the sound pressure to the square of the reference sound pressure [ $P_0 = 20 \mu\text{Pa}$  ( $2 \times 10^{-5} \text{ Pa}$ )] expressed in decibels

### 3.3 measurement surface index

$L_S$

ten times the logarithm to the base 10 of the ratio of the measurement surface  $S$  to the reference surface [ $S_0 = 1 \text{ m}^2$ ] expressed in decibels

### 3.4 maximum value

value that defines the upper limit without further tolerance

## 4 Methods of measurement

4.1 Sound pressure level measurements and calculation of sound power level produced by the machine shall be made in accordance with ISO 3744, unless one of the alternative methods specified in 4.3 or 4.4 below applies.

NOTE It is general practice to use the parallelepiped method for all shaft heights.

4.2 The maximum sound power levels specified in Table 1, Table 2 and Table 3 or adjusted by Table 4 relate to measurements made in accordance with 4.1.

4.3 When appropriate, one of the methods of precision or engineering grade accuracy, such as the methods of ISO 3741, ISO 3743-1, ISO 3743-2, ISO 3745, ISO 9614-1 or ISO 9614-2, may be used to determine sound power levels.

4.4 The simpler but less accurate method specified in ISO 3746 or ISO 3747 may be used, especially when the environmental conditions required by ISO 3744 cannot be satisfied (for example, for large machines).

However, to prove compliance with this document, unless a correction due to inaccuracy of the measurement has already been applied to the values determined by this method in accordance with ISO 3746 or ISO 3747, the levels of Table 1, Table 2 and Table 3 shall be decreased by 2 dB.

4.5 If testing under rated load conditions, the methods of ISO 9614 are preferred. However, other methods are allowed when the load machine and auxiliary equipment are acoustically isolated or located outside the test environment.

## 5 Test conditions

### 5.1 Machine mounting

#### 5.1.1 Precautions

Care should be taken to minimize the transmission and the radiation of structure-borne noise from all mounting elements including the foundation. This can be achieved by the resilient mounting for smaller machines; however, larger machines can usually only be tested under rigid mounting conditions.

Machines tested under load conditions shall be rigidly mounted.

### 5.1.2 Resilient mounting

The natural frequency of the support system and the machine under test shall be lower than a third of the frequency corresponding to the lowest rotational speed of the machine.

The effective mass of the resilient support shall be not greater than one-tenth of that of the machine under test.

### 5.1.3 Rigid mounting

The machines shall be rigidly mounted to a surface with dimensions adequate for the machine type (for example by foot or flange fixed in accordance with the manufacturer's instructions). The machine shall not be subject to additional mounting stresses from incorrect shimming or fasteners.

## 5.2 Test operating conditions

The following test conditions shall apply:

- a) The machine shall operate at rated voltage(s), rated frequency or rated speed(s) and with appropriate field current(s) (when applicable). These shall be measured with instruments of an accuracy of 1 % or better.
    - The standard load condition shall be no-load, except for series wound motors.
    - When required, the machine shall be operated at an agreed load condition.
  - b) Machines shall be tested in their operating position within their specified duty that generates the greatest noise.
  - c) For an AC motor, the waveform and the degree of unbalance of the supply system shall comply with the requirements of IEC 60034-1.  
IEC 60034-9:2021  
<https://standards.iteh.ai/catalog/standards/sis/854e25c-e19e-4b3d-b96e-9bb4b13e3e3e/iec-60034-9-2021>
- NOTE Any increase of voltage (and current) waveform distortion and unbalance will result in an increase of noise.
- d) A synchronous motor with adjustable excitation field shall be run with excitation to obtain unity power factor or for large machines tested as a generator.
  - e) A generator shall be either run as a motor or driven at rated speed with excitation to obtain the rated voltage on open circuit.
  - f) A machine suitable for more than one speed shall be evaluated over the operating speed range.
  - g) A motor intended to be reversible shall be operated in both directions unless no difference in sound power level is expected. A unidirectional motor shall be tested in its design direction.

## 6 Sound power level limits

Where a machine is tested under the conditions specified in Clause 5, the sound power level of the machine shall not exceed the relevant value(s) specified as follows:

- a) A machine, other than those specified in b), operating at no-load shall be as specified in Table 1.
- b) A single-speed three-phase cage induction motor with cooling classification IC411, IC511, IC611, IC01, IC11, IC21, IC31, IC71 and IC81, at 50 Hz or 60 Hz, shaft heights from 90 up to and including 560, and with rated output not less than 1,0 kW and not exceeding 1 000 kW:
  - operating at no-load shall be as specified in Table 2 and Table 3
  - operating at rated load shall be the sum of the values established in Table 2, Table 3 and Table 4
  - Grade A in Table 3 is the maximum level that a standard 60 Hz motor shall meet

- Grade B in Table 3 is a reduced level for 60 Hz motors that will meet the more stringent requirements of the end-user
- unless grade B is specifically requested, grade A is to be used as the default noise level for 60 Hz motors.

NOTE 1 The limits of Table 1, Table 2 and Table 3 recognize class 2 accuracy grade levels of measurement uncertainty and production variations.

NOTE 2 Sound power levels, under full-load condition, are normally higher than those at no-load. Generally, if ventilation noise is predominant the change may be small; but if the electromagnetic noise is predominant the change may be significant.

NOTE 3 The limits are irrespective of the direction of rotation. A machine with a unidirectional ventilator is generally less noisy than one with a bi-directional ventilator. This effect is more significant for high-speed machines, which may be designed for unidirectional operation only.

NOTE 4 For some machines, the limits in Table 1 may not apply for speeds below nominal speed. In such a case, or where the relationship between noise level and load is important, limits should be agreed between the manufacturer and the purchaser.

NOTE 5 For multispeed machines the values in the Table 1 apply.

## 7 Determination of sound pressure level

Sound pressure levels are not required as part of this document.

However, if requested by end user to provide pressure levels, for example in accordance with Annex A, it shall be per agreement between user and manufacturer. An A-weighted sound pressure level may be determined directly from the sound power level as follows:

$$L_p = L_W - L_S$$

<https://standards.iteh.ai/catalog/standards/sist/8f64e25c-e19e-4bcd-b96e-9bb4b13e3e3e/iec-60034-9-2021>

$$L_S = 10 \log_{10} \left( \frac{S}{S_0} \right)$$

where:

- $L_p$  is the sound pressure level in a free field over a reflecting plane at 1 m distance from the machine;
- $L_W$  is the sound power level determined according to this document;
- $L_S$  is the measurement surface index;
- $S_0$  is 1,0 m<sup>2</sup>;
- $S$  is the area of the surface enveloping the machine at a distance of 1 m according to ISO 3744, 7.2.4. (Parallelepiped measurement surface).

NOTE 1 These sound pressure levels are for free field, over a reflecting plane. The sound pressure level for *in situ* conditions (that is, for hearing protection requirements) is different.

NOTE 2 For typical values of the measurement surface index used for conversions from sound power to sound pressure levels for machines in Table 2 and Table 3, see Annex A.

## 8 Declaration and verification of sound power values

A machine can be declared to comply with this document if, when tested under the conditions specified in Clause 5, the sound power level of the machine does not exceed the value specified in Clause 6.

The method selected and the type of measurement surface used shall be reported.

When requested sound power values determined according to this document can be reported according to the procedures of ISO 4871 using the dual-number presentation (determined sound power level  $L$  and uncertainty  $K$ ).

Values for the uncertainty  $K$  are:

- a) single machine
  - 1,5 dB (grade 1: laboratory)
  - 2,5 dB (grade 2: expertise)
  - 4,5 dB (grade 3: verification) (confidence 95 %).
- b) set of machines of the same batch
  - 1,5 dB to 4,0 dB (grades 1 and 2)
  - 4,0 dB to 6,0 dB (grade 3).

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[IEC 60034-9:2021](https://standards.iteh.ai/catalog/standards/sist/8f64e25c-e19e-4bcd-b96e-9bb4b13e3e3e/iec-60034-9-2021)

<https://standards.iteh.ai/catalog/standards/sist/8f64e25c-e19e-4bcd-b96e-9bb4b13e3e3e/iec-60034-9-2021>