



Designation: D5232 – 19

Standard Practice for Determining the Stability and Miscibility of a Solid, Semi-Solid, or Liquid Waste Material¹

This standard is issued under the fixed designation D5232; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice is designed to determine whether a waste material reacts when it is mixed with air, water, strong acid, strong base, an oil/solvent mixture, other waste mixtures, or solid media such as a geological formation or solidification agents.

1.2 The miscibility of the waste material with the above media can also be defined.

NOTE 1—The following ASTM standards provide supplemental information: Test Methods [D4978](#), [D4980](#), [D4982](#), [D5049](#), and [D5057](#) and Practices [D4979](#), [D4981](#), and [D5058](#).

1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.* For specific hazard statements, see Section 8.

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

[D1193](#) Specification for Reagent Water

[D4978](#) Test Methods for Screening of Reactive Sulfides in Waste

¹ This practice is under the jurisdiction of ASTM Committee D34 on Waste Management and is the direct responsibility of Subcommittee D34.01.06 on Analytical Methods.

Current edition approved Sept. 1, 2019. Published September 2019. Originally approved in 1992. Last previous edition approved in 2013 as D5232 – 13. DOI: 10.1520/D5232-19.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

[D4979](#) Practice for Physical Description Screening Analysis in Waste

[D4980](#) Test Methods for Screening of pH in Waste (Withdrawn 2009)³

[D4981](#) Practice for Screening of Oxidizers in Waste

[D4982](#) Test Methods for Flammability Potential Screening Analysis of Waste

[D5049](#) Test Method for Screening Cyanides In Waste (Withdrawn 1999)³

[D5057](#) Test Method for Screening Apparent Specific Gravity and Bulk Density of Waste

[D5058](#) Practices for Compatibility of Screening Analysis of Waste

[D5681](#) Terminology for Waste and Waste Management

3. Terminology

3.1 Definitions of terms in this practice appear in Terminology [D5681](#).

4. Summary of Practice

4.1 The stability and miscibility of a waste material are observed when the waste is mixed with various media.

5. Significance and Use

5.1 This practice will identify waste materials that are potentially unstable when they come in contact with other materials at a waste treatment or disposal site.

5.2 This practice will serve to determine the miscibility of waste materials with various media, including other wastes.

5.3 This practice may not be applicable to all wastes. The appropriateness of these tests depends upon the proposed management of the waste.

5.4 Since the initiation of some chemical reactions are slow to take place, the user may wish to establish reagent-to-waste contact times prior to observing the mixes for any reactions.

6. Apparatus and Materials

6.1 *Disposable Cups*, minimum 40-mL total volume. Select plastics or other materials compatible with the reagents involved.

³ The last approved version of this historical standard is referenced on www.astm.org.