

INTERNATIONAL STANDARD



**Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range
from 64,0 MHz to 108,0 MHz –
Part 2: Message format: coding and definitions of RDS features**

Document Preview

[IEC 62106-2:2021](#)

<https://standards.iteh.ai/catalog/standards/iec/bdec93e0-43f3-40db-91a9-062413fd0be7/iec-62106-2-2021>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

International Standards
standards.iteh.ai
Document Preview

[IEC 62106-2:2021](https://standards.iteh.ai/catalog/standards/iec/bdec93e0-43f3-40db-91a9-062413fd0be7/iec-62106-2-2021)

<https://standards.iteh.ai/catalog/standards/iec/bdec93e0-43f3-40db-91a9-062413fd0be7/iec-62106-2-2021>



IEC 62106-2

Edition 2.0 2021-02
REDLINE VERSION

INTERNATIONAL STANDARD



**Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range
from 64,0 MHz to 108,0 MHz –
Part 2: Message format: coding and definitions of RDS features**

Document Preview

[IEC 62106-2:2021](#)

<https://standards.iteh.ai/catalog/standards/iec/bdec93e0-43f3-40db-91a9-062413fd0be7/iec-62106-2-2021>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.160.40

ISBN 978-2-8322-9484-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	2
1 Scope.....	10
2 Normative references	10
3 Terms, definitions, abbreviated terms and conventions.....	10
3.1 Terms and definitions.....	10
3.2 Abbreviated terms.....	10
3.3 Notation and conventions.....	12
4 Message format.....	12
4.1 Design principles	12
4.2 Group structure.....	13
4.2.1 Group type A structure.....	13
4.2.2 Group type B structure.....	14
4.2.3 Group type C structure	14
4.2.4 RFT ODA pipe/channel.....	15
4.3 Group type A and B usage	16
4.4 Group type C usage	17
4.4.1 Transmitting legacy data using data-streams 1, 2 and 3.....	17
4.4.2 Transmitting group type C ODA data	17
4.4.3 AID and channel number assignment for group type C ODAs.....	18
5 Description of the RDS features.....	19
5.1 Alternative Frequencies list (AFs)	19
5.2 Clock Time and date (CT)	19
5.3 Dynamic PTY Indicator (PTYI) using DI.....	19
5.4 Extended Country Code (ECC)	19
5.5 Enhanced Other Networks information (EON)	19
5.6 Linkage information	20
5.7 Open Data Applications (ODAs).....	20
5.8 Programme Identification (PI).....	20
5.9 Programme Service name – (PS).....	21
5.10 Long Programme Service name – (LPS)	21
5.11 Programme Type (PTY)	21
5.12 Programme Type Name (PTYN).....	21
5.13 RadioText (RT)	22
5.14 enhanced RadioText (eRT)	22
5.15 RadioText Plus (RT+ and eRT+)	22
5.16 Traffic Programme identification (TP).....	22
5.17 Traffic Announcement identification (TA).....	22
5.18 Traffic Message Channel (TMC).....	23
6 Coding of the group types.....	23
6.1 Groups of type 0A and 0B: Basic tuning and switching information with PS name	23
6.2 Group type 1A: Slow labelling codes	24
6.3 Group type 2A and 2B: RadioText.....	25
6.4 Group type 3A: Application identification for any specific ODA using groups of type A or B.....	26

6.5	Group type 4A: Clock-Time and date.....	26
6.6	Group type 10A: Programme Type Name PTYN.....	27
6.7	Group type 14A and B: Enhanced Other Networks information (EON).....	28
6.8	Group type 15A: Long Programme Service name – 32 bytes with UTF-8 coding.....	28
6.9	Group type 15B: Fast basic tuning and switching information.....	29
7	Coding of RDS features for control.....	30
7.1	Programme Identification (PI) codes and Extended Country Codes (ECC).....	30
7.1.1	PI structure.....	30
7.1.2	Country Identifier (CI) codes: 'Nibble 1'.....	30
7.1.3	Extended Country Codes (ECC).....	30
7.1.4	Programme service in terms of area coverage (codes for fixed location transmitters only): 'Nibble 2'.....	31
7.1.5	Programme reference number: 'Nibbles 3 and 4'.....	31
7.1.6	PI codes for low-power short range transmitting devices.....	31
7.2	Programme Type (PTY) codes.....	32
7.3	Traffic Programme (TP) and Traffic Announcement (TA) codes.....	32
7.4	Decoder Identification (DI) and dynamic PTY Indicator (PTYI) codes.....	32
7.5	Coding of Alternative Frequencies (AFs).....	33
7.5.1	AF code tables.....	33
7.5.2	Use of Alternative Frequencies in group type 0A.....	35
7.5.3	Use of AF codes in group type 14A.....	37
7.6	Coding of Enhanced Other Networks information (EON).....	38
7.6.1	General.....	38
7.6.2	Coding of frequencies for cross-referenced programme services in EON.....	39
7.6.3	Use of the TP and TA features with EON.....	39
7.6.4	Use of PTY with EON.....	40
8	Required main RDS feature repetition rates on data-stream 0.....	40
	Annex A (normative) Method for linking RDS programme services – Linkage information – Group type 1A and 14A.....	45
A.1	General.....	45
A.2	LA – Linkage Actuator.....	46
A.3	EG – Extended Generic indicator.....	46
A.4	ILS – International Linkage Set indicator.....	46
A.5	LSN – Linkage Set Number.....	46
	Annex B (informative) Conversion between time and date conventions.....	48
	Annex C (normative) RDS2 File Transfer protocol RFT for files up to 163 kB.....	50
C.1	Group coding of the ODA-AID assignment groups.....	50
C.1.1	General principles.....	50
C.1.2	Variant 0.....	50
C.1.3	Variant 1.....	51
C.1.4	Variants 2 to 15.....	52
C.2	Coding of the RFT data group used to carry the file data bytes.....	52
	Annex D (informative) CRC-16 ITU-T/CCITT checkword calculation.....	54
D.1	General.....	54
D.2	PASCAL listing of CRC-16-calculation routine.....	54
D.3	C listing of the CRC-16 calculation routine.....	54
D.4	Fictitious example.....	55
	Bibliography.....	56

Figure 1 – Group type A structure	13
Figure 2 – Group type B structure	14
Figure 3 – Group type C structure	14
Figure 4 – Tunnelling structure for group types A and B.....	17
Figure 5 – Basic tuning and switching information – Group type 0A	23
Figure 6 – Basic tuning and switching information – Group type 0B	24
Figure 7 – Slow labelling codes – Group type 1A	24
Figure 8 – RadioText – Group type 2A.....	25
Figure 9 – RadioText – Group type 2B	26
Figure 10 – Application identification for any specific ODA – Group type 3A	26
Figure 11 – Clock-Time and date transmission – Group type 4A	27
Figure 12 – Programme Type Name PTYN – Group type 10A	27
Figure 13 – Enhanced Other Networks information – Group type 14A	28
Figure 14 – Enhanced Other Networks information – Group type 14B	28
Figure 15 – Long PS, UTF-8 coded – Group type 15A.....	29
Figure 16 – Fast basic tuning and switching information – Group type 15B	29
Figure 17 – PI code structure.....	30
Figure A.1 – Structure of group type 1A, block 3	45
Figure A.2 – Structure of group type 14A variant 12, block 3 (Linkage information) – National link.....	46
Figure A.3 – Structure of group type 14A variant 12, block 3 (Linkage information) – International link	47
Figure B.1 – Conversion routes between Modified Julian Date (MJD) and Coordinated Universal Time (UTC)	48
Figure C.1 – AID assignment group coding for variant 0.....	50
Figure C.2 – AID assignment group coding for variant 1.....	52
Figure C.3 – AID assignment group coding for variant 2 to 15.....	52
Figure C.4 – RFT data group	53
Table 1 – Group type C Function Header definition	15
Table 2 – Group type A and B usage	16
Table 3 – Group type C assignment methods used to connect channel numbers with one or more AIDs.....	18
Table 4 – Assignment of up to three successive channel numbers to multiple AIDs.....	19
Table 5 – Area coverage codes.....	31
Table 6 – Programme service reference number codes.....	31
Table 7 – PI codes for short range transmitting devices	32
Table 8 – Codes for TP and TA.....	32
Table 9 – Meaning of bits d_0 to d_3	33
Table 10 – VHF frequencies 87,6 MHz to 107,9 MHz code table	33
Table 11 – Special meanings AF code table.....	34
Table 12 – LF/MF code table – ITU regions 1 and 3 (9 kHz spacing).....	34
Table 13 – MF code table – ITU region 2 (10 kHz spacing)	35

Table 14 – Example including AFs for the extended FM Band	38
Table 15 – Data-stream 0 group repetition rates: Transmitter not part of a multi-programme service network: no TMC and only 'basic' RDS features.....	41
Table 16 – Data-stream 0 group repetition rates: Transmitter part of a multi-programme service network: no TMC	41
Table 17 – Data-stream 0 group repetition rates: Transmitter not part of a multi-programme service network: with TMC	42
Table 18 – Data-stream 0 group repetition rates: Transmitter not part of a multi-programme service network: no TMC and with support for UTF-8 coded characters.....	43
Table 19 – Data-stream 0 group repetition rates: Transmitter part of a multi-programme service network: with TMC	44
Table B.1 – Symbols used for time and date calculation.....	48
Table C.2 – Relation between chunk size, max. file size and max.chunk address	51

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 62106-2:2021](#)

<https://standards.iteh.ai/catalog/standards/iec/bdec93e0-43f3-40db-91a9-062413fd0be7/iec-62106-2-2021>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**RADIO DATA SYSTEM (RDS) –
VHF/FM SOUND BROADCASTING IN THE FREQUENCY
RANGE FROM 64,0 MHz TO 108,0 MHz –****Part 2: Message format: coding and definitions of RDS features****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 62106-2:2018. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 62106-2 has been prepared by technical area 1: Terminals for audio, video and data services and contents, of IEC technical committee 100: Audio, video and multimedia systems and equipment. It is an International Standard.

This second edition cancels and replaces the first edition published in 2018. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62106-2:2018:

- a) Subclause 4.2.4 has been added;
- b) Tables 1 and 13 have been modified;
- c) The new function RDS2 file transfer has been added and it is detailed in Annex C; this uses a CRC-16, which is specified in Annex D.

The text of this International Standard is based on the following documents:

CDV	Report on voting
100/3464/CDV	100/3547/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 62106 series, published under the general title *Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*, can be found on the IEC website.

The language used for the development of this International Standard is English,

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Since the mid-1980s, a fascinating development has taken place. Most of the multimedia applications and standards have been created or redefined significantly. Hardware has become extremely powerful with dedicated software and middleware. In the mid-1980s, Internet as well as its protocols did not exist. Navigation systems became affordable in the late 1990s, and a full range of attractive smartphones now exist. The computing power of all these new products is comparable with that of the mainframe installations in that era.

Listener expectations have grown faster than the technology. Visual experience is now very important, like the Internet look and feel. Scrolling text or delivering just audio is nowadays perceived as insufficient for FM radio, ~~specifically~~ especially for smartphone users. New types of radio receivers with added value features are therefore required. RDS has so far proven to be very successful.

FM radio with RDS is an analogue-digital hybrid system, which is still a valid data transmission technology and only the applications need adaptation. Now the time has come to solve the only disadvantage, the lack of sufficient data capacity. With RDS2, the need to increase the data capacity can be fulfilled.

RDS was introduced in the early 1980s. During the introductory phase in Europe, the car industry became very involved and that was the start of an extremely successful roll-out. Shortly afterwards, RDS (RBDS) was launched in the USA [1, 2, 3, 4, 5]¹.

The RDS Forum has investigated a solution to the issue of limited data capacity. For RDS2, both sidebands around the RDS 57 kHz subcarrier can be repeated a few times, up to three, centred on additional subcarriers higher up in the FM multiplex while still remaining compatible with the ITU Recommendations.

The core elements of RDS2 are the additional subcarriers, which will enable a significant increase of RDS data capacity to be achieved, and then only new additional data applications will have to be created, using the RDS-ODA feature, which has been part of the RDS standard IEC 62106 for many years.

In order to update IEC 62106:2015 to the specifications of RDS2, IEC 62106 has been restructured as follows:

Part 1: Modulation characteristics and baseband coding

Part 2: RDS message format, coding and definition of RDS features

Part 3: Usage and registration of Open Data Applications ODAs

Part 4: Registered code tables

Part 5: Marking of RDS and RDS2 devices

Part 6: Compilation of technical specifications for Open Data Applications in the public domain

~~The following future parts are planned:~~

Part ~~7~~9: RBDS – RDS variant used in North America

Part ~~8~~10: Universal Encoder Communication Protocol UECP

The original specifications of the RDS system have been maintained and the extra functionalities of RDS2 have been added.

¹ Numbers in square brackets refer to the Bibliography.

~~Obsolete or unused functions from the original RDS standard IEC 62106:2015 have been deleted.~~ The presentation in Parts 1, 2 and 3 follows the OSI basic reference model for information processing systems [6].

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 62106-2:2021](#)

<https://standards.iteh.ai/catalog/standards/iec/bdec93e0-43f3-40db-91a9-062413fd0be7/iec-62106-2-2021>

RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –

Part 2: Message format: coding and definitions of RDS features

1 Scope

This part of IEC 62106 defines the coding and definition of features for the Radio Data System (RDS).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62106 (all parts), *Radio Data System (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*

ISO/IEC 10646, *Information technology – Universal Coded Character Set (UCS)*

ISO 14819 (all parts), *Intelligent transport systems – Traffic and travel information messages via traffic message coding*

3 Terms, definitions, abbreviated terms and conventions

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62106-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.2 Abbreviated terms

For the purposes of this document, the abbreviated terms given in IEC 62106-1 and the following apply.

AF Alternative Frequency

NOTE 1 Alternative Frequencies are given in the form of lists (method A or B or mapped).

AID Application IDentification for ODAs

CI Country Identifier

CRC-16 16 bit Cyclic Redundancy Check

CT Clock Time

NOTE 2 In RDS, Clock Time includes the date.

DI Decoder Identification

ECC Extended Country Code

EG Extended Generic indicator

EON Enhanced Other Network information

eRT enhanced RadioText

EWS Emergency Warning System

NOTE 3 EWS was used in previous editions of IEC 62106. It can now be an ODA.

FH Function Header in group type C composed of FID and FN

FID Function Identifier

FN Function Number

hex hexadecimal

IH In-House application

NOTE 4 IH was used in previous editions of IEC 62106. It can now be an ODA.

ILS International Linkage Set indicator

LA Linkage Actuator

LI Linkage Indicator

LPS Long Programme Service name

lsb least significant bit or least significant byte

LSN Linkage Set Number

MS Music Speech switch

NOTE 5 MS was used in previous editions of IEC 62106. It is now obsolete.

msb most significant bit or most significant byte

ODA Open Data Application

ON Other Network

PI Programme Identification

PIN Programme Item Number

NOTE 6 PIN was used in previous editions of IEC 62106. It is now obsolete.

PS Programme Service name

PTY Programme Type

PTYI Programme Type Indicator

PTYN Programme Type Name

RFT RDS2 File Transfer protocol

rfu reserved for future use

RP Radio Paging

NOTE 7 RP was used in previous editions of IEC 62106. It is now obsolete.

RT RadioText

RT+ RadioText plus

TA Traffic Announcement

TDC Transparent Data Channel

NOTE 8 TDC was used in previous editions of IEC 62106. It can now be an ODA.

TMC Traffic Message Channel

TN Tuned Network

TP Traffic Programme

3.3 Notation and conventions

The notation and conventions given in IEC 62106-1 apply.

4 Message format

4.1 Design principles

The basic design principles underlying the message format and addressing structure are as follows:

- a) The original single RDS data-stream (now referred to as data-stream 0) has been supplemented by three new RDS data-streams referred to as data-streams 1, 2 and 3. Data-stream 0 will continue to only carry group types A and B (referred to as legacy data). Data-streams 1, 2 and 3 will only carry a new group type C. Legacy data groups A and B can be carried on data-streams 1, 2 and 3, but first need to be packaged within a type C group, using a mechanism referred to as "tunnelling".
- b) The mixture of different kinds of messages within any type A or B group is minimized. For example, one group type is reserved for basic tuning information, another for RadioText, etc. This is important so that broadcasters, who do not wish to transmit messages of certain kinds, are not forced to waste channel capacity by transmitting groups with unused blocks. Instead, they are able to repeat more frequently those group types which contain the messages they want to transmit.
- c) Data that has to be acquired quickly for receiver operation and for which a short acquisition time is required, for example Programme Identification (PI), Programme Type (PTY), and Traffic Programme flag (TP) are transmitted frequently and are always transmitted in data-stream 0. In data-stream 0, these features are present in every group and occupy the same fixed positions. They can therefore be decoded without reference to any block outside the one which contains the information.
- d) The Programme Service name (PS), a fundamental feature of RDS, is also always transmitted in data-stream 0, using a fixed group type – 0A or 0B for the short form, 15A for the longer (UTF-8, see ISO/IEC 10646) form. By having a fixed group type (i.e. not an ODA), the PS name can be decoded without reference to any other group.
- e) For compatibility with existing receivers, other RDS features will continue to use fixed group types and be transmitted in data-stream 0. These include Slow-labelling (1A), Clock-time (4A), RadioText (2A or 2B), PTYN (10A), EON (14A and 14B) and TA status control bursts (15B).
- f) The practice of allowing future applications to be defined by using an Open Data Application has been extended, and the data formatting has been made more flexible. In addition to an Open Data Application (see IEC 62106-3) using legacy group types A or B in data-stream 0 (see Table 2), a new group type C Open Data Application has been specified to allow greater data capacity in data-streams 1, 2 and 3.
- g) Open Data Applications defined by group types A or B can be carried in any data-stream 0, 1, 2 and 3, although use of data-streams 1 – 3 requires the use of tunnelling.
- h) Open Data Applications defined by group type C can only be carried in data-streams 1, 2 and 3. The essential core RDS features (PI, PTY, PS, etc.) will always be transmitted in data-stream 0 in every programme service using group types A or B.