

INTERNATIONAL ELECTROTECHNICAL COMMISSION
COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

IEC 60384-26
Edition 2.0 2018-05

IEC 60384-26
Edition 2.0 2018-05

**FIXED CAPACITORS FOR USE IN ELECTRONIC
EQUIPMENT –**

**CONDENSATEURS FIXES UTILISÉS
DANS LES ÉQUIPEMENTS ÉLECTRONIQUES –**

**Part 26: Sectional specification –
Fixed aluminium electrolytic
capacitors with conductive polymer solid
electrolyte**

**Partie 26: Spécification intermédiaire –
Condensateurs fixes
électrolytiques en aluminium à électrolyte solide
en polymère conducteur**

CORRIGENDUM 1

Corrections to the French version appear after the English text.

Les corrections à la version française sont données après le texte anglais.

In Table 3, Group 0, 4.3 Dimension (detail), in the column "Conditions of test and measurements", replace the text "See 4.3.2" with "See 4.3.1".

| Group 0 | ND | See Table 2 | |
|--------------------------------------|------------|-------------|---|
| 4.22 High surge current ^e | See 4.22.1 | | |
| 4.3 Visual examination | See 4.3.1 | | No visible damage Legible marking and as specified in the detail specification |
| 4.3 Dimension (detail) | See 4.3.1 | | See detail specification |

In Table 3, Group 2, 4.13.5 Final inspections, Leakage current, in the column "Performance requirements", replace the text "≤ 5 times of the limit in 4.4.3.1" with "≤ 5 times the limit in 4.4.1.3".

| Group 2 | D | See Table 2 | |
|--|------------|-------------|--------------------------------------|
| 4.13 Damp heat, steady state | See 4.13.1 | | |
| 4.13.2 Initial inspection Capacitance | See 4.4.2 | | |
| 4.13.4 Recovery | See 4.13.4 | | |
| 4.13.5 Final inspections Visual examination | See 4.3.1 | | No visible damage Legible marking |
| Leakage current | See 4.4.1 | | ≤ 5 times the limit in 4.4.1.3 |