

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



**Industrial communication networks – Fieldbus specifications –  
Part 2: Physical layer specification and service definition**

**Réseaux de communication industriels – Spécifications des bus de terrain –  
Partie 2: Spécification et définition des services de la couche physique**

<https://standards.iteh.ai/catalog/standards/sist/c8ac3f03-b177-4459-a7d4-0733c712e9c5/iec-61158-2-2023>



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

#### IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

### A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

### A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

#### Recherche de publications IEC -

##### [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

#### Service Clients - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: [sales@iec.ch](mailto:sales@iec.ch).

#### IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 300 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 19 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



**Industrial communication networks – Fieldbus specifications –  
Part 2: Physical layer specification and service definition**

**Réseaux de communication industriels – Spécifications des bus de terrain –  
Partie 2: Spécification et définition des services de la couche physique**

<https://standards.iteh.ai/catalog/standards/sist/c8ac3f03-b177-4459-a7d4-0733c712e9c5/iec-61158-2-2023>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

ICS 25.040.40; 35.100.20; 35.240.50

ISBN 978-2-8322-6552-9

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## CONTENTS

|   |    |
|---|----|
| FOREWORD.....   | 36 |
| 0 INTRODUCTION .....  | 38 |
| 0.1 General.....  | 38 |
| 0.2 Physical layer overview.....                                    | 38 |
| 0.3 Document overview.....  | 38 |
| 0.4 Major physical layer variations specified in this document..... | 39 |
| 0.4.1 Type 1 media .....  | 39 |
| 0.4.1.1 Type 1: Wire media.....                                     | 39 |
| 0.4.1.2 Type 1: Optical media .....                                 | 39 |
| 0.4.2 Type 2: Coaxial wire and optical media .....                  | 39 |
| 0.4.3 Type 3: Twisted-pair wire and optical media.....              | 39 |
| 0.4.4 Type 4: Wire medium .....                                     | 40 |
| 0.4.5 Type 8: Twisted-pair wire and optical media.....              | 40 |
| 0.4.6 Type 12: Wire medium .....                                    | 40 |
| 0.4.7 Type 16: optical media .....                                  | 40 |
| 0.4.8 Type 18: Media .....  | 40 |
| 0.4.8.1 Type 18: Basic media.....                                   | 40 |
| 0.4.8.2 Type 18: Powered media .....                                | 40 |
| 0.4.9 Type 20: Media .....  | 41 |
| 0.4.10 Type 24: Media .....   | 41 |
| 0.4.10.1 Type 24: Basic media .....                                 | 41 |
| 0.4.10.2 Type 24: Powered media .....                               | 41 |
| 0.4.11 Type 28: Media .....   | 41 |
| 0.5 Patent declaration.....   | 41 |
| 1 Scope.....  | 43 |
| 2 Normative references .....  | 43 |
| 3 Terms and definitions .....                                       | 46 |
| 3.1 Common terms and definitions.....                               | 46 |
| 3.2 Type 1: Terms and definitions .....                             | 50 |
| 3.3 Type 2: Terms and definitions .....                             | 53 |
| 3.4 Type 3: Terms and definitions .....                             | 57 |
| 3.5 Type 4: Terms and definitions .....                             | 60 |
| 3.6 Void.....   | 61 |
| 3.7 Type 8: Terms and definitions .....                             | 61 |
| 3.8 Type 12: Terms and definitions .....                            | 64 |
| 3.9 Type 16: Terms and definitions .....                            | 64 |
| 3.10 Type 18: Terms and definitions .....                           | 67 |
| 3.11 Type 24: Terms and definitions .....                           | 68 |
| 3.12 Type 20: Terms and definitions .....                           | 70 |
| 3.13 Type 28: Terms and definitions .....                           | 72 |
| 4 Symbols and abbreviated terms.....                                | 74 |
| 4.1 Symbols.....  | 74 |
| 4.1.1 Type 1: Symbols.....  | 74 |
| 4.1.2 Type 2: Symbols .....   | 75 |
| 4.1.3 Type 3: Symbols .....   | 76 |
| 4.1.4 Type 4: Symbols .....   | 76 |
| 4.1.5 Void.....   | 76 |

|        |   |    |
|--------|---|----|
| 4.1.6  | Type 8: Symbols .....                     | 76 |
| 4.1.7  | Type 12: Symbols .....                    | 77 |
| 4.1.8  | Type 16: Symbols .....                    | 77 |
| 4.1.9  | Type 18: Symbols .....                    | 77 |
| 4.1.10 | Type 24: Symbols .....                    | 78 |
| 4.1.11 | Type 20: Symbols .....                    | 78 |
| 4.1.12 | Type 28: Symbols .....                    | 78 |
| 4.2    | Abbreviated terms .....                   | 79 |
| 4.2.1  | Type 1: Abbreviations .....               | 79 |
| 4.2.2  | Type 2: Abbreviations .....               | 80 |
| 4.2.3  | Type 3: Abbreviations .....               | 80 |
| 4.2.4  | Type 4: Abbreviations .....               | 82 |
| 4.2.5  | Void .....                                | 82 |
| 4.2.6  | Type 8: Abbreviations .....               | 82 |
| 4.2.7  | Type 12: Abbreviations .....              | 84 |
| 4.2.8  | Type 16: Abbreviations .....              | 84 |
| 4.2.9  | Type 18: Abbreviations .....              | 84 |
| 4.2.10 | Type 24: Abbreviations .....              | 85 |
| 4.2.11 | Type 20: Abbreviations .....              | 85 |
| 4.2.12 | Type 28: Abbreviations .....              | 85 |
| 5      | DLL – PhL interface .....                 | 86 |
| 5.1    | General .....                             | 86 |
| 5.2    | Type 1: Required services .....           | 87 |
| 5.2.1  | Primitives of the PhS .....               | 87 |
| 5.2.2  | Notification of PhS characteristics ..... | 88 |
| 5.2.3  | Transmission of Ph-user-data .....        | 89 |
| 5.2.4  | Reception of Ph-user-data .....           | 89 |
| 5.3    | Type 2: Required services .....           | 89 |
| 5.3.1  | General .....                             | 89 |
| 5.3.2  | M_symbols .....                           | 89 |
| 5.3.3  | PH-LOCK indication .....                  | 90 |
| 5.3.4  | PH-FRAME indication .....                 | 90 |
| 5.3.5  | PH-CARRIER indication .....               | 90 |
| 5.3.6  | PH-DATA indication .....                  | 90 |
| 5.3.7  | PH-STATUS indication .....                | 90 |
| 5.3.8  | PH-DATA request .....                     | 91 |
| 5.3.9  | PH-FRAME request .....                    | 91 |
| 5.3.10 | PH-JABBER indication .....                | 91 |
| 5.3.11 | Ph-JABBER-CLEAR request .....             | 91 |
| 5.3.12 | Ph-JABBER-TYPE request .....              | 91 |
| 5.4    | Type 3: Required services .....           | 92 |
| 5.4.1  | Synchronous transmission .....            | 92 |
| 5.4.2  | Asynchronous transmission .....           | 92 |
| 5.5    | Type 4: Required services .....           | 93 |
| 5.5.1  | General .....                             | 93 |
| 5.5.2  | Primitives of the PhS .....               | 93 |
| 5.5.3  | Transmission of Ph-user data .....        | 94 |
| 5.6    | Void .....                                | 94 |
| 5.7    | Type 8: Required services .....           | 95 |

|        |  |     |
|--------|--|-----|
| 5.7.1  | General .....                                    | 95  |
| 5.7.2  | Primitives of the PhS .....                      | 95  |
| 5.7.3  | Overview of the Interactions .....               | 96  |
| 5.8    | Type 12: Required services.....                  | 102 |
| 5.9    | Type 16: Required services.....                  | 103 |
| 5.9.1  | Primitives of the PhS .....                      | 103 |
| 5.9.2  | Transmission of Ph-user-data .....               | 103 |
| 5.9.3  | Reception of Ph-user-data .....                  | 104 |
| 5.10   | Type 18: Required services.....                  | 104 |
| 5.10.1 | General .....                                    | 104 |
| 5.10.2 | Primitives of the PhS .....                      | 104 |
| 5.10.3 | Transmission of Ph-user-data .....               | 105 |
| 5.10.4 | Reception of Ph-user-data .....                  | 105 |
| 5.11   | Type 24: Required services.....                  | 105 |
| 5.11.1 | General .....                                    | 105 |
| 5.11.2 | DL_Symbols .....                                 | 106 |
| 5.11.3 | PLS_CARRIER indication .....                     | 106 |
| 5.11.4 | PLS_SIGNAL indication .....                      | 106 |
| 5.11.5 | PLS_DATA_VALID indication.....                   | 106 |
| 5.11.6 | PLS_DATA indication .....                        | 106 |
| 5.11.7 | PLS_DATA request.....                            | 106 |
| 5.12   | Type 20: Required services.....                  | 106 |
| 5.12.1 | Facilities of the physical layer services .....  | 106 |
| 5.12.2 | Sequence of primitives .....                     | 107 |
| 5.12.3 | PH-START service .....                           | 107 |
| 5.12.4 | PH-DATA service .....                            | 108 |
| 5.12.5 | PH-END service .....                             | 108 |
| 5.13   | Type 28: Required services.....                  | 109 |
| 5.13.1 | General .....                                    | 109 |
| 5.13.2 | Ph-Param (para, value).....                      | 109 |
| 5.13.3 | Ph-Data (length, data, status).....              | 110 |
| 5.13.4 | Ph-Clock-Sync (command, data, ofdmtiming).....   | 111 |
| 6      | Systems management – PhL interface .....         | 112 |
| 6.1    | General.....                                     | 112 |
| 6.2    | Type 1: Systems management – PhL interface.....  | 112 |
| 6.2.1  | Required services .....                          | 112 |
| 6.2.2  | Service primitive requirements.....              | 112 |
| 6.3    | Type 3: Systems management – PhL interface.....  | 114 |
| 6.3.1  | Synchronous transmission .....                   | 114 |
| 6.3.2  | Asynchronous transmission .....                  | 114 |
| 6.4    | Type 4: Systems management – PhL interface.....  | 119 |
| 6.4.1  | Required Services .....                          | 119 |
| 6.4.2  | Service primitive requirements.....              | 120 |
| 6.5    | Void.....  | 120 |
| 6.6    | Type 8: Systems management – PhL interface.....  | 120 |
| 6.6.1  | Functionality of the PhL Management .....        | 120 |
| 6.6.2  | PhL-PNM1 Interface .....                         | 120 |
| 6.7    | Type 12: Systems management – PhL interface..... | 125 |
| 6.8    | Type 18: Systems management – PhL interface..... | 125 |

|        |  |     |
|--------|--|-----|
| 6.8.1  | General .....  | 125 |
| 6.8.2  | Required services .....                                      | 125 |
| 6.8.3  | Service primitive requirements .....                         | 125 |
| 6.9    | Type 24: Systems management – PhL interface .....            | 126 |
| 6.10   | Type 28: Systems management – PhL interface .....            | 126 |
| 6.10.1 | General .....  | 126 |
| 6.10.2 | PhL related management information table .....               | 126 |
| 6.10.3 | Service primitive .....                                      | 132 |
| 7      | DCE independent sublayer (DIS) .....                         | 135 |
| 7.1    | General .....  | 135 |
| 7.2    | Type 1: DIS .....  | 136 |
| 7.3    | Type 3: DIS .....  | 136 |
| 7.3.1  | Synchronous transmission .....                               | 136 |
| 7.3.2  | Asynchronous transmission .....                              | 136 |
| 7.4    | Void .....   | 136 |
| 7.5    | Type 8: DIS .....  | 136 |
| 7.5.1  | General .....  | 136 |
| 7.5.2  | Function .....   | 136 |
| 7.5.3  | Serial transmission .....                                    | 136 |
| 7.5.4  | MDS coupling .....   | 137 |
| 7.6    | Type 12: DIS .....   | 138 |
| 7.7    | Type 28: DIS .....   | 138 |
| 8      | DTE – DCE interface and MIS-specific functions .....         | 138 |
| 8.1    | General .....  | 138 |
| 8.2    | Type 1: DTE – DCE interface .....                            | 139 |
| 8.2.1  | Services .....   | 139 |
| 8.2.2  | Signaling interfaces .....                                   | 140 |
| 8.3    | Type 3: DTE – DCE interface .....                            | 149 |
| 8.3.1  | Synchronous transmission .....                               | 149 |
| 8.3.2  | Asynchronous transmission .....                              | 149 |
| 8.4    | Type 8: MIS – MDS interface .....                            | 150 |
| 8.4.1  | General .....  | 150 |
| 8.4.2  | Services .....   | 150 |
| 8.4.3  | Interface signals .....                                      | 151 |
| 8.4.4  | Converting the services to the interface signals .....       | 152 |
| 8.5    | Type 12: DTE – DCE interface .....                           | 159 |
| 8.6    | Type 28: DTE – DCE interface and MIS Specific function ..... | 159 |
| 8.6.1  | General .....  | 159 |
| 8.6.2  | MIS Specific function .....                                  | 159 |
| 8.6.3  | DTE – DCE interface .....                                    | 166 |
| 9      | Medium dependent sublayer (MDS) .....                        | 168 |
| 9.1    | General .....  | 168 |
| 9.2    | Type 1: MDS: Wire and optical media .....                    | 168 |
| 9.2.1  | PhPDU .....  | 168 |
| 9.2.2  | Encoding and decoding .....                                  | 168 |
| 9.2.3  | Polarity detection .....                                     | 170 |
| 9.2.4  | Start of frame delimiter .....                               | 170 |
| 9.2.5  | End of frame delimiter .....                                 | 170 |
| 9.2.6  | Preamble .....   | 170 |

|        |   |     |
|--------|---|-----|
| 9.2.7  | Synchronization .....                                     | 171 |
| 9.2.8  | Post-transmission gap .....                               | 171 |
| 9.2.9  | Inter-channel signal skew .....                           | 171 |
| 9.3    | Void .....  | 171 |
| 9.4    | Type 2: MDS: Wire and optical media .....                 | 172 |
| 9.4.1  | General .....   | 172 |
| 9.4.2  | Clock accuracy .....                                      | 172 |
| 9.4.3  | Data recovery .....                                       | 172 |
| 9.4.4  | Data encoding rules .....                                 | 172 |
| 9.5    | Type 3: MDS: Wire and optical media .....                 | 173 |
| 9.5.1  | Synchronous transmission .....                            | 173 |
| 9.5.2  | Asynchronous transmission .....                           | 173 |
| 9.6    | Type 4: MDS: Wire medium .....                            | 173 |
| 9.6.1  | Half-duplex .....   | 173 |
| 9.6.2  | Full-duplex .....   | 175 |
| 9.6.3  | Full-duplex UDP .....                                     | 177 |
| 9.7    | Void .....  | 178 |
| 9.8    | Type 8: MDS: Wire and optical media .....                 | 178 |
| 9.8.1  | Function .....  | 178 |
| 9.8.2  | PhPDU formats .....                                       | 179 |
| 9.8.3  | Idle states .....   | 183 |
| 9.8.4  | Reset PhPDU .....   | 183 |
| 9.8.5  | MAU coupling .....  | 184 |
| 9.9    | Type 12: MDS: Wire media .....                            | 185 |
| 9.10   | Type 16: MDS: Optical media .....                         | 185 |
| 9.10.1 | Data encoding rules .....                                 | 185 |
| 9.10.2 | Telegrams and fill characters .....                       | 186 |
| 9.11   | Type 18: MDS: Wire media .....                            | 186 |
| 9.11.1 | Overview .....  | 186 |
| 9.11.2 | Transmission .....  | 187 |
| 9.11.3 | Reception .....   | 187 |
| 9.12   | Type 24: MDS: Twisted-pair wire .....                     | 187 |
| 9.12.1 | General .....   | 187 |
| 9.12.2 | Clock accuracy .....                                      | 187 |
| 9.12.3 | Data recovery .....                                       | 188 |
| 9.12.4 | Data encoding rules .....                                 | 188 |
| 9.13   | Type 28: MDS: Twisted-pair wire and coaxial media .....   | 189 |
| 9.13.1 | General .....   | 189 |
| 9.13.2 | MDS specification .....                                   | 189 |
| 10     | MDS – MAU interface .....                                 | 196 |
| 10.1   | General .....   | 196 |
| 10.2   | Type 1: MDS – MAU interface: Wire and optical media ..... | 197 |
| 10.2.1 | Services .....  | 197 |
| 10.2.2 | Service specifications .....                              | 197 |
| 10.2.3 | Signal characteristics .....                              | 197 |
| 10.2.4 | Communication mode .....                                  | 198 |
| 10.2.5 | Timing characteristics .....                              | 198 |
| 10.3   | Void .....  | 198 |
| 10.4   | Type 2: MDS – MAU interface: Wire and optical media ..... | 198 |



|        |   |     |
|--------|---|-----|
| 10.4.1 | MDS – MAU interface: general.....   | 198 |
| 10.4.2 | MDS – MAU interface: 5 Mbit/s, voltage-mode, coaxial wire.....  | 199 |
| 10.4.3 | MDS – MAU interface 5 Mbit/s, optical medium.....   | 199 |
| 10.4.4 | MDS – MAU interface Network Access Port (NAP).....  | 200 |
| 10.5   | Type 3: MDS – MAU interface: Wire and optical media .....   | 200 |
| 10.5.1 | Synchronous transmission .....  | 200 |
| 10.5.2 | Asynchronous transmission .....   | 201 |
| 10.6   | Type 8: MDS – MAU interface: Wire and optical media .....   | 201 |
| 10.6.1 | Overview of the services.....   | 201 |
| 10.6.2 | Description of the services.....  | 201 |
| 10.6.3 | Time response.....  | 202 |
| 10.6.4 | Transmission mode .....   | 202 |
| 10.7   | Type 18: MDS – MAU interface: Wire media .....  | 203 |
| 10.7.1 | General .....   | 203 |
| 10.7.2 | Services .....  | 203 |
| 10.7.3 | Service specifications .....  | 203 |
| 10.7.4 | Signal characteristics.....   | 203 |
| 10.7.5 | Communication mode .....  | 204 |
| 10.7.6 | Timing characteristics .....  | 204 |
| 10.8   | Type 24: MDS – MAU interface: Twisted-pair wire medium .....  | 204 |
| 10.8.1 | Overview of service .....   | 204 |
| 10.8.2 | Description of the services.....  | 204 |
| 10.9   | Type 28: MDS – MAU interface: Twisted-pair wire and coaxial media .....                                       | 205 |
| 10.9.1 | General .....   | 205 |
| 10.9.2 | Services .....  | 205 |
| 10.9.3 | Service process.....  | 206 |
| 10.9.4 | Service specifications .....  | 206 |
| 10.9.5 | Transmit specifications .....   | 207 |
| 11     | Types 1 and 7: Medium attachment unit: voltage mode, linear-bus-topology 150 Ω twisted-pair wire medium ..... | 208 |
| 11.1   | General.....  | 208 |
| 11.2   | Bit-rate-dependent quantities .....   | 208 |
| 11.3   | Network specifications .....  | 209 |
| 11.3.1 | Components .....  | 209 |
| 11.3.2 | Topologies.....   | 209 |
| 11.3.3 | Network configuration rules .....   | 210 |
| 11.3.4 | Power distribution rules for network configuration .....  | 211 |
| 11.4   | MAU transmit circuit specification .....  | 211 |
| 11.4.1 | Summary .....   | 211 |
| 11.4.2 | MAU test configuration .....  | 212 |
| 11.4.3 | MAU output level requirements .....   | 213 |
| 11.4.4 | MAU output timing requirements .....  | 214 |
| 11.4.5 | Signal polarity.....  | 215 |
| 11.5   | MAU receive circuit specification.....  | 216 |
| 11.5.1 | Summary .....   | 216 |
| 11.5.2 | Input impedance .....   | 216 |
| 11.5.3 | Receiver sensitivity and noise rejection .....  | 217 |
| 11.5.4 | Received bit cell jitter .....  | 217 |
| 11.5.5 | Interference susceptibility and error rates .....   | 217 |

|        |  |     |
|--------|--|-----|
| 11.6   | Jabber inhibit .....   | 218 |
| 11.7   | Power distribution .....   | 218 |
| 11.7.1 | Overview .....   | 218 |
| 11.7.2 | Supply voltage .....   | 219 |
| 11.7.3 | Powered via signal conductors .....  | 219 |
| 11.7.4 | Powered separately from signal conductors .....  | 220 |
| 11.7.5 | Electrical isolation .....   | 220 |
| 11.8   | Medium specifications .....  | 221 |
| 11.8.1 | Connector .....  | 221 |
| 11.8.2 | Standard test cable .....  | 221 |
| 11.8.3 | Coupler .....  | 222 |
| 11.8.4 | Splices .....  | 222 |
| 11.8.5 | Terminator .....   | 222 |
| 11.8.6 | Shielding rules .....  | 222 |
| 11.8.7 | Grounding (earthing) rules .....   | 223 |
| 11.8.8 | Color coding of cables .....   | 223 |
| 12     | Types 1 and 3: Medium attachment unit: 31,25 kbit/s, voltage-mode with low-power option, bus- and tree-topology, 100 Ω wire medium ..... | 223 |
| 12.1   | General .....  | 223 |
| 12.2   | Transmitted bit rate .....   | 224 |
| 12.3   | Network specifications .....   | 224 |
| 12.3.1 | Components .....   | 224 |
| 12.3.2 | Topologies .....   | 224 |
| 12.3.3 | Network configuration rules .....  | 225 |
| 12.3.4 | Power distribution rules for network configuration .....   | 226 |
| 12.4   | MAU transmit circuit specification .....   | 227 |
| 12.4.1 | Summary .....  | 227 |
| 12.4.2 | MAU test configuration .....   | 227 |
| 12.4.3 | MAU output level requirements .....  | 227 |
| 12.4.4 | Output timing requirements .....   | 228 |
| 12.4.5 | Signal polarity .....  | 229 |
| 12.4.6 | Transition from receive to transmit .....  | 229 |
| 12.5   | MAU receive circuit specification .....  | 229 |
| 12.5.1 | Summary .....  | 229 |
| 12.5.2 | Input impedance .....  | 230 |
| 12.5.3 | Receiver sensitivity and noise rejection .....   | 230 |
| 12.5.4 | Received bit cell jitter .....   | 230 |
| 12.5.5 | Interference susceptibility and error rates .....  | 230 |
| 12.6   | Jabber inhibit .....   | 231 |
| 12.7   | Power distribution .....   | 231 |
| 12.7.1 | General .....  | 231 |
| 12.7.2 | Supply voltage .....   | 232 |
| 12.7.3 | Powered via signal conductors .....  | 232 |
| 12.7.4 | Power supply impedance .....   | 234 |
| 12.7.5 | Powered separately from signal conductors .....  | 237 |
| 12.7.6 | Electrical isolation .....   | 237 |
| 12.8   | Medium specifications .....  | 237 |
| 12.8.1 | Connector .....  | 237 |
| 12.8.2 | Standard test cable .....  | 237 |

|        |  |     |
|--------|--|-----|
| 12.8.3 | Coupler.....   | 238 |
| 12.8.4 | Splices .....  | 239 |
| 12.8.5 | Terminator .....   | 239 |
| 12.8.6 | Shielding rules.....   | 240 |
| 12.8.7 | Grounding (earthing) rules.....  | 240 |
| 12.8.8 | Color coding of cables .....   | 240 |
| 12.9   | Intrinsic safety .....   | 241 |
| 12.9.1 | General .....  | 241 |
| 12.9.2 | Intrinsic safety barrier .....   | 241 |
| 12.9.3 | Barrier and terminator placement.....  | 241 |
| 12.10  | Galvanic isolators .....   | 241 |
| 13     | Type 1: Medium attachment unit: current mode, twisted-pair wire medium .....       | 241 |
| 13.1   | General.....   | 241 |
| 13.2   | Transmitted bit rate.....  | 242 |
| 13.3   | Network specifications .....   | 242 |
| 13.3.1 | Components .....   | 242 |
| 13.3.2 | Topologies.....  | 242 |
| 13.3.3 | Network configuration rules .....  | 242 |
| 13.3.4 | Power distribution rules for network configuration .....                           | 244 |
| 13.4   | MAU transmit circuit specification .....   | 244 |
| 13.4.1 | General .....  | 244 |
| 13.4.2 | Test configuration.....  | 245 |
| 13.4.3 | Output level requirements.....   | 245 |
| 13.4.4 | Output timing requirements.....  | 245 |
| 13.5   | MAU receive circuit specification.....   | 246 |
| 13.5.1 | General .....  | 246 |
| 13.5.2 | Input impedance .....  | 247 |
| 13.5.3 | Receiver sensitivity and noise rejection .....                                     | 247 |
| 13.5.4 | Received bit cell jitter .....   | 247 |
| 13.5.5 | Interference susceptibility and error rates .....                                  | 247 |
| 13.6   | Jabber inhibit .....   | 248 |
| 13.7   | Power distribution .....   | 248 |
| 13.7.1 | General .....  | 248 |
| 13.7.2 | Powered via signal conductors .....  | 249 |
| 13.7.3 | Powered separately from signal.....  | 249 |
| 13.7.4 | Electrical isolation .....   | 249 |
| 13.8   | Medium specifications.....   | 250 |
| 13.8.1 | Connector.....   | 250 |
| 13.8.2 | Standard test cable.....   | 250 |
| 13.8.3 | Coupler.....   | 251 |
| 13.8.4 | Splices .....  | 251 |
| 13.8.5 | Terminator .....   | 251 |
| 13.8.6 | Shielding rules.....   | 251 |
| 13.8.7 | Grounding rules.....   | 252 |
| 13.8.8 | Color coding of cables .....   | 252 |
| 14     | Type 1: Medium attachment unit: current mode (1 A), twisted-pair wire medium ..... | 252 |
| 14.1   | General.....   | 252 |
| 14.2   | Transmitted bit rate.....  | 252 |
| 14.3   | Network specifications .....   | 252 |

|        |   |     |
|--------|---|-----|
| 14.3.1 | Components .....  | 252 |
| 14.3.2 | Topologies.....   | 253 |
| 14.3.3 | Network configuration rules .....                                     | 253 |
| 14.3.4 | Power distribution rules for network configuration .....              | 255 |
| 14.4   | MAU transmit circuit specification .....                              | 255 |
| 14.4.1 | General .....   | 255 |
| 14.4.2 | Configuration.....  | 255 |
| 14.4.3 | Output level requirements.....  | 256 |
| 14.4.4 | Output timing requirements.....                                       | 256 |
| 14.5   | MAU receive circuit specification.....                                | 257 |
| 14.5.1 | General .....   | 257 |
| 14.5.2 | Input impedance .....   | 257 |
| 14.5.3 | Receiver sensitivity and noise rejection .....                        | 257 |
| 14.5.4 | Received bit cell jitter .....  | 257 |
| 14.5.5 | Interference susceptibility and error rates .....                     | 258 |
| 14.6   | Jabber inhibit .....  | 258 |
| 14.7   | Power distribution .....  | 258 |
| 14.7.1 | General .....   | 258 |
| 14.7.2 | Powered via signal conductors .....                                   | 259 |
| 14.7.3 | Powered separately from signal.....                                   | 260 |
| 14.7.4 | Electrical isolation .....  | 260 |
| 14.8   | Medium specifications.....  | 260 |
| 14.8.1 | Connector.....  | 260 |
| 14.8.2 | Standard test cable.....  | 260 |
| 14.8.3 | Coupler.....  | 260 |
| 14.8.4 | Splices .....   | 260 |
| 14.8.5 | Terminator .....  | 260 |
| 14.8.6 | Shielding rules.....  | 261 |
| 14.8.7 | Grounding rules .....   | 261 |
| 14.8.8 | Color coding of cables .....  | 261 |
| 15     | Types 1 and 7: Medium attachment unit: dual-fiber optical media ..... | 261 |
| 15.1   | General.....  | 261 |
| 15.2   | Bit-rate-dependent quantities .....                                   | 261 |
| 15.3   | Network specifications .....  | 262 |
| 15.3.1 | Components .....  | 262 |
| 15.3.2 | Topologies.....   | 262 |
| 15.3.3 | Network configuration rules .....                                     | 262 |
| 15.4   | MAU transmit circuit specifications.....                              | 263 |
| 15.4.1 | Test configuration.....   | 263 |
| 15.4.2 | Output level specification.....                                       | 263 |
| 15.4.3 | Output timing specification.....                                      | 263 |
| 15.5   | MAU receive circuit specifications.....                               | 264 |
| 15.5.1 | General .....   | 264 |
| 15.5.2 | Receiver operating range.....   | 264 |
| 15.5.3 | Maximum received bit cell jitter.....                                 | 264 |
| 15.5.4 | Interference susceptibility and error rates .....                     | 265 |
| 15.6   | Jabber inhibit .....  | 266 |
| 15.7   | Medium specifications.....  | 266 |
| 15.7.1 | Connector.....  | 266 |

|        |   |     |
|--------|---|-----|
| 15.7.2 | Standard test fiber .....   | 266 |
| 15.7.3 | Optical passive star .....  | 266 |
| 15.7.4 | Optical active star .....   | 266 |
| 16     | Type 1: Medium attachment unit: 31,25 kbit/s, single-fiber optical medium .....   | 268 |
| 16.1   | General.....  | 268 |
| 16.2   | Transmitted bit rate.....   | 268 |
| 16.3   | Network specifications .....  | 268 |
| 16.3.1 | Components .....  | 268 |
| 16.3.2 | Topologies.....   | 268 |
| 16.3.3 | Network configuration rules .....   | 268 |
| 16.4   | MAU transmit circuit specifications.....  | 269 |
| 16.4.1 | Test configuration.....   | 269 |
| 16.4.2 | Output level specification.....   | 269 |
| 16.4.3 | Output timing specification.....  | 269 |
| 16.5   | MAU receive circuit specifications .....  | 269 |
| 16.5.1 | General .....   | 269 |
| 16.5.2 | Receiver operating range.....   | 269 |
| 16.5.3 | Maximum received bit cell jitter.....   | 269 |
| 16.5.4 | Interference susceptibility and error rates .....                                 | 269 |
| 16.6   | Jabber inhibit .....  | 269 |
| 16.7   | Medium specifications.....  | 270 |
| 16.7.1 | Connector.....  | 270 |
| 16.7.2 | Standard test fiber .....   | 270 |
| 16.7.3 | Optical passive star .....  | 270 |
| 16.7.4 | Optical active star.....  | 270 |
| 17     | Void.....   | 271 |
| 18     | Type 2: Medium attachment unit: 5 Mbit/s, voltage-mode, coaxial wire medium ..... | 271 |
| 18.1   | General.....  | 271 |
| 18.2   | Transceiver: 5 Mbit/s, voltage-mode, coaxial wire .....                           | 272 |
| 18.3   | Transformer 5 Mbit/s, voltage-mode, coaxial wire .....                            | 277 |
| 18.4   | Connector 5 Mbit/s, voltage-mode, coaxial wire medium .....                       | 278 |
| 18.5   | Topology 5 Mbit/s, voltage-mode, coaxial wire medium .....                        | 278 |
| 18.6   | Taps 5 Mbit/s, voltage-mode, coaxial wire medium.....                             | 280 |
| 18.6.1 | Description .....   | 280 |
| 18.6.2 | Requirements .....  | 280 |
| 18.6.3 | Spur .....  | 282 |
| 18.7   | Trunk 5 Mbit/s, voltage-mode, coaxial wire medium .....                           | 282 |
| 18.7.1 | Trunk Cable.....  | 282 |
| 18.7.2 | Connectors .....  | 283 |
| 19     | Type 2: Medium attachment unit: 5 Mbit/s, optical medium .....                    | 283 |
| 19.1   | General.....  | 283 |
| 19.2   | Transceiver 5 Mbit/s, optical medium .....  | 283 |
| 19.3   | Topology 5 Mbit/s, optical medium .....   | 284 |
| 19.4   | Trunk fiber 5 Mbit/s, optical medium.....   | 284 |
| 19.5   | Trunk connectors 5 Mbit/s, optical medium .....                                   | 285 |
| 19.6   | Fiber specifications 5 Mbit/s, optical medium .....                               | 285 |
| 20     | Type 2: Medium attachment unit: network access port (NAP).....                    | 288 |
| 20.1   | General.....  | 288 |

|         |  |     |
|---------|--|-----|
| 20.2    | Signaling.....   | 289 |
| 20.3    | Transceiver.....   | 290 |
| 20.4    | Connector.....   | 290 |
| 20.5    | Cable.....   | 290 |
| 21      | Type 3: Medium attachment unit: synchronous transmission, 31,25 kbit/s, voltage mode, wire medium..... | 291 |
| 21.1    | General.....   | 291 |
| 21.2    | Transmitted bit rate.....  | 292 |
| 21.3    | Network specifications.....  | 292 |
| 21.3.1  | Components.....  | 292 |
| 21.3.2  | Topologies.....  | 293 |
| 21.3.3  | Network configuration rules.....   | 293 |
| 21.3.4  | Power distribution rules for network configuration.....  | 295 |
| 21.4    | Transmit circuit specification for 31,25 kbit/s voltage-mode MAU.....                                  | 295 |
| 21.4.1  | Summary.....   | 295 |
| 21.4.2  | Test configuration.....  | 295 |
| 21.4.3  | Impedance.....   | 295 |
| 21.4.4  | Symmetry.....  | 296 |
| 21.4.5  | Output level requirements.....   | 298 |
| 21.4.6  | Output timing requirements.....  | 298 |
| 21.4.7  | Signal polarity.....   | 298 |
| 21.5    | Receive circuit specification for 31,25 kbit/s voltage-mode MAU.....                                   | 298 |
| 21.6    | Jabber inhibit.....  | 298 |
| 21.7    | Power distribution.....  | 298 |
| 21.7.1  | General.....   | 298 |
| 21.7.2  | Supply voltage.....  | 299 |
| 21.7.3  | Powered via signal conductors.....   | 299 |
| 21.7.4  | Electrical isolation.....  | 300 |
| 21.8    | Medium specifications.....   | 301 |
| 21.8.1  | Connector.....   | 301 |
| 21.8.2  | Standard test cable.....   | 301 |
| 21.8.3  | Coupler.....   | 301 |
| 21.8.4  | Splices.....   | 301 |
| 21.8.5  | Terminator.....  | 301 |
| 21.8.6  | Shielding rules.....   | 302 |
| 21.8.7  | Grounding rules.....   | 302 |
| 21.8.8  | Cable colours.....   | 302 |
| 21.9    | Intrinsic safety.....  | 302 |
| 21.9.1  | General.....   | 302 |
| 21.9.2  | Intrinsic safety barrier.....  | 302 |
| 21.9.3  | Barrier and terminator placement.....  | 303 |
| 21.10   | Galvanic isolators.....  | 303 |
| 21.11   | Coupling elements.....   | 303 |
| 21.11.1 | General.....   | 303 |
| 21.11.2 | MBP-IS repeater.....   | 303 |
| 21.11.3 | MBP-IS – RS 485 signal coupler.....  | 304 |
| 21.12   | Power supply.....  | 305 |
| 21.12.1 | General.....   | 305 |
| 21.12.2 | Non-intrinsically safe power supply.....   | 306 |

|         |   |     |
|---------|---|-----|
| 21.12.3 | Intrinsically safe power supply .....   | 306 |
| 21.12.4 | Power supply of the category "ib" .....   | 307 |
| 21.12.5 | Power supply in category "ia" .....   | 308 |
| 21.12.6 | Reverse powering .....  | 309 |
| 22      | Type 3: Medium attachment unit: asynchronous transmission, wire medium .....    | 309 |
| 22.1    | Medium attachment unit for non intrinsic safety .....                           | 309 |
| 22.1.1  | Characteristics .....   | 309 |
| 22.1.2  | Medium specifications .....   | 311 |
| 22.1.3  | Transmission method .....   | 314 |
| 22.2    | Medium attachment unit for intrinsic safety .....                               | 315 |
| 22.2.1  | Characteristics .....   | 315 |
| 22.2.2  | Medium specifications .....   | 317 |
| 22.2.3  | Transmission method .....   | 319 |
| 22.2.4  | Intrinsic safety .....  | 323 |
| 23      | Type 3: Medium attachment unit: asynchronous transmission, optical medium ..... | 326 |
| 23.1    | Characteristic features of optical data transmission .....                      | 326 |
| 23.2    | Basic characteristics of an optical data transmission medium .....              | 327 |
| 23.3    | Optical network .....   | 327 |
| 23.4    | Standard optical link .....   | 328 |
| 23.5    | Network structures built from a combination of standard optical links .....     | 328 |
| 23.6    | Bit coding .....  | 329 |
| 23.7    | Optical signal level .....  | 329 |
| 23.7.1  | General .....   | 329 |
| 23.7.2  | Characteristics of optical transmitters .....                                   | 329 |
| 23.7.3  | Characteristics of optical receivers .....                                      | 331 |
| 23.8    | Temporal signal distortion .....  | 332 |
| 23.8.1  | General .....   | 332 |
| 23.8.2  | Signal shape at the electrical input of the optical transmitter .....           | 332 |
| 23.8.3  | Signal distortion due to the optical transmitter .....                          | 332 |
| 23.8.4  | Signal distortion due to the optical receiver .....                             | 333 |
| 23.8.5  | Signal influence due to coupling components .....                               | 334 |
| 23.8.6  | Chaining standard optical links .....   | 334 |
| 23.9    | Bit error rate .....  | 335 |
| 23.10   | Connectors for fiber optic cable .....  | 335 |
| 23.11   | Redundancy in optical transmission networks .....                               | 335 |
| 24      | Type 4: Medium attachment unit: RS-485 .....                                    | 335 |
| 24.1    | General .....   | 335 |
| 24.2    | Overview of the services .....  | 335 |
| 24.3    | Description of the services .....   | 336 |
| 24.3.1  | Transmit signal (TxS) .....   | 336 |
| 24.3.2  | Transmit enable (TxE) .....   | 336 |
| 24.3.3  | Receive signal (RxS) .....  | 336 |
| 24.4    | Network .....   | 336 |
| 24.4.1  | General .....   | 336 |
| 24.4.2  | Topology .....  | 336 |
| 24.5    | Electrical specification .....  | 336 |
| 24.6    | Time response .....   | 336 |
| 24.7    | Interface to the transmission medium .....                                      | 336 |
| 24.8    | Specification of the transmission medium .....                                  | 337 |