



Designation: B370 – 12 (Reapproved 2019)

# Standard Specification for Copper Sheet and Strip for Building Construction<sup>1</sup>

This standard is issued under the fixed designation B370; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the U.S. Department of Defense.*

## 1. Scope\*

1.1 This specification establishes the requirements for rolled copper sheet and strip in flat lengths or coils in ounce-weight thicknesses for roofing, flashing, gutters, downspouts, and general sheet metal work in building construction.

1.1.1 Products produced to this specification are not intended for electrical applications.

1.2 *Units*—The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

NOTE 1—Specification B101 is an associated specification for lead-coated copper sheets and strip for building construction.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

## 2. Referenced Documents

2.1 *ASTM Standards*:<sup>2</sup>

**B101** Specification for Lead-Coated Copper Sheet and Strip for Building Construction

**B248** Specification for General Requirements for Wrought Copper and Copper-Alloy Plate, Sheet, Strip, and Rolled Bar

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee B05 on Copper and Copper Alloys and is the direct responsibility of Subcommittee B05.01 on Plate, Sheet, and Strip.

Current edition approved Oct. 1, 2019. Published October 2019. Originally approved in 1961. Last previous edition approved in 2012 as B370–12. DOI: 10.1520/B0370–12R19.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

**B601** Classification for Temper Designations for Copper and Copper Alloys—Wrought and Cast

**B846** Terminology for Copper and Copper Alloys

**E3** Guide for Preparation of Metallographic Specimens

**E8/E8M** Test Methods for Tension Testing of Metallic Materials

**E112** Test Methods for Determining Average Grain Size

**E255** Practice for Sampling Copper and Copper Alloys for the Determination of Chemical Composition

**E478** Test Methods for Chemical Analysis of Copper Alloys

## 3. General Requirements

3.1 The following sections of Specification B248 constitute a part of this specification:

3.1.1 Terminology;

3.1.2 Materials and Manufacture;

3.1.3 Workmanship, Finish, and Appearance;

3.1.4 Specimen Preparation;

3.1.5 Test Methods;

3.1.6 Significance of Numerical Limits;

3.1.7 Inspection;

3.1.8 Certification;

3.1.9 Mill Test Report;

3.1.10 Packaging and Package Marking; and

3.1.11 Supplementary Requirements.

3.2 In addition, when a section with a title identical to that referenced in 3.1, above, appears in this specification, it contains additional requirements, which supplement those appearing in Specification B248.

## 4. Terminology

4.1 *Definitions*:

4.1.1 For definitions of terms related to copper and copper alloys, refer to Terminology B846.

4.1.2 *coil, n*—a length of the product wound into a series of connected turns.

4.1.2.1 *Discussion*—The unqualified term “coil” as applied to “flat product” usually refers to a coil in which the product is spirally wound, with the successive layers on top of one another (sometimes called a “roll”).

4.1.3 *lengths, mill, n*—straight lengths, including ends, that are manufactured conveniently in the mills.

\*A Summary of Changes section appears at the end of this standard

**TABLE 1 Thickness Tolerances of Sheet and Strip**

Ounce-Weight/ft <sup>2</sup>	Theoretical Thickness, <sup>A</sup> in. (mm)	Tolerances, Plus and Minus in. (mm)
6	0.0081 (0.206)	0.001 (0.026)
8	0.0108 (0.274)	0.0011 (0.028)
10	0.0135 (0.343)	0.0011 (0.028)
12	0.0162 (0.411)	0.0012 (0.030)
16	0.0216 (0.549)	0.0012 (0.031)
20	0.0270 (0.686)	0.0012 (0.031)
24	0.0323 (0.820)	0.0015 (0.038)
32	0.0431 (1.09)	0.002 (0.05)
48	0.0646 (1.64)	0.0025 (0.06)

<sup>A</sup> Based on a density of 0.322 lb/in.<sup>3</sup> (8.91 g/cm<sup>3</sup>).

4.1.3.1 *Discussion*—Full length pieces usually are 8 or 10 ft (2.4 or 3.0 m) and subject to established length tolerances.

4.1.4 *length, stock, n*—straight lengths that are mill cut and stored in advance of orders.

4.1.4.1 *Discussion*—They usually are 8 or 10 ft (2.4 or 3.0 m) and subject to established length tolerances.

4.1.5 *ounce-weight, n*—the weight of copper sheet or strip expressed in ounces per square foot.

4.1.6 *sheet, for building construction, n*—a rolled flat product over 24 in. (610 mm) in width and of ounce-weight thickness from 8 to 48 oz.

4.1.7 *strip, for building construction, n*—a rolled flat product up to 24 in. (610 mm), inclusive, in width and of ounce-weight thickness from 8 to 48 oz.

NOTE 2—In 4.1.6 and 4.1.7, the 8 to 48 oz refers to the names commonly used in the building industry for the sizes used. The respective sizes that correspond to these names are listed in Table 1.

## 5. Ordering Information

5.1 Include the following information when placing orders for product under this specification, as applicable:

5.1.1 ASTM designation and year of issue (for example, B370–XX);

5.1.2 Temper (Section 8);

5.1.3 Dimensions: tolerances (Section 12);

5.1.4 How furnished: flat lengths or coils (4.1.2 – 4.1.4);

5.1.5 Quantity: total weight or number of pieces of each form and size; and

5.1.6 When product is purchased for agencies of the U.S. Government (Section 11).

5.2 The following are options available under this specification and should be specified in the contract or purchase order when required:

5.2.1 Heat identification or traceability details,

5.2.2 Certification, and

5.2.3 Mill test report.

## 6. Materials and Manufacture

6.1 *Materials*—The material shall be any copper conforming with the chemical composition requirements (Section 7).

6.2 *Manufacture*:

6.2.1 *Sheet*—The product shall be manufactured in flat sheets.

**TABLE 2 Thickness Tolerances of Sheet and Strip to be Coated for Flashing**

Ounce-Weight/ft <sup>2</sup>	Theoretical Thickness, <sup>A</sup> in. (mm)	Tolerances, Plus and Minus in. (mm)
2	0.0027 (0.068)	0.0004 (0.010)
3	0.004 (0.103)	0.0005 (0.013)
4	0.0054 (0.138)	0.0006 (0.0152)
5	0.0067 (0.171)	0.0006 (0.0152)

<sup>A</sup> Based on a density of 0.322 lb/in.<sup>3</sup> (8.91 g/cm<sup>3</sup>).

6.2.2 *Strip*—The product shall be manufactured in flat lengths or in coils (rolls) of one single continuous length not less than 25 ft (7.5 m) wound into a cylindrical spiral.

## 7. Chemical Composition

7.1 The material shall be any copper with a minimum copper content, including silver, of 99.5 %.

7.1.1 Limits shall be established and analysis required for unnamed elements by agreement between the manufacturer and the purchaser.

## 8. Temper

8.1 The standard tempers for products described in this specification are given in Table 3.

8.2 Cold Rolled tempers as defined in Classification B601: H00 (cold-rolled), H01 (cold-rolled, high yield), H02 (half hard), H03 (three-quarter hard), and H04 (hard).

8.3 Annealed temper as defined in Classification B601: O60 (soft)

NOTE 3—The purchaser should confer with the manufacturer or supplier concerning the availability of a specific temper and form.

NOTE 4—H00 temper is commonly known in the building industry as cold-rolled temper.

NOTE 5—H01 temper is commonly known in the building industry as cold-rolled, high yield temper.

## 9. Physical Property Requirements

9.1 *Grain Size*—Although no grain size has been established for temper O60, the product shall be recrystallized fully as determined by Test Methods E112.

## 10. Mechanical Property Requirements

10.1 *Tensile and Yield Strength Requirements*:

10.1.1 The product shall conform to the requirements specified in Table 3 for the specific temper when subjected to test in accordance with Test Methods E8/E8M.

10.1.2 Acceptance or rejection for mechanical properties shall be based upon the results of the tensile and yield strength tests.

10.2 *Rockwell Hardness Requirement*—The approximate Rockwell values given in Table 3 are for general information and assistance in testing and shall not be a basis for product rejection.

NOTE 6—The Rockwell hardness test offers a quick and convenient method of checking for general conformity to the specification requirements for temper and tensile strength.