

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Fibre optic interconnecting devices and passive components – Performance standard –

Part 081-03: Non-connectorized single-mode fibre optic middle-scale 1 × N DWDM devices for category OP – Outdoor protected environment

Dispositifs d'interconnexion et composants passifs fibroniques – Norme de performance –

Partie 081-03: Dispositifs DWDM 1 × N de milieu d'échelle fibroniques unimodaux non-connectorisés pour la catégorie OP – Environnement extérieur protégé



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Products & Services Portal - products.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 300 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 19 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Fibre optic interconnecting devices and passive components – Performance standard –

Part 081-03: Non-connectorized single-mode fibre optic middle-scale 1 × N DWDM devices for category OP – Outdoor protected environment

Dispositifs d'interconnexion et composants passifs fibroniques – Norme de performance –

Partie 081-03: Dispositifs DWDM 1 × N de milieu d'échelle fibroniques unimodaux non-connectorisés pour la catégorie OP – Environnement extérieur protégé

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.180.10

ISBN 978-2-8322-7838-3

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references	5
3 Terms and definitions	7
4 Test.....	7
5 Test report.....	8
6 Performance requirements.....	8
6.1 Reference components	8
6.2 Dimensions	8
6.3 Sample size	8
6.4 Test details and requirements	8
Annex A (normative) Sample size	17
Bibliography.....	18
Table 1 – Single-mode spectral bands	7
Table 2 – Test details and requirements for type A (Gaussian passband profile).....	8
Table 3 – Test details and requirements for type B (Flat-top passband profile)	11
Table 4 – Environmental test for all types	14
Table A.1 – Sample size	17

Document Preview

[IEC 61753-081-03:2023](https://standards.iteh.ai/standards/iec/f566f7e0-f25a-4271-8bf3-cbdbcf5bc64a/iec-61753-081-03-2023)

<https://standards.iteh.ai/catalog/standards/iec/f566f7e0-f25a-4271-8bf3-cbdbcf5bc64a/iec-61753-081-03-2023>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**FIBRE OPTIC INTERCONNECTING DEVICES
AND PASSIVE COMPONENTS –
PERFORMANCE STANDARD –****Part 081-03: Non-connectorized single-mode fibre optic middle-scale
1 × N DWDM devices for category OP – Outdoor protected environment**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61753-081-03 has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
86B/4803/FDIS	86B/4821/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts of IEC 61753 series, published under the general title *Fibre optic interconnecting devices and passive components – Performance standard*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 61753-081-03:2023](https://standards.iteh.ai/catalog/standards/iec/f566f7e0-f25a-4271-8bf3-cbdbcf5bc64a/iec-61753-081-03-2023)

<https://standards.iteh.ai/catalog/standards/iec/f566f7e0-f25a-4271-8bf3-cbdbcf5bc64a/iec-61753-081-03-2023>

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – PERFORMANCE STANDARD –

Part 081-03: Non-connectorized single-mode fibre optic middle-scale 1 × N DWDM devices for category OP – Outdoor protected environment

1 Scope

This part of IEC 61753 contains the minimum initial test and measurement requirements and severities which a fibre optic middle-scale 1 × N ($16 \leq N \leq 64$) DWDM (dense wavelength division multiplexing) arrayed waveguide grating device with channel spacing of 50 GHz, 100 GHz or 200 GHz satisfies in order to be categorized as meeting the requirements of category OP (outdoor protected environment). The requirements are given for the DWDM devices with Gaussian passband profile and flat-top passband profile. The requirements exclude the devices with dynamic electrical temperature control.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60793-2-50, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 60794-2-50, *Optical fibre cables – Part 2-50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies*

IEC 61300 (all parts), *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures*

IEC 61300-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 1: General and guidance*

IEC 61300-2-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)*

IEC 61300-2-4, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-4: Tests – Fibre or cable retention*

IEC 61300-2-5, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-5: Tests – Torsion*

IEC 61300-2-9, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests – Shock*

IEC 61300-2-14, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-14: Tests – High optical power*

IEC 61300-2-17, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-17: Tests – Cold*

IEC 61300-2-18, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-18: Tests – Dry heat*

IEC 61300-2-22, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-22: Tests – Change of temperature*

IEC 61300-2-26, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-26: Tests – Salt mist*

IEC 61300-2-27, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-27: Tests – Dust – Laminar flow*

IEC 61300-2-44, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-44: Tests – Flexing of the strain relief of fibre optic devices*

IEC 61300-2-46, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-46: Tests – Damp heat, cyclic*

IEC 61300-3-2, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-2: Examination and measurements – Polarization dependent loss in a single-mode fibre optic device*

IEC 61300-3-6, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-6: Examinations and measurements – Return loss*

IEC 61300-3-20, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-20: Examinations and measurements – Directivity of fibre optic branching devices*

IEC 61300-3-28, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-28: Examinations and measurements – Transient loss*

IEC 61300-3-29, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-29: Examinations and measurements – Spectral transfer characteristics of DWDM devices*

IEC 61300-3-32, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-32: Examinations and measurements – Polarization mode dispersion measurement for passive optical components*

IEC 61300-3-38, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-38: Examinations and measurements – Group delay, chromatic dispersion and phase ripple*

IEC 61753-1, *Fibre optic interconnecting devices and passive components – Performance standard – Part 1: General and guidance*

IEC 61753-081-02, *Fibre optic interconnecting devices and passive components – Performance standard – Part 081-02: Non-connectorized single-mode fibre optic middle-scale 1 × N DWDM devices for category C – Controlled environments*

IEC 62074-1, *Fibre optic interconnecting devices and passive components – Fibre optic WDM devices – Part 1: Generic specification*

IEC TS 62627-09, *Fibre optic interconnecting devices and passive components – Vocabulary for passive optical devices*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61753-081-02, IEC 62074-1 and IEC TS 62627-09, apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

4 Test

Unless otherwise specified, all test methods shall be in accordance with the IEC 61300 series. The samples shall be terminated onto single-mode fibres as per IEC 60793-2-50 category B-652.B, B-652.D or B-657 on either coated fibres (primary and secondary) or reinforced cable format as per IEC 60794-2-50. DWDM devices used for the test are intended to be previously unstressed new samples but may also be selected from previously used samples, if desired. All measurements shall be carried out at the standard atmospheric condition defined in IEC 61300-1, unless otherwise stated. If the device is provided with temperature control, this shall be set at the set-point specified by the manufacturer.

The requirements apply to every combination of input and output port.

All tests shall be carried out to validate performance over the required operating wavelength range. As a result, single or multiple spectral bands may be chosen for the qualification and differing target specifications may be assigned to each spectral band.

Table 1 is intended to provide guidance on the wavelength ranges of the various spectral bands. It is not intended for specification. Values of operating wavelength used in performance verification shall be defined in the manufacturer's specification.

Table 1 – Single-mode spectral bands¹

Band	Descriptor	Range nm
O-band	Original	1 260 to 1 360
E-band	Extended	1 360 to 1 460
S-band	Short wavelength	1 460 to 1 530
C-band	Conventional	1 530 to 1 565
L-band	Long wavelength	1 565 to 1 625
U-band	Ultralong wavelength	1 625 to 1 675

¹ Reproduced from ITU-T G-series Recommendations – Supplement 39, with the permission of ITU-T.

5 Test report

Fully documented test reports and supporting evidence shall be prepared and be available for inspection as evidence that the tests have been carried out and complied with.

6 Performance requirements

6.1 Reference components

The testing for these devices does not require the use of reference components.

6.2 Dimensions

Dimensions shall comply with either an appropriate IEC interface standard or with those given in appropriate manufacturers drawings, where the IEC interface standard does not exist or cannot be used.

6.3 Sample size

Sample sizes are defined in Table A.1 of Annex A.

6.4 Test details and requirements

The requirements are given only for pigtailed DWDM devices. For connectorized components, the connector performances shall be in compliance with IEC 61753-1.

The minimum length of fibre or cable of 1,0 m per port on each pigtailed side shall be used for all tests.

Test details and minimum requirements for category OP is shown in Table 2, Table 3 and Table 4.

Table 2 – Test details and requirements for type A (Gaussian passband profile)

No	Tests	Requirements	Details	
1A	Number of channels: N	$16 \leq N \leq 64$	Operating wavelength: NOTE	ITU-T grid (ITU-T Recommendation G.694.1) or custom design. Design information (not test item).
2A	Channel frequency range	Channel central frequency $\pm 0,125 \times \Delta f$ where Δf is the channel spacing.	Channel central frequency: NOTE	ITU-T grid (ITU-T Recommendation G.694.1) or custom design. Design information (not test item).
3A	Attenuation (insertion loss) IEC 61300-3-29	$\leq 6,0$ dB (channel spacing with 50 GHz). $\leq 4,5$ dB (channel spacing with 100 GHz, 200 GHz). Maximum allowable attenuation (insertion loss) over the channel frequency range.	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m $\leq 0,2$ dB The attenuation (insertion loss) is determined as the maximum value over all states of polarization.

No	Tests	Requirements	Details	
4A	Channel non-uniformity IEC 61300-3-29	$\leq 1,5$ dB Maximum allowable channel non-uniformity of attenuation.	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m $\leq 0,2$ dB The channel non-uniformity is determined as the maximum value over all states of polarization.
5A	1 dB passband width IEC 61300-3-29	$\geq 0,25 \times \Delta f$ where Δf is the channel spacing. Minimum allowable 1 dB passband width (centred at the channel frequency).	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m $\leq 0,01 \times \Delta f$ The 1 dB passband width is determined as the minimum value over all states of polarization.
6A	3 dB passband width IEC 61300-3-29	$\geq 0,4 \times \Delta f$ where Δf is the channel spacing (channel spacing with 200 GHz). $\geq 0,5 \times \Delta f$ where Δf is the channel spacing (channel spacing with 50 GHz, 100 GHz). Minimum allowable 3 dB passband width (centred at the channel frequency).	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m $\leq 0,01 \times \Delta f$ The 3 dB passband width is determined as the minimum value over all states of polarization.
7A	Passband ripple IEC 61300-3-29	$\leq 1,5$ dB Maximum attenuation variation within the channel frequency range.	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m $\leq 0,2$ dB The passband ripple is determined as the maximum value over all states of polarization.
8A	Adjacent channel crosstalk IEC 61300-3-29	≤ -25 dB Maximum allowable adjacent channel crosstalk over the channel frequency range.	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m ≤ 1 dB The adjacent channel crosstalk is specified only for demultiplexer. The adjacent channel crosstalk is determined as the maximum value over all states of polarization.
9A	Non-adjacent channel crosstalk IEC 61300-3-29	≤ -30 dB Maximum allowable non-adjacent channel crosstalk over the channel frequency range.	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m ≤ 1 dB The non-adjacent channel crosstalk is specified only for demultiplexer. The non-adjacent channel crosstalk is determined as the maximum value over all states of polarization.

No	Tests	Requirements	Details	
10A	Total channel crosstalk IEC 61300-3-29	≤ -20 dB Maximum allowable total channel crosstalk value.	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m ≤ 1 dB The total channel crosstalk is specified only for demultiplexer. The total channel crosstalk is determined as the maximum value over all states of polarization.
11A	Polarization dependent loss (PDL) IEC 61300-3-2	$\leq 0,75$ dB Maximum allowable PDL over the channel frequency range.	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m $\leq 0,10$ dB The allowable PDL combination applies to all combination of input and output ports.
12A	Polarization mode dispersion (PMD) IEC 61300-3-32	$\leq 0,5$ ps Maximum allowable PMD over the channel frequency range.	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m $\leq 0,1$ ps The allowable PMD combination applies to all combination of input and output ports.
13A	Chromatic dispersion (CD) IEC 61300-3-38	≤ 20 ps/nm Maximum allowable CD over the channel frequency range (absolute value).	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m ≤ 1 ps/nm The allowable CD combination applies to all combination of input and output ports.
14A	Return loss IEC 61300-3-6	≥ 40 dB Minimum allowable return loss.	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m ≤ 1 dB All ports not under test are terminated to avoid unwanted reflections contributing to the measurement.
15A	Directivity IEC 61300-3-20	≥ 40 dB Minimum allowable directivity.	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m ≤ 1 dB All ports not under test are terminated to avoid unwanted reflections contributing to the measurement. The directivity is measured between any pair of input or output ports.