

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Fuel cell technologies – Part 6-107: Micro fuel cell power systems – Safety – Indirect water-reactive (Division 4.3) compounds

Technologies des piles à combustible – Partie 6-107: Systèmes à micropiles à combustible – Sécurité – Composés hydroréactifs indirects (Division 4.3)

<https://standards.iteh.ai/catalog/standards/iec/4fb474e2-a649-4911-aab6-6e7c4362e0e9/iec-62282-6-107-2024>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.



INTERNATIONAL STANDARD

NORME INTERNATIONALE

Fuel cell technologies –
Part 6-107: Micro fuel cell power systems – Safety – Indirect water-reactive
(Division 4.3) compounds

Technologies des piles à combustible –
Partie 6-107: Systèmes à micropiles à combustible – Sécurité – Composés
hydroréactifs indirects (Division 4.3)

<https://standards.iteh.ai/catalog/standards/iec/4fb474e2-a649-4911-aab6-6e7c4362e0e9/iec-62282-6-107-2024>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 27.070

ISBN 978-2-8322-8462-9

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references	5
3 Terms and definitions	5
4 Safety principles.....	6
5 General safety requirements.....	6
5.1 General.....	6
5.2 Chemical safety requirements.....	6
5.3 Material requirements	7
5.4 Mechanical design requirements	7
5.4.1 General	7
5.4.2 Micro fuel cell power system.....	8
5.4.3 Fuel cartridge	8
5.4.4 Fuel valves and connections.....	8
5.5 Electrical requirements	8
5.6 Hazard analysis and risk assessment.....	8
5.7 Functional safety requirements	8
5.8 Small parts	8
6 Abnormal operating and fault conditions testing and requirements.....	8
7 Instructions and warnings for micro fuel cell power systems and fuel cartridges	8
8 Type tests for micro fuel cell power systems and fuel cartridges.....	9
8.1 General.....	9
8.2 General leakage and gas loss measurement protocols.....	9
8.2.1 General protocols	9
8.2.2 Tests	9
8.3 Type tests.....	10
8.3.1 Pressure differential tests	10
8.3.2 Vibration test	10
8.3.3 Temperature cycling test	10
8.3.4 High-temperature exposure test.....	10
8.3.5 Drop test	11
8.3.6 Compressive loading test.....	11
8.3.7 External short-circuit test.....	11
8.3.8 Surface, component and exhaust gas temperature test.....	11
8.3.9 Long-term storage test.....	11
8.3.10 High-temperature connection test	11
8.3.11 Connection cycling tests	11
8.3.12 Gas loss tests.....	12
Bibliography.....	13
Table 1 – Emission and gas loss limits.....	7

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FUEL CELL TECHNOLOGIES –

**Part 6-107: Micro fuel cell power systems – Safety –
Indirect water-reactive (Division 4.3) compounds**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62282-6-107 has been prepared by IEC technical committee 105: Fuel cell technologies. It is an International Standard.

This first edition, together with the other parts of the IEC 62282-6-1XX series, cancels and replaces IEC 62282-6-100:2010 and IEC 62282-6-100:2010/AMD1:2012.

This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62282-6-100:2010 and IEC 62282-6-100:2010/AMD1:2012:

- a) A new structure has been set up: IEC 62282-6-101 covers the general safety requirements common to all fuel types whereas IEC 62282-6-102 and subsequent parts of the IEC 62282-6-1XX series cover particular requirements for individual fuel types.

The text of this International Standard is based on the following documents:

Draft	Report on voting
105/1018/FDIS	105/1033/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62282 series, published under the general title *Fuel cell technologies*, can be found on the IEC website.

This document is to be used in conjunction with IEC 62282-6-101:2024 and is not to be used as a stand-alone document. This document provides additional requirements specific to water-reactive fuel formulations, which apply in addition to the general requirements specified in IEC 62282-6-101:2024. The (sub)clause numbers in this document are aligned with those of IEC 62282-6-101:2024 and are intended to provide additional information and refined requirements, as appropriate.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

NOTE The attention of National Committees is drawn to the fact that equipment manufacturers and testing organizations may need a transitional period following publication of a new, amended or revised IEC publication in which to make products in accordance with the new requirements and to equip themselves for conducting new or revised tests.

It is the recommendation of the committee that the content of this publication be adopted for implementation nationally not earlier than 12 months from the date of publication.

FUEL CELL TECHNOLOGIES –

Part 6-107: Micro fuel cell power systems – Safety – Indirect water-reactive (Division 4.3) compounds

1 Scope

This part of IEC 62282 covers micro fuel cell power systems, micro fuel cell power units and fuel cartridges using hydrogen produced from water-reactive (UN Division 4.3) compounds as fuel. These systems and units use proton exchange membrane (PEM) fuel cell technologies. The designs can include fuel processing subsystems to derive hydrogen gas from the water-reactive fuel formulation.

This document only applies to water-reactive (UN Division 4.3) solid compounds which solely evolve hydrogen gas upon contact with water (or non-hazardous aqueous solutions). This document does not apply to compounds with a subsidiary hazard risk, or which are not permitted to be transported by air according to the International Civil Aviation Organization (ICAO) Technical Instructions.

IEC 62282-6-101:2024, Figure 1 is applicable.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[IEC 62282-6-107:2024](https://standards.iteh.ai/catalog/standards/iec/40b474e2-a649-4911-aab6-6e7c4362e0e9/iec-62282-6-107-2024)

IEC 62282-6-101:2024, *Fuel cell technologies – Part 6-101: Micro fuel cell power systems – Safety – General requirements*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62282-6-101 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

fuel

water-reactive (UN Division 4.3) solid formulation of compounds comprising constituents selected from the following groups used as fuel for an indirect PEM micro fuel cell power system: (water reactive) mixtures, metals, alloys, compounds or chemical hydrides of the following materials: sodium, calcium, magnesium, borohydride compounds, silicon, silicon dioxide, iron, nickel, cobalt, aluminium

Note 1 to entry: The formulation may contain a non-hazardous activator to facilitate the production of hydrogen, or a stabilizer to modulate or inhibit the production of hydrogen or both.

3.2

borohydride compound

sodium or potassium borohydride, or a mixture thereof

3.3

liquid fuel component

Class 8 (corrosive), or non-hazardous, aqueous solutions, which may contain activators, inhibitors, or freezing point suppressors

Note 1 to entry: Liquid fuel components are used to react with the water-reactive fuel to produce hydrogen.

3.4

activator

substance that facilitates the production of hydrogen from fuel, such as a catalyst

3.5

stabilizer

substance that modulates or inhibits the production of hydrogen from fuel

4 Safety principles

The safety principles included in IEC 62282-6-101:2024, Clause 4 apply in their entirety to technologies included in this document.

5 General safety requirements

5.1 General

The general safety requirements of IEC 62282-6-101:2024, 5.1 shall apply as written with the following addition.

NOTE The limited quantity exception for cargo transport of fuel cell cartridges containing water-reactive fuel is 500 g of solid fuel according to the UN Model Regulations. For passenger carriage in the aircraft cabin or in checked baggage the maximum quantity of water reactive fuel permitted inside the cartridge is 200 g of solid fuel according to the 2013 edition of the ICAO Technical Instructions.

5.2 Chemical safety requirements

Consistent with IEC 62282-6-101:2024, Table 4, the following limits given in Table 1 shall apply for the emission and gas loss measurements for micro fuel cell power systems and fuel cartridges tested in accordance with this document.

Table 1 – Emission and gas loss limits

Constituent	Concentration limit ^a (Operating devices)	Gas loss rate limit ^b (Operating devices)	Gas loss rate limit ^c (Non-operating devices)
Non-hazardous aqueous solutions	Unlimited for pH between 3,5 and 10,5	Unlimited for pH between 3,5 and 10,5	Unlimited for pH between 3,5 and 10,5
Hydrogen	0,8 g/m ³	0,8 g/h total 0,016 g/h from single point leak ^d	0,003 2 g/h total (impermissible H ₂ gas loss)
Formaldehyde ^e 9	0,000 1 g/m ³	0,000 6 g/h	0,000 6 g/h
CO ^g	0,029 g/m ³	0,290 g/h	0,290 g/h
CO ₂ ^g	9 g/m ³	60 g/h ^f	60 g/h ^f
Methyl formate ^g	0,245 g/m ³	2,45 g/h	0,4 g/h

^a The concentration limit for chemical compounds of interest shall be based on internationally recommended values. All toxicity based limits listed in this Table 1 are based on long-term, time-averaged limits, for instance TWA for ICSC's occupational limit. The gas loss rate limit shall be obtained using similar computation as used in this Table 1 to ensure that overall gas loss rates do not exceed time-averaged limits for the constituent of interest. For such constituents, short-term increases in gas loss rate may be permissible, provided that the transient rate does not exceed the short-term exposure limit (STEL) for that constituent and the overall gas loss rate does not exceed the time-averaged rate specified in this Table 1.

^b The "operating" emission rate limit was based on 10 m³ ACH, selected as the product of the reference volume times the air changes per hour (ACH) because it covers the reasonably foreseeable environments where micro fuel cell power systems will be used. The interior space in a small car and the minimum volume per person on a commercial aircraft is at 1 m³. The minimum ACH used on a passenger aircraft is 10 and the lowest ventilation setting in cars is 10 ACH. Homes and offices may have ACH levels as low as 0,5 but the per-person volume is over 20 m³, so a product of 10 is conservative.

^c The non-operating limits have been chosen based on a scenario of devices in an enclosed space with no ventilation. The space chosen has a volume of 0,28 m³, or approximately 10 cubic feet. The criterion has been specified so that a concentration of greater than 25 % of the lower flammability limit (LFL) is not permitted to develop over a twenty-four hour (24 h) period, if three devices are in the enclosed space. For example, this criterion is applied for the determination of a maximum gas-loss rate based on the emission of flammable constituents from non-operating micro fuel cell power systems. Note that the control volume for non-operating systems should not be applied using toxicity limits, as the core principle of this enclosed space is that of a storage space, not one that a person can spend time in. For the determination of non-operating limits for constituents with both flammable and toxic properties, the lower of the flammability based limit for the "non-operating" control volume and the toxicity based limit for the "operating" control volume shall apply.

^d 0,016 g/h reflects an emission rate lower than the limit reported by Swain, et al, (Proceedings of the 2001 DOE Program Review; NREL/CP-570-30535; M.R. Swain and M.N. Swain, Codes and Standards Analysis, 2001 (USA); available at: <http://www1.eere.energy.gov/hydrogenandfuelcells/pdfs/30535bc.pdf>) wherein "no hole was able to support a hydrogen flame at less than 3.5 cc/min." (3.5 cc/min ≈ 0,018 g/h). This value was chosen in conformance with the guidelines in IEC 62282-6-101:2024, Table 3.

^e The WHO guideline limit is 0,000 1 g/m³. Background levels are 0,000 03 g/m³. The emission limit cannot push the background level above the guideline limit.

^f A seated human adult has a CO₂ emission rate of 30 g/h. The fuel cell plus human adult emission rates are limited such that the CO₂ concentration does not reach the WHO eight-hour concentration limit of 9 g/m³. In an environment with 10 m³ ACH, this limits the contribution from the fuel cell to 60 g/h.

^g Testing for the presence of these constituents may be omitted for micro fuel cell power systems and fuel cartridges that do not contain, or have the potential to evolve, carbon-based compounds. In such cases, the rationale for such omission shall be documented in the hazard analysis and risk assessment.

5.3 Material requirements

The requirements of IEC 62282-6-101:2024, 5.3 shall apply as written.

5.4 Mechanical design requirements

5.4.1 General

The requirements of IEC 62282-6-101:2024, 5.4.1 shall apply as written.

5.4.2 Micro fuel cell power system

The general requirements of IEC 62282-6-101:2024, 5.4.2.1 and 5.4.2.2 shall apply as written.

5.4.3 Fuel cartridge

The general requirements of IEC 62282-6-101:2024, 5.4.3 shall apply as written with the following additions.

In addition, the following fuel specific requirements shall apply:

- In cases where materials (either solid or liquid) are present and are incompatible with either the water-reactive fuel or liquid fuel component, the design of the fuel cartridge and micro fuel cell power system shall provide a means for preventing inadvertent or uncontrolled mixing of these materials.
- Two independent means for preventing inadvertent or uncontrolled mixing of these materials shall be provided during transportation and storage prior to use. Illustrative examples of these means include but are not limited to: positive activation by the control system; physical removal of an impermeable barrier preventing contact; opening of a normally closed manually controlled valve preventing contact. At least one of these means for preventing uncontrolled mixing shall require the user to take positive action to remove or deactivate it prior to use.
- At least one means for preventing uncontrolled mixing of these materials shall be provided during use and storage after use. This means may include active control by system electronics, subject to the required hazard analysis and risk assessment.

5.4.4 Fuel valves and connections

The general requirements of IEC 62282-6-101:2024, 5.4.4.1 and 5.4.4.2 shall apply as written.

5.5 Electrical requirements

The general requirements of IEC 62282-6-101:2024, 5.5 shall apply as written.

5.6 Hazard analysis and risk assessment

The general requirements of IEC 62282-6-101:2024, 5.6 shall apply as written.

5.7 Functional safety requirements

The general requirements of IEC 62282-6-101:2024, 5.7 shall apply as written.

5.8 Small parts

The general requirements of IEC 62282-6-101:2024, 5.8 shall apply as written.

6 Abnormal operating and fault conditions testing and requirements

The general requirements of IEC 62282-6-101:2024, Clause 6 shall apply as written.

7 Instructions and warnings for micro fuel cell power systems and fuel cartridges

The general requirements of IEC 62282-6-101:2024, Clause 7 shall apply as written with the following addition.

In addition, both fuel cartridges and micro fuel cell power systems shall also include the following marking:

"MAY CONTAIN FLAMMABLE GAS."

8 Type tests for micro fuel cell power systems and fuel cartridges

8.1 General

The general requirements of IEC 62282-6-101:2024, 8.1 shall apply as written.

8.2 General leakage and gas loss measurement protocols

8.2.1 General protocols

The general requirements and principles of IEC 62282-6-101:2024, 8.2 shall be applied as appropriate for each of the type tests required in IEC 62282-6-101:2024, 8.3.1 through 8.3.8 with the following addition.

For fuel cartridges and micro fuel cell power systems tested in accordance with this document, in general, concentration-based measurements are recommended over mass-based measurements. It is possible that mass-based measurements will not be appropriate for fuel cartridges containing water-reactive fuel, as leakage can be indicated by an increase in overall mass (e.g. absorption of water) rather than mass loss. If mass-based measurements are utilized for any type test, the test method shall be verified and validated prior to use for assessing compliance.

8.2.2 Tests

8.2.2.1 General

Following each type test, all test samples shall be checked for leakage and gas loss in accordance with the following procedures.

8.2.2.2 Leakage and gas loss test procedures for fuel cartridges

1) Perform a visual inspection of all possible leak locations for leakage as follows:

The method for the detection of accessible hazardous liquids given in IEC 62282-6-101:2024, 8.2.8 or an equivalent method, shall be used to detect any hazardous liquid leakage.

2) Perform a water immersion test following each type test using the protocol described in IEC 62282-6-101:2024, 8.2.6, or an equivalent method to check for leakage.

3) Check for hydrogen gas loss using a liquid leak detector on possible leak locations of fuel cartridges using the protocol described in IEC 62282-6-101:2024, 8.2.5, or an equivalent method. For fuel cartridges, the check for hydrogen gas loss may be performed simultaneously with the check for leakage in Step 2).

If the fuel cartridge is of the type that is refillable by the manufacturer (automated or by trained technicians), it shall be filled to its rated capacity prior to testing. If the fuel cartridge is not refillable, it shall be tested in the condition in which it completed the type test in question. The fuel cartridge shall be tested for leaks at laboratory temperature. There shall be no leakage or gas loss from any point on the fuel cartridge.

8.2.2.3 Leakage and gas loss test procedures for micro fuel cell power systems

1) Perform a visual inspection of all possible leak locations for leakage as follows:

The method for the detection of accessible hazardous liquids given in IEC 62282-6-101:2024, 8.2.8 or an equivalent method, shall be used to detect any hazardous liquid leakage.